

Commission Regulation (EU) No 1235/2011 of 29 November 2011 amending Regulation (EC) No 1222/2009 of the European Parliament and of the Council with regard to the wet grip grading of tyres, the measurement of rolling resistance and the verification procedure (Text with EEA relevance)

Article 1

Amendment to Regulation (EC) No 1222/2009

Regulation (EC) No 1222/2009 is amended as follows:

(1) Annex I, part A: Fuel efficiency classes, the first sentence is replaced by the following:

The fuel efficiency class must be determined on the basis of the rolling resistance coefficient (*RRC*) according to the “A” to “G” scale specified below and measured in accordance with Annex 6 of UNECE Regulation No 117 and its subsequent amendments and aligned according to the procedure laid down in Annex IVa.;

(2) in Annex I, part B: Wet grip classes, the text and table are replaced by the following:

1. The wet grip class of C1 tyres must be determined on the basis of the wet grip index (*G*) according to the “A” to “G” scale specified in the table below, calculated in accordance with point 3 and measured in accordance with Annex V.

2. The wet grip class of C2 and C3 tyres must be determined on the basis of the wet grip index (*G*) according to the “A” to “G” scale specified in the table below, calculated in accordance with point (3) and measured in accordance with ISO 15222:2011 whereby the following Standard Reference Test Tyres (SRTT) must be used:

(i) for C2 tyres, the SRTT 225/75 R 16 C, ASTM F 2872-11;

(ii) for C3 tyres having Nominal Section Width lower than 285 mm, the SRTT 245/70R19.5, ASTM F 2871-11;

(iii) for C3 tyres having Nominal Section Width greater than or equal to 285 mm, the SRTT 315/70R22.5, ASTM F 2870-11.

3. Calculation of wet grip index (*G*)

$$G = G(T) - 0,03$$

where: *G(T)* = wet grip index of the candidate tyre as measured in one test cycle

C1 tyres		C2 tyres		C3 tyres	
<i>G</i>	Wet grip class	<i>G</i>	Wet grip class	<i>G</i>	Wet grip class
$1,55 \leq G$	A	$1,40 \leq G$	A	$1,25 \leq G$	A
$1,40 \leq G \leq 1,54$	B	$1,25 \leq G \leq 1,39$	B	$1,10 \leq G \leq 1,24$	B

Changes to legislation: Commission Regulation (EU) No 1235/2011 is up to date with all changes known to be in force on or before 26 January 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

$1,25 \leq G \leq 1,39$	C	$1,10 \leq G \leq 1,24$	C	$0,95 \leq G \leq 1,09$	C
Empty	D	Empty	D	$0,80 \leq G \leq 0,94$	D
$1,10 \leq G \leq 1,24$	E	$0,95 \leq G \leq 1,09$	E	$0,65 \leq G \leq 0,79$	E
$G \leq 1,09$	F	$G \leq 0,94$	F	$G \leq 0,64$	F
Empty	G	Empty	G	Empty	G

(3) Annex IV: Verification procedure, is replaced by the following:

ANNEX IV

Verification procedure

The conformity of the declared fuel efficiency and wet grip classes, as well as the declared external rolling noise class and declared value, must be assessed for each tyre type or each grouping of tyres as determined by the supplier, according to one of the following procedures:

- (a)
 - (i) a single tyre or tyre set is tested first. If the measured values meet the declared classes or external rolling noise declared value to within the tolerance defined in Table 1, the test is successfully passed; and
 - (ii) if the measured values do not meet the declared classes or external rolling noise declared value within the range defined in Table 1, three more tyres or tyre sets are tested. The average measurement value stemming from the three tyres or tyre sets tested is used to assess conformity with the declared information within the range defined in Table 1; or
- (b) where the labelled classes or values are derived from type approval test results obtained in accordance with Directive 2001/43/EC, Regulation (EC) No 661/2009, or UNECE Regulation No 117 and its subsequent amendments, Member States may make use of measurement data obtained from conformity of production tests on tyres.

Assessment of the measurement data obtained from the conformity of production tests must take into account the allowances defined in Table 1.

TABLE 1

Measured parameter	Verification tolerances
Rolling resistance coefficient (fuel efficiency)	The aligned measured value shall not be greater than the upper limit (the highest <i>RRC</i>) of the declared class by more than 0,3 kg/1 000kg.

Changes to legislation: Commission Regulation (EU) No 1235/2011 is up to date with all changes known to be in force on or before 26 January 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

External rolling noise	The measured value shall not be greater than the declared value of <i>N</i> by more than 1 dB(A).
Wet grip	The measured value shall not be lower than the lower limit (the lowest value of <i>G</i>) of the declared class.

(4) the text set out in the Annex to this Regulation is added as Annex IVa.

Article 2

Entry into force

This Regulation shall enter into force on the 20th day following its publication in the *Official Journal of the European Union*.

This Regulation shall apply from 30 May 2012.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 29 November 2011.

For the Commission

The President

José Manuel BARROSO

Changes to legislation:

Commission Regulation (EU) No 1235/2011 is up to date with all changes known to be in force on or before 26 January 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations.

[View outstanding changes](#)

Changes and effects yet to be applied to :

- Regulation implicit repeal by [EUR 2020/740](#) Regulation