

Commission Regulation (EU) No 1299/2014 of 18 November 2014 on the technical specifications for interoperability relating to the ‘infrastructure’ subsystem of the rail system in the European Union (Text with EEA relevance) (revoked)

Article 1	Subject matter
Article 2	Scope
Article 3	Open points
Article 4	Specific cases
Article 5	Notification of bilateral agreements
Article 6	Projects at an advanced stage of development
Article 7	‘EC’ certificate of verification
Article 8	Conformity assessment
Article 9	Implementation
Article 10	Innovative solutions
Article 11	Repeal
Article 12	Entry into force
	Signature

---

ANNEX

1. INTRODUCTION
  - 1.1. Technical Scope
  - 1.2. Geographical Scope
  - 1.3. Content of this TSI
2. DEFINITION AND SCOPE OF SUBSYSTEM
  - 2.1. Definition of the infrastructure subsystem
  - 2.2. Interfaces of this TSI with other TSIs
  - 2.3. Interfaces of this TSI with the Persons with Reduced Mobility...
  - 2.4. Interfaces of this TSI with the Safety in Railway Tunnels...
  - 2.5. Relation to the safety management system
3. ESSENTIAL REQUIREMENTS
4. DESCRIPTION OF THE INFRASTRUCTURE SUBSYSTEM
  - 4.1. Introduction
  - 4.2. Functional and technical specifications of the infrastructure subsystem
    - 4.2.1. TSI Categories of Line
    - 4.2.2. Basic parameters characterising the infrastructure subsystem
      - 4.2.2.1. List of Basic Parameters
      - 4.2.2.2. Requirements for Basic Parameters
    - 4.2.3. Line layout
      - 4.2.3.1. Structure gauge
      - 4.2.3.2. Distance between track centres
      - 4.2.3.3. Maximum gradients
      - 4.2.3.4. Minimum radius of horizontal curve

- 4.2.3.5. Minimum radius of vertical curve
- 4.2.4. Track parameters
  - 4.2.4.1. Nominal track gauge
  - 4.2.4.2. Cant
  - 4.2.4.3. Cant deficiency
  - 4.2.4.4. Abrupt change of cant deficiency
  - 4.2.4.5. Equivalent conicity
  - 4.2.4.6. Railhead profile for plain line
  - 4.2.4.7. Rail inclination
    - 4.2.4.7.1. Plain line
    - 4.2.4.7.2. Requirements for switches and crossings
- 4.2.5. Switches and crossings
  - 4.2.5.1. Design geometry of switches and crossings
  - 4.2.5.2. Use of swing nose crossing
  - 4.2.5.3. Maximum unguided length of fixed obtuse crossings
- 4.2.6. Track resistance to applied loads
  - 4.2.6.1. Track resistance to vertical loads
  - 4.2.6.2. Longitudinal track resistance
    - 4.2.6.2.1. Design forces
    - 4.2.6.2.2. Compatibility with braking systems
  - 4.2.6.3. Lateral track resistance
- 4.2.7. Structures resistance to traffic loads
  - 4.2.7.1. Resistance of new bridges to traffic loads
    - 4.2.7.1.1. Vertical loads
      - 4.2.7.1.1.1. Allowance for dynamic effects of vertical loads
      - 4.2.7.1.1.2. Centrifugal forces
      - 4.2.7.1.1.3. Nosing forces
      - 4.2.7.1.1.4. Actions due to traction and braking (longitudinal loads)
      - 4.2.7.1.1.5. Design track twist due to rail traffic actions
  - 4.2.7.2. Equivalent vertical loading for new earthworks and earth pressure effects...
  - 4.2.7.3. Resistance of new structures over or adjacent to tracks
  - 4.2.7.4. Resistance of existing bridges and earthworks to traffic loads
- 4.2.8. Immediate action limits on track geometry defects
  - 4.2.8.1. The immediate action limit for alignment
  - 4.2.8.2. The immediate action limit for longitudinal level
  - 4.2.8.3. The immediate action limit for track twist
  - 4.2.8.4. The immediate action limit of track gauge as an isolated...
  - 4.2.8.5. The immediate action limit for cant
  - 4.2.8.6. The immediate action limits for switches and crossings
- 4.2.9. Platforms
  - 4.2.9.1. Usable length of platforms
  - 4.2.9.2. Platform height
  - 4.2.9.3. Platform offset
  - 4.2.9.4. Track layout alongside platforms
- 4.2.10. Health, safety and environment
  - 4.2.10.1. Maximum pressure variations in tunnels
  - 4.2.10.2. Effect of crosswinds
  - 4.2.10.3. Aerodynamic effect on ballasted track
    - (1) The aerodynamic interaction between rolling stock and infrastructure may cause...

- (2) The requirements for the infrastructure subsystem aimed at mitigating the...
    - (3) The requirements of point (2) above are an open point....
  - 4.2.11. Provision for operation
    - 4.2.11.1 Location markers
    - 4.2.11.2 Equivalent conicity in service
  - 4.2.12. Fixed installations for servicing trains
    - 4.2.12.1 General
    - 4.2.12.2 Toilet discharge
    - 4.2.12.3 Train external cleaning facilities
    - 4.2.12.4 Water restocking
    - 4.2.12.5 Refuelling
    - 4.2.12.6 Electrical shore supply
  - 4.3. Functional and technical specification of the interfaces
    - 4.3.1. Interfaces with the rolling stock subsystem
    - 4.3.2. Interfaces with the energy subsystem
    - 4.3.3. Interfaces with the control command and signalling subsystem
    - 4.3.4. Interfaces with the operation and traffic management subsystem
  - 4.4. Operating rules
  - 4.5. Maintenance rules
    - 4.5.1. Maintenance file
    - 4.5.2. Maintenance plan
  - 4.6. Professional qualifications
  - 4.7. Health and safety conditions
- 5. INTEROPERABILITY CONSTITUENTS
  - 5.1. Basis on which interoperability constituents have been selected
  - 5.2. List of constituents
  - 5.3. Constituents performances and specifications
    - 5.3.1. The rail
      - 5.3.1.1. Railhead profile
      - 5.3.1.2. Rail steel
    - 5.3.2. The rail fastening systems
    - 5.3.3. Track sleepers
- 6. ASSESSMENT OF CONFORMITY OF INTEROPERABILITY CONSTITUENTS AND EC VERIFICATION OF...
  - 6.1. Interoperability Constituents
    - 6.1.1. Conformity assessment procedures
    - 6.1.2. Application of modules
    - 6.1.3. Innovative solutions for interoperability constituents
    - 6.1.4. EC declaration of conformity for interoperability constituents
      - 6.1.4.1. Interoperability constituents subject to other European Union Directives
        - (1) in accordance with Article 10(3) of Directive (EU) 2016/797, for...
        - (2) in accordance with Annex I to Commission Implementing Regulation (EU)...
      - 6.1.4.2. EC declaration of conformity for rails
      - 6.1.4.3. EC declaration of conformity for rail fastening systems
      - 6.1.4.4. EC declaration of conformity for track sleepers
    - 6.1.5. Particular assessment procedures for interoperability constituents

- 
- 6.1.5.1. Assessment of rails
  - 6.1.5.2. Assessment of sleepers
  - 6.2. Infrastructure subsystem
    - 6.2.1. General provisions
    - 6.2.2. Application of modules
      - 6.2.2.1. Application of module SG
      - 6.2.2.2. Application of module SH1
    - 6.2.3. Innovative solutions
    - 6.2.4. Particular assessment procedures for infrastructure subsystem
      - 6.2.4.1. Assessment of Structure gauge
      - 6.2.4.2. Assessment of distance between track centres
      - 6.2.4.3. Assessment of nominal track gauge
      - 6.2.4.4. Assessment of track layout
      - 6.2.4.5. Assessment of cant deficiency for trains designed to travel with...
      - 6.2.4.6. Assessment of design values for equivalent conicity
      - 6.2.4.7. Assessment of railhead profile
      - 6.2.4.8. Assessment of switches and crossings
      - 6.2.4.9. Assessment of new structures, earthworks and earth pressure effects
      - 6.2.4.10. Assessment of existing structures
      - 6.2.4.11. Assessment of platform offset
      - 6.2.4.12. Assessment of maximum pressure variations in tunnels
      - 6.2.4.13. Assessment of effect of crosswinds
      - 6.2.4.14. Assessment of fixed installations for servicing trains
      - 6.2.4.15. Assessment of compatibility with braking systems
    - 6.2.5. Technical solutions giving presumption of conformity at design stage
      - 6.2.5.1. Assessment of track resistance for plain line
      - 6.2.5.2. Assessment for switches and crossing
  - 6.3. EC Verification when speed is used as a migration criterion...
  - 6.4. Assessment of maintenance file
  - 6.5. Subsystems containing Interoperability constituents not holding an EC declaration
    - 6.5.1. Conditions
    - 6.5.2. Documentation
    - 6.5.3. Maintenance of the subsystems certified according to 6.5.1.
  - 6.6. Subsystem containing serviceable interoperability constituents that are suitable for reuse...
    - 6.6.1. Conditions
    - 6.6.2. Documentation
    - 6.6.3. Use of serviceable interoperability constituents in maintenance
7. IMPLEMENTATION OF THE INFRASTRUCTURE TSI
- 7.1. Application of this TSI to railway lines
  - 7.2. Application of this TSI to new railway lines
  - 7.3. Application of this TSI to existing railway lines
    - 7.3.1. Upgrading or renewal of a line
      - (1) In accordance with Article 2(14) of Directive (EU) 2016/797, ‘...
      - (2) The infrastructure subsystem of a line is considered to be...
      - (3) In accordance with Article 2(15) of Directive (EU) 2016/797, ‘...

- (4) For this purpose, major substitution should be interpreted as a...
  - (5) The scope of the upgrading or renewal of the infrastructure...
  - (6) Where a new authorisation is required, parts of the infrastructure...
  - (7) Where a new authorisation for placing in service is not...
- 7.3.2. Renewal of a line
  - 7.3.3. Substitution in the framework of maintenance
  - 7.3.4. Existing lines that are not subject to a renewal or...
- 7.4. Application of this TSI to existing platforms
  - 7.5. Speed as an implementation criterion
  - 7.6. Route compatibility checks before the use of authorised vehicles
  - 7.7. Specific cases
    - 7.7.1. Particular features on the Austrian network
      - 7.7.1.1. Platform height (4.2.9.2)  
P cases
    - 7.7.2. Particular features on the Belgian network
      - 7.7.2.1. Platform offset (4.2.9.3)  
P cases
    - 7.7.3. Particular features on the Bulgarian network
      - 7.7.3.1. Platform height (4.2.9.2)  
P cases
      - 7.7.3.2. Platform offset (4.2.9.3)  
P cases
    - 7.7.4. Particular features on the Danish network
      - 7.7.4.1. Platform height (4.2.9.2)  
P cases
    - 7.7.5. Particular features on the Estonian network
      - 7.7.5.1. Nominal track gauge (4.2.4.1)  
P cases
      - 7.7.5.2. Resistance of new bridges to traffic loads (4.2.7.1)  
P cases
      - 7.7.5.3. The immediate action limit for switches and crossing (4.2.8.6)  
P cases
    - 7.7.6. Particular features on the Finnish network
      - 7.7.6.1. TSI Categories of line (4.2.1)  
P cases
      - 7.7.6.2. Structure gauge (4.2.3.1)  
P cases
      - 7.7.6.3. Distance between track centres (4.2.3.2)  
P cases
      - 7.7.6.4. Minimum radius of horizontal curve (4.2.3.4)  
P cases
      - 7.7.6.5. Nominal track gauge (4.2.4.1)  
P cases
      - 7.7.6.6. Cant (4.2.4.2)  
P cases
      - 7.7.6.7. Maximum unguided length of fixed obtuse crossings (4.2.5.3)  
P cases
      - 7.7.6.8. The immediate action limit of track gauge as an isolated...  
P cases
      - 7.7.6.9. The immediate action limit of cant (4.2.8.5)  
P cases

**Changes to legislation:** There are currently no known outstanding effects for the Commission Regulation (EU) No 1299/2014. (See end of Document for details)

---

- 7.7.6.10 The immediate action limits for switches and crossings (4.2.8.6)
  - P cases
- 7.7.6.11 Platform offset (4.2.9.3)
  - P cases
- 7.7.6.12 Train external cleaning facilities (4.2.12.3)
  - P cases
- 7.7.6.13 Assessment of structure gauge (6.2.4.1)
  - P cases
- 7.7.7. Particular features on the French network
  - 7.7.7.1. Platform height (4.2.9.2)
    - P cases
- 7.7.8. Particular features on the German network
  - 7.7.8.1. Platform height (4.2.9.2)
    - P cases
- 7.7.9. Particular features on the Hellenic network
  - 7.7.9.1. Platform height (4.2.9.2)
    - P cases
- 7.7.10. Particular features on the Italian network
  - 7.7.10.1 Platform offset (4.2.9.3)
    - P cases
  - 7.7.10.2 Equivalent conicity (4.2.4.5)
    - P cases
  - 7.7.10.3 Equivalent conicity in service (4.2.11.2)
    - P cases
- 7.7.11. Particular features on the Latvian network
  - 7.7.11.1 Resistance of new bridges to traffic loads — vertical loads...
    - P cases
- 7.7.12. Particular features on the Polish network
  - 7.7.12.1 TSI Categories of line (4.2.1)
    - P cases
  - 7.7.12.2 Distance between track centres (4.2.3.2)
    - P cases
  - 7.7.12.3 Minimum radius of horizontal curve (4.2.3.4)
    - P cases
  - 7.7.12.4 Minimum radius of vertical curve (4.2.3.5)
    - P cases
  - 7.7.12.5 Cant deficiency (4.2.4.3)
    - P cases
  - 7.7.12.6 Abrupt change of cant deficiency (4.2.4.4)
    - P cases
  - 7.7.12.7 The immediate action limit for track twist (4.2.8.3)
    - P cases
  - 7.7.12.8 The immediate action limit of track gauge as an isolated...
    - P cases
  - 7.7.12.9 The immediate action limits for switches and crossings (4.2.8.6)
    - P cases
  - 7.7.12.10 Platform height (4.2.9.2)
    - P cases
  - 7.7.12.11 Equivalent conicity in service (4.2.11.2)
    - T cases
  - 7.7.12.12 Track sleepers (5.3.3)

- P cases
- 7.7.13. Particular features on the Portuguese network
  - 7.7.13.1 Structure gauge (4.2.3.1)
    - P cases
  - 7.7.13.2 Distance between track centres (4.2.3.2)
    - P cases
  - 7.7.13.3 The immediate action limit of track gauge as an isolated...
    - P cases
  - 7.7.13.4 The immediate action limit for switches and crossings (4.2.8.6)
    - P cases
  - 7.7.13.5 Platform height (4.2.9.2)
  - 7.7.13.6 Platform offset (4.2.9.3)
    - P cases
  - 7.7.13.7 Assessment of structure gauge (6.2.4.1)
    - P cases
  - 7.7.13.8 Assessment of maximum pressure variations in tunnels (6.2.4.12)
    - P cases
- 7.7.14. Particular features on the Ireland network
  - 7.7.14.1 Structure gauge (4.2.3.1)
    - P cases
  - 7.7.14.2 Distance between track centres (4.2.3.2)
    - P cases
  - 7.7.14.3 Assessment of structure gauge (6.2.4.1)
    - P cases
- 7.7.15. Particular features on the Spanish network
  - 7.7.15.1 Structure gauge (4.2.3.1)
    - P cases
  - 7.7.15.2 Distance between track centres (4.2.3.2)
    - P cases
  - 7.7.15.3 Design track twist due to rail traffic actions (4.2.7.1.6)
    - P cases
  - 7.7.15.4 The immediate action limit of track gauge as an isolated...
    - P cases
  - 7.7.15.5 The immediate action limits for switches and crossings (4.2.8.6)
    - P cases
  - 7.7.15.6 Platform height (4.2.9.2)
    - P cases
  - 7.7.15.7 Platform offset (4.2.9.3)
    - P cases
  - 7.7.15.8 Assessment of structure gauge (6.2.4.1)
    - P cases
  - 7.7.15.9 Assessment of maximum pressure variations in tunnels (6.2.4.12)
    - P cases
- 7.7.16. Particular features on the Swedish network
  - 7.7.16.1 General
    - P cases
  - 7.7.16.2 Platform offset (4.2.9.3)
    - P cases
- 7.7.17. Particular features on the UK network for Great Britain
  - 7.7.17.1 TSI categories of line (4.2.1)

**Changes to legislation:** There are currently no known outstanding effects for the Commission Regulation (EU) No 1299/2014. (See end of Document for details)

---

- P cases
- 7.7.17.2 Structure gauge (4.2.3.1)
  - P cases
- 7.7.17.3 Distance between track centres (4.2.3.2)
  - P cases
- 7.7.17.3 Equivalent conicity (4.2.4.5)
  - P cases
- 7.7.17.4 Maximum unguided length of fixed obtuse crossings (4.2.5.3)
  - P cases
- 7.7.17.5 The immediate action limits for switches and crossings (4.2.8.6)
  - P cases
- 7.7.17.6 Platform height (4.2.9.2)
  - P cases
- 7.7.17.7 Platform offset (4.2.9.3)
  - P cases
- 7.7.17.8 Equivalent conicity in service (4.2.11.2)
  - P cases
- 7.7.17.9 Assessment of structure gauge (6.2.4.1)
  - P cases
- 7.7.17.10 Assessment of distance between track centres (6.2.4.2)
  - P cases
- 7.7.17.11 Assessment of platform offset (6.2.4.11)
  - P cases
- 7.7.18. Particular features on the UK network for Northern Ireland
  - 7.7.18.1 Structure gauge (4.2.3.1)
    - P cases
  - 7.7.18.2 Distance between track centres (4.2.3.2)
    - P cases
  - 7.7.18.3 Assessment of structure gauge (6.2.4.1)
    - P cases
- 7.7.19. Particular features on the Slovak network
  - 7.7.19.1 TSI categories of line (4.2.1)
    - P cases
  - 7.7.19.2 Minimum radius of horizontal curve (4.2.3.4)
    - P cases
  - 7.7.19.3 Minimum radius of vertical curve (4.2.3.5)
    - P cases
  - 7.7.19.4 Cant deficiency (4.2.4.3)
    - P cases
  - 7.7.19.5 The immediate action limit for track twist (4.2.8.3)
    - P cases
  - 7.7.19.6 The immediate action limit of track gauge as an isolated...
    - P cases
  - 7.7.19.7 The immediate action limit for cant (4.2.8.5)
    - P cases
  - 7.7.19.8 The immediate action limits for switches and crossings (4.2.8.6)
    - P cases
  - 7.7.19.9 Platform height (4.2.9.2)
    - P cases
  - 7.7.19.10 Equivalent conicity in service (4.2.11.2)
    - T cases



### 7.7.19.1 Track sleepers (5.3.3) P cases

#### Appendix A

##### Assessment of interoperability constituents

The characteristics of the interoperability constituents to be assessed by...

There are no particular assessment procedures required for interoperability constituents...

#### Appendix B

##### Assessment of the infrastructure subsystem

The characteristics of the subsystem to be assessed in the...

Where no assessment by a notified body is required, this...

Definition of assessment phases:

(1) 'Design review' it includes checking of correctness of values/parameters...

Column 3 gives references to point 6.2.4 'Particular assessment procedures...

#### Appendix C

##### Technical characteristics of track design and switches and crossings design

#### Appendix C.1

##### Technical characteristics of track design

Track design shall be at least defined by the technical...

Rail Profile(s) & grades Continuous welded rail or length of...

#### Appendix C.2

##### Technical characteristics of switches and crossings design

Switches and crossings design shall be at least defined by...

Rail Profile(s) & grades (switch rail, stock rail) Continuous welded...

#### Appendix D

##### Conditions of use of track design and switches and crossings design

## Appendix D.1

### Conditions of use of track design

Conditions of use of track design are defined to be...  
Maximum axle load [t] Maximum line speed [km/h] Minimum horizontal...

## Appendix D.2

### Conditions of use of switches and crossings design

Conditions of use of switches and crossings design are defined...  
Maximum axle load [t] Maximum line speed [km/h] on through...

## Appendix E

### Capability requirements for structures according to traffic code

The minimum capability requirements for structures are defined in Table...  
EN line category is a function of axle load and...  
Notes:

## Appendix F

### Capability requirements for structures according to traffic code in the United Kingdom of Great Britain and Northern Ireland

The minimum capability requirements for structures are defined in Table...  
The Route Availability number is a function of axle load...  
Notes:

## Appendix G

### Speed conversion to miles per hour for Ireland and the United Kingdom of Great Britain and Northern Ireland

## Appendix H

### Structure gauge for the 1 520 mm track gauge system

Figure 3 Structure gauge S for the 1 520 mm track...  
Clarifications for Figure 3:  
All horizontal dimensions shall be measured from the centre of...  
Application of specific parts of the contour:  
1,I — 1, I — contour of structure gauge for...  
For nominal track gauge of 1 520 mm  $a_1 = 670$  mm and...  
For nominal track gauge of 1 524 mm  $a_1 = 672$  mm and...  
Figure 4 Reference profile of the lower parts on tracks...

Clarification for Figure 4:

The distance of 760 mm is for track gauge 1 520 mm,...

Figure 5 Reference profile of the lower parts on marshalling...

### Appendix I

Reverse curves with radii in the range from 150 m up to 300 m

The values in Table 43 are based on a reference...

The values in Table 44 are based on a reference...

Due to local settings it can be necessary to require...

### Appendix J

Safety assurance over fixed obtuse crossings

(J.1) The fixed obtuse crossings should be designed in order not...

(J.2) If one or more of the above requirements is not...

(J.3) The design shall be checked for wheels with diameter between...

(J.4) The following graphs allow simple verification of unguided length for...

(J.5) For track gauge systems other than 1 435 mm, specific calculations...  
Figure 8 Minimum wheel diameter against crossing angle for 450 m...  
1 Minimum wheel diameter [mm] 2 N for crossing angle...  
Figure 9 Minimum wheel diameter against crossing angle for straight...  
1 Minimum wheel diameter [mm] 2 N for crossing angle...

### Appendix K

Basis of minimum requirements for structures for passenger coaches and multiple units

The following mass definitions for passenger carriages and multiple units...

The EN line categories in Appendix E are based upon...

Where checks on the dynamic response of rail bridges are...

.....

### Appendix L

Definition of EN line category a12 for traffic code P6

.....

.....

.....

.....

.....

Figure 1 Reference wagon of EN line category a12

Figure 1 Load model of EN line category a12

#### Appendix M

##### Specific case on the Estonian network

- (1) Locomotive
- (2) Distributed load: 140 kN/m
- (3) Wagon

#### Appendix N

##### Specific cases of the Hellenic network

Deleted

#### Appendix O

##### Specific case on the Ireland and United Kingdom of Northern Ireland networks

Rules and drawings related to gauges IRL1, IRL2 and IRL3...

#### Appendix P

Structure gauge for the lower parts for the 1 668 mm track gauge on the Spanish network

Structures gauges shall be obtained on the basis of the...  
Calculations of structure gauge shall be done using the kinematic...

- P.1. REFERENCE PROFILES
  - P.1.1. Kinematic reference profile GEI1
  - P.1.2. Kinematic reference profile GEI2
- P.2. ASSOCIATED RULES
- P.3. VERTICAL LOWERING

#### Appendix Q

##### National technical rules for UK-GB Specific Cases

The National Technical Rules for UK-GB specific cases referred to...

## Appendix R

### List of open points

- (1) Immediate action limits for isolated defects in alignment for speeds...
- (2) Immediate action limits for isolated defects in longitudinal level for...
- (3) The minimum allowed value of distance between track centres for...
- (4) EN Line Category — Associated Speed [km/h] for Traffic codes...
- (5) Route Availability Number — Associated Speed [miles/h] for Traffic codes...
- (6) Rules and drawings related to gauges IRL1, IRL2 and IRL3...
- (7) The requirements for mitigating the risk for ballast pick up...

## Appendix S

### Glossary

#### Figure 14 Geometry of switches and crossings

- (1) 1 Free wheel passage in switches (2) Fixed nose...

## Appendix T

### List of referenced standards

**Changes to legislation:**

There are currently no known outstanding effects for the Commission Regulation (EU) No 1299/2014.