

Commission Regulation (EU) 2016/1199 of 22 July 2016 amending Regulation (EU) No 965/2012 as regards operational approval of performance-based navigation, certification and oversight of data services providers and helicopter offshore operations, and correcting that Regulation

COMMISSION REGULATION (EU) 2016/1199

of 22 July 2016

amending Regulation (EU) No 965/2012 as regards operational approval of performance-based navigation, certification and oversight of data services providers and helicopter offshore operations, and correcting that Regulation

THE EUROPEAN COMMISSION,

Having regard to the Treaty on the Functioning of the European Union,

Having regard to Regulation (EC) No 216/2008 of the European Parliament and of the Council of 20 February 2008 on common rules in the field of civil aviation and establishing a European Aviation Safety Agency, and repealing Council Directive 91/670/EEC, Regulation (EC) No 1592/2002 and Directive 2004/36/EC⁽¹⁾, and in particular Article 8(5) thereof,

Whereas:

- (1) Commission Regulation (EU) No 965/2012⁽²⁾ establishes conditions for the safe operation of aircraft.
- (2) Incorrect aeronautical data or information being fed into airborne aircraft systems can pose significant risks to flight safety. It should therefore be ensured that data services providers process aeronautical data and information in a way that guarantees their quality and meets the requirements set by aircraft manufacturers for the airspace end-users' intended use.
- (3) Regulation (EU) No 965/2012 requires a specific approval for all performance-based navigation ('PBN') operations, except for some basic navigational methods. Cases requiring specific approval should be significantly reduced in order to alleviate the unnecessary economic and administrative burden on the general aviation operators, taking into account the experience and maturity already reached in approach operations utilising the global navigation satellite system ('GNSS'), and in order to ensure consistency with the latest international safety standards.
- (4) In order to facilitate compliance by the operators with the rules related to transport of dangerous goods as well as those related to upper torso restraint systems on flight crew seats and on passenger seats of certain small aeroplanes, and thus to improve safety, it is necessary to adapt those rules to the type of operation and to the complexity of aircraft used.
- (5) Pursuant to Regulation (EU) No 965/2012, certain small non-commercial operators must establish a management system within their organisation because they operate complex motor-powered aircraft. However, in certain cases, such as in the non-

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

commercial operation of lighter twin-turboprop aeroplanes, those operators may have difficulties in implementing the management system requirements contained in Annex III to that Regulation. As the compliance effort that is required of such operators is disproportionate to the benefits that implementing those requirements bring to the safety of their operations, those operators should be excluded from the scope of Annex VI to Regulation (EU) No 965/2012 and, instead, be allowed to comply with the requirements set out in its Annex VII. For consistency, training organisations which conduct flight training on the same lighter twin-turboprop aeroplanes should also be allowed to comply with the requirements set out in its Annex VII.

- (6) Annex VII to Regulation (EU) No 965/2012 requires carrying and using oxygen when flying above a fixed pressure altitude. Based on the principle of risk differentiation, whereby the level of regulatory protection afforded to stakeholders depends on their ability to assess and control risks, the need of oxygen in non-pressurised aircraft engaged in non-commercial operations should be determined by the pilot of such aircraft, taking into account certain objective factors.
- (7) Helicopter offshore operations ('HOFO') pose certain specific safety risks which are not adequately addressed by Regulation (EU) No 965/2012 as it stands. Some Member States therefore adopt additional requirements, including the mandatory use of new technologies, to mitigate such risks and maintain safety levels. However, in order to ensure that the safety objectives of Regulation (EC) No 216/2008 are achieved and in order to guarantee a level playing field for air operators, common safety measures should be established at Union level, taking into account the experience at national level as well as the developments in the sector of helicopter offshore operations.
- (8) Certain editorial errors leading to implementation difficulties have also been identified in Regulation (EU) No 965/2012.
- (9) Regulation (EU) No 965/2012 should therefore be amended and corrected accordingly.
- (10) It is necessary to provide sufficient time for the operators concerned and the competent authorities of the Member States to adjust to the new rules on aeronautical data and information and on helicopter offshore operations provided for in this Regulation.
- (11) The Commission intends to revise the rules related to balloons and sailplanes set out in Regulation (EU) No 965/2012, in the context of the initiative for simpler, lighter and better legislation on civil aviation. The preparatory work for that revision is currently ongoing. The date of application of those rules should therefore now be adapted so as to ensure that that revision can be completed and those rules can be amended where necessary before they start to apply.
- (12) In the interest of legal clarity and harmonised implementation of the common requirements throughout the Union there should be fixed dates of application of those requirements, either immediately upon entry into force or at a future time. The transitional measures and tasks to be duly implemented by all Member States should be included in the legal act, so as to avoid legal concerns and uncertainty. The possibility to use opt-outs as provided for in some Commission implementing regulations in the field of aviation safety should be restricted to duly justified cases, where it is absolutely

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

necessary, and a predictable and transparent system should be employed, instead. It is therefore imperative that Regulation (EU) No 965/2012 is amended to account for these considerations.

- (13) The measures provided for in this Regulation are based on the opinions⁽³⁾ issued by the European Aviation Safety Agency in accordance with Article 17(2)(b) and Article 19(1) of Regulation (EC) No 216/2008.
- (14) The measures provided for in this Regulation are in accordance with the opinion of the Committee established by Article 65 of Regulation (EC) No 216/2008,

HAS ADOPTED THIS REGULATION:

Article 1 **U.K.**

Regulation (EU) No 965/2012 is amended as follows:

- (1) Article 5(2) is amended as follows:
- (a) the word ‘and’ at the end of point (e) is deleted;
 - (b) the following point (g) is added:
 - (g) helicopters used for offshore operations (HOFO).
- (2) Article 6 is amended as follows:
- (a) paragraph 4 is replaced by the following:

4. Notwithstanding Article 5, Member States may, until 30 June 2018, continue to require a specific approval and additional requirements regarding operational procedures, equipment, crew qualification and training for CAT helicopter offshore operations in accordance with their national law. Member States shall notify the Commission and the Agency of the additional requirements being applied to such specific approvals. Those requirements shall not be less restrictive than those of Annexes III and IV.;
 - (b) paragraph 7 is deleted;
 - (c) the following paragraphs 8 and 9 are added:

8. By way of derogation from the first sentence of Article 5(3), operators of complex motor-powered aeroplanes with a maximum certificated take-off mass (MCTOM) at or below 5 700 kg, equipped with turboprop engines, involved in non-commercial operations, shall operate those aircraft only in accordance with Annex VII.

9. By way of derogation from Article 5(5)(a), training organisations shall, when conducting flight training on complex motor-powered aeroplanes with a maximum certificated take-off mass (MCTOM) at or below 5 700 kg, equipped with turboprop engines, operate those aircraft in accordance with Annex VII.
- (3) Article 10 is replaced by the following:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

Article 10

Entry into force

1 This Regulation shall enter into force on the third day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 28 October 2012, subject to paragraphs 2, 3, 4, 5 and 6 below.

2 Annexes II and VII shall apply to non-commercial operations with balloons and sailplanes from 25 August 2013, except for Member States that have decided not to apply all or part of them in accordance with the provisions in force at the time of that decision and to the extent they have decided to do so. Those Member States shall apply Annexes II and VII from 8 April 2018 to non-commercial operations with balloons and from 8 April 2019 to non-commercial operations with sailplanes or from the dates indicated in their decision, as the case may be.

3 Annexes II, III, VII and VIII shall apply to specialised operations with balloons and sailplanes from 1 July 2014, except for Member States that have decided not to apply all or part of them in accordance with the provisions in force at the time of that decision, and to the extent they have decided to do so. Those Member States shall apply Annexes II, III, VII and VIII from 8 April 2018 to specialised operations with balloons and from 8 April 2019 to specialised operations with sailplanes or from the dates indicated in their decision, as the case may be.

4 Annexes II, III, VII and VIII shall apply to specialised operations with aeroplanes and helicopters from 1 July 2014, except for Member States that have decided not to apply all or part of them in accordance with the provisions in force at the time of that decision and to the extent they have decided to do so. Those Member States shall apply Annexes II, III, VII and VIII to specialised operations with aeroplanes and helicopters from 21 April 2017 or from the dates indicated in their decision, as the case may be.

5 Annexes II, III and IV shall apply to:

- a CAT operations starting and ending at the same aerodrome or operating site with Performance class B aeroplanes or non-complex helicopters from 1 July 2014, except for Member States that have decided not to apply all or part of them in accordance with the provisions in force at the time of that decision and to the extent they have decided to do so. Those Member States shall apply Annexes II, III and IV to CAT operations starting and ending at the same aerodrome or operating site with Performance class B aeroplanes or non-complex helicopters from 21 April 2017 or from the dates indicated in their decision, as the case may be;
- b CAT operations with balloons and sailplanes from 1 July 2014, except for Member States that have decided not to apply all or part of them in accordance with the provisions in force at the time of that decision and to the extent they have decided to do so. Those Member States shall apply Annexes II, III and IV from 8 April 2018 to CAT operations with balloons, and from 8 April 2019 to CAT operations with sailplanes or from the dates indicated in their decision, as the case may be.

6 The following shall apply during the periods provided for in paragraphs 2, 3, 4 and 5 of this Article, as applicable:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- a The competent authorities shall, from the date of entry into force of the requirements of this Regulation, take gradual and effective measures to comply with those requirements, including by adapting their organisation and management system, training of personnel, procedures and manuals and oversight programme;
 - b Operators shall adapt their management system, training programmes, procedures and manuals to be compliant with the requirements of this Regulation, as relevant, no later than the date of application of those requirements;
 - c Until the date of application of the relevant requirements of this Regulation, Member States shall continue to issue, renew or modify certificates, authorisations and approvals in accordance with the rules in force before the entry into force of those requirements or, in the case of CAT operations starting and ending at the same aerodrome or operating site with Performance class B aeroplanes or non-complex helicopters, in accordance with:
 - Annex III to Regulation (EEC) No 3922/91 and related national exemptions in accordance with Article 8(2) of Regulation (EEC) No 3922/91, for aeroplanes; and
 - national requirements, for helicopters.
 - d) Certificates, authorisations and approvals issued by Member States before the date of application of the relevant requirements of this Regulation shall be deemed to have been issued in accordance with those requirements. However, they shall be replaced by certificates, authorisations and approvals, as appropriate, issued in accordance with this Regulation no later than six months from the date of application of the relevant requirements of this Regulation;
 - e) Operators subject to a declaration obligation in accordance with this Regulation shall submit their declarations no later than the date of application of the relevant requirements of this Regulation.
- (4) Annexes I, II, IV, V, VI, VII and VIII are amended in accordance with the Annex to this Regulation.

Article 2 **U.K.**

Regulation (EU) No 965/2012 is corrected as follows:

- (1) In Annex IV (Part-CAT), CAT.POL.A.240, point (b)(4) is replaced by the following:
 - (4) the flight crew has obtained adequate knowledge of the route to be flown and of the procedures to be used in accordance with Subpart FC of Part-ORO.;
- (2) In Annex VII (Part-NCO), the text of NCO.GEN.103 is replaced by the following:

Introductory flights referred to in Article 6(4a)(c) of this Regulation, when conducted in accordance with this Annex, shall:

 - (a) start and end at the same aerodrome or operating site, except for balloons and sailplanes;
 - (b) be operated under VFR by day;
 - (c) be overseen by a nominated person responsible for their safety; and
 - (d) comply with any other conditions stipulated by the competent authority..

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

Article 3 **U.K.**

This Regulation shall enter into force on the twentieth day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 25 August 2016.

However,

- (a) point 1 of Article 1 and points 1(a), 1(b), 1(c), 1(d), 2(c), 3(a), 3(e), 3(g), 3(m), 3(n), 3(o), 4(c), 5(d), 5(j), 5(k), 5(l), 7(d), 7(k) and 7(l) of the Annex shall apply from 1 July 2018;
- (b) points 3(l), 3(q), 5(i), 5(n), 6(k), 6(n), 7(j) and 7(n) of the Annex shall apply from 1 January 2019.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 22 July 2016.

For the Commission

The President

Jean-Claude JUNCKER

ANNEX **U.K.**

Annexes I, II, IV, V, VI, VII and VIII to Regulation (EU) No 965/2012 are amended as follows:

- (1) In Annex I (Definitions):
- (a) point (69) is replaced by the following:
 - (69) ‘hostile environment’ means:
 - (a) an area in which:
 - (i) a safe forced landing cannot be accomplished because the surface is inadequate; or
 - (ii) the helicopter occupants cannot be adequately protected from the elements; or
 - (iii) search and rescue response/capability are not provided consistent with anticipated exposure; or
 - (iv) there is an unacceptable risk of endangering persons or property on the ground;
 - (b) in any case, the following areas:
 - (i) for overwater operations, the open sea area north of 45 N and south of 45 S, unless any part is designated as non-hostile by the responsible authority of the State in which the operations take place; and
 - (ii) those parts of a congested area without adequate safe forced landing areas.;
 - (b) point (86) is replaced by the following:
 - (86) ‘offshore operation’ means a helicopter operation that has a substantial proportion of any flight conducted over open sea areas to or from an offshore location.;
 - (c) the following point (86a) is inserted:
 - (86a) ‘offshore location’ means a facility intended to be used for helicopter operations on a fixed or floating offshore structure or a vessel.;
 - (d) the following point (86b) is inserted:
 - (86b) ‘open sea area’ means the area of water to seaward of the coastline.;
 - (e) the following point (103a) is inserted:
 - (103a) ‘required navigation performance (RNP) specification’ means a navigation specification for PBN operations which includes a requirement for on-board navigation performance monitoring and alerting.;
- (2) In Annex II (Part-ARO):
- (a) the following ARO.OPS.240 is added:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

ARO.OPS Specific approval of RNP AR APCH

- (a) When compliance with the requirements in SPA.PBN.105 has been demonstrated by the applicant, the competent authority shall grant a generic specific approval or a procedure-specific approval for RNP AR APCH.
- (b) In the case of a procedure-specific approval, the competent authority shall:
 - (1) list the approved instrument approach procedures at specific aerodromes in the PBN approval;
 - (2) establish coordination with the competent authorities for these aerodromes, if appropriate; and
 - (3) take into account possible credits stemming from RNP AR APCH specific approvals already issued to the applicant.;
- (b) Appendix II is replaced by the following:

Appendix
II

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

Helicopter offshore operations	<input type="checkbox"/>	<input type="checkbox"/>		
Cabin crew training ⁽¹⁷⁾	<input type="checkbox"/>	<input type="checkbox"/>		
Issue of CC attestation ⁽¹⁸⁾	<input type="checkbox"/>	<input type="checkbox"/>		
Continuing airworthiness	<input type="checkbox"/>	<input type="checkbox"/>	⁽¹⁹⁾	
Others ⁽²⁰⁾				

- ⁽¹⁾ Telephone and fax contact details of the competent authority, including the country code. E-mail to be provided.
- ⁽²⁾ Insertion of associated air operator certificate (AOC) number.
- ⁽³⁾ Insertion of the operator's registered name and the operator's trading name, if different. Insert 'Dba' before 'Doing business as'.
- ⁽⁴⁾ Issue date of the operations specifications (dd-mm-yyyy) and signature of the competent authority representative.
- ⁽⁵⁾ Insertion of ICAO designation of the aircraft make, model and series, or master series, if a series (e.g. Boeing-737-3K2 or Boeing-777-232).
- ⁽⁶⁾ Either the registration marks are listed in the operations specifications or in the operations manual. In the operations specifications must make a reference to the related page in the operation manual. In case not all to the aircraft model, the registration marks of the aircraft could be entered in the remark column to the related page in the operations manual.
- ⁽⁷⁾ Listing of geographical area(s) of authorised operation (by geographical coordinates or specific routes, flight paths, national or regional boundaries).
- ⁽⁸⁾ Listing of applicable special limitations (e.g. VFR only, Day only, etc.).
- ⁽⁹⁾ List in this column the most permissive criteria for each approval or the approval type (with appropriate criteria).
- ⁽¹⁰⁾ Insertion of applicable precision approach category: LTS CAT I, CAT II, OTS CAT II, CAT IIIA, CAT IIIB, minimum runway visual range (RVR) in meters and decision height (DH) in feet. One line is used per listed category.
- ⁽¹¹⁾ Insertion of approved minimum take-off RVR in metres. One line per approval may be used if different approvals are applicable.
- ⁽¹²⁾ Not Applicable (N/A) box may be checked only if the aircraft maximum ceiling is below FL290.
- ⁽¹³⁾ Extended range operations (ETOPS) currently applies only to two-engined aircraft. Therefore, the Not Applicable (N/A) box may be checked if the aircraft model has more or less than two engines.
- ⁽¹⁴⁾ The threshold distance may also be listed (in NM), as well as the engine type.
- ⁽¹⁵⁾ Performance-Based Navigation (PBN): one line is used for each complex PBN specific approval (e.g. RNP APCH, RNP AR, RNP 4, RNP 5, RNP 10, RNP 15, RNP 20, RNP 25, RNP 30, RNP 40, RNP 50, RNP 60, RNP 75, RNP 100, RNP 150, RNP 200, RNP 250, RNP 300, RNP 350, RNP 400, RNP 450, RNP 500, RNP 550, RNP 600, RNP 650, RNP 700, RNP 750, RNP 800, RNP 850, RNP 900, RNP 950, RNP 1000, RNP 1050, RNP 1100, RNP 1150, RNP 1200, RNP 1250, RNP 1300, RNP 1350, RNP 1400, RNP 1450, RNP 1500, RNP 1550, RNP 1600, RNP 1650, RNP 1700, RNP 1750, RNP 1800, RNP 1850, RNP 1900, RNP 1950, RNP 2000, RNP 2050, RNP 2100, RNP 2150, RNP 2200, RNP 2250, RNP 2300, RNP 2350, RNP 2400, RNP 2450, RNP 2500, RNP 2550, RNP 2600, RNP 2650, RNP 2700, RNP 2750, RNP 2800, RNP 2850, RNP 2900, RNP 2950, RNP 3000, RNP 3050, RNP 3100, RNP 3150, RNP 3200, RNP 3250, RNP 3300, RNP 3350, RNP 3400, RNP 3450, RNP 3500, RNP 3550, RNP 3600, RNP 3650, RNP 3700, RNP 3750, RNP 3800, RNP 3850, RNP 3900, RNP 3950, RNP 4000, RNP 4050, RNP 4100, RNP 4150, RNP 4200, RNP 4250, RNP 4300, RNP 4350, RNP 4400, RNP 4450, RNP 4500, RNP 4550, RNP 4600, RNP 4650, RNP 4700, RNP 4750, RNP 4800, RNP 4850, RNP 4900, RNP 4950, RNP 5000, RNP 5050, RNP 5100, RNP 5150, RNP 5200, RNP 5250, RNP 5300, RNP 5350, RNP 5400, RNP 5450, RNP 5500, RNP 5550, RNP 5600, RNP 5650, RNP 5700, RNP 5750, RNP 5800, RNP 5850, RNP 5900, RNP 5950, RNP 6000, RNP 6050, RNP 6100, RNP 6150, RNP 6200, RNP 6250, RNP 6300, RNP 6350, RNP 6400, RNP 6450, RNP 6500, RNP 6550, RNP 6600, RNP 6650, RNP 6700, RNP 6750, RNP 6800, RNP 6850, RNP 6900, RNP 6950, RNP 7000, RNP 7050, RNP 7100, RNP 7150, RNP 7200, RNP 7250, RNP 7300, RNP 7350, RNP 7400, RNP 7450, RNP 7500, RNP 7550, RNP 7600, RNP 7650, RNP 7700, RNP 7750, RNP 7800, RNP 7850, RNP 7900, RNP 7950, RNP 8000, RNP 8050, RNP 8100, RNP 8150, RNP 8200, RNP 8250, RNP 8300, RNP 8350, RNP 8400, RNP 8450, RNP 8500, RNP 8550, RNP 8600, RNP 8650, RNP 8700, RNP 8750, RNP 8800, RNP 8850, RNP 8900, RNP 8950, RNP 9000, RNP 9050, RNP 9100, RNP 9150, RNP 9200, RNP 9250, RNP 9300, RNP 9350, RNP 9400, RNP 9450, RNP 9500, RNP 9550, RNP 9600, RNP 9650, RNP 9700, RNP 9750, RNP 9800, RNP 9850, RNP 9900, RNP 9950, RNP 10000, RNP 10050, RNP 10100, RNP 10150, RNP 10200, RNP 10250, RNP 10300, RNP 10350, RNP 10400, RNP 10450, RNP 10500, RNP 10550, RNP 10600, RNP 10650, RNP 10700, RNP 10750, RNP 10800, RNP 10850, RNP 10900, RNP 10950, RNP 11000, RNP 11050, RNP 11100, RNP 11150, RNP 11200, RNP 11250, RNP 11300, RNP 11350, RNP 11400, RNP 11450, RNP 11500, RNP 11550, RNP 11600, RNP 11650, RNP 11700, RNP 11750, RNP 11800, RNP 11850, RNP 11900, RNP 11950, RNP 12000, RNP 12050, RNP 12100, RNP 12150, RNP 12200, RNP 12250, RNP 12300, RNP 12350, RNP 12400, RNP 12450, RNP 12500, RNP 12550, RNP 12600, RNP 12650, RNP 12700, RNP 12750, RNP 12800, RNP 12850, RNP 12900, RNP 12950, RNP 13000, RNP 13050, RNP 13100, RNP 13150, RNP 13200, RNP 13250, RNP 13300, RNP 13350, RNP 13400, RNP 13450, RNP 13500, RNP 13550, RNP 13600, RNP 13650, RNP 13700, RNP 13750, RNP 13800, RNP 13850, RNP 13900, RNP 13950, RNP 14000, RNP 14050, RNP 14100, RNP 14150, RNP 14200, RNP 14250, RNP 14300, RNP 14350, RNP 14400, RNP 14450, RNP 14500, RNP 14550, RNP 14600, RNP 14650, RNP 14700, RNP 14750, RNP 14800, RNP 14850, RNP 14900, RNP 14950, RNP 15000, RNP 15050, RNP 15100, RNP 15150, RNP 15200, RNP 15250, RNP 15300, RNP 15350, RNP 15400, RNP 15450, RNP 15500, RNP 15550, RNP 15600, RNP 15650, RNP 15700, RNP 15750, RNP 15800, RNP 15850, RNP 15900, RNP 15950, RNP 16000, RNP 16050, RNP 16100, RNP 16150, RNP 16200, RNP 16250, RNP 16300, RNP 16350, RNP 16400, RNP 16450, RNP 16500, RNP 16550, RNP 16600, RNP 16650, RNP 16700, RNP 16750, RNP 16800, RNP 16850, RNP 16900, RNP 16950, RNP 17000, RNP 17050, RNP 17100, RNP 17150, RNP 17200, RNP 17250, RNP 17300, RNP 17350, RNP 17400, RNP 17450, RNP 17500, RNP 17550, RNP 17600, RNP 17650, RNP 17700, RNP 17750, RNP 17800, RNP 17850, RNP 17900, RNP 17950, RNP 18000, RNP 18050, RNP 18100, RNP 18150, RNP 18200, RNP 18250, RNP 18300, RNP 18350, RNP 18400, RNP 18450, RNP 18500, RNP 18550, RNP 18600, RNP 18650, RNP 18700, RNP 18750, RNP 18800, RNP 18850, RNP 18900, RNP 18950, RNP 19000, RNP 19050, RNP 19100, RNP 19150, RNP 19200, RNP 19250, RNP 19300, RNP 19350, RNP 19400, RNP 19450, RNP 19500, RNP 19550, RNP 19600, RNP 19650, RNP 19700, RNP 19750, RNP 19800, RNP 19850, RNP 19900, RNP 19950, RNP 20000, RNP 20050, RNP 20100, RNP 20150, RNP 20200, RNP 20250, RNP 20300, RNP 20350, RNP 20400, RNP 20450, RNP 20500, RNP 20550, RNP 20600, RNP 20650, RNP 20700, RNP 20750, RNP 20800, RNP 20850, RNP 20900, RNP 20950, RNP 21000, RNP 21050, RNP 21100, RNP 21150, RNP 21200, RNP 21250, RNP 21300, RNP 21350, RNP 21400, RNP 21450, RNP 21500, RNP 21550, RNP 21600, RNP 21650, RNP 21700, RNP 21750, RNP 21800, RNP 21850, RNP 21900, RNP 21950, RNP 22000, RNP 22050, RNP 22100, RNP 22150, RNP 22200, RNP 22250, RNP 22300, RNP 22350, RNP 22400, RNP 22450, RNP 22500, RNP 22550, RNP 22600, RNP 22650, RNP 22700, RNP 22750, RNP 22800, RNP 22850, RNP 22900, RNP 22950, RNP 23000, RNP 23050, RNP 23100, RNP 23150, RNP 23200, RNP 23250, RNP 23300, RNP 23350, RNP 23400, RNP 23450, RNP 23500, RNP 23550, RNP 23600, RNP 23650, RNP 23700, RNP 23750, RNP 23800, RNP 23850, RNP 23900, RNP 23950, RNP 24000, RNP 24050, RNP 24100, RNP 24150, RNP 24200, RNP 24250, RNP 24300, RNP 24350, RNP 24400, RNP 24450, RNP 24500, RNP 24550, RNP 24600, RNP 24650, RNP 24700, RNP 24750, RNP 24800, RNP 24850, RNP 24900, RNP 24950, RNP 25000, RNP 25050, RNP 25100, RNP 25150, RNP 25200, RNP 25250, RNP 25300, RNP 25350, RNP 25400, RNP 25450, RNP 25500, RNP 25550, RNP 25600, RNP 25650, RNP 25700, RNP 25750, RNP 25800, RNP 25850, RNP 25900, RNP 25950, RNP 26000, RNP 26050, RNP 26100, RNP 26150, RNP 26200, RNP 26250, RNP 26300, RNP 26350, RNP 26400, RNP 26450, RNP 26500, RNP 26550, RNP 26600, RNP 26650, RNP 26700, RNP 26750, RNP 26800, RNP 26850, RNP 26900, RNP 26950, RNP 27000, RNP 27050, RNP 27100, RNP 27150, RNP 27200, RNP 27250, RNP 27300, RNP 27350, RNP 27400, RNP 27450, RNP 27500, RNP 27550, RNP 27600, RNP 27650, RNP 27700, RNP 27750, RNP 27800, RNP 27850, RNP 27900, RNP 27950, RNP 28000, RNP 28050, RNP 28100, RNP 28150, RNP 28200, RNP 28250, RNP 28300, RNP 28350, RNP 28400, RNP 28450, RNP 28500, RNP 28550, RNP 28600, RNP 28650, RNP 28700, RNP 28750, RNP 28800, RNP 28850, RNP 28900, RNP 28950, RNP 29000, RNP 29050, RNP 29100, RNP 29150, RNP 29200, RNP 29250, RNP 29300, RNP 29350, RNP 29400, RNP 29450, RNP 29500, RNP 29550, RNP 29600, RNP 29650, RNP 29700, RNP 29750, RNP 29800, RNP 29850, RNP 29900, RNP 29950, RNP 30000, RNP 30050, RNP 30100, RNP 30150, RNP 30200, RNP 30250, RNP 30300, RNP 30350, RNP 30400, RNP 30450, RNP 30500, RNP 30550, RNP 30600, RNP 30650, RNP 30700, RNP 30750, RNP 30800, RNP 30850, RNP 30900, RNP 30950, RNP 31000, RNP 31050, RNP 31100, RNP 31150, RNP 31200, RNP 31250, RNP 31300, RNP 31350, RNP 31400, RNP 31450, RNP 31500, RNP 31550, RNP 31600, RNP 31650, RNP 31700, RNP 31750, RNP 31800, RNP 31850, RNP 31900, RNP 31950, RNP 32000, RNP 32050, RNP 32100, RNP 32150, RNP 32200, RNP 32250, RNP 32300, RNP 32350, RNP 32400, RNP 32450, RNP 32500, RNP 32550, RNP 32600, RNP 32650, RNP 32700, RNP 32750, RNP 32800, RNP 32850, RNP 32900, RNP 32950, RNP 33000, RNP 33050, RNP 33100, RNP 33150, RNP 33200, RNP 33250, RNP 33300, RNP 33350, RNP 33400, RNP 33450, RNP 33500, RNP 33550, RNP 33600, RNP 33650, RNP 33700, RNP 33750, RNP 33800, RNP 33850, RNP 33900, RNP 33950, RNP 34000, RNP 34050, RNP 34100, RNP 34150, RNP 34200, RNP 34250, RNP 34300, RNP 34350, RNP 34400, RNP 34450, RNP 34500, RNP 34550, RNP 34600, RNP 34650, RNP 34700, RNP 34750, RNP 34800, RNP 34850, RNP 34900, RNP 34950, RNP 35000, RNP 35050, RNP 35100, RNP 35150, RNP 35200, RNP 35250, RNP 35300, RNP 35350, RNP 35400, RNP 35450, RNP 35500, RNP 35550, RNP 35600, RNP 35650, RNP 35700, RNP 35750, RNP 35800, RNP 35850, RNP 35900, RNP 35950, RNP 36000, RNP 36050, RNP 36100, RNP 36150, RNP 36200, RNP 36250, RNP 36300, RNP 36350, RNP 36400, RNP 36450, RNP 36500, RNP 36550, RNP 36600, RNP 36650, RNP 36700, RNP 36750, RNP 36800, RNP 36850, RNP 36900, RNP 36950, RNP 37000, RNP 37050, RNP 37100, RNP 37150, RNP 37200, RNP 37250, RNP 37300, RNP 37350, RNP 37400, RNP 37450, RNP 37500, RNP 37550, RNP 37600, RNP 37650, RNP 37700, RNP 37750, RNP 37800, RNP 37850, RNP 37900, RNP 37950, RNP 38000, RNP 38050, RNP 38100, RNP 38150, RNP 38200, RNP 38250, RNP 38300, RNP 38350, RNP 38400, RNP 38450, RNP 38500, RNP 38550, RNP 38600, RNP 38650, RNP 38700, RNP 38750, RNP 38800, RNP 38850, RNP 38900, RNP 38950, RNP 39000, RNP 39050, RNP 39100, RNP 39150, RNP 39200, RNP 39250, RNP 39300, RNP 39350, RNP 39400, RNP 39450, RNP 39500, RNP 39550, RNP 39600, RNP 39650, RNP 39700, RNP 39750, RNP 39800, RNP 39850, RNP 39900, RNP 39950, RNP 40000, RNP 40050, RNP 40100, RNP 40150, RNP 40200, RNP 40250, RNP 40300, RNP 40350, RNP 40400, RNP 40450, RNP 40500, RNP 40550, RNP 40600, RNP 40650, RNP 40700, RNP 40750, RNP 40800, RNP 40850, RNP 40900, RNP 40950, RNP 41000, RNP 41050, RNP 41100, RNP 41150, RNP 41200, RNP 41250, RNP 41300, RNP 41350, RNP 41400, RNP 41450, RNP 41500, RNP 41550, RNP 41600, RNP 41650, RNP 41700, RNP 41750, RNP 41800, RNP 41850, RNP 41900, RNP 41950, RNP 42000, RNP 42050, RNP 42100, RNP 42150, RNP 42200, RNP 42250, RNP 42300, RNP 42350, RNP 42400, RNP 42450, RNP 42500, RNP 42550, RNP 42600, RNP 42650, RNP 42700, RNP 42750, RNP 42800, RNP 42850, RNP 42900, RNP 42950, RNP 43000, RNP 43050, RNP 43100, RNP 43150, RNP 43200, RNP 43250, RNP 43300, RNP 43350, RNP 43400, RNP 43450, RNP 43500, RNP 43550, RNP 43600, RNP 43650, RNP 43700, RNP 43750, RNP 43800, RNP 43850, RNP 43900, RNP 43950, RNP 44000, RNP 44050, RNP 44100, RNP 44150, RNP 44200, RNP 44250, RNP 44300, RNP 44350, RNP 44400, RNP 44450, RNP 44500, RNP 44550, RNP 44600, RNP 44650, RNP 44700, RNP 44750, RNP 44800, RNP 44850, RNP 44900, RNP 44950, RNP 45000, RNP 45050, RNP 45100, RNP 45150, RNP 45200, RNP 45250, RNP 45300, RNP 45350, RNP 45400, RNP 45450, RNP 45500, RNP 45550, RNP 45600, RNP 45650, RNP 45700, RNP 45750, RNP 45800, RNP 45850, RNP 45900, RNP 45950, RNP 46000, RNP 46050, RNP 46100, RNP 46150, RNP 46200, RNP 46250, RNP 46300, RNP 46350, RNP 46400, RNP 46450, RNP 46500, RNP 46550, RNP 46600, RNP 46650, RNP 46700, RNP 46750, RNP 46800, RNP 46850, RNP 46900, RNP 46950, RNP 47000, RNP 47050, RNP 47100, RNP 47150, RNP 47200, RNP 47250, RNP 47300, RNP 47350, RNP 47400, RNP 47450, RNP 47500, RNP 47550, RNP 47600, RNP 47650, RNP 47700, RNP 47750, RNP 47800, RNP 47850, RNP 47900, RNP 47950, RNP 48000, RNP 48050, RNP 48100, RNP 48150, RNP 48200, RNP 48250, RNP 48300, RNP 48350, RNP 48400, RNP 48450, RNP 48500, RNP 48550, RNP 48600, RNP 48650, RNP 48700, RNP 48750, RNP 48800, RNP 48850, RNP 48900, RNP 48950, RNP 49000, RNP 49050, RNP 49100, RNP 49150, RNP 49200, RNP 49250, RNP 49300, RNP 49350, RNP 49400, RNP 49450, RNP 49500, RNP 49550, RNP 49600, RNP 49650, RNP 49700, RNP 49750, RNP 49800, RNP 49850, RNP 49900, RNP 49950, RNP 50000, RNP 50050, RNP 50100, RNP 50150, RNP 50200, RNP 50250, RNP 50300, RNP 50350, RNP 50400, RNP 50450, RNP 50500, RNP 50550, RNP 50600, RNP 50650, RNP 50700, RNP 50750, RNP 50800, RNP 50850, RNP 50900, RNP 50950, RNP 51000, RNP 51050, RNP 51100, RNP 51150, RNP 51200, RNP 51250, RNP 51300, RNP 51350, RNP 51400, RNP 51450, RNP 51500, RNP 51550, RNP 51600, RNP 51650, RNP 51700, RNP 51750, RNP 51800, RNP 51850, RNP 51900, RNP 51950, RNP 52000, RNP 52050, RNP 52100, RNP 52150, RNP 52200, RNP 52250, RNP 52300, RNP 52350, RNP 52400, RNP 52450, RNP 52500, RNP 52550, RNP 52600, RNP 52650, RNP 52700, RNP 52750, RNP 52800, RNP 52850, RNP 52900, RNP 52950, RNP 53000, RNP 53050, RNP 53100, RNP 53150, RNP 53200, RNP 53250, RNP 53300, RNP 53350, RNP 53400, RNP 53450, RNP 53500, RNP 53550, RNP 53600, RNP 53650, RNP 53700, RNP 53750, RNP 53800, RNP 53850, RNP 53900, RNP 53950, RNP 54000, RNP 54050, RNP 54100, RNP 54150, RNP 54200, RNP 54250, RNP 54300, RNP 54350, RNP 54400, RNP 54450, RNP 54500, RNP 54550, RNP 54600, RNP 54650, RNP 54700, RNP 54750, RNP 54800, RNP 54850, RNP 54900, RNP 54950, RNP 55000, RNP 55050, RNP 55100, RNP 55150, RNP 55200, RNP 55250, RNP 55300, RNP 55350, RNP 55400, RNP 55450, RNP 55500, RNP 55550, RNP 55600, RNP 55650, RNP 55700, RNP 55750, RNP 55800, RNP 55850, RNP 55900, RNP 55950, RNP 56000, RNP 56050, RNP 56100, RNP 56150, RNP 56200, RNP 56250, RNP 56300, RNP 56350, RNP 56400, RNP 56450, RNP 56500, RNP 56550, RNP 56600, RNP 56650, RNP 56700, RNP 56750, RNP 56800, RNP 56850, RNP 56900, RNP 56950, RNP 57000, RNP 57050, RNP 57100, RNP 57150, RNP 57200, RNP 57250, RNP 57300, RNP 57350, RNP 57400, RNP 57450, RNP 57500, RNP 57550, RNP 57600, RNP 57650, RNP 57700, RNP 57750, RNP 57800, RNP 57850, RNP 57900, RNP 57950, RNP 58000, RNP 58050, RNP 58100, RNP 58150, RNP 58200, RNP 58250, RNP 58300, RNP 58350, RNP 58400, RNP 58450, RNP 58500, RNP 58550, RNP 58600, RNP 58650, RNP 58700, RNP 58750, RNP 58800, RNP 58850, RNP 58900, RNP 58950, RNP 59000, RNP 59050, RNP 59100, RNP 59150, RNP 59200, RNP 59250, RNP 59300, RNP 59350, RNP 59400, RNP 59450, RNP 59500, RNP 59550, RNP 59600, RNP 59650, RNP 59700, RNP 59750, RNP 59800, RNP 59850, RNP 59900, RNP 59950, RNP 60000, RNP 60050, RNP 60100, RNP 60150, RNP 60200, RNP 60250, RNP 60300, RNP 60350, RNP 60400, RNP 60450, RNP 60500, RNP 60550, RNP 60600, RNP 60650, RNP 60700, RNP 60750, RNP 60800, RNP 60850, RNP 60900, RNP 60950, RNP 61000, RNP 61050, RNP 61100, RNP 61150, RNP 61200, RNP 61250, RNP 61300, RNP 61350, RNP 61400, RNP 61450, RNP 61500, RNP 61550, RNP 61600, RNP 61650, RNP 61700, RNP 61750, RNP 61800, RNP 61850, RNP 61900, RNP 61950, RNP 62000, RNP 62050, RNP 62100, RNP 62150, RNP 62200, RNP 62250, RNP 62300, RNP 62350, RNP 62400, RNP 62450, RNP 62500, RNP 62550, RNP 62600, RNP 62650, RNP 62700, RNP 62750, RNP 62800, RNP 62850, RNP 62900, RNP 62950, RNP 63000, RNP

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (b) the aircraft is operated in conformance with the relevant navigation specification and limitations in the AFM or other document referred above.;
- (c) CAT.OP.MPA.135(a)(1) is replaced by the following:
 - (1) space-based facilities, ground facilities and services, including meteorological services, adequate for the planned operation are provided;;
- (d) in CAT.OP.MPA.175(b):
 - (i) point (6) is replaced by the following:
 - (6) space-based facilities, ground facilities and services that are required for the planned flight are available and adequate;
 - (ii) the word ‘and’ at the end of point (7) is deleted;
 - (iii) the following point (7a) is inserted:
 - (7a) any navigational database required for performance-based navigation is suitable and current; and;
- (e) CAT.OP.MPA.181 is replaced by the following:

CAT.OP.MPA.181 of aerodromes and operating sites — helicopters

- (a) For flights under instrument meteorological conditions (IMC), the commander shall select a take-off alternate aerodrome within one hour flying time at normal cruising speed if it would not be possible to return to the site of departure due to meteorological reasons.
- (b) For IFR flights or when flying under VFR and navigating by means other than by reference to visual landmarks, the commander shall specify at least one destination alternate aerodrome in the operational flight plan unless:
 - (1) for a flight to any other land destination, the duration of the flight and the meteorological conditions prevailing are such that, at the estimated time of arrival at the site of intended landing, an approach and landing is possible under visual meteorological conditions (VMC); or
 - (2) the site of intended landing is isolated and no alternate is available; in this case, a point of no return (PNR) shall be determined.
- (c) The operator shall select two destination alternate aerodromes when:
 - (1) the appropriate weather reports and/or forecasts for the destination aerodrome indicate that during a period commencing one hour before and ending one hour after the estimated time of arrival, the weather conditions will be below the applicable planning minima; or

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (2) no meteorological information is available for the destination aerodrome.
- (d) The operator shall specify any required alternate aerodrome(s) in the operational flight plan.;
- (f) the following CAT.OP.MPA.182 is inserted:

CAT.OP.MPA.182 on aerodromes — instrument approach operations

The operator shall ensure that sufficient means are available to navigate and land at the destination aerodrome or at any destination alternate aerodrome in the case of loss of capability for the intended approach and landing operation.;

- (g) point (b) in CAT.OP.MPA.247 is deleted;
- (h) CAT.OP.MPA.295 is replaced by the following:

CAT.OP.MPA.295 airborne collision avoidance system (ACAS)

The operator shall establish operational procedures and training programmes when ACAS is installed and serviceable so that the flight crew is appropriately trained in the avoidance of collisions and competent in the use of ACAS II equipment.;

- (i) point (a)(3) of CAT.IDE.A.205 is replaced by the following:
 - (3) a seat belt with upper torso restraint system on each passenger seat and restraining belts on each berth in the case of aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine, having an individual CofA first issued on or after 8 April 2015.;
- (j) point (b) of CAT.IDE.A.205 is replaced by the following:
 - (b) A seat belt with upper torso restraint system shall have:
 - (1) a single point release;
 - (2) on the seats for the minimum required cabin crew, two shoulder straps and a seat belt that may be used independently; and
 - (3) on flight crew seats and on any seat alongside a pilot's seat:
 - (i) two shoulder straps and a seat belt that may be used independently; or
 - (ii) a diagonal shoulder strap and a seat belt that may be used independently for the following aeroplanes:
 - (A) aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine that are compliant with the emergency landing dynamic conditions defined in the applicable certification specification;

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (B) aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine that are not compliant with the emergency landing dynamic conditions defined in the applicable certification specification and having an individual CofA first issued before 28 October 2014; and
 - (C) aeroplanes certified in accordance with CS-VLA or equivalent and CS-LSA or equivalent.;
- (k) the following point (f) is added in CAT.IDE.A.345:
- (f) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.
- (l) CAT.IDE.A.355 is replaced by the following:

CAT.IDE.A.355 Management of aeronautical databases

- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
 - (b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to all aircraft that require them.
 - (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the operator shall inform flight crew and other personnel concerned, and shall ensure that the affected data is not used.;
- (m) point (b) in CAT.IDE.H.280 is deleted;
- (n) CAT.IDE.H.295 is replaced by the following:

CAT.IDE.H.295 survival suits

Each crew member shall wear a survival suit when operating in performance class 3 on a flight over water beyond autorotational distance or safe forced landing distance from land, when the weather report or forecasts available to the commander indicate that the sea temperature will be less than plus 10 °C during the flight.;

- (o) CAT.IDE.H.310 is deleted;
- (p) the following point (e) is added in CAT.IDE.H.345:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

(e) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.;

(q) the following CAT.IDE.H.355 is added:

CAT.IDE.H.355 Management of aeronautical databases

(a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.

(b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to all aircraft that require them.

(c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the operator shall inform flight crew and other personnel concerned, and shall ensure that the affected data is not used.;

(4) In Annex V (Part-SPA):

(a) SPA.PBN.100 PBN is replaced by the following:

SPA.PBN.100 operations

(a) An approval is required for each of the following PBN specifications:

- (1) RNP AR APCH; and
- (2) RNP 0.3 for helicopter operation.

(b) An approval for RNP AR APCH operations shall allow operations on public instrument approach procedures which meet the applicable ICAO procedure design criteria.

(c) A procedure-specific approval for RNP AR APCH or RNP 0.3 shall be required for private instrument approach procedures or any public instrument approach procedure that does not meet the applicable ICAO procedure design criteria, or where required by the Aeronautical Information Publication (AIP) or the competent authority.;

(b) SPA.PBN.105 PBN is replaced by the following:

SPA.PBN.105 operational approval

To obtain a PBN specific approval from the competent authority, the operator shall provide evidence that:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (a) the relevant airworthiness approval, suitable for the intended PBN operation, is stated in the AFM or other document that has been approved by the certifying authority as part of an airworthiness assessment or is based on such approval;
 - (b) a training programme for the flight crew members and relevant personnel involved in the flight preparation has been established;
 - (c) a safety assessment has been carried out;
 - (d) operating procedures have been established specifying:
 - (1) the equipment to be carried, including its operating limitations and appropriate entries in the minimum equipment list (MEL);
 - (2) flight crew composition, qualification and experience;
 - (3) normal, abnormal and contingency procedures; and
 - (4) electronic navigation data management;
 - (e) a list of reportable events has been specified; and
 - (f) a management RNP monitoring programme has been established for RNP AR APCH operations, if applicable.;
- (c) the following Subpart K is added:

SUBPART ~~HELICOPTER OFFSHORE OPERATIONS~~

K

SPA.HOFO.100 Helicopter offshore operations (HOFO)

The requirements of this Subpart apply to:

- (a) a commercial air transport operator holding a valid AOC in accordance with Part-ORO;
- (b) a specialised operations operator having declared its activity in accordance with Part-ORO; or
- (c) a non-commercial operator having declared its activity in accordance with Part-ORO.

SPA.HOFO.105 Approval for helicopter offshore operations

- (a) Prior to engaging in operations under this Subpart, a specific approval by the competent authority shall have been issued to the operator.
- (b) To obtain such approval, the operator shall submit an application to the competent authority as specified in SPA.GEN.105, and shall demonstrate compliance with the requirements of this Subpart.
- (c) The operator shall, prior to performing operations from a Member State other than the Member State that issued the approval under (a), inform the competent authorities in both Member States of the intended operation.

SPA.HO.00100 Operating procedures

- (a) The operator shall, as part of its safety management process, mitigate and minimise risks and hazards specific to helicopter offshore operations. The operator shall specify in the operations manual the:
- (1) selection, composition and training of crews;
 - (2) duties and responsibilities of crew members and other involved personnel;
 - (3) required equipment and dispatch criteria; and
 - (4) operating procedures and minima, such that normal and likely abnormal operations are described and adequately mitigated.
- (b) The operator shall ensure that:
- (1) an operational flight plan is prepared prior to each flight;
 - (2) the passenger safety briefing also includes any specific information on offshore related items and is provided prior to boarding the helicopter;
 - (3) each member of the flight crew wears an approved survival suit:
 - (i) when the weather report or forecasts available to the pilot-in-command/commander indicate that the sea temperature will be less than plus 10 °C during the flight; or
 - (ii) when the estimated rescue time exceeds the calculated survival time; or
 - (iii) when the flight is planned to be conducted at night in a hostile environment;
 - (4) where established, the offshore route structure provided by the appropriate ATS is followed;
 - (5) pilots make optimum use of the automatic flight control systems (AFCS) throughout the flight;
 - (6) specific offshore approach profiles are established, including stable approach parameters and the corrective action to be taken if an approach becomes unstable;
 - (7) for multi-pilot operations, procedures are in place for a member of the flight crew to monitor the flight instruments during an offshore flight, especially during approach or departure, to ensure that a safe flight path is maintained;
 - (8) the flight crew takes immediate and appropriate action when a height alert is activated;

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (9) procedures are in place to require the emergency flotation systems to be armed, when safe to do so, for all overwater arrivals and departures; and
- (10) operations are conducted in accordance with any restriction on the routes or the areas of operation specified by the competent authority or the appropriate authority responsible for the airspace.

SPA.HOT.015 Offshore locations

The operator shall only use offshore locations that are suitable in relation to size and mass of the type of helicopter and to the operations concerned.

SPA.HOT.020 Selection of aerodromes and operating sites

- (a) *Onshore destination alternate aerodrome.* Notwithstanding CAT.OP.MPA.181, NCC.OP.152, and SPO.OP.151, the pilot-in-command/commander does not need to specify a destination alternate aerodrome in the operational flight plan when conducting flights from an offshore location to a land aerodrome if either:
 - (1) the destination aerodrome is defined as a coastal aerodrome, or
 - (2) the following criteria are met:
 - (i) the destination aerodrome has a published instrument approach;
 - (ii) the flight time is less than 3 hours; and
 - (iii) the published weather forecast valid from 1 hour prior, and 1 hour subsequent to the expected landing time specifies that:
 - (A) the cloud base is at least 700 feet above the minima associated with the instrument approach, or 1 000 feet above the destination aerodrome, whichever is the higher; and
 - (B) visibility is at least 2 500 meters.
- (b) *Offshore destination alternate helideck.* The operator may select an offshore destination alternate helideck when all of the following criteria are met:
 - (1) An offshore destination alternate helideck shall be used only after the point of no return (PNR) and when an onshore destination alternative aerodrome is not geographically available. Prior to the PNR, an onshore destination alternate aerodrome shall be used.
 - (2) One engine inoperative (OEI) landing capability shall be attainable at the offshore destination alternate helideck.

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (3) To the extent possible, helideck availability shall be guaranteed prior to PNR. The dimensions, configuration and obstacle clearance of individual helidecks or other sites shall be suitable for its use as an alternate helideck by each helicopter type intended to be used.
- (4) Weather minima shall be established taking into account the accuracy and reliability of meteorological information.
- (5) The MEL shall contain specific provisions for this type of operation.
- (6) An offshore destination alternate helideck shall only be selected if the operator has established a procedure in the operations manual.

SPA.HOR.125 ~~FC.125~~ Radar approaches (ARAs) to offshore locations — CAT operations

- (a) A commercial air transport (CAT) operator shall establish operational procedures and ensure that ARAs are only flown if:
 - (1) the helicopter is equipped with a radar that is capable of providing information regarding the obstacle environment; and
 - (2) either:
 - (i) the minimum descent height (MDH) is determined from a radio altimeter; or
 - (ii) the minimum descent altitude (MDA) plus an adequate margin is applied.
- (b) ARAs to rigs or vessels in transit shall be flown as multi-pilot operations.
- (c) The decision range shall provide adequate obstacle clearance in the missed approach from any destination for which an ARA is planned.
- (d) The approach shall only be continued beyond decision range or below the minimum descent altitude/height (MDA/H) when visual reference to the destination has been established.
- (e) For single-pilot CAT operations, appropriate increments shall be added to the MDA/H and decision range.
- (f) When an ARA is flown to a non-moving offshore location (i.e. fixed installation or moored vessel) and a reliable GPS position for the location is available in the navigation system, the GPS/area navigation system shall be used to enhance the safety of the ARA.

SPA.HOR.130 ~~FC.130~~ Meteorological conditions

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

Notwithstanding CAT.OP.MPA.247, NCC.OP.180 and SPO.OP.170, when flying between offshore locations located in class G airspace where the overwater sector is less than 10 NM, VFR flights may be conducted when the limits are at, or better than, the following:

MINIMA FOR FLYING BETWEEN OFFSHORE LOCATIONS LOCATED IN CLASS G AIRSPACE

	Day		Night	
	Height ^a	Visibility	Height ^a	Visibility
Single pilot	300 feet	3 km	500 feet	5 km
Two pilots	300 feet	2 km ^b	500 feet	5 km ^c

a The cloud base shall allow flight at the specified height to be below and clear of cloud.

b Helicopters may be operated in flight visibility down to 800 m, provided the destination or an intermediate structure is continuously visible.

c Helicopters may be operated in flight visibility down to 1 500 m, provided the destination or an intermediate structure is continuously visible.

SPA.HOPO.135 ~~OPA.135~~ Limitations for operations to offshore locations

Operation to an offshore location shall only be performed when the wind speed at the helideck is reported to be not more than 60 knots including gusts.

SPA.HOPO.140 ~~OPA.140~~ Performance requirements at offshore locations

Helicopters taking off from and landing at offshore locations shall be operated in accordance with the performance requirements of the appropriate Annex according to their type of operation.

SPA.HOPO.145 ~~OPA.145~~ Flight data monitoring (FDM) system

- (a) When conducting CAT operations with a helicopter equipped with a flight data recorder, the operator shall establish and maintain a FDM system, as part of its integrated management system, by 1 January 2019.
- (b) The FDM system shall be non-punitive and contain adequate safeguards to protect the source(s) of the data.

SPA.HOPO.150 ~~OPA.150~~ Aircraft tracking system

An operator shall establish and maintain a monitored aircraft tracking system for offshore operations in a hostile environment from the time the helicopter departs until it arrives at its final destination.

SPA.HOPO.155 ~~OPA.155~~ Vibration health monitoring (VHM) system

- (a) The following helicopters conducting CAT offshore operations in a hostile environment shall be fitted with a VHM system capable of monitoring the status of critical rotor and rotor drive systems by 1 January 2019:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (1) complex motor-powered helicopters first issued with an individual Certificate of Airworthiness (C of A) after 31 December 2016;
 - (2) all helicopters with a maximum operational passenger seating configuration (MOPSC) of more than 9 and first issued with an individual C of A before 1 January 2017;
 - (3) all helicopters first issued with an individual C of A after 31 December 2018.
- (b) The operator shall have a system to:
- (1) collect the data including system generated alerts;
 - (2) analyse and determine component serviceability; and
 - (3) respond to detected incipient failures.

SPA.HOR.Equipment requirements

- (a) The operator shall comply with the following equipment requirements:
- (1) Public Address (PA) system in helicopters used for CAT and non-commercial operations with complex motor-powered helicopters (NCC):
 - (i) Helicopters with a maximum operational passenger seat configuration (MOPSC) of more than 9 shall be equipped with a PA system.
 - (ii) Helicopters with an MOPSC of 9 or less need not be equipped with a PA system if the operator can demonstrate that the pilot's voice is understandable at all passengers' seats in flight.
 - (2) *Radio altimeter*

Helicopters shall be equipped with a radio altimeter that is capable of emitting an audio warning below a pre-set height and a visual warning at a height selectable by the pilot.
- (b) *Emergency exits*
- All emergency exits, including crew emergency exits, and any door, window or other opening that is suitable for emergency egress, and the means for opening them shall be clearly marked for the guidance of occupants using them in daylight or in the dark. Such markings shall be designed to remain visible if the helicopter is capsized or the cabin is submerged.
- (c) *Helicopter terrain awareness warning system (HTAWS)*
- Helicopters used in CAT operations with a maximum certificated take-off mass of more than 3 175 kg or a MOPSC of more than 9

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

and first issued with an individual C of A after 31 December 2018 shall be equipped with an HTAWS that meets the requirements for class A equipment as specified in an acceptable standard.

SPA.HOP.015 Additional procedures and equipment for operations in a hostile environment

(a) *Life jackets*

Approved life jackets shall be worn at all times by all persons on board unless integrated survival suits that meet the combined requirement of the survival suit and life jacket are worn.

(b) *Survival suits*

All passengers on board shall wear an approved survival suit:

- (1) when the weather report or forecasts available to the commander/pilot-in-command indicate that the sea temperature will be less than plus 10 °C during the flight; or
- (2) when the estimated rescue time exceeds the calculated survival time; or
- (3) when the flight is planned to be conducted at night.

(c) *Emergency breathing system*

All persons on board shall carry and be instructed in the use of emergency breathing systems.

(d) *Life rafts*

- (1) All life rafts carried shall be installed so as to be usable in the sea conditions in which the helicopter's ditching, flotation, and trim characteristics were evaluated for certification.
- (2) All life rafts carried shall be installed so as to facilitate their ready use in an emergency.
- (3) The number of life rafts installed:
 - (i) in the case of a helicopter carrying less than 12 persons, at least one life raft with a rated capacity of not less than the maximum number of persons on board; or
 - (ii) in the case of a helicopter carrying more than 11 persons, at least two life rafts, sufficient together to accommodate all persons capable of being carried on board and, if one is lost, the remaining life raft(s) having the overload capacity sufficient to accommodate all persons on the helicopter.
- (4) Each life raft shall contain at least one survival emergency locator transmitter (ELT(S)); and
- (5) Each life raft shall contain life-saving equipment, including means of sustaining life, as appropriate to the flight to be undertaken.

(e) *Emergency cabin lighting*

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

The helicopter shall be equipped with an emergency lighting system with an independent power supply to provide a source of general cabin illumination to facilitate the evacuation of the helicopter.

- (f) *Automatically deployable emergency locator transmitter (ELT(AD))*

The helicopter shall be equipped with an ELT(AD) that is capable of transmitting simultaneously on 121,5 MHz and 406 MHz.

- (g) *Securing of non-jettisonable doors*

Non-jettisonable doors that are designated as ditching emergency exits shall have a means of securing them in the open position so that they do not interfere with the occupants' egress in all sea conditions up to the maximum sea conditions required to be evaluated for ditching and flotation.

- (h) *Emergency exits and escape hatches*

All emergency exits, including crew emergency exits, and any door, window or other opening suitable to be used for the purpose of underwater escape shall be equipped so as to be operable in an emergency.

- (i) Notwithstanding (a), (b) and (c) above the operator may, based on a risk assessment, allow passengers, medically incapacitated at an offshore location, to partly wear or not wear life jackets, survival suits or emergency breathing systems on return flights or flights between offshore locations.

SPA.HOR.0170 requirements

- (a) The operator shall establish:

- (1) criteria for the selection of flight crew members, taking into account the flight crew members' previous experience;
- (2) a minimum experience level for a commander/pilot-in-command intending to conduct offshore operations; and
- (3) a flight crew training and checking programme that each flight crew member shall complete successfully. Such programme shall be adapted to the offshore environment and include normal, abnormal and emergency procedures, crew resource management, water entry and sea survival training.

- (b) *Recency requirements*

A pilot shall only operate a helicopter carrying passengers:

- (1) at an offshore location, as commander or pilot-in-command, or co-pilot, when he or she has carried out in the preceding 90 days at least 3 take-offs, departures, approaches and landings at an offshore location in a helicopter of the same type or a full flight simulator (FFS) representing that type; or

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (2) by night at an offshore location, as commander or pilot-in-command, or co-pilot, when he/she has carried out in the preceding 90 days at least 3 take-offs, departures, approaches and landings at night at an offshore location in a helicopter of the same type or an FFS representing that type.
- The 3 take-offs and landings shall be performed in either multi-pilot or single-pilot operations, depending on the operation to be performed.
- (c) Specific requirements for CAT:
- (1) The 90-day period presented in points (b)(1) and (2) above may be extended to 120 days as long as the pilot undertakes line flying under the supervision of a type rating instructor or examiner.
- (2) If the pilot does not comply with the requirements in (1), he/she shall complete a training flight in the helicopter or an FFS of the helicopter type to be used, which shall include at least the requirements described in (b)(1) and (2) before he or she can exercise his or her privileges.
- (5) In Annex VI (Part-NCC):
- (a) NCC.GEN.106 is amended as follows:
- (i) the word ‘and’ at the end of point (a)(4)(vii) is deleted;
- (ii) the word ‘and’ at the end of point (a)(4)(viii) is inserted;
- (iii) a new point (a)(4)(ix) is inserted as follows:
- (ix) any navigational database required for performance-based navigation is suitable and current.;
- (b) the following NCC.OP.116 is inserted:
- NCC.OP.116 Performance-based navigation — aeroplanes and helicopters**
- The operator shall ensure that, when PBN is required for the route or procedure to be flown:
- (a) the relevant PBN specification is stated in the AFM or other document that has been approved by the certifying authority as part of an airworthiness assessment or is based on such approval; and
- (b) the aircraft is operated in conformance with the relevant navigation specification and limitations in the AFM or other document mentioned above.;
- (c) point (a) of NCC.OP.145 is replaced by the following:
- (a) Before commencing a flight, the pilot-in-command shall ascertain by every reasonable means available that the space-based facilities, ground and/or water facilities, including communication facilities and navigation aids available and directly required on such flight,

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

for the safe operation of the aircraft, are adequate for the type of operation under which the flight is to be conducted.;

(d) NCC.OP.152 is amended as follows:

- (i) the word ‘and’ at the end of point (b)(2)(ii) is deleted;
- (ii) point (b)(3) is deleted;

(e) the following NCC.OP.153 is inserted:

NCC.OP.153 Destination aerodromes — instrument approach operations

The pilot-in-command shall ensure that sufficient means are available to navigate and land at the destination aerodrome or at any destination alternate aerodrome in the case of loss of capability for the intended approach and landing operation.;

(f) NCC.OP.220 is amended as follows:

NCC.OP.220 Airborne collision avoidance system (ACAS)

The operator shall establish operational procedures and training programs when ACAS is installed and serviceable so that the flight crew is appropriately trained in the avoidance of collisions and competent in the use of ACAS II equipment.;

(g) point (b) of NCC.IDE.A.180 is replaced by the following:

- (b) A seat belt with upper torso restraint system shall have:
 - (1) a single point release;
 - (2) on the seats for the minimum required cabin crew, two shoulder straps and a seat belt that may be used independently; and
 - (3) on flight crew seats and on any seat alongside a pilot's seat:
 - (i) two shoulder straps and a seat belt that may be used independently; or
 - (ii) a diagonal shoulder strap and a seat belt that may be used independently for the following aeroplanes:
 - (A) aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine that are compliant with the emergency landing dynamic conditions defined in the applicable certification specification;
 - (B) aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine that are not compliant with the emergency landing dynamic conditions defined in the applicable certification specification and having an individual CofA first issued before 25 August 2016.;

(h) the following point (d) is added in NCC.IDE.A.250:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (d) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.;
- (i) NCC.IDE.A.260 is replaced by the following:

NCC.IDE.A.260 Management of aeronautical databases

- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
- (b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to all aircraft that require them.
- (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the operator shall inform flight crew and other personnel concerned, and shall ensure that the affected data is not used.;
- (j) point (b) of NCC.IDE.H.215 is deleted;
- (k) NCC.IDE.H.226 is replaced by the following:

NCC.IDE.H.226 Survival suits

Each crew member shall wear a survival suit when so determined by the pilot-in-command based on a risk assessment taking into account the following conditions:

- (a) flights over water beyond autorotational distance or safe forced landing distance from land, where in the case of a critical engine failure, the helicopter is not able to sustain level flight; and
- (b) the weather report or forecasts available to the commander/pilot-in-command indicate that the sea temperature will be less than plus 10 °C during the flight.;
- (l) NCC.IDE.H.231 is deleted;
- (m) the following point (d) is added in NCC.IDE.H.250:
 - (d) When PBN is required the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.;
- (n) the following NCC.IDE.H.260 is added:

NCC.IDE.H.260 Management of aeronautical databases

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
- (b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to all aircraft that require them.
- (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the operator shall inform flight crew and other personnel concerned, and shall ensure that the affected data is not used.;

(6) In Annex VII (Part-NCO):

- (a) NCO.GEN.105 is amended as follows:
 - (i) the word ‘and’ at the end of point (a)(4)(v) is deleted;
 - (ii) the word ‘and’ at the end of point (a)(4)(vi) is inserted;
 - (iii) the following point (a)(4)(vii) is inserted:
 - (vii) any navigational database required for PBN is suitable and current.;
- (b) the following point (f) is added in NCO.GEN.140:
 - (f) Reasonable quantities of articles and substances that would otherwise be classified as dangerous goods and that are used to facilitate flight safety, where carriage aboard the aircraft is advisable to ensure their timely availability for operational purposes, shall be considered authorised under paragraph 1;2.2.1(a) of the Technical Instructions. This is regardless of whether or not such articles and substances are required to be carried or intended to be used in connection with a particular flight.

The packing and loading on board of the above-mentioned articles and substances shall be performed, under the responsibility of the pilot in command, in such a way as to minimise the risks posed to crew members, passengers, cargo or the aircraft during aircraft operations.;

- (c) the following NCO.OP.116 is inserted:

NCO.OP.116 Performance-based navigation — aeroplanes and helicopters

The pilot-in-command shall ensure that, when PBN is required for the route or procedure to be flown:

- (a) the relevant PBN navigation specification is stated in the AFM or other document that has been approved by the certifying authority

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

as part of an airworthiness assessment or is based on such approval;
and

- (b) the aircraft is operated in conformance with the relevant navigation specification and limitations in the AFM or other document mentioned above.;
- (d) point (a) of NCO.OP.135 is replaced by the following:
 - (a) Before commencing a flight, the pilot-in-command shall ascertain by every reasonable means available that the space-based facilities, ground and/or water facilities, including communication facilities and navigation aids available and directly required on such flight, for the safe operation of the aircraft, are adequate for the type of operation under which the flight is to be conducted.;
- (e) the following NCO.OP.142 is inserted:

NCO.OP.142 Destination aerodromes — instrument approach operations

The pilot-in-command shall ensure that sufficient means are available to navigate and land at the destination aerodrome or at any destination alternate aerodrome in the case of loss of capability for the intended approach and landing operation.;

- (f) NCO.OP.190 is replaced by the following:

NCO.OP.190 of supplemental oxygen

- (a) The pilot-in-command shall ensure that all flight crew members engaged in performing duties essential to the safe operation of an aircraft in flight use supplemental oxygen continuously whenever he/she determines that at the altitude of the intended flight the lack of oxygen might result in impairment of the faculties of crew members, and shall ensure that supplemental oxygen is available to passengers when lack of oxygen might harmfully affect passengers.
- (b) In any other case when the pilot-in-command cannot determine how the lack of oxygen might affect all occupants on board, he/she shall ensure that:
 - (1) all crew members engaged in performing duties essential to the safe operation of an aircraft in flight use supplemental oxygen for any period in excess of 30 minutes when the pressure altitude in the the passenger compartment will be between 10 000 ft and 13 000 ft; and
 - (2) all occupants use supplemental oxygen for any period that the pressure altitude in the the passenger compartment will be above 13 000 ft.;
- (g) the following NCO.OP.220 is added:

NCO.OP.220 Airborne collision avoidance system (ACAS II)

When ACAS II is used, pilot-in-command shall apply the appropriate operational procedures and be adequately trained.;

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (h) point (a)(4) of NCO.IDE.A.140 is replaced by the following:
- (4) a seat belt with upper torso restraint system on each flight crew seat, having a single point release for aeroplanes having a CofA first issued on or after 25 August 2016.;
- (i) NCO.IDE.A.155 is replaced by the following:
- NCO.IDE.A.155 Supplemental oxygen — non-pressurised aeroplanes**
- Non-pressurised aeroplanes operated when an oxygen supply is required in accordance with NCO.OP.190 shall be equipped with oxygen storage and dispensing apparatus capable of storing and dispensing the required oxygen supplies.;
- (j) the following point (d) is added in NCO.IDE.A.195:
- (d) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.;
- (k) the following NCO.IDE.A.205 is added:
- NCO.IDE.A.205 Management of aeronautical databases**
- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
- (b) The pilot-in-command shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to the aircraft that require them.
- (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the pilot-in-command shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to a flight.
- In such cases, the pilot-in-command shall not use the affected data.;
- (l) NCO.IDE.H.155 is replaced by the following:
- NCO.IDE.H.155 Supplemental oxygen — non-pressurised helicopters**
- Non-pressurised helicopters operated when an oxygen supply is required in accordance with NCO.OP.190 shall be equipped with oxygen storage and dispensing apparatus capable of storing and dispensing the required oxygen supplies.;
- (m) the following point (d) is added in NCO.IDE.H.195:
- (d) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.;
- (n) the following NCO.IDE.H.205 is added:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

NCO.IDE.H.205 Management of aeronautical databases

- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
- (b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to the aircraft that require them.
- (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the pilot-in-command shall not use the affected data.;

- (o) NCO.IDE.S.130 is replaced by the following:

NCO.IDE.S.130 Supplemental oxygen

Sailplanes operated when an oxygen supply is required in accordance with NCO.OP.190 shall be equipped with oxygen storage and dispensing apparatus capable of storing and dispensing the required oxygen supplies.;

- (p) point (f) of NCO.SPEC.110 is replaced by the following:

- (f) ensure that task specialists and crew members use supplemental oxygen continuously whenever he/she determines that at the altitude of the intended flight the lack of oxygen might result in impairment of the faculties of crew members or harmfully affect task specialists. If the pilot-in-command cannot determine how the lack of oxygen might affect the occupants on board, he/she shall ensure that task specialists and crew members use supplemental oxygen continuously whenever the cabin altitude exceeds 10 000 ft for a period of more than 30 minutes and whenever the cabin altitude exceeds 13 000 ft.;

- (7) In Annex VIII (Part-SPO):

- (a) SPO.GEN.107 is amended as follows:

- (i) the word ‘and’ at the end of point (a)(4)(v) is deleted;
- (ii) the word ‘and’ at the end of point (a)(4)(vi) is inserted;
- (iii) a new point (a)(4)(vii) is inserted as follows:
 - (vii) any navigational database required for PBN is suitable and current.;

- (b) the following SPO.OP.116 is inserted:

SPO.OP.116 Performance-based navigation — aeroplanes and helicopters

The operator shall ensure that, when PBN is required for the route or procedure to be flown:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (a) the relevant PBN specification is stated in the AFM or other document that has been approved by the certifying authority as part of an airworthiness assessment or is based on such approval; and
- (b) the aircraft is operated in conformance with the relevant navigation specification and limitations in the AFM or other document mentioned above.;
- (c) point (a) in SPO.OP.140 is replaced by the following:
 - (a) Before commencing a flight, the pilot-in-command shall ascertain by every reasonable means available that the space-based facilities, ground and/or water facilities, including communication facilities and navigation aids available and directly required on such flight, for the safe operation of the aircraft, are adequate for the type of operation under which the flight is to be conducted.;
- (d) point (b)(3) of SPO.OP.151 is deleted;
- (e) the following SPO.OP.152 is inserted:

SPO.OP.152 Destination aerodromes — instrument approach operations

The pilot-in-command shall ensure that sufficient means are available to navigate and land at the destination aerodrome or at any destination alternate aerodrome in the case of loss of capability for the intended approach and landing operation.;
- (f) point (a) of SPO.OP.205 is replaced by the following:
 - (a) The operator shall establish operational procedures and training programmes when ACAS is installed and serviceable so that the flight crew is appropriately trained in the avoidance of collisions and competent in the use of ACAS II equipment.;
- (g) points (c) and (d) in SPO.IDE.A.160 are replaced by the following:
 - (c) for other-than-complex motor-powered aeroplanes, a seat belt with upper torso restraint system on each flight crew seat, having a single point release for aeroplanes having a CofA first issued on or after 25 August 2016;
 - (d) for complex motor-powered aeroplanes, a seat belt with upper torso restraint system, incorporating a device that will automatically restrain the occupant's torso in the event of rapid deceleration:
 - (1) on each flight crew seat and on any seat alongside a pilot's seat; and
 - (2) on each observer's seat located in the flight crew compartment.;
- (h) the following point (e) is added in SPO.IDE.A.160:
 - (e) The seat belt with upper torso restraint system required by (d) shall have:

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (1) a single point release;
- (2) on flight crew seats and on any seat alongside a pilot's seat:
 - (i) two shoulder straps and a seat belt that may be used independently; or
 - (ii) a diagonal shoulder strap and a seat belt that may be used independently for the following aeroplanes:
 - (A) aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine that are compliant with the emergency landing dynamic conditions defined in the applicable certification specification;
 - (B) aeroplanes with an MCTOM of less than 5 700 kg and with an MOPSC of less than nine that are not compliant with the emergency landing dynamic conditions defined in the applicable certification specification and having an individual CofA first issued before 25 August 2016.;
- (i) the following point (d) is added in SPO.IDE.A.220:
 - (d) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.;
- (j) the following SPO.IDE.A.230 is added:

SPO.IDE.A.230 Management of aeronautical databases

- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
- (b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to all aircraft that require them.
- (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the operator shall inform flight crew and other personnel concerned, and shall ensure that the affected data is not used.;
- (k) SPO.IDE.H.198 is replaced by the following:

SPO.IDE.H.198 Helicopter suits — complex motor-powered helicopters

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

Each person on board shall wear a survival suit when so determined by the pilot-in-command based on a risk assessment taking into account the following conditions:

- (a) flights over water beyond autorotational distance or safe forced-landing distance from land, where, in the case of a critical engine failure, the helicopter is not able to sustain level flight; and
 - (b) the weather report or forecasts available to the pilot-in-command indicate that the sea temperature will be less than plus 10 °C during the flight.;
- (l) SPO.IDE.H.201 is deleted;
 - (m) the following point (d) is added in SPO.IDE.H.220:
 - (d) For PBN operations the aircraft shall meet the airworthiness certification requirements for the appropriate navigation specification.
 - (n) the following SPO.IDE.H.230 is added:

SPO.IDE.H.230 Management of aeronautical databases

- (a) Aeronautical databases used on certified aircraft system applications shall meet data quality requirements that are adequate for the intended use of the data.
- (b) The operator shall ensure the timely distribution and insertion of current and unaltered aeronautical databases to all aircraft that require them.
- (c) Notwithstanding any other occurrence reporting requirements as defined in Regulation (EU) No 376/2014, the operator shall report to the database provider instances of erroneous, inconsistent or missing data that might be reasonably expected to constitute a hazard to flight.

In such cases, the operator shall inform flight crew and other personnel concerned, and shall ensure that the affected data is not used.;

Changes to legislation: There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199. (See end of Document for details)

- (1) [OJ L 79, 19.3.2008, p. 1.](#)
- (2) Commission Regulation (EU) No 965/2012 of 5 October 2012 laying down technical requirements and administrative procedures related to air operations pursuant to Regulation (EC) No 216/2008 of the European Parliament and of the Council ([OJ L 296, 25.10.2012, p. 1](#)).
- (3) European Aviation Safety Agency Opinion No 02/2015 of 12.3.2015 for a Commission Regulation establishing technical requirements and operating procedures for the provision of data to airspace users for the purpose of air navigation; European Aviation Safety Agency Opinion No 03/2015 of 31.3.2015 for a Commission Regulation on revision of operational approval criteria for Performance Based Navigation (PBN); European Aviation Safety Agency Opinion No 04/2015 of 8.5.2015 for a Commission Regulation on specific approval for helicopter offshore operations.

Changes to legislation:

There are currently no known outstanding effects for the Commission Regulation (EU) 2016/1199.