STATUTORY INSTRUMENTS

1999 No. 1053

ENVIRONMENTAL PROTECTION

The Non-Road Mobile Machinery (Emission of Gaseous and Particulate Pollutants) Regulations 1999

Made	28th March 1999
Laid before Parliament	31st March 1999
Coming into force	26th April 1999

THE NON-ROAD MOBILE MACHINERY (EMISSION OF GASEOUS AND PARTICULATE POLLUTANTS) REGULATIONS 1999

PART I

- 1. Citation and commencement
- 2. Interpretation

PART II

- 3. Scope and Exclusions
- 4. General duty relating to placing on the market
- 5. Categories of engines
- 6. Provisions for grant of type approval certificate
- 7. Transitional provisions in respect of placing on the market
- 8. Application for type approval
- 9. Approval of engines
- 10. Amendments to approvals
- 11. Conformity
- 12. Provision of Technical Service
- 13. Non-conformity with the approved type or family
- 14. Fees
- 15. Exemptions and alternative procedures

PART III

- 16. Enforcement Authorities
- 17. Offences

- 18. Penalty
- 19. Defence of due diligence
- 20. Liability of persons other than the principal offender Signature

SCHEDULE 1 — (Annex 1 to Directive 97/68/EC)

- [1 This section is implemented by regulation 3.]
- 2. DEFINITIONS, SYMBOLS AND ABBREVIATIONS
- 2.1 compression ignition (C.I.) engine shall mean an engine which works...
- 2.2 gaseous pollutants shall mean carbon monoxide, hydrocarbons (assuming a ratio...
- 2.3 particulate pollutants shall mean any material collected on a specified...
- 2.4 net power shall mean the power in "EEC kW" obtained...
- 2.5 rated speed shall mean the maximum full load speed allowed...
- 2.6 per cent load shall mean the fraction of the maximum...
- 2.7 maximum torque speed shall mean the engine speed at which...
- 2.8 intermediate speed shall mean that engine speed which meets one...
- 2.9 Symbols and Abbreviations
- 2.9.1 Symbols for test parameters Symbol Unit Term AP m2 Cross...
- 2.9.2 Symbols for the chemical components CO Carbon monoxide CO2 Carbon...
- 2.9.3 Abbreviations FID Flame ionization detector HFID Heated flame ionization detector...
 - 3. ENGINE MARKINGS
- 3.1 The engine approved as a technical unit must bear:
- 3.1.1 the trade mark or trade name of the manufacturer of...
- 3.1.2 the engine type, engine family (if applicable), and a unique...
- 3.1.3 the EC type-approval number as described in Annex VII.
- 3.2 These marks must be durable for the useful life of...
- 3.3 These marks must be secured to an engine part necessary...
- 3.3.1 These marks must be located so as to be readily...
- 3.3.2 Each engine must be provided with a supplementary movable plate...
- 3.4 The coding of the engines in context with the identification...
- 3.5 Before leaving the production line the engines must bear all...
- 3.6 The exact location of the engine markings shall be declared...
- 4. SPECIFICATIONS AND TESTS
- 4.1 General
- 4.2 Specifications concerning the emissions of pollutants
- 4.2.1 The emissions of the carbon monoxide, the emissions of hydrocarbons,...
- 4.2.2 The emission limits given in paragraph 4.2.1 are engine-out limits...
- 4.2.3 The emissions of the carbon monoxide, the emissions of hydrocarbons,...
- 4.2.4 Where, as defined according to Section 6 in conjunction with...
- 4.3 Installation on the mobile machinery
- 4.3.1 intake depression shall not exceed that specified for the approved...
- 4.3.2 exhaust back pressure shall not exceed that specified for the...
 5. SPECIFICATION OF CONFORMITY OF PRODUCTION ASSESSMENTS
 - 5.1 With regard to the verification of the existence of satisfactory...
- 5.2 The holder of the approval shall in particular:
- 5.2.1 ensure existence of procedures for the effective control of the...
- 5.2.2 have access to the control equipment necessary for checking the...

- 5.2.3 ensure that data of test results are recorded and that...
- 5.2.4 analyse the results of each type of test, in order...
- 5.2.5 ensure that any sampling of engines or components giving evidence...
- 5.3 The competent authority which has granted type approval may at...
- 5.3.1 In every inspection, the test books and production survey record...
- 5.3.2 When the quality level appears unsatisfactory or when it seems...
- 5.3.2.1 an engine is taken from the series and subjected to...
- 5.3.2.2 if the engine taken from the series does not satisfy...
 - 5.3.3 The approval authority or the technical service responsible for verifying...
 - 5.3.4 The normal frequency of inspections authorized by the competent authority...
 - 6. PARAMETERS DEFINING THE ENGINE FAMILY
 - 6.1 Combustion cycle: 2 cycle 4 cycle
 - 6.2 Cooling medium: air water oil
 - 6.3 Individual cylinder displacement: engines to be within a total spread...
 - 6.4 Method of air aspiration: naturally aspirated pressure charged
 - 6.5 Combustion chamber type/design: pre-chamber swirl chamber open chamber
 - 6.6 Valve and porting—configuration, size and number: cylinder head cylinder wall...
 - 6.7 Fuel system: pump-line-injector in-line pump distributor pump single element unit...
 - 6.8 Miscellaneous features: exhaust gas recirculation water injection/emulsion air injection charge...
 - 6.9 Exhaust after-treatment: oxidation catalyst reduction catalyst thermal reactor particulates trap...
 - 7. CHOICE OF THE PARENT ENGINE
 - 7.1 The parent engine of the family shall be selected using...
 - 7.2 If engines within the family incorporate other variable features which...

SCHEDULE 2 — (Annex II to Directive 97/68/EC)

SCHEDULE 3 — (Annex III to Directive 97/68/EC)

- 1. INTRODUCTION
- 1.1 This Annex describes the method of determining emissions of gaseous...
- 1.2 The test shall be carried out with the engine mounted...
- 2. TEST CONDITIONS
- 2.1 General Requirements
- 2.2 Engine test conditions
- 2.2.1 The absolute temperature Ta of the engine intake air expressed...
- 2.2.2 Test validity
- 2.2.3 Engines with charge air cooling
 - 2.3 Engine air inlet system
 - 2.4 Engine exhaust system
 - 2.5 Cooling system
 - 2.6 Lubricating oil
 - 2.7 Test fuel
 - 2.8 Determination of dynamometer settings
 - 3. TEST RUN
 - 3.1 Preparation of the sampling filters
 - 3.2 Installation of the measuring equipment
 - 3.3 Starting the dilution system and engine
 - 3.4 Adjustment of the dilution ratio

- 3.5 Checking the analysers
- 3.6 Test cycle
- 3.6.1 Specification A of machinery according to Section I of Annex...
- 3.6.1.1 The following 8-mode cycle shall be followed in dynamometer operation...
- 3.6.2 Conditioning of the Engine
- 3.6.3 Test sequence
- 3.6.4 Analyser response
- 3.6.5 *Particulate sampling*
- 3.6.6 Engine conditions
 - 3.7 Re-checking the analysers Appendix 1 —
 - 1. MEASUREMENT AND SAMPLING PROCEDURES
 - 1.1 Dynamometer specification
 - 1.2 Exhaust gas flow
- 1.2.1 Direct measurement method
- 1.2.2 Air and fuel measurement method
- 1.2.3 Carbon balance method
- 1.2.4 Total dilute exhaust gas flow
 - 1.3 Accuracy
 - 1.4 Determination of the gaseous components
- 1.4.1 General analyser specifications
- 1.4.1.1 Measurement error
- 1.4.1.2 Repeatability
- 1.4.1.3 Noise
- 1.4.1.4 Zero drift
- 1.4.1.5 Span drift
- 1.4.2 Gas drying
- 1.4.3 Analysers
- 1.4.3.1 Carbon monoxide (CO) analysis
- 1.4.3.2 Carbon dioxide (CO₂) analysis
- 1.4.3.3 Hydrocarbon (HC) analysis
- 1.4.3.4 Oxides of nitrogen (NO_X) analysis
- 1.4.4 Sampling for gaseous emissions
 - 1.5 Determination of the particulates
- 1.5.1 Particulate sampling filters
- 1.5.1.1 Filter specification
- 1.5.1.2 Filter size
- 1.5.1.3 Primary and back-up filters
- 1.5.1.4 Filter face velocity
- 1.5.1.5 Filter loading
 - 1.5.2 Weighing chamber and analytical balance specifications
- 1.5.2.1 Weighing chamber conditions
- 1.5.2.2 Reference filter weighing
- 1.5.2.3 Analytical balance
- 1.5.2.4 Elimination of static electricity effects
 - 1.5.3 Additional specifications for particulate measurement

Appendix 2 —

- 1. CALIBRATION OF THE ANALYTICAL INSTRUMENTS
- 1.1 Introduction
- 1.2 Calibration gases
- 1.2.1 Pure gases
- 1.2.2 Calibration and span gases

- 1.3 Operating procedure for analysers and sampling system
- 1.4 Leakage test
- 1.5 Calibration procedure
- 1.5.1 Instrument assembly
- 1.5.2 Warming-up time
- 1.5.3 NDIR and HFID analyser
- 1.5.4 *Calibration*
- 1.5.5 Establishment of the calibration curve
- 1.5.5.1 General guidelines
- 1.5.5.2 Calibration below 15% of full scale
- 1.5.5.3 Alternative methods
 - 1.6 Verification of the calibration
 - 1.7 Efficiency test of the NO_X converter
 - 1.7.1 *Test set-up*
 - 1.7.2 Calibration
 - 1.7.3 Calculation
 - 1.7.4 Adding of oxygen
 - 1.7.5 Activation of the ozonator
 - 1.7.6 $NO_X mode$
 - 1.7.7 **De-activation of the ozonator**
 - 1.7.8 *NO mode*
 - 1.7.9 Test interval
- 1.7.10 *Efficiency requirement*
- 1.8 Adjustment of the FID
- 1.8.1 **Optimization of the detector response**
- 1.8.2 Hydrocarbon response factors
- 1.8.3 Oxygen interference check
- 1.9 Interference effects with NDIR and CLD analysers
- 1.9.1 CO analyser interference check
- 1.9.2 NO_X analyser quench checks
- 1.9.2.1 CO_2 quench check
- 1.9.2.2 Water quench check
 - 1.10 Calibration intervals
 - 2. CALIBRATION OF THE PARTICULATE MEASURING SYSTEM
 - 2.1 Introduction
 - 2.2 Flow measurement
 - 2.3 Checking the dilution ratio
 - 2.4 Checking the partial flow conditions
 - 2.5 Calibration intervals

Appendix 3 —

- 1. DATA EVALUATION AND CALCULATIONS
- 1.1 Gaseous emissions data evaluation
- 1.2 Particulate emissions
- 1.3 Calculation of the gaseous emissions
- 1.3.1 Determination of the exhaust gas flow
- 1.3.2 Dry/wet correction
- 1.3.3 Humidity correction for NO_X
- 1.3.4 Calculation of emission mass flow rates
- 1.3.5 Calculation of the specific emissions
- 1.4 Calculation of the particulate emission
- 1.4.1 Humidity correction factor for particulates

- 1.4.2 *Partial flow dilution system*
- 1.4.2.1 Isokinetic systems G EDFW, i = G EXHW, i x q i...
- 1.4.2.2 Systems with measurement of CO2 or NOX concentration G EDFW,i...
- 1.4.2.3 Systems with CO2 measurement and carbon balance method G EDFW,i...
- 1.4.2.4 Systems with flow measurement G EDFW, i = G EXHW, i x...
 - 1.4.3 Full flow dilution system
 - 1.4.4 Calculation of the particulate mass flow rate
- 1.4.5 Calculation of the specific emissions
- 1.4.6 *Effective weighting factor*

SCHEDULE 4 — (Annex IV to Directive 97/68/EC)

SCHEDULE 5 — (ANNEX V to Directive 97/68/EC)

- 1.1 Determination of the gaseous emissions
- 1.1.1 Gaseous exhaust components CO, CO₂, HC, NO_X

Figure 2

Flow diagram of exhaust gas analysis system for CO, CO₂ and HC

Figure 3

Flow diagram of dilute exhaust gas analysis system for CO, CO₂, NO_X and HC

- Descriptions—Figures 2 and 3
- 1.2 Determination of the particulates
- 1.2.1 Dilution system
- 1.2.1.1 Partial flow system (Figures 4 to 12)

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Figure 4

Partial flow dilution system with isokinetic probe and fractional sampling (SB control)

Figure 5

Partial flow dilution system with isokinetic probe and fractional sampling (PB control)

Figure 6

Partial flow dilution system with CO_2 or NO_X concentration measurement and fractional sampling

Figure 7

Partial flow dilution system with CO₂ concentration measurement, carbon balance and total sampling

Figure 8

Partial flow dilution system with single venturi, concentration measurement and fractional sampling

Figure 9

Partial flow dilution system twin venturi or twin orifice, concentration measurement and fractional sampling

Figure 10

Partial flow dilution system with multiple tube splitting, concentration measurement and fractional sampling

Figure 11

Partial flow dilution system with flow control and total sampling

Figure 12

Partial flow dilution system with flow control and fractional sampling

Description-Figures 4 to 12

- EP exhaust pipe

- SP Sampling probe (Figures 6 to 12)
- ISP isokinetic sampling probe (Figures 4 and 5)
- FD1, FD2 flow divider (Figure 9)
- FD3 flow divider (Figure 10)
- EGA exhaust gas analyser (Figures 6 to 10)
- TT Transfer tube (Figures 4 to 12)
- **DPT differential pressure transducer** (Figures 4, 5 and 10)
- FCI flow controller (Figures 4, 5 and 10)
- PCVI, PCV2 pressure control valve (Figure 9)
- *DC damping chamber* (Figure 10)

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

— VN venturi (Figure 8)

- *FC2 flow controller* (Figures 6, 7, 11 and 12, optional)
- FM1 flow measurement device (Figures 6, 7, 11 and 12)
- *FM2 flow measurement device* (Figure 12)
- **PB** pressure blower (Figures 4, 5, 6, 7, 8, 9 and 12)
- **DAF dilution air filter** (Figures 4 to 12)
- **PSP** particulate sampling probe (Figures 4, 5, 6, 8, 9, 10 and 12)
- *DT dilution tunnel* (Figures 4 to 12)
- *HE heat exchanger* (Figures 9 and 10)
- 1.2.1.2 Full flow dilution system (Figure 13)
 - Descriptions—Figure 13
 - EP exhaust pipe

Figure 13

Full flow dilution system

- PDP positive displacement pump
- CFV critical flow venturi
- HE heat exchanger (optional if EFC is used)
- —*EFC electronic flow compensation* (optional if HE is used)
- DT dilution tunnel
- DAF dilution air filter
- PSP particulate sampling probe
- 1.2.2 *Particulate sampling system (Figures 14 and 15)* Descriptions—Figures 14 and 15
 - PSP particulate sampling probe (Figures 14 and 15)

Figure 14

Particulate sampling system

Figure 15

Dilution system (full flow system only)

- *PTT particulate transfer tube* (Figures 14 and 15)
- *SDT secondary dilution tunnel* (Figure 15)
- *FH filter holder(s)* (Figures 14 and 15)
- *P sampling pump* (Figures 14 and 15)
- **DP** dilution air pump (Figure 15) (full flow double dilution only)
- FC3 flow controller (Figures 14 and 15)

— *FM3 flow measurement device* (Figures 14 and 15) (particulate sample flow)

— *FM4 flow measurement device* (Figure 15) (dilution air, full flow double dilution only)

- BV ball valve (optional)

Schedule 6 —

Schedule 7 — (ANNEX VII to Directive 97/68/EC)APPROVAL CERTIFICATE NUMBERING SYSTEM(see Article 4(2))

- 1. The number shall consist of five sections separated by the...
- 2. Example of the third approval (with, as yet, no extension)...

3. Example of the second extension to the fourth approval corresponding...

Explanatory Note