WELSH STATUTORY INSTRUMENTS

2015 No. 1513 (W. 175) CLEAN AIR, WALES

The Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2015

Made - - - - 8 July 2015
Laid before the National
Assembly for Wales - - 15th July 2015
Coming into force - - 11 August 2015

The Welsh Ministers in exercise of the powers conferred upon the Secretary of State by section 21 of the Clean Air Act 1993(1) and now vested in the Welsh Ministers(2) so far as exercisable in relation to Wales, and being satisfied that the fireplaces exempted by this Order can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke, make the following Order:

Title, commencement and application

- 1.—(1) The title of this Order is the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2015 and it comes into force on 11 August 2015.
 - (2) This Order applies in relation to Wales.

Fireplaces exempted from section 20 of the Clean Air Act 1993

2. The fireplaces described in the Schedule are, subject to the conditions listed, exempted from the provisions of section 20 of the Clean Air Act 1993 (which prohibits smoke emissions in smoke control areas).

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2014(3) is revoked.

^{(1) 1993} c.11.

⁽²⁾ The relevant functions of the Secretary of State were, so far as exercisable in relation to Wales, transferred to the National Assembly for Wales by virtue of article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672). Those functions are now exercisable by the Welsh Ministers by virtue of section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c.32).

⁽³⁾ S.I. 2014/694 (W. 75)

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Carl Sargeant
Minister for Natural Resources, one of the Welsh
Ministers

8 July 2015

SCHEDULE

Article 2

EXEMPTED FIREPLACES

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC, Hamlet Solution 5 SC and Villager Espirit 5 SC. Manufactured by Arada Ltd., The Fire Works, Millwey Industrial Estate, Axminster, Devon, EX13 5HU.	Instruction manual reference "Rev 02" dated April 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond 20mm from the closed position and 50 mm beyond the fully open position.	Wood logs ⁽¹⁾ .
Aarrow 1 Series 400 wood burning inset roomheater and 400 T F wood burning stove. Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft Avenue, Axminster, Devon EX13 5HU.	Operating and installation manual reference "Part No. AFS 1589de" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 10mm open position.	Wood logs ⁽¹⁾
Aarrow 1 Series 500 wood burning inset roomheater. Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft Avenue, Axminster, Devon EX13 5HU.	Operating and installation manual reference "Part No. AFS 1789de" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 10mm open position.	Wood logs ⁽¹⁾ .
Aarrow 1 Series 600 wood burning inset roomheater. Manufactured by Arada Stoves Ltd., The Fireworks,	Operating and installation manual reference "Part No. AFS 1789de" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air control	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
W. O. A	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Weycroft Avenue, Axminster, Devon EX13 5HU.	lever closure beyond the 9mm open position.	
Aarrow 1 Series 750 wood burning inset roomheater.	Operating and installation manual reference "Part No. AFS 1789de" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Arada Stoves Ltd., The Fireworks, Weycroft Avenue, Axminster, Devon EX13 5HU.	The appliance must be fitted with a mechanical stop to prevent air control lever closure beyond the 7mm open position.	
Acquisitions Bloomsbury 5kW stove.	Instruction manual reference "01/12 (PP)" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a system that prevents the closure of the air controls beyond the 50% open position.	
Acquisitions Bloomsbury SE 8kW Smoke Exempt Multi- Fuel Stove.	Instruction manual reference "AB-8kW-I05-310114" dated 31st January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.		
Acquisitions Cannonbury 4 and 5. Manufactured by Esse Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick,	Installation and operating instruction manual reference "v71 of 09/11/2010" dated 9th November 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Lancashire, BB18 6BN.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ACR Astwood Multifuel stove AW1MF. Manufactured by ACR Heat Products Ltd., Unit 1, Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Instruction manual reference "AW1MF 0101 Version 3" dated 28th January 2013. The appliance must be fitted with a mechanical stop to prevent the closure of the secondary air control lever beyond 12mm open position.	Wood logs ⁽¹⁾ .
Aduro 15 and 15-1 6.5kW wood burning stoves Manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark.	Instruction manual reference "Version 1 – 2014-07" dated July 2014. The appliance must be fitted with a permanent stop to prevent closure of the secondary air slider beyond the 55% open position.	Wood logs ⁽¹⁾ .
Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves. Manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark, and previously manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.	Instruction manual reference "Pexex1001/AH/ver1" dated June 2011. The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	Dry wood logs ⁽¹⁾ .
Aduro 9D wood burning stove. Manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark, and previously	Instruction manual reference "Pevex1002/AH/ver1" dated June 2011. The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls	Dry wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.	do not close beyond 95% and 50% respectively.	
AGA Dorrington SE 6kW wood burning stove.	Installation and operating instructions, reference "NOO647AXX Rev.001" dated 16th July 2014	Wood logs ⁽¹⁾ .
Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 7mm open position.	
AGA Hadley SE 8kW wood burning stove.	Installation and operating instructions reference "NOO645AXX Rev.001" dated 16th July 2014.	Wood logs ⁽¹⁾ .
Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 5mm open position.	
AGA Hanwood SE 9kW wood burning stove.	Installation and operating instructions reference "NOO643AXX Rev.001" dated 17th July 2014.	Wood logs ⁽¹⁾ .
Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.		
AGA Lawley SE 4kW wood burning stove.	Installation and operating instructions reference "NOO646AXX Rev.001" dated 17th July 2014.	Wood logs ⁽¹⁾ .
Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 4mm open position.	
AGA Shawbury SE 7kW wood burning stove.	Installation and operating instructions reference "NOO642AXX Rev.001" dated 16th July 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 6mm open position.	
AGA Westbury SE 6kW wood burning stove.	Installation and operating instructions reference "NOO644AXX Rev.001" dated 15th July 2014.	Wood logs ⁽¹⁾ .
Manufactured by AGA Rangemaster, Station Road, Ketley, Telford, Shropshire TF1 5AQ.	The appliance must be fitted with a modified air control slider to prevent closure beyond the 35mm open position.	
Alberg 7. Manufactured by Elite Group Trading Ltd., Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	Instruction manual reference "EGTL03A Version 1.4" dated 21st December 2012.	Wood logs ⁽¹⁾ .
Alpha I model number AL905-SE Wood Burning Stove.	Instruction manual reference "HF277-SE/UK-NI-ROI/V2D.18-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hi- Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Alpha II model number AL907-SE Wood Burning Stove.	Instruction manual reference "AL907-SE/UK-NI-ROI/V3-D.14-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hi- Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Chapel, Cheshire, CW4 8AF.	of the door rope seal to allow a constant flow of air.	
Angus Orligno 200 18kW, 25kW, 40kW, 60kW and 80kW gasification boilers.	Instruction manual reference "EV-20111002" dated October 2011.	Wood logs ⁽¹⁾ .
Manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Orligno 500 7-25kW boiler.	Instruction manual reference "EV 20121003" dated 3rd October 2012.	Wood pellets (1).
Manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Super 18, 25, 40, 60 and 80kW gasification boilers.	Instruction manual reference "EV-20111001" dated October 2011.	Wood logs ⁽¹⁾ .
Manufactured by Eko-Vimar Orlanski Spółka z ograniczoną odpowiedzialnością, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Super 96 and 130kW gasification boilers.	Instruction manual reference "EV-20131002" dated October 2013.	Wood logs ⁽¹⁾ .
Manufactured by Eko-Vimar Orlanski, Spólka z ograniczona odpowiedzialnoscia, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Apollo 8 Inset stove. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH8K Apollo – V2" dated 31st October 2011. The appliance must be fitted with a system that prevents closure of the air controls further than 40mm from open.	Wood logs ⁽¹⁾ .
Arimax Bio 300kW, Arimax Bio 400kW and Arimax Bio 500kW.	Instruction manual reference "Installation and Operation Manual Arimax Bio 120-3000kW" dated 30th March 2010.	6-8mm wood pellets with a moisture content less than 10% (1).
Manufactured by Artierm Oy, Kimmo Kantalainen, PO Box 59, Fin – 43101, Saarijärvi, Finland.		
Ariterm BioCompPX boiler and PX52 pellet burner and Ariterm BioCompPX Ultra- light boiler and PX52 pellet burner.	Instruction manual reference "Ariterm-SP-PX28327.1" dated 6th November 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm Sweden AB, Flottijvagen 15, 392 41 KALMAR, Sweden Limited.		
Ariterm Ekerum 6kW pellet stove and Neptuni 6kW pellet stove.	Instruction manual reference "ARITERM-SP-PX26868-B.2" dated 15th December 2011.	Wood pellets ⁽¹⁾ .
Manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Ariterm Mysinge 6kW pellet stove.	Instruction manual reference "ARITERM-SP-PX26868-B.1" dated 15th December 2011.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Arizona Stoves Crete inset multi-fuel stove. Manufactured by Micon Distribution	Operation and installation manual reference "Version A (MZSCRE5SE)" dated 24th November 2014.	Wood logs ⁽¹⁾ .
Ltd., 1a Hallstown Road, Ballinderry Upper, Lisburn BT28 2NE.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 75% open position.	
Ashwell Green-Tec 150 boiler.	Instruction manual reference "ASH-gt150/101 Version 1.2" dated June 2009.	Wood pellets (1).
Manufactured by Ashwell Biomass Ltd., Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	2007.	
Ashwell Green-Tec 195 boiler.	Instruction manual reference "ASH-gt195/102 Version 1.2" dated June 2009.	Wood pellets (1).
Manufactured by Ashwell Biomass Ltd., Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.	2007.	
Ashwell Green-Tec 300 boiler.	Instruction manual reference "ASH-gt300/103 Version 1.2" dated June 2009.	Wood pellets ⁽¹⁾ .
Manufactured by Ashwell Biomass Ltd., Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.		
ATOM 198kW boiler and cyclone. Manufactured by	Operating and maintenance instruction manual reference "2.1114.00 – EN Release 1.1" dated July 2014.	Wood chips or wood pellets (1).
Uniconfort srl, Via dell'Industria 21,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
35018, San Martino Di Lupari, (PD), Italy.		
Avalon 4 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAV04 Rev C" dated 13th June 2012. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾ .
Avalon 5 Slimline stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVS05 Rev C" dated 13th June 2012.	Wood logs ⁽¹⁾ .
Avalon 6 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVA06 Rev C" dated 13th June 2012.	Wood logs ⁽¹⁾ .
Avalon Compact 5 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINAVC05 Rev C" dated 13th June 2012. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾ .
Avalon Slimline 8 stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge,	Instruction manual reference "JINAVS08 Rev B" dated 27th June 2012.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Camelford, Cornwall, PL32 9TT.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Barbas Cuatro-3 57 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "01-333659" dated 15th June 2013 and instructions for use & maintenance manual reference "01-333655" dated 15th June 2013. The appliance must be fitted with a redesigned air slide equivalent to a minimum closure position of 23.5 cm of the type-tested prototype appliance.	Wood logs ⁽¹⁾ .
Barbas Cuatro-3 70 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "03-336146" dated 26th May 2014 and instructions for use and maintenance manual reference "03-336145" dated 27th May 2014. The appliance must be fitted with an air slide which has a circular opening of 32mm diameter (800 mm² area) so as to provide air supply when the air slide is fully closed.	Wood logs ⁽¹⁾ .
Barbas Cuatro-3 75 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "01-333861" dated 15th June 2013 and instructions for use & maintenance manual reference "01-333855" dated 15th June 2013.	Wood logs ⁽¹⁾ .
Barbas Cuatro-3 80 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	Installation instructions and manual for annual maintenance dated reference "03-335878" dated 26th May 2014 and instructions for use and maintenance manual reference "03-335877" dated 26th May 2014. The appliance must be fitted with an air slide which has a circular opening	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	of 32mm diameter (800 mm ² area) so as to provide air supply when the air slide is fully closed.	
Barbas Cuatro-3 90 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Installation instructions and manual for annual maintenance reference "01-332965" dated 15th June 2013 and instructions for use and maintenance manual reference "01-332875" dated 10th June 2013.	Wood logs ⁽¹⁾ .
Barbas ECO 40, 5kW wood burning roomheater.	Instruction manual reference "Version 01-327332" dated October 2009.	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.		
Barbas ECO 52 Stove. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.	Instruction manual reference "02 - 327332" dated March 2010.	Wood logs ⁽¹⁾ .
Barbas ECO-55 stove appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	Installation instructions manual and directions for use reference "03-334744" dated January 2014. The appliance must be fitted with an air valve incorporating seven rectangular holes of dimension 24 x 20 mm and marked 'UK55'.	Wood logs ⁽¹⁾ .
Barbas EVO 80-65 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	Installation instructions and manual for annual maintenance reference "02-334801" dated 20th May 2014 and instructions for use and maintenance manual reference "02-334744" dated 20th May 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	The appliance must be fitted with an air slide which has a circular opening of 30mm diameter (700mm ² area) so as to provide air supply when the air slide is fully closed.	
Barbas EVO 100-50 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	Installation instructions and manual for annual maintenance reference "02-336024" dated 20th May 2014 and instructions for use and maintenance manual reference "02-336020" dated 20th May 2014. The appliance must be fitted with an air slide which has a circular opening of 30mm diameter (700mm² area) so as to provide air supply when the air slide is fully closed.	Wood logs ⁽¹⁾ .
Barbas Unilux 3-40, 5kW wood burning insert.	Instruction manual reference "Version 01 – 326587" dated August 2009.	Wood logs ⁽¹⁾ .
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.		
Barbas Unilux 3-52 Stove.	Instruction manual reference "03 - 326587" dated March 2010.	Wood logs (1).
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, Bladel, The Netherlands.		
Barbas Unilux-3 55 Inset appliance.	Installation instructions and directions for use manual reference "05-326587" dated January 2014.	Wood logs (1).
Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands.	The appliance must be fitted with an air valve incorporating seven rectangular holes of dimension 24 x 20 mm and marked 'UK55'.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Barbas Unilux-3 65 Inset appliance. Manufactured by Interfocos BV, Hallenstraat 17, 5531 AB, BLADEL, The Netherlands. Bari C.11 wood	Installation instructions and directions for use manual reference "05-326587" dated January 2014. The appliance must be fitted with an air valve incorporating seven rectangular holes of dimension 24 x 20 mm and marked 'UK65'. Instruction manual reference	Wood logs ⁽¹⁾ . Wood logs ⁽¹⁾ .
burning stove. Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier.	"Bari_R1" dated November 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 42mm open position.	
Baxi Bioflo. Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.	Operating instruction manual reference "720574401" dated 2010 and installation and servicing instruction manual reference "720574501" dated 2010.	Wood pellets ⁽¹⁾ .
Be Modern Monroe 5, Monroe 5, Be Modern Monterrey 5, Monterrey 5 and York Midi Multi Fuel Stoves. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "OCT10/GB" dated 6th October 2010. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	Wood logs ⁽¹⁾ .
Be Modern Monterrey 7, Monterrey 7, Be Modern Monroe 7 and Monroe 7 Multi Fuel Stoves.	Instruction manual reference "OCT10/GB" dated 6th October 2010. The appliance must be fitted with a system that prevents the closure of	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	the secondary air flaps to be less than 10mm open position.	
Berkeley SE multifuel stove and Berkeley SE multifuel stove with stoveasy grate. Manufactured by Newman Fireplaces Limited, Unit 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	Instruction manual reference "NS 7 Issue 1" dated 8th January 2014. The tertiary air control must be fully open when burning wood.	Wood logs ⁽¹⁾ .
Binder Wood Fired Boiler models RRK 22 – 49 (49kW output). Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips (1).
Binder Wood Fired Boiler models RRK 80 – 175 (75 – 149kW output) with cyclone models ZA 80 – 175. Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Binder Wood Fired Boiler model RRK 130 – 250 (185 - 230kW output) 200-350 (250-300kW output) 400-600 (350-500kW output) 640-850 (650-840kW output) with cyclone (model type ZA).	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips (1).
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
Binder Wood Fired Boiler model RRK 1000 (1200kW output) with multi-cyclone (model MZA).	Installation, commissioning and maintenance manual reference "WELBinderManual rev0.doc, revision 0" dated 17th May 2005.	Wood pellets or wood chips (1).
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
Binder Wood Fired Boiler model RRK 1200-1650 with Binder model MZA multi-cyclone and automatic ignition.	Operating instructions reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8" dated 15th July 2009.	Wood pellets or wood chips (1).
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
5 A 9572 Davids d	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 1800-2300 with Binder model MZA multi-cyclone and automatic ignition.	Operating instructions reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8" dated 15th July 2009.	Wood pellets or wood chips (1).
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
Binder Wood Fired Boiler model RRK 2500-3000 with Binder model MZA multi-cyclone and automatic ignition.	Operating instructions reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8" dated 15th July 2009.	Wood pellets or wood chips (1).
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
Bioclass NG 10, NG 16,	Installation and operating Instructions manual reference "CDOC000682" dated July 2014.	Wood pellets (1).
NG 25 and NG 43 wood pellet boilers.		
Manufactured by		
Domusa S.Coop		
B° San Esteban s/n		
20737, Errezil, Spain.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Bioflame 15 Slim Wood Pellet Boiler.	Installation and operation manual reference "V.1.1" dated June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Biokaitra BIO models 30 and 50 pellet boilers.	Instruction manual version 1 reference "User manual, User guide, Installation, Use and Maintenance of the Boiler" dated November 2013.	Wood pellets ⁽¹⁾ .
Manufactured by UAB Biokaitra, Šv. Stepono 27, LT-01312, Vilnius, Lithuania.		
Biomatic +20 boiler. Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	Instruction manual reference "ARITERM-VTT-S-07229-11.1" dated 21st May 2012.	Wood pellets ⁽¹⁾ .
Biomatic +20 light boiler and Biomatic +20 ultra light boiler.	Instruction manual reference "ARITERM-VTT-S-07229-11.2" dated 21st May 2012.	Wood pellets (1).
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Biomatic +40 boiler.	Instruction manual reference "ARITERM-VTT-S-06765-11.1"	Wood pellets (1).
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	dated 21st May 2012.	
Biomatic +40 light boiler and Biomatic +40 ultra light boiler.	Instruction manual reference "ARITERM-VTT-S-06765-11.2" dated 21st May 2012.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Biomatic 220 and 250 fitted with Zyklovent 220-250 cyclone separator.	Manufacturer's instructions reference "Bedienungsanleitung Englisch v2.0 doc." dated April 2005.	Wood chips, wood pellets, or planed wood shavings ⁽¹⁾ .
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Straße 22,		
A-1230 Wien, Austria.		
Biomatic 300, 350, 400 and 500 fitted with Zyklovent 300-500 cyclone separator.	Manufacturer's instructions reference "Bedienungsanleitung Englisch v2.0 doc." dated April 2005.	Wood chips, wood pellets, or planed wood shavings ⁽¹⁾ .
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Straße 22,		
A-1230 Wien, Austria.		
Biotech Top Light, Top Light M, Top Light M MBW, PZ8RL, PZ25RL and PZ35RL wood pellet boilers.	Instruction manual reference "Top Light/Top Light M/ Top Light M/MBW/PZ8RL/ PZ25RL/PZ32RL/PZ35RL Version 9400000100030 06/13 ENG" dated June 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Biotech Energietechnik GmbH, Mayrwiesstrasse 125300 Hallwang bei Salzburg, Austria.		
Boru 4.9kW Stove.	Instruction manual reference "BFF010" dated 26th January 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Manufactured by Righpur Ltd., T/A Boru Stoves, The Hive, Ballydine, Gooldscross, Ireland.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The air controls must be fixed such they cannot be closed more than: — Primary air slide 2mm; — Secondary air slide 2mm; — Tertiary air slide 30%.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Breckwell ETR002. Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.	Operation and instruction manual reference "852288" dated October 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 12mm open position.	Wood logs ⁽¹⁾ .
Breckwell model ESWC 11 wood burning stove. Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.	Instruction manual reference "852330" dated December 2014. The appliance must be fitted with a system to prevent closure of one of the eight secondary air slots beyond the 3.5mm open position, and with the tertiary air control fixed in the fully open position.	Wood logs ⁽¹⁾ .
Breckwell ESWC31. Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA. Breckwell ESWC21.	Operation and instruction manual reference "852286 A" dated October 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 6mm open position. Operation and instruction manual	Wood logs ⁽¹⁾ . Wood logs ⁽¹⁾ .
Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA. BST83X multifuel stove.	Installation and operation manual reference "1.01" dated July 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Manufactured by Hebei Chida Manufacture and Trade Co Ltd., No. B2305, Times Ark Building, 36 Guang'an Street, Shijiazhuang, 050011, China.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 15mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Burley Brampton 8kW stove.	Instruction manual reference "BUR/11/10" dated October 2011.	Wood logs ⁽¹⁾ .
Manufactured by Burley Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 6RB.		
Burley Debdale 4kW stove.	Instruction manual reference "BUR/11/10" dated October 2011.	Wood logs ⁽¹⁾ .
Manufactured by Burley Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 6RB.	The radius of the air inlet hole must be 19mm.	
Burley Hollywell SE.	Instruction manual reference "BUR/11/05" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Burley Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 6RB.	The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	
Bushman Large Commercial Pizza Oven.	Instruction manual reference "LCOINST" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Bushman Large Domestic Pizza Oven.	Instruction manual reference "LDOINST" dated January 2011.	Wood logs (1).
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		
Bushman Medium Commercial Pizza Oven.	Instruction manual reference "MCOINST" dated January 2011.	Wood logs (1).
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		
Bushman Medium Domestic Pizza Oven.	Instruction manual reference "MDOINST" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		
Bushman Small Commercial Pizza Oven.	Instruction manual reference "SCOINST" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Bushman Small Domestic Pizza Oven.	Instruction manual reference "SDOINST" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Dingley Dell Enterprises Ltd., PO Box 3534, Kidderminster, Worcestershire, DY14 9ZE.		
Buxton Multifuel stove (Model BX1MF).	Technical manual reference "BX1MF 0101" dated 17th October 2013.	Wood logs ⁽¹⁾ .
Manufactured by ACR Heat Products Ltd, Unit 1, Weston Works, Weston Lane, Tyseley, Birmingham, West Midlands,	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control lever beyond 12mm open.	
B11 3RP.		
Camelot 4 stove. Manufactured by Hunter Stoves	Instruction manual reference "JINCAM04 Rev B" dated 24th April 2012.	Wood logs ⁽¹⁾ .
Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Camelot 5 Compact stove.	Instruction manual reference "JINCAC05 Rev B" dated 14th June 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Camelot 5 Slimline stove.	Instruction manual reference "JINCAS05 Rev B" dated 15th June 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.		
Camelot 6 stove.	Instruction manual reference "JINCAM06 Rev B" dated 24th April	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	2012.	
Camelot Slimline 8 stove.	Instruction manual reference "JINCAS08 Rev B" dated 27th June 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	2012.	
Carillon 4:3 and Carillon 16:9 Crystal.	Instruction manual reference "7196755-Rev.09" dated 22nd December 2010.	Wood logs ⁽¹⁾ .
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Carron Dante SE. Manufactured	Instruction manual reference "BHC401-406" dated 12th January 2011.	Wood logs ⁽¹⁾ .
by JIG UK Ltd., Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 14mm.	
Carron Stove.	Instruction manual reference '91-62351' dated July 2009.	Dry and split wood logs of a maximum length of 23cm ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by JIG UK Ltd., Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.		
Carron Stove SE. Manufactured by JIG UK Ltd., Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	Instruction manual reference "BHC501-506" dated 12th January 2011. The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 3mm.	Wood logs ⁽¹⁾ .
Carron 11kW SE Stove. Manufactured by JIG UK Ltd., Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	Instruction manual reference "Carron 11kW Stove model September 2012 (Smoke Exempt)". The appliance must be fitted with a modification to the secondary air control preventing closure beyond 4mm.	Wood logs ⁽¹⁾ .
Cast Tec Arbeia Juno freestanding woodburning stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	Installation and operating instructions reference "Juno & Vulcan Issue 01" dated June 2013. The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	Wood logs ⁽¹⁾ .
Cast Tec Arbeia Titus wood-burning inset stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford	Installation and operating instructions reference "Trajan & Titus Issue 01" dated June 2013. The appliance must be fitted with a system that prevents closure of the	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Park 2, Telford, Shropshire, TF3 3AR.	secondary air control slots beyond the 9mm open position.	
Cast Tec Arbeia Trajan wood-burning inset stove.	Installation and operating instructions reference "Trajan & Titus Issue 01" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
Cast Tec Arbeia Vulcan freestanding wood-burning stove.	Installation and operating instructions reference "Juno & Vulcan Issue 01" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 5mm open position.	
Cast Tec Cougar 4.7kW multi-fuel stove.	Instruction manual reference "T1202 v1" dated 22nd April 2014.	Wood logs ⁽¹⁾ .
Manufactured by Arbeia Trading Ltd, Unti 3A East Side, Tyne Dock, South Shields, Tyne and Wear, NE33 5SP.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position. The appliance must be fitted with a mechanical stop to fix the tertiary air control fully open.	
CB800 Skagen. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall,	Instruction manual reference "JINHCE08 revE" dated 6th December 2011 and instruction manual reference "JINHCE08SCK revB" dated 6th December 2011. The appliance must be fitted with	Wood logs ⁽¹⁾ .
PL32 9TT.	The appliance must be fitted with smoke control area kit JHCE0801.	
Charnwood Bay 5 GT 5.8kW wood burning inset stove.	Operating and installation instructions reference "Bay 5.5GTv3" dated April 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by A.J. Wells and Sons Limited, Bishops Way, Newport, Isle of Wight, PO30 5WS.		
Charnwood C-Four stove.	Instruction manual reference "CFOUR V1" dated August 2011.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.		
Charnwood C-Five wood burning stove.	Instruction manual reference "C-series v2" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 58mm open position.	
Charnwood C-Six stove.	Instruction manual reference "Ref. C-4 C-6 v1" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a system that prevents the closure of the air control opening beyond 58mm of the open position.	
Charnwood C-Seven wood burning stove.	Instruction manual reference "C-series v2" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 64mm open position.	
Charnwood C-Eight wood burning stove.	Instruction manual reference "C-series v2" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by A.J Wells and Sons Ltd., Bishops Way,	The appliance must be fitted with a mechanical stop that prevents the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Newport, Isle of Wight, PO30 5WS.	closure of the air control opening beyond the 64mm open position.	
Charnwood Country 4 wood burning stove. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Modification instruction manual reference "TIS.95" dated January 2011 and instruction manual reference "Country 4 MKII" dated January 2011. The appliance must be fitted with the manufacturer's smoke reduction kit to fix the minimum aperture of the secondary air inlets to a minimum of 21mm open.	Wood logs ⁽¹⁾ .
Charnwood Cove 1SR. Manufactured by A.J Wells and Sons	Installation and use instruction manual reference "COVE1SR01.10 Issue A". The air control must be adjusted such	Wood logs ⁽¹⁾ .
Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	that the minimum closure of the air control is equivalent to that found with the control pushed in 15mm from the fully open position.	
Charnwood Island 1. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. The appliance must be fitted with a stop bracket (Kit No. 010/AY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs ⁽¹⁾ .
Charnwood Island 2. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010. The appliance must be fitted with a stop bracket (Kit No. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	Wood logs ⁽¹⁾ .
Charnwood Island 3.	Instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with a stop bracket (Kit No. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Tor stove. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Installation and use instruction manual reference "Tor 02.10 Issue A".	Wood logs ⁽¹⁾ .
Charnwood Tor Pico. Manufactured by A.J Wells and Sons Ltd., Bishops Way, Newport, Isle of Wight, PO30 5WS.	Instruction manual reference "Tor & Tor Pico 12.10 IssueB" dated December 2010.	Wood logs ⁽¹⁾ .
Chelsea SE 4.7kW multifuel inset room heater.	Installation and user instructions manual reference "NS-4 Issue 1" dated 8th January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Newman Fireplaces Ltd, Units 6&7 Rawreth Barns, Dollyman's Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air supply control beyond 7mm open.	
Chesneys 4 Series (4.6kW) Stoves: Flatford 4; Hampstead 4, Alpine 4 also sold as: Sunbeam 4, Dakota 4, Providence 4, Pacific 4 also sold as: Milan 4, Murano 4, Apollo 4, Chelsea 4 also sold as: Wellington 4,	Instruction manual reference "CH4K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 34mm open position.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Guernsey 4, Belgravia 4. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW1 14ND.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Chesneys 6 Series (7kW) Stoves: Flatford 6, Petworth 6, Barrington 6, Hampstead 6, Alpine 6 also sold as: Sunbeam 6, Dakota 6, Providence 6; Chelsea 6 also sold as: Wellington 6, Guernsey 6, Belgravia 6.	Instruction manual reference "CH6K-V4" dated 7th December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position.	Wood logs ⁽¹⁾ .
Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW1 14ND.		
Classic model 25, 35, 40, 49 and 60 wood pellet boilers. Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	Installation manual reference "No. 22, Pellet Boilers, Type Classic 25, 31, 35, 40, 49, 60, reference BA Classic 25L-60L Nr 21 0508".	Wood pellets ⁽¹⁾ .
Clean Air Systems CAS 200, 400 and 600 hand-fed airheaters. Manufactured by Inventair Ltd., Lancaster Road,	Handbook reference "24600H version 1" dated January 2011.	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.		
Clean Air Systems CAS 300 Max airheater and cyclone.	Handbook reference "300A version 1" dated January 2011.	Chipped or sawdust softwood, hardwood, medium density fibreboard (MDF) or chipboard
Manufactured by Inventair Ltd., Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.		·
Cleanburn CB900 Inset & Cleanburn CB900 Sonderskoven Inset wood burning stoves.	Instruction manual reference "JINHCN09 Slider Stop Rev A" dated 17th January 2012 and instruction manual reference "JINHCN09 Rev F" dated 24th January 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Cleanburn Inset Sønderskoven 8 multi- fuel inset stove. Manufactured by Hunter	Installation and operating instructions manual reference "JINCN09 RevF" dated 20th March 2012 and modification instructions reference "JINHCN09 Slider Stop Rev B"	Wood logs ⁽¹⁾ .
Stoves Limited, Trevilla Park, Slaughterbridge, Camelford,	dated 25th September 2013. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Cornwall, PL32 9TT.		
Cleanburn R4.	Instruction manual reference "JINCLR04 Rev E" dated 2nd December 2011 and instruction	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	manual reference "JINCLR04SCK revB" dated 5th December 2011. The appliance must be fitted with smoke control area kit JCLR0401.	
Cleanburn R5 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCLR05 Rev B" dated 10th December 2012 and instruction manual reference "JINCLR05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit JCLR0501.	Wood logs ⁽¹⁾ .
Cleanburn R6 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCLR06 Rev B" dated 10th December 2012 and instruction manual reference "JINCLR05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit JCLR0501.	Wood logs ⁽¹⁾ .
Cleanburn Sonderskoven 5 Inset stove.	Instruction manual reference "JINHCN05 Rev B" dated 4th October 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The valve plate adjusted by the secondary air control must contain six 5mm holes.	
Clearburn Junior SE. Manufactured by Dean Forge Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 0LS.	Instruction manual reference "JRSE Issue 1" dated March 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves.	Operating instructions reference "V1/42" stamped and signed "Smoke Control" dated 1st July 2006. The appliance must be fitted with a	Air-dried wood logs (1).
Manufactured by Clearview Stoves, More Works, Bishops Castle, Shropshire, SY9 5HH.	tamperproof mechanical stop on the air slide/damper.	
CLM Vesuvio 400kW stone wood-fired automatic pizza oven. Formerly known as	Instruction manual reference "Manual English Review 2.1" dated 25th July 2013.	'CalorPan' 100% beech briquette, octagonal section, length 260-300mm, width and height 75-90mm manufactured from dried beech sawdust or
the Vesuvio 400kW automatic pizza oven manufactured by CLM srl, Via I Maggio 35, 31043, Fontanelle (Treviso), Italy, and now manufactured by CLM Bakery System srl, Via Monteli, 3 - 33092 Meduno (PN), Italy.		'Eden Beech Wood Briquettes' that are cylindrical and of length 247-273mm and have diameter of 95mm manufactured from dried beech sawdust (1).
Contura 510, 520T, 550, 550A, 550W, 560T, 560K, 570, 580, 585, 590 and Contura T.	Manufacturer's installation instructions reference "IAV SE/EX 0726-6 611821" and Lighting instruction reference "BAV SA/EX 0717-2 611820".	Untreated dry wood with less than 20% moisture ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	
Contura 556 woodburning stove. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	User manual reference "611 820 BAV C500 SE/EX – 6" dated 20th October 2011 and installation instruction manual reference "811116 IAV SE-EX C556 - 2" dated 14th November 2012 and supplementary instruction manual reference "811142 BAV GB - 3" dated August 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a system to prevent closure of the air	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	control vent beyond the 20% open position.	
Contura 580W. Manufactured by Nibe AB, Box 134, SE-285	Manufacturer's installation instructions reference "IAV SE/EX 0740-1 511911".	Untreated dry wood with less than 20% moisture ⁽¹⁾ .
23 Markaryd, Sweden.	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	
Contura 586 woodburning stove. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	User manual reference "611 820 BAV C500 SE/EX – 6" dated 20th October 2011, installation instruction manual reference "811117 IAV SE-EX C586 -2" dated 15th November 2012 and supplementary instruction manual reference "811142 BAV GB - 3" dated August 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 20% open position.	
Contura 750, 750A and 780.	Instruction manual reference "811064 BAV SE-EX C750/780-1".	Wood logs ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to prevent closure of the air control vent beyond the 28% open position.	
Contura 810, Contura 820 T, Contura 850, Contura 860 T and Contura 880.	Instruction manual reference "811118 BAV SE-EX C800-1" dated 28th June 2011 and supplementary operating instructions reference "811142 BAV GB-2" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 38% open position.	
Contura i4 FS Classic and Contura i4 FS	Instruction manual reference "811164 BAV C i4 SE-EX-1" dated	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Modern multi-fuel stoves.	03/02/2012, installation instruction manual reference "811191 IAV Ci4 FS GB-1" dated 3rd June 2013 and	
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	supplementary operating instruction manual reference "811142 BAV GB - 4" dated August 2011.	
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 30% open position.	
Contura i4 Modern and Contura i4 Classic.	Instruction manual reference "811136 BAV C i4 GB-1" dated 0	Dry wood logs ⁽¹⁾ .
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	4th July 2011 and supplementary operating instructions reference "811142 BAV GB-2" dated June 2011.	
	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Contura i5 Panorama and i5 Double Door wood-burning insert stoves. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	Installation and lighting instruction manual reference "811175 IAC SE-EX Ci5-5" dated November 2012, additional installation instruction manual reference "811188 Kompletterande IAV Ci5 - 2" dated 14th September 2012 and supplementary instruction manual reference "811142 BAV GB - 4" dated August 2011.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a system to prevent closure of the air control vent beyond the 30% open position.	
Contura i30, i31, i40, i41 Wood burning inset appliances. Manufactured by Nibe AB, Box 134,	Instruction manual reference "811212 BAV SE-EX Ci30/Ci40-1" dated 14th June 2013 and supplementary operating instruction manual reference "811142 BAV GB–5" dated January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
SE-285 23, Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 27% open position.	
Coseyfire CF001SE. Manufactured by Stove World UK Limited, Unit 24 Folly Farm, Ramsdell, RG26 5RJ.	Installation and operating instructions reference "Version 1.0" dated April 2014. The appliance must be fitted with a modified secondary air supply fixed in the fully open position.	Wood logs ⁽¹⁾ .
Country Hearth EC410.	Instruction manual reference "852292" dated October 2014.	Wood logs ⁽¹⁾ .
Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.		
Country Hearth EC1100.	Instruction manual reference "852290" dated October 2014.	Wood logs ⁽¹⁾ .
Manufactured by United States Stove Company, 227 Industrial Park Road, South Pittsburg, TN 37380 USA.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 12mm open position.	
Cove 2 SR. Manufactured by A.J Wells and Sons Ltd. of Bishops Way, Newport, Isle of Wight, PO30 5WS.	Manufacturer's instruction manual reference "Cove2SR 07.09 IssB" dated July 2009. The appliance must be fitted with a permanent stop on air control to prevent closure beyond 14mm from the fully closed position.	Dry and split wood logs of a maximum length of 23cm ⁽¹⁾ .
Crator JS5500 multi- fuel stove. Manufactured by James Smellie Ltd., Unit N, Leona	Instruction manual reference "Crator multi-fuel stove instruction manual Issue 1" dated June 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Industrial Estate, Nimmings Road, Halesowen, West Midlands, B62 9JQ.		
CTC Ecoflex 15 and 20. Manufactured by Enertech AB, Box 313, S-341 26 Ljungby, Sweden.	Manufacturer's instructions reference "161 505 27 06/1" dated 20th February 2007.	Wood pellets ⁽¹⁾ .
D'Alessandro GSA 130. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "2.0-1-QGSA130XEN0612" dated 26th June 2012.	Wood chips ⁽¹⁾ .
D'Alessandro Termomeccanica CS and CSA boilers 40, 60, 80 and 100kW. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "Ver. 2.0 - QCSA100XXIT0209 [UK SMOKE CONTROL]" dated February 2009.	Wood pellets ⁽¹⁾ .
D'Alessandro Termomeccanica CS and CSA 130, 180, 230 and 300kW. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "Ver. 2.0 - QCSA2000XEN0209 [UK SMOKE CONTROL]" dated February 2009.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
D'Alessandro Termomeccanica CS and CSA 400, 500, 650, 800, 950, 1300, 1650 and 2000kW. Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	Instruction manual reference "Ver. 2.0 - QCSA2000XEN0209 [UK SMOKE CONTROL]" dated February 2009. The appliance must be fitted with the optional multi-cyclone.	Wood pellets ⁽¹⁾ .
D'Alessandro Termomeccanica CSI 20kW.	Instruction manual reference "Ver. 2.0 -QCSI100XXIT0209" dated February 2009.	Wood pellets ⁽¹⁾ .
Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.		
Dartmoor 5 SE. Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	Instruction manual reference "DM5 Issue 1" dated March 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	Wood logs ⁽¹⁾ .
Dean Stoves Clearburn Slimline 5 SE multifuel stove. Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	Instruction manual reference "SL5SE issue 1" dated 25th April 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 15mm open position.	Wood logs ⁽¹⁾ .
Dean Stoves Clearburn Small SE multifuel stove.	Instruction manual reference "CBS8SE issue 1" dated 25 April 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 15mm open position.	
Dean Stoves Dartmoor 6 SE Wood Burning Stove.	Operating instructions manual reference "DM6 issue 1" dated 2nd July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent secondary air spin wheel control closure beyond the 40% open position.	
Dean Stoves Dartmoor W5 SE Wood Burning Stove.	Operating instructions manual reference "DMW5 issue 1" dated 2nd July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent secondary air spin wheel control closure beyond the 40% open position.	
Dean Stoves Hembury 5 SE Wood Burning Stove.	Operating Instructions manual reference "HEM5SE issue" dated 2nd July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 0LS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	
Dean Stoves Hembury Slimline 5 SE multifuel stove.	Instruction manual reference "HEMSL5SE issue 1" dated 25 April 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 8mm open position.	
Dean Stoves Hembury 8 SE multifuel stove.	Instruction manual reference "HEM8SE issue 1" dated 25 April 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 8mm open position.	
Dean Stoves Junior 105 SE Wood Burning Stove.	Operating instructions manual reference "JR105SE Issue 1" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dean Forge Fabrication Ltd., Dean Prior, Buckfastleigh, Devon, TQ11 OLS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	
Design 800 Green wood burning stove.	Instruction manual reference "07DH8000A" dated November 2011.	Wood logs ⁽¹⁾ .
Manufactured by Bodart & Gonay Ltd., Rue De Lambinon, 3 Harze, Belgium, 4920.	The appliance must be fitted with a "UK kit for smokeless areas Design 800".	
Desire 5, Desire 5LS, Desire 6, Desire 6LS, Desire 7, Desire 7LS, Ignite 5, Ignite 5LS, Ignite 6, Ignite 6LS, Ignite 7 and Ignite 7LS multi fuel stoves. Manufactured by Broseley Fires Ltd, First Floor,	Installation and operating instructions manual reference "Mar 14/GB Issue 4" dated 3rd December 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slide beyond the 10mm open position.	Wood logs ⁽¹⁾ .
Unit B Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3GA.		
Di Lusso R4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge,	Instruction manual reference "JINDLU04 Rev E" dated 2nd December 2011 and instruction manual reference "JINDLU04SCK revB" dated 5th December 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with smoke control area kit JDLU0401.	
Di Lusso R5 inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINDLU05 Rev B" dated 10th December 2012 and additional instructions reference "JINDLU05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit JDLU0501.	Wood logs ⁽¹⁾ .
Di Lusso R6 inset	Instruction manual reference	Wood logs ⁽¹⁾ .
stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	"JINDLU06 Rev B" dated 10th December 2012 and instruction manual reference "JINDLU05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit JDLU0501.	Wood logs .
Dik Geurts Instyle 500, Dik Geurts Prostyle 500,	Installation instruction manual reference "DRU392187-409050-NL-NL-0614-5" dated March 2014 and user manual reference "DRU180452-363097-nl-NL-0614-3 1" dated 19th June 2014.	Wood logs ⁽¹⁾ .
Dik Geurts Instyle 550,	2021	
Dik Geurts Prostyle 550		
5 kW inset roomheaters.		
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, The Netherlands.		
Dik Geurts Instyle 600,	Installation instruction manual reference "DRU392187-410127-	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Dik Geurts Prostyle	NL-NL-0614-3" dated June	
600 5 kW inset	2014 and user manual reference	
roomheaters and	"DRU180452-363097-nl-NL-0614-3. 1" dated 19th June 2014.	
Dik Geurts Instyle 650,	1 dated 19th June 2014.	
Dik Geurts Prostyle 650 6kW		
Inset roomheaters.		
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, Nederland.		
Dik Geurts Instyle 700, Dik Geurts Prostyle 700 10kW inset roomheaters.	Installation instruction manual reference "DRU392187-408668-NL-NL-0314-7" dated June 2014 and user manual reference "DRU180452-363097-nl-NL-0614-3. 1" dated 19th June 2014.	Wood logs ⁽¹⁾ .
Manufactured by DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, Nederland.		
Dik Geurts Keld Low EA,	Installation manual reference "DRU392187-566405-nl- NL-0614-1 39"dated 19th June	Wood logs ⁽¹⁾ .
Keld High EA,	2014 and user manual reference	
Ivar Low EA,	"DRU180452-363097-nl-NL-0614-3" dated 19th June 2014.	
Ivar High EA,	The appliance must be fitted with a	
Jannik Medium Low EA 5kW wood- burning stoves.	modification to prevent closure of the secondary air control beyond 22mm open in its minimum position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by		
DRU Verwarming B.V, Postbus 1021, 6920 BA, Duiven, Ratio 8, 6921 RW Duiven, Nederland.		
Dimplex Langbrook 5kW Clean Burn Stove.	Instruction manual reference "08/51568/0 – Issue 3" dated 28th June 2012.	Wood logs ⁽¹⁾ .
Manufactured by Dimplex, GDC Group Ltd., Millbrook House, Grange Drive, Hedge End, Southampton, SO30 2DF.	The appliance must be fitted with a mechanical stop to prevent secondary air control slider closure beyond the 40% open position.	
Dimplex SE Selbourne 5.	Instruction manual reference "SE Selbourne 5 Issue 1" dated August 2009.	Wood logs ⁽¹⁾ .
Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	
Dovre 225 MF 4.6 kW multifuel stove.	Installation instructions and operating manual reference "03.27125.000" dated June 2013 and additional	Wood logs ⁽¹⁾ .
Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde,	instruction manual reference "PM1030 Issue 2" dated January 2014.	
Belgium.	The appliance must be fitted with the smoke control kit DV-225SCKIT.	
Dovre 250 (model DV-250).	Manufacturer's instructions reference "PM250 Issue 1".	Untreated dry wood ⁽¹⁾ .
Manufactured by Dovre NV, Nijverheidsstraat 18,	The appliance must be fitted with a permanent stop on the secondary air	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
BE-2381 Weelde, Belgium.	inlet to prevent closure beyond the 75% open position.	
Dovre 425 CBW wood burning stove. Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	Installation instructions and operating manual reference "03.27986.100" dated February 2012 and additional installation and operating instructions for use in smoke control areas reference "PM1191 Issue 1" dated December 2014. The appliance must be fitted with smoke control kit Part. No. DV425SZKIT to prevent closure of the secondary air control slider beyond the 15mm open position.	Wood logs ⁽¹⁾ .
Dovre 525MF 8 kW multifuel stove. Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	Installation instructions and operating manual reference "03.27109.100" dated February 2013 and smoke control kit additional installation and operating instructions reference "PM1030 Issue 2" dated January 2014. The appliance must be fitted with the smoke control kit DV-225SCKIT.	Wood logs ⁽¹⁾ .
Dovre Sense 100 (DV-SENSE100), 103 (DV-SENSE103), 200 (DV-SENSE200) and 203 (DV-SENSE203) wood burning stoves. Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	Installation instructions and operating manual reference "03.27151.000" dated July 2014 and smoke control kit additional installation and operating instructions for use in smoke control areas reference "PM1070 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond 8mm open.	Wood logs ⁽¹⁾ .
Dovre Vintage 30 (DV-VIN30, DV- VIN30WH, DV- TBVIN30 and DV- TBVIN30WH),	Instruction manual reference "03.27681.100" dated April 2011 and instruction manual reference "PM813 Issue 1" dated May 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Dovre Vintage 35	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
(DV-VIN35, DV-VIN35WH, DV-TBVIN35 and DV-TBVIN35 and DV-TBVIN35WH) and Dovre Vintage 50 (DV-VIN50, DV-VIN50WH, DV-TBVIN50WH) stoves. Manufactured by Dovre NV, Nijverheidsstraat 18, B-2381 Weelde, Belgium.	permanent stop preventing closure of the secondary air supply beyond 50%.	
Dunsley Yorkshire Stove. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Manufacturer's instructions reference "A/22160" dated 5th August 1998 as amended by manufacturer's instructions reference "D13" dated 4th December 2004.	Untreated dry wood (1); Peat or peat briquettes with, in either case, less than 25% moisture; Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight; CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels: and have a sulphur content not exceeding 1.8% of the total
		weight.
Dunsley Yorkshire Multifuel Stove. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Manufacturer's instructions reference "A/22160" dated 5th August 1998 as amended by manufacturer's instructions reference "D13" dated 4th December 2004.	Untreated dry wood (1); Peat or peat briquettes with, in either case, less than 25% moisture; Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight; CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process.
		constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.
Dunsley Yorkshire Multifuel Stove and Boiler. Manufactured by Dunsley Heat Ltd., Bridge Mills,	Manufacturer's instructions reference "A/22160" dated 5th August 1998 as amended by manufacturer's instructions reference "GHD/DUN4B/1" dated 4th October 2004.	Untreated dry wood ⁽¹⁾ ; Peat or peat briquettes with, in either case, less than 25% moisture; Union Coal Briketts,
Huddersfield Road,		manufactured by Rheinbraun AG of Germany comprising

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Holmfirth, Yorkshire, HD9 3TW.		lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight;
		CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.
Dunsley Yorkshire Woodburning Stove. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Manufacturer's instructions reference "D13W" dated 4th December 2004.	Untreated dry wood (1).
Dunsley Yorkshire Woodburning Stove and Boiler. Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Manufacturer's instructions reference "D13W" dated 4th December 2004 and manufacturer's instructions reference "GHD/DUN4B/1" dated 4th October 2004.	Untreated dry wood ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
E-Compact 15 wood pellet stove boiler.	Instruction manual reference "E-COMPACT 15 Outdoor Pellet Boiler v1.5" dated May 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	V1.3 dated May 2012.	
E-Compact 28 Pellet Boiler. Manufactured by Wood Energy Solutions Ltd., Donaskeigh,	Instruction manual reference "Installation & Operation Manual V.2.1" dated July 2012.	6mm wood pellets ⁽¹⁾ .
Tipperary, Co. Tipperary, Ireland.		
Earlswood. Manufactured by ACR Heat Products Ltd., Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Instruction manual reference "EW1MF technical manual" dated February 2009. When the primary air control is in the closed position, it must remain permanently open by 5mm and be prevented from closing fully by a screw.	Wood logs ⁽¹⁾ .
Ecco Stove E580. Manufactured by Landy Vent UK Ltd., Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	Instruction manual reference "Ecco Stove 580 manual" dated 12th December 2011.	Wood logs ⁽¹⁾ .
Ecco Stove E678. Manufactured by Landy Vent UK Ltd., Foster House, 2 Redditch	Instruction manual reference "01/11/3" dated 28th January 2011. The appliance must be fitted with a system to fix the secondary air (airwash) to a 4mm open position.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Road, Studley, Warwickshire, B80 7AX.		
Ecco Stove E730. Manufactured by Landy Vent UK Limited, Foster House, 2 Redditch Road, Studley, Warwickshire B80 7AX.	Instruction manual reference "020114/D002" dated 2nd January 2014. The appliance must be fitted with a mechanical stop to prevent the secondary air control closing beyond the 4 mm open position. All other air controls must be permanently fixed in position.	Dry wood logs ⁽¹⁾ .
Ecco Stove E850. Manufactured by Landy Vent UK Ltd., Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	Instruction manual reference "02/10" dated 10th October 2010. The appliance must be fitted with a system that prevents closure of the secondary air flaps beyond 4mm (3 turns).	Wood logs ⁽¹⁾ .
Ecofire Barbara wood pellet stove boiler. Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual reference "cod. 004770900" dated October 2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference "004723000" dated January 2012.	Wood pellets ⁽¹⁾ .
Ecofire Giulia Idro, Ecofire Kelly Idro Plus and Ecofire Tania Idro wood pellet stove boilers. Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual reference "cod. 004770432" dated February 2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference "004723000" dated January 2012.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Eco-Ideal Eco 1 Stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINECO01 revC" dated 20th July 2011. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Dry wood logs ⁽¹⁾ .
Eco-Ideal Eco 2 Stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINECO02 revC" dated 20th July 2011. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Dry wood logs ⁽¹⁾ .
Eco-Ideal Eco 3 multifuel stove. Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Exeter, EX5 4RJ.	Installation and operating instructions reference "JINECO03 RevB" dated 17th July 2014.	Wood logs ⁽¹⁾ .
Eco-Ideal Eco 4 Stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINEC004 revC" dated 20th July 2011.	Dry wood logs ⁽¹⁾ .
ECO-Ideal Eco 5 multifuel stove. Manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge, Camelford,	Installation and operating instructions ref. "JINECO05 RevB" dated 20th June 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 40% open position.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Cornwall, PL32 9TT.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Eco-Ideal Eco 6 Stove.	Instruction manual reference	- (1)
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	"JINEC006 revC" dated 20th July 2011.	Dry wood logs ⁽¹⁾ .
ECO-Ideal Inset Eco 8 multi-fuel stove.	Installation and operating instructions manual reference	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge,	"JINECI08 Rev B" dated 14th February 2013 and modification instructions reference "JINEC108 Slider Stop Rev B" dated 25th September 2013.	
Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Effecta Komplett 20 boiler.	Instruction manual reference "Rev. EA.013-10-18" dated 18th October 2013.	Wood pellets (1).
Manufactured by Effecta AB	2013.	
Västra Rågdalsvägen 21,		
434 96, Kungsbacka, Sweden.		
Effecta Komplett III 25kW and Effecta Komplett III light 25kW pellet boilers.	Installing, maintenance, service and assembly instruction manual reference "Rev. EA. 014-02-25" dated 25th February 2014.	Wood logs ⁽¹⁾ .
Manufactured by		
Effecta Energy Solutions AB, Västra Rågdalsvägen 21,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
434 99 Kungsbacka, Sweden.		
Effecta Komplett III 35kW and Effecta Komplett III light 35kW pellet boilers.	Installing, maintenance, service and assembly instruction manual reference "Rev. EA. 014-02-25" dated 25th February 2014.	Wood logs ⁽¹⁾ .
Manufactured by Effecta Energy Solutions AB, Västra Rågdalsvägen 21, 434 99 Kungsbacka, Sweden.		
Effecta Lambda 25, 35 and 60 boilers.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Effecta AB	"Rev.EA. 013-10-20" dated 20th October 2013.	
Västra Rågdalsvägen 21,		
434 96, Kungsbacka, Sweden.		
Ekoheat 900 9.4kW,	Installation and operating instructions manual reference "CDOC000682"	Wood logs ⁽¹⁾ .
Ekoheat 1500 15kW.	dated May 2013.	
Ekoheat 2500 24.9kW Ekoheat 4000 42.7kW, pellet boilers.		
Manufactured by EkpowerAps, Falstervej 285500, Middelfart, Denmark.		
Ekol Clarity 5 woodburning stove.	Installation and operating instructions manual reference "Ekol Clarity 5 Manual 1.0" dated 4th July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Saltfire Stoves Ltd., Station Works, Johns	The appliance must be modified to allow an ingress of air through the secondary air control.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	,
Dood Worshore	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Road, Wareham, BH20 4BG.	The appliance must be fitted with a stop in the tertiary air system to maintain a gap of 4mm between the circular plates and the openings at the rear of the appliance measured by the maximum aperture resulting from the opening.	
Ekol Clarity 8 wood- burning stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions manual reference "Ekol Clarity 8 Manual 1.0" dated 4th July 2013.	Wood logs ⁽¹⁾ .
Ekol Clarity 12 wood- burning stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions manual reference "Ekol Clarity 12 Manual 1.0" dated 4th July 2013. The appliance must be modified to allow an ingress of air through the secondary air control. The appliance must be fitted with a stop in the tertiary air system to maintain a gap of 4mm between the circular plates and the openings at the rear of the appliance measured by the maximum aperture resulting from the opening.	Wood logs ⁽¹⁾ .
Ekol Clarity 20 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions reference "Ekol Clarity 20 Boiler Wood Version, Manual Version 1.1" dated 22nd January 2014. The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 25mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	Wood logs ⁽¹⁾ .
Ekol Clarity 30 Wood Burning Stove.	Installation and operating instructions reference "Ekol Clarity 30 Boiler	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	The fireplace must be installed, maintained and operated in accordance with the following specifications: Wood Version, Manual Version 1.1" dated 22nd January 2014. The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 30mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ekol Clarity Double Sided wood-burning stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating Instructions manual reference "Ekol Clarity Double Sided Manual 1.0" dated 4th July 2013. The appliance must be modified so that when the primary and secondary air controls are in the fully closed position they will be fixed at 3.5mm open. The appliance must be fitted with a tertiary air control system comprising two 7mm holes on each side of the appliance and a fixed opening of 4 cm² on the underside of the stove.	Wood logs ⁽¹⁾ .
Ekol Inset 5 wood- burning inset stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions manual reference "Ekol Inset 5 Manual 1.0" dated 4th July 2013. The appliance must be modified so that when the secondary air supply is in its fully closed position it will be fixed at 4mm open.	Wood logs ⁽¹⁾ .
Ekol Inset 8 wood- burning inset stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instruction manual reference "Ekol Inset 8 Manual 1.0" dated 4th July 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Elegance Junior UK and Elegance Junior Wall UK 5kW wood burning stoves.	Instruction manual reference "User's manual Revision 1, dated 28th November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	The appliance must be modified to fix the secondary air control to 698mm ² in its minimum position.	
Ellipse. Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030,	Instruction manual reference "7196901-Rev.09" dated 22nd December 2010. The appliance must be fitted with a mechanical stop to prevent closure of	Wood logs ⁽¹⁾ .
Vicenza, Italy.	the secondary air control beyond the 40% open position.	
En-tech model ENP 10, 15, 18, 25 and 35 boilers.	Manufacturer's installation manual reference "IMENP 10-35 11/2009" for the Firefox pellet boiler dated November 2009.	Wood pellets ⁽¹⁾ .
Manufactured by En-tech Energietechnikpprodukt Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria.	tion,	
En-tech model PK15 and 25 boilers.	Installation manual reference "IMPK PK 15/25 11/2009 EN" dated November 2009.	Wood pellets (1).
Manufactured by En-tech Energietechnikpprodukt Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
En-tech model PK45 boilers.	Installation manual reference "IMPK PK 45 11/2009 EN" dated November 2009.	Wood pellets ⁽¹⁾ .
Manufactured by En-tech Energietechnikpproduk Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria.		
Endress USF-W 250. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual reference "Operating and Maintenance manual Endress USF -W250" reference "EMAN – USFW250" dated March 2010.	Wood chips and pellets (1).
Endress USF-W 350. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress USF –W350" reference "EMAN – USFW350" dated March 2010.	Wood chips and pellets (1).
Endress USF-W 500. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress USF -W500" reference "EMAN – USFW500" dated March 2010.	Wood chips and pellets ⁽¹⁾ .
Endress USF-W 800. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße	Instruction manual "Operating and Maintenance manual Endress USF –W800" reference "EMAN – USFW800" dated March 2010.	Wood chips and pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
10 D 01500	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
18, D-91593 Burgbernheim.		
Endress USF-W 1000. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress USF—W1000" reference "EMAN—USFW1000" dated March 2010.	Wood chips and pellets ⁽¹⁾ .
Endress VR-S 300. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress VR-S300" reference "EMAN – VRS300" dated March 2010.	Wood chips and pellets (1).
Endress VR-W 400. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress VR –W400" reference "EMAN – VRW400" dated March 2010.	Wood chips and pellets (1).
Endress VR-W 600. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress VR-W600" reference "EMAN – VRW600" dated March 2010.	Wood chips and pellets (1).
Endress VR-W 900. Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestraße 18, D-91593 Burgbernheim.	Instruction manual "Operating and Maintenance manual Endress VR-W900" reference "EMAN – VRW900" dated March 2010.	Wood chips and pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
EOS 30 346kW output wood pellet boiler with multicyclone.	Use and maintenance manual reference "Uniconfort EOS30 Manual v1" dated July 2011.	Wood pellets (1).
Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.		
EOS 35 407kW output wood pellet boiler with multicyclone.	Use and maintenance manual reference "Uniconfort EOS35 Manual v1" dated July 2011.	Wood pellets (1).
Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.		
EOS 40 464kW output wood pellet boiler with multicyclone.	Use and maintenance manual reference "Uniconfort EOS40 Manual v1" dated July 2011.	Wood pellets (1).
Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.		
EOS 60 700kW output wood pellet boiler with multicyclone.	Installation instruction manual reference "K135-07332 Uniconfort MUN v 2" dated September 2010.	6mm diameter wood pellets ⁽¹⁾ .
Manufactured by Uniconfort srl. Via dell'Industria 21, 35018, San Martino Di Lupari, (PD) Italy.		
Esse 1 wood burning stove.	Installation and User Instructions reference "ONE-SE-104-29.10.2014" dated 29 October 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Limited, Ouzledale Foundry, Long	The appliance must be fitted with a mechanical stop to prevent secondary	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ing, Barnoldswick, Lancashire, BB18 6BN.	air control closure beyond the 50% open position.	
Esse 100 SE Smoke Exempt woodburning stove. Manufactured by	Manufacturer's instruction manual reference "100 SE Issue 1" dated February 2009.	Untreated dry wood with a maximum moisture content of 20% maximum length of 200 mm and maximum width or diameter of 120 mm (1).
ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswisk, Lancashire, BB18 6BN.		
Esse 100DD SE 5kW stove.	Instruction manual reference "10/11 (PP) INSTR.ST-100DDSE/u" dated October 2011.	Wood logs ⁽¹⁾ .
Manufactured by ESSE Engineering Ltd., Ouzedale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a system to prevent closure of the air controls beyond the 50% open position.	
Esse 125 SE. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18	Instruction manual reference "Esse 125SE Issue 1" dated August 2009. The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	Wood logs ⁽¹⁾ .
6BN.	Instruction manual reference "200 SE	(I)
Esse 200XK-SE, DD-SE, Podium-SE & Contemporary-SE Smoke Exempt Wood Burning Stoves.	Instruction manual reference "200-SE-I03-310114" dated 31st January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Barnoldswick, BB18 6BN.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Esse 301 SE stove. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual reference "v45" dated 9th November 2010. The primary air control must not be fully air tight when closed.	Wood logs ⁽¹⁾ .
Esse 350 stove. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual reference "v45" dated 9th November 2010.	Wood logs ⁽¹⁾ .
Esse 500 SE & 525 SE Wood Burning Stoves. Manufactured by Esse Engineering Limited, Long Ing, Barnoldswick Lancashire, BB18 6BN.	Installation and user instructions reference "1.01" dated October 2013.	Wood logs ⁽¹⁾ .
Esse 700-SE Smoke Exempt Wood Burning Stove. Manufactured by Esse Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.	Instruction manual reference "700-SE-I03-310114" dated 31st January 2014.	Wood logs ⁽¹⁾ .
Esse 990N wood burning cooker & Esse	Operating instructions reference "1" dated January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
990D wood burning cooker with boiler.		
Manufactured by Esse Engineering Limited, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.		
Esse 1622 inset stove. Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Installation and operation manual reference "1622/Integra INSET revision c" dated July 2010. The appliance must be fitted with a mechanical stop to fix secondary air control fully open.	Dry wood logs ⁽¹⁾ .
Esse Plus 1 wood burning cooker & Esse Plus 1D wood burning cooker with boiler. Manufactured by Esse Engineering Limited, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.	Installation commissioning and operating instructions reference "1" dated January 2014.	Wood logs ⁽¹⁾ .
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers. Manufactured by ETA Heiztechnik Gesellschaft mit	Instruction manual reference "HACK20-200_Bedienung_2011-06_I dated June 2011. The appliance must be fitted with an integrated flue gas recirculation system must be used when using	Wood chips ⁽¹⁾ .
beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	wood chips with a moisture content below 15%.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers.	Instruction manual reference "HACK20-200_Bedienun 2011-06_EN" dated June 2011.	Wood pellets (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	An integrated flue gas recirculation system must be used when burning wood pellets.	
ETA Hack 45 woodchip boiler.	Operation manual reference "0000000079 V.003" dated 23rd June 2014.	Wood chips (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A4716 Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%.	
ETA Hack 45 woodchip boiler	Operation manual reference "0000000079 V.003" dated 23rd June 2014.	Wood pellets (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A4716 Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	Integrated flue gas recirculation system must be used when using wood pellets.	
ETA PC 20, 25 and 32 wood pellet boilers.	Instruction manual reference "PC20-32_Bedienung_2011-06_EN" dated June 2011.	Wood pellets (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
(GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
ETA PE-K 35, 50, 70 and 90 wood pellet boilers.	Instruction manual reference "PE-K35-90_Bedienung_2011-06_EN" dated June 2011.	Wood pellets ⁽¹⁾ .
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
ETA PE-K 45 wood pellet boiler.	Operation manual reference "0000000083 V.007" dated 25th June 2014.	Wood pellets (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A4716 Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	2014.	
ETA PU 7, 11 and 15 wood pellet boilers.	Instruction manual reference "PU7-15_Bedienung_2011-06_EN" dated June 2011.	Wood pellets ⁽¹⁾ .
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ETA SH 20, 30, 40, 50 and 60 wood gasification boilers.	Instruction manual reference "SH20-60_Bedienung_2011-06_EN" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
eVolution 4 Inset. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "eVo 4&7 Inset MS11-11" dated 9th November 2011. The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 15mm open position.	Wood logs ⁽¹⁾ .
eVolution 5 model number M-EVO5. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "eVo 5 MS07-11" dated 8th July 2011. The appliance must be fitted with a system that prevents the closure of the air control to less than 70% open.	Wood logs ⁽¹⁾ .
eVolution 7 Inset. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "eVo 4&7 Inset MS11-11" dated 9th November 2011. The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 8mm open position.	Wood logs ⁽¹⁾ .
eVolution 26 boiler stove. Manufactured by Broseley Fires	Instruction manual reference "MS10-11c" dated 9th January 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 40% open position.	
Evotherm P50, P100, P120, P150, P170, P200 pellet boilers.	Manufacturer's instructions operating manual reference "Version 1/2010/ Rev. 4.21".	Wood pellets (1).
Manufactured by Evotherm, Heiztechnik Vertriebs Gesellschadft mit beschrankter Haftung (GmbH), Seeleiten 24, AT 5120, St Pantaleon, Austria.		
Evoworld HS50 boiler.	Operation manual reference "OM_HS50_14 Version 1.2" dated January 2014.	Wood chips (1).
Manufactured by Evoworld		
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS75 ECO boiler.	Operation manual reference "OM_HS75_14 Version 1.2" dated January 2014.	Wood chips (1).
Manufactured by Evoworld	Junuary 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS100 ECO boiler.	Operation manual reference "OM_HS100_14 Version 1.2" dated January 2014	Wood chips (1).
Manufactured by Evoworld		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS120 ECO boiler.	Operation manual reference "OM_HS120_14 Version 1.2" dated January 2014.	Wood chips (1).
Manufactured by Evoworld	January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS150 ECO boiler.	Operation manual reference "OM_HS150_14 Version 1.2" dated January 2014.	Wood chips (1).
Manufactured by Evoworld	January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS170 ECO boiler.	Operation manual reference "OM_HS170_14 Version 1.2" dated January 2014.	Wood chips (1).
Manufactured by Evoworld	January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		
Austria.		
Evoworld HS200 ECO boiler.	Operation manual reference "OM_HS200_14 Version 1.2" dated	Wood chips (1).
Manufactured by Evoworld	January 2014.	
Seeleiten 24, 5120 St. Pantaleon,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Austria.		
Extraflame: Babyfiamma, Bella and Bella Lux, Clementina Comfort Maxi, Contessa, Divina, Divina Plus and Divina Steel, Duchessa and Duchessa Steel, Ecologica, Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina, Preziosa. Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	Manufacturer's instructions reference "004275101 011" dated 5th March 2007.	Wood pellets ⁽¹⁾ .
Extraflame Comfort Mini. Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	Manufacturer's instructions reference "004275115 REV 005" dated 2nd October 2006.	Wood pellets ⁽¹⁾ .
Extraflame Idro. Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	Manufacturer's instructions reference "004275128 REV 002" dated 28th August 2006.	Wood pellets ⁽¹⁾ .
Extraflame Lucrezia Idro and Lucrezia Steel.	Manufacturer's instructions reference "004275110 REV 011" dated 12th July 2006.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.		
FDC5 Stove.	Instruction manual reference "FDC Issue 02" dated April 2012.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
FDC5i inset stove.	Instruction manual reference "FDCi Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
FDC5iT Taper inset stove.	Instruction manual reference "FDCiT Issue 1" dated April 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
FDC5iW Wide inset stoves.	Instruction manual reference "FDCi Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
FDC5W Wide stove.	Instruction manual reference "FDC Issue 02" dated April 2012.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
FDC 8 Freestanding Wood Burning Stove.	Instruction manual reference "FDC issue 03" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
FDC 8i Inset Wood Burning Stove.	Instruction manual reference "FDCi issue 03" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position.	
Fireball. Manufactured by	Instruction manual reference "7196801-Rev.07" dated 22nd December 2010.	Wood logs ⁽¹⁾ .
LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Firebelly FB 5kW woodburning stove.	Instruction manual reference "EZKA/12 090-3 dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Firebelly Stoves Ltd., Unit B, Marshall Hall Mills, Elland, HX5 9DU.		
Firebelly FB2 12Kw wood burning stove.	Instruction manual reference "EZKA/12 090-2" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Firebelly Stoves Ltd., Unit B, Marshall Hall Mills, Elland, HX5 9DU.	The appliance must be fitted with a permanent stop to fix the secondary air control to 8mm open when in the closed position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Firebird SE 5kW multifuel dry inset room heater.	Instruction manual reference "Print Revision 01: July 2014" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Firebird Heating Solutions Limited, Ballymakeera, Co. Cork, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 32mm open position.	
Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405 Clean Burn and Sirius 405 Classic Clean Burn. Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual reference "FF5CBII REV: A" dated June 2011. The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs ⁽¹⁾ .
Firefox 5CB (4.9kW); Vega 100CB (4.9kW); Sirius 405CB (4.9kW); Flame 5CB (4.9kW). Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual reference "FFXCBA" dated January 2010.	Wood logs ⁽¹⁾ .
Firefox 8 Clean Burn, Gallery Classic 8 Clean Burn, Sirius 545 Clean Burn and Sirius 545 Classic Clean Burn.	Instruction manual reference "FF8CB REV: A" dated June 2011. The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.		
Fireline FGi5 stove. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	Instruction manual reference "FGi.FPi.FXi Issue 06" dated March 2012. The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	Wood logs ⁽¹⁾ .
Fireline FGi8, FXi8, & FPi8 Cassette Inset Wood Burning Stoves.	Instruction manual reference "FGi.FPi.FXi issue 07" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position.	
Fireline FP5W and FX5W Freestanding stove.	Instruction manual reference "FX.FP.Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	
Fireline FPi5T, FGi5T and FXi5T Taper inset stoves.	Instruction manual reference "FXiT.FPiT.FGiT Issue 01" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fireline FPi5W, FGi5W and FXi5W Wide inset stoves.	Instruction manual reference "FGi.FPi.FXi Issue 06" dated March 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
Fireline FX8, & FP8 Freestanding Wood Burning Stoves.	Instruction manual reference "FX.FP. Issue 08" dated September 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
Fireline FXi 5kW, Fireline FPi 5kW, Fireline FX5 and Fireline FP5. Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	Instruction manual reference "Issue 03" dated March 2010. The appliance must be fitted with a system that prevents the closure of the secondary air control beyond the 3.5mm open position.	Wood logs ⁽¹⁾ .
Fireline Purevision 5kW Freestanding Wood burning Stove.	Installation and operating instructions manual reference "Purevision Freestanding Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 18mm open position.	
Fireline Purevision 5kW i5 Inset	Installation and operating instructions manual reference "Purevision Inset Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Wood burning Stove.	The appliance must be fitted with a mechanical stop to prevent air	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	supply closure beyond the 18mm open position.	
Fireline Purevision 5kW Wide Freestanding Wood burning Stove.	Installation and operating instructions manual reference "Purevision Freestanding Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 15mm open position.	
Fireline Purevision 5kW i5 Wide Inset Wood burning Stove.	Installation and operating instructions manual reference "Purevision Inset Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 15mm open position.	
Fireline Purevision 8.5kW Freestanding Wood burning Stove.	Installation and operating instructions manual reference "Purevision Freestanding Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 22mm open position.	
Fireline Purevision 8.5kW i8.5 Inset Wood burning Stove.	Installation and operating instructions manual reference "Purevision Inset Issue 02" dated January 2014.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent air supply closure beyond the 22mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Firematic 25, 50, 90 and 150. Manufactured by HERZ Armaturen Ges.m.b.H, Richard-Strauss-Straße 22, A-1230 Wien, Austria.	Manufacturer's instructions reference "Bedienungsanleitung Firematic V 1.1 ENG doc" dated June 2005.	Chipped wood, wood pellets, or planed wood shavings ⁽¹⁾ .
Firematic 45 and 60. Manufactured by HERZ Armaturen Ges.m.b.H., Richard- Strauss-Straße 22, A-1230 Wien, Austria.	Instruction manual reference "05.007 Operating Instructions – FM (1Ph) 20 35 45 60 v2.3" dated August 2009.	Wood pellets conforming to ÖNORM M7135 with diameter of 6mm or wood chips up to a maximum size of 50mm and maximum water content 35% (1).
Firematic FM 130, FM 151, FM 180 and FM 199. Manufactured by Herz Energietechnik GmbH, Herzstraße 1, 7423 Pinkafeld, Austria.	Instruction manual reference "Operating Instructions Herz firematic 130 – 199 BioControl" version Betriebsanleitung firematic 20-201 BioControl Englisch V 3.1.	Wood chips and wood pellets (1).
Firenzo Aucklander stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "AL" dated 15th January 2013 and instruction manual reference "AU" dated 1st February 2013. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5mm open position.	Wood logs ⁽¹⁾ .
Firenzo Bronte stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "BI" dated 15th January 2013 and instruction manual reference "BU" dated 1st February 2013. The appliance must be fitted with a mechanical stop to prevent air control	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: slots closure beyond the 6.5mm open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Firenzo Contessa stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "CI" dated 15th January 2013 and instruction manual reference "CU" dated 1st February 2013. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6mm open position.	Wood logs ⁽¹⁾ .
Firenzo Fires Hastings 4.8kW wood burning stove. Manufactured by Firenzo Fires,	User manual reference "HU 2014-10-16" dated 16th October 2014 and installation manual reference "HI 2014-10-16" dated 16th October 2014.	Wood logs ⁽¹⁾ .
98 Niven Street, Napier4142, New Zealand.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 6mm open position.	
Firenzo Lady Kitchener stove. Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street, Napier 4142, New Zealand.	Instruction manual reference "LKI" dated 15th January 2013 and instruction manual reference "LKU" dated 1st February 2013. The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5mm open position.	Wood logs ⁽¹⁾ .
Firenzo Napier 4.8kW free standing wood burning stove. Manufactured by	Installation manual reference "UKNapierInstall/4.8/v1 dated 24th January 2014 and instruction manual reference "UKNapierUser/4.8/v1 dated 24th January 2014.	Dry wood logs ⁽¹⁾ .
Hewitsons ltd, 98 Niven street, Onekawa, Napier, New Zealand.	The appliance must be fitted with a permanent stop to prevent closure of the air slide beyond 7mm.	
Firenzo Wellingtonian stove.	Instruction manual reference "WI" dated 15th January 2013 and	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Firenzo Woodfires UK Ltd., 98 Niven Street,	instruction manual reference "WU" dated 1st February 2013.	
Napier 4142, New Zealand.	The appliance must be fitted with a mechanical stop to prevent air control slots closure beyond the 6.5mm open position.	
Firestorm 4.5 SE. Manufactured by The	Instruction manual reference "4.5KW SE Issue (6928) 1" dated 28th April 2012.	Wood logs ⁽¹⁾ .
Heat Resistant Glass Company Ltd., Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The appliance must be fitted with a stop that will only allow a minimum 3mm air gap between the air control plate and the appliance when the secondary air is turned down to its minimum position.	
Firestorm 6.5 SE. Manufactured by The Heat Resistant Glass	Instruction manual reference "6.5KW SE Issue (6928) 3" dated 28th April 2012.	Wood logs ⁽¹⁾ .
Company Ltd., Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The appliance must be fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.	
Firestorm 10 SE. Manufactured by The Heat Resistant Glass	Instruction manual reference "10KW SE Issue (6928) 2" dated 28th April 2012.	Wood logs ⁽¹⁾ .
Company Ltd., Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The appliance must be fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.	
Firewarm 4SE stove.	Instruction manual reference "FW468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial	The appliance must be fitted with a system to prevent closure of the	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Estate, Naas Road, Dublin 12, Ireland.	secondary air control beyond 5mm open.	
Firewarm 06C inset stove.	Instruction manual reference "FW06C" dated 26th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Firewarm 6SE stove.	Instruction manual reference "FW468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	
Firewarm 8SE stove.	Instruction manual reference "FW468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	
Firewarm 11C Inset stove.	Instruction manual reference "FW11C" dated 26th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Firewarm FW5i Multi- fuel inset stove.	Installation and operating instructions reference "FW5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial	The appliance must be fitted with a mechanical stop to prevent secondary	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Estate, Naas Road, Dublin 12, Ireland.	The fireplace must be installed, maintained and operated in accordance with the following specifications: air control closure beyond 3.5mm open.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Flatford 5K, Barrington 5K and Hampstead 5K wood burning stoves. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH5K – V1" dated 14th March 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 18mm open position.	Wood logs ⁽¹⁾ .
Fogo Montanha Versatile S600SE, Versatile S600 SE Table, Versatile S600 SE Spider, Versatile S600 SE Square,	Instruction manual reference "S600 – UK V1" dated 2014. The appliance must be fitted with a permanent stop or other measure to prevent closure of the air control beyond the 40% open position.	Wood pellets ⁽¹⁾ .
Versatile S600 SE Cube,		
Versatile S600 SE 2X Cube and Versatile S600 SE Round wood-burning stoves manufactured by		
Fogo Montanha (Solzaima, S.A.)		
Rua dos Outarelos, 111 3750-362 Belazamia do Chao, Portugal.		
Franco Belge Model 134 08 11 Savoy EA (8kW output) wood burning stove.	Instructions manual reference "1290-1" dated 9th July 2009.	Wood logs ⁽¹⁾ .
Manufactured by Franco Belge, Staub		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.		
Franco Belge Model 134 08 09 Savoy Mk II Elegance multifuel stove with KEA 13408 smoke control kit.	Instructions manual reference "1290-1" dated 9th July 2009.	Wood logs ⁽¹⁾ .
Manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.		
Franco Belge Montfort MK2 wood burning stove.	Instruction manual reference "1295-3" dated 17th November 2009.	Wood logs ⁽¹⁾ .
Manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	
Fröling Lambdamat commercial wood chip boiler models 500, 750 and 1000.	Operating and installation manual reference "B 069 01 04" dated February 2004.	Wood chips (1).
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Froling P1 7, 10, 15 and 20 pellet boilers. Manufactured by Froling Heizkessel	Operating instructions manual reference "B1000013_en Edition 15/07/2014" dated 15th July 2014.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
und Behalterbau GmbH, A-4710 Grieskirchen, Industriestrasse 12, Austria.		
Froling P4 45 pellet boiler.	Operating instructions manual reference "BO870114_en Edition 18/07/2014" dated 18th July 2014.	Wood pellets (1).
Manufactured by Froling Heizkessel und Behalterbau GmbH, A-4710 Grieskirchen, Industriestrasse 12, Austria.		
Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 pellet boilers.	Instruction manual reference "BO430408 _en" dated July 2009.	Wood pellets with a diameter of 6mm ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Fröling P4 80 and P4 100 wood pellet boilers.	Instruction manual reference "B043 – Version 8" dated May 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Froling S4 Turbo 15 15kW; Froling S4 Turbo 22 22kW; Froling S4 Turbo 28 28kW; Froling S4 Turbo 34 34kW;	Assembly instruction manual reference "M0970208" dated November 2008 and operating instruction manual reference "B0510108" dated November 2008.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Froling S4 Turbo 40 40kW; Froling S4 Turbo 50 50kW; and Froling S4 Turbo 60 60kW.		
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Froling T4 130 and 150 wood chip and pellet boilers.	Operating instructions manual reference "BO830113_en Edition 06/11/2013" dated 6th November 2013.	Wood pellets or wood chips (1).
Manufactured by Froling Heizkessel und Behalterbau GmbH, A-4710 Grieskirchen, Industriestrasse 12, Austria.		
Fröling T4 24, 30, 40, 50, 60, 75, 90, 100 and 110kW boilers.	Instruction manual reference "B071 - Version 05" dated May 2012.	Wood pellets or wood chips (1).
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Fröling Turbomatic 28, 35, 48 and 55. Manufactured by Fröling Heizkesselund Behälterbau Ges.m.b.H., Industriestraße 12,	Installation instructions reference "M 060 01 03" dated November 2003 and operating instructions reference "99229a" dated August 2002.	Wood chips with less than 35% moisture content that meet ÖNORM (a) M 7133: 1998 size class G30 or wood pellets of 6mm diameter and a moisture content below 10% (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
A-4710 Grieskirchen, Austria.		
Fröling Turbomatic 85, 100 and 110. Manufactured by Fröling Heizkesselund Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.	Installation instructions reference "M 060 01 03" dated November 2003 and operating instructions reference "99229a" dated August 2002.	Wood chips with less than 35% moisture content that meet ÖNORM (a) M 7133; 1998 size class G30 or G50, wood pellets of 6mm diameter and a moisture content below 10% ⁽¹⁾ .
Fröling Turbomat 150 and 220.	Manufacturer's instructions reference "BO310003" dated August 2003.	Wood pellets, or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Fröling Turbomat 320 and 500.	Manufacturer's instructions reference "B0340004" dated November 2004.	Wood pellets, or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Fröling TX150 150kW boiler with Exhaust Gas Recirculation device. Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12,	Installation instruction manual reference "M1130009" dated September 2010 and operating instruction manual reference "B 067 00 09" dated September 2010.	Wood chips with a moisture content \leq 30% and a maximum cross sectional area of 5cm2 or wood pellets with a moisture content of \leq 10% and a maximum diameter of 10mm $^{(1)}$.

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
A-4710 Grieskirchen, Austria.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fröling TX 200 199kW and TX 250 250kW boilers with Exhaust Gas Recirculation device.	Instruction manual reference "B067 – Version 03" dated May 2012.	Wood pellets or wood chips (1).
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Fröling:	Operating instructions reference "B0760212" en Edition 09/10/2012"	Wood logs or wood pellets (1).
SP Dual 15kW boiler;	dated 9th October 2012.	
SP Dual 22kW boiler;		
SP Dual 28kW boiler;		
SP Dual 34kW boiler; and		
SP Dual 40kW boiler.		
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestraße 12, A-4710 Grieskirchen, Austria.		
Future Fires Panoramic FX1.	Instruction manual reference "PANFXREV2" dated 31st October	Wood logs ⁽¹⁾ .
Manufactured by Gen- Fab Ltd., Swinton Bridge Industrial Estate, Whitelee Rd, Swinton, S64 8BH.	2012.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Gilles HPK-RA 13kW, 15kW, 20kW, 25kW, 30kW, 35kW, 40kW, 45kW, 49kW, 60kW, 70kW, 75kW, 85kW, 95kW, 100kW, 120kW, and 145kW. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Manufacturer's instructions reference "Gilles/0-145/1" dated January 2007.	Wood pellets, or wood chips ⁽¹⁾ .
Gilles HPK-RA 160. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	Instruction and operating manuals reference "BD-200-01a-01" dated November 2008, "BD-200-01a-02" dated November 2008, "BD-200-01a-03" dated November 2008, "BD-200-01a-04" dated November 2008, "BD-200-01a-06" dated November 2008, "BD-200-03a-07" dated November 2008, and "BD-200-03a-09" dated November 2008.	Wood chips and wood pellets (1).
Gilles HPK USK 150kW, 180kW, 240kW and 300kW.	Manufacturer's instructions reference "Gilles/150-300/1" dated January 2007.	Wood pellets, or wood chips ⁽¹⁾ .
Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.		
Gilles HPK USK 360kW. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str.	Manufacturer's operating instructions reference "Gilles 360/1" dated January 2008.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
16A-4810 Gmunden, Austria.		
Gilles HPKI-K 180, 195, 240, 300, 360, 450, 550, 700, 900, 995, 1200 and 1600. Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str.	Instruction manual reference "Operating Instruction HPKI-K Underfeed Stoking. 1-general-hpki-k underfeed stoking" dated November 2008.	Wood chips and pellets ⁽¹⁾ .
16A-4810 Gmunden, Austria.		
Gilles HPKI-R 999 kW biomass boiler manufactured by	Installation, operation and maintenance manual reference "BD-HPKI-R-999-01.1 Version 02/2014" dated 23rd July 2014.	Wood chips (1).
Gilles Energie und Umwelttechnik GmbH & Co KG Limited, Koaserbauerstraβe, A-4180 Gmuden, Austria.	The appliance must be fitted with cyclone dust arrestment.	
Gilles UTSK 450kW, 550kW, 700kW, 900kW, 1200kW, and 1600kW Boilers.	Manufacturer's operating instructions reference "Gilles 360/1" dated January 2008.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Gilles Energie – und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.		
Gozney G1200/W, G1400/W, G1600/W and G1800/W wood- burning pizza ovens.	Operational manual reference "Version 1.1" dated July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Gozney Ltd., Units 18 & 19, Radar Way, Christchurch Business		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Park, The Runway, Christchurch, BH23 4JE.		
Grant Spira Condensing Wood Pellet Boiler 6-26kW model number WPS626 and 9-36kW model number WPS936.	Instruction manual reference "IRL NO.012 Rev; 1" dated April 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Grant UK Ltd., Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU.		
Graphite 5 model number GR905 4.9 kW multifuel stove.	Instruction manual reference "GR905/UK/NI/ROI/V3 18-07-14" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Graphite 8 model number GR908 8kW multifuel stove.	Instruction manual reference "GR908/UK/NI/ROI/V4-D 18-07-14" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal.	
Greencast 5MF Traditional, Greencast 5MF Modern, Greencast 8MF	Installation and operating instructions manual reference "Greencast MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Traditional and	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with the	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Greencast 8MF Modern multifuel stoves.	manufacturer's smoke control kit.	
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Greencast 5WD Traditional and Greencast 5WD Modern woodburning stoves.	Installation and operating instructions manual reference "Greencast MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Greencast 8WD Traditional and Greencast 8WD Modern wood-burning stoves.	Installation and operating instructions manual reference "Greencast MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Green Energy Engineering PROPEL P70 and P100 Pellet Boilers.	Instruction manual reference "PROPEL Wood Pellet Boiler Models: P70 – P100 Version 2" dated 23rd September 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Kozlusan – Salih Kozlu, Kayalioilu Kasabasi, Akhisar,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manisa, PK 23, Turkey.		
Green Energy Engineering PROPEL P25 and P40 wood pellet boilers. Manufactured by	Instruction manual reference "Owner's Manual PROPEL Wood Pellet Boiler Version 2" dated 23rd September 2012.	Wood pellets ⁽¹⁾ .
Kozlusan – Salih Kozlu, Kayalioilu Kasabasi, Akhisar, Manisa, PK 23, Turkey.		
Green Energy Engineering SLIMPEL S25.	Instruction manual reference "Owner's Manual SLIMPEL Wood Pellet Boiler Version 2" dated 23rd September 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Kozlusan – Salih Kozlu, Kayalioilu Kasabasi, Akhisar, Manisa, PK 23, Turkey.		
Greenflame 28 Pellet Boiler.	Instruction manual reference "Installation & Operation Manual V.2.1" dated July 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Trianco Ltd., Thorncliffe, Chapletown, Sheffield, S35 2PH.		
Guntamatic Biocom and Powercorn 50 and 75.	Instruction manual reference "GUN/BIO/OP/ VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾ .
Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Guntamatic Biocom and Powercorn 100. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/BIO/OP/VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip with less than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30 ⁽¹⁾ .
Guntamatic Powerchip 50 and 75. Manufactured by Guntamatic Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/POW/OP/VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾ .
Guntamatic Powerchip 100. Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.	Instruction manual reference "GUN/POW/OP/VI/0709" dated 29th July 2009.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm, or wood chip less with than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30 ⁽¹⁾ .
Guntamatic PRO 175, PRO 199, PRO 250. Manufactured by GUNTAMATIC Heiztechnik GmbH A – 4722 PEUERBACH, Bruck 7, Austria.	Operating instructions and system log book reference "PRO-13-00-00-00-01-BADE" dated October 2013.	Wood chips or wood pellets (1).
Guntamatic PRO-Flex 175, PRO-Flex 199, PRO-Flex 250. Manufactured by GUNTAMATIC Heiztechnik GmbH A	Operating instructions and system log book reference "PRO-Flex-A-00-00-01-BADE" dated October 2013.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
– 4722 PEUERBACH, Bruck 7, Austria.		
Hamont CATfire 350 USZI pellet boiler fitted with CATfire 300 cyclone.	Operating instruction reference "Operating Manual for Boilers CATfire 150-500kW" dated 1st January 2008.	Wood pellets with a diameter of 6mm and a maximum length of 30 mm ⁽¹⁾ .
Manufactured by Hamont Contracting and Trading, spol. s.r.o., Sedlište 227, postal code 739 36, district Frýdek-Mistek, Czech Republic.		
Hampstead 8, Hampstead LS 8, Hampstead XLS 8, Belgravia 8, Barrington 8, Petworth 8 and Flatford 8 stoves. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH8K - V12" dated 31st October 2011. The appliance must be fitted with a system that prevents closure of the air controls further than 40mm from open and with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾ .
Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T,Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 3. Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.	Installation instructions reference "IAV SE/EX 0811-4 511941" and lighting instructions reference "BAV SE/EX H30 511942". The appliance must be fitted with a permanent stop on the air inlet to prevent closure beyond the 45% open position.	Untreated dry wood with less than 20% moisture (1).
Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54,	Installation instructions reference "IAV SE/EX 0737-4 511866" and lighting instructions reference "BAV SE/EX 0717-1 511865".	Untreated dry wood with less than 20% moisture ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Handöl 54T, Handöl 51L,Varde Ovne S1, Varde Ovne S2, Varde Ovne S3.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a permanent stop on the air inlet to prevent closure beyond the 45% open position.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Nibe AB, Box 134, SE-285 23 Markaryd, Sweden.		
Harrie Leenders Boxer Plus & Boxer Black Wood Burning Stoves. Manufactured by Harrie	Instruction manual reference "Boxer Plus manual Issue 1" dated January 2014.	Wood logs ⁽¹⁾ .
Leenders Industrieweg 25 5688 DP Oirschot Netherlands.		
Harrie Leenders Cylon; Harrie Leenders Doran 160; Harrie Leenders Doran 190; Harrie Leenders Fuga S; Harrie Leenders Fuga eL; Harrie Leenders Stor; Harrie Leenders Signa.	Instruction manual reference "Supplementary Instructions Amended June 2010" dated June 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 15mm open position.	Wood logs ⁽¹⁾ .
Manufactured by Harrie Leenders, Industrieweg 25, 5688 DP Oirschot, The Netherlands.		
HDG Compact models 25/35 (25kW, 35kW) wood chip and pellet boilers.	Operating instructions reference "HDG Compact Version V01" dated April 2009.	Wood chips or wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Compact 45 (45 kW) boiler. Manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH) Siemensstraße 22 D-84323 Massing, Germany.	Manual reference "9980001529 V 05.1" dated April 2014 and additional supplementary installation instructions reference "IN1295" dated July 2014.	Wood chips or wood pellets ⁽¹⁾ .
HDG Compact models 50/65 (50kW, 65kW) wood chip and pellet boilers. Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	"HDG Compact Version V03" dated April 2009.	Wood chips or wood pellets (1).
HDG Compact model 80 (80kW) wood chip and pellet boiler. Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	Operating instructions reference "HDG Compact Version V03" dated April 2009.	Wood chips or wood pellets ⁽¹⁾ .
HDG Compact 99 (99 kW), 194 (194 kW) and Compact	Manual reference "9980001520 V.03.01" dated March 2013 and additional supplementary installation	Wood chips or wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
199 (199 kW) boilers	The fireplace must be installed, maintained and operated in accordance with the following specifications: instructions reference "IN1296" dated	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
with model HDG 3113 cyclone.	July 2014.	
Manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH) Siemensstraße 22 D-84323 Massing, Germany.		
HDG Compact model 100 (100kW) wood chip and pellet boiler; HDG Compact model 150, 200 (150kW, 200kW) wood chip and pellet boiler with model HDG 3113 cyclone.	Operating instructions reference "HDG Compact 100-200 Version V1" dated July 2008.	Wood chips or wood pellets (1).
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Euro models 30, 40 and 50 (30kW, 40kW and 50kW) wood log boilers.	Operating instructions reference "HDG Euro V3.0 with HDG Lambda Control 1 Version V1" dated June 2008.	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20% (1).
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
HDG K10, K15, K21 and K26 pellet boilers.	Operation manual reference "Manual ref: 99800001036" dated November 2011 and additional supplementary	Wood pellets (1).
Manufactured by	installation instructions K and R Series reference "IN2014" dated	
HDG Bavaria GmbH	January 2014.	
Heating systems for wood		
Siemensstraße 22		
D-84323 Massing, Germany.		
HDG Navaro models 20, 25 and 30 (20kW, 25kW and 30kW) wood log boilers.	Operating instructions reference "HDG Navora 20/25/30 with HDG Lambda Control 1 Version V2" dated June 2008.	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20% (1).
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Pelletmaster model PM15, 15kW wood pellet boiler.	Operating instructions reference "HDG Pelletmaster Version 1" dated October 2006.	Wood pellets (1).
Manufactured by HDG Bavaria Gesellschaft mit beschrankter Haftung (GmbH) Siemensstraße 22 D-84323 Massing, Germany.		
HDG R20, R25 and R30 wood log boilers. Manufactured by HDG Bavaria GmbH	Manual reference "9980000819" dated August 2011 and additional supplementary installation instructions K and R Series reference "IN2014" dated January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heating systems for wood, Siemensstraße 22,		
D-84323 Massing, Germany		
Heat Design TR5c inset stove.	Instruction manual reference "TRc Issue 02" dated April 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
Heat Design TR5iT Taper inset stove.	Instruction manual reference "TRiT Issue 01" dated April 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
Heat Design TR6c Wide inset stove.	Instruction manual reference "TRc Issue 02" dated April 2012.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
Heat Design of Dublin TR8 Curved Freestanding Wood Burning Stove.	Instruction manual reference "HD TR Freestanding. Issue 01" dated January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
Heat Design of Dublin TR8c Cassette Inset Wood Burning Stove.	Instruction manual reference "TRc issue 03" dated July 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Charlton & Jenrick Ltd., Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 1mm open position.	
Henley Achill Wood Burning Stove.	Instruction manual reference "Version 1" dated November 2012.	Wood logs ⁽¹⁾ .
Manufactured by Henley Stoves Ltd., Ard Ri Marble, Curraheen, Tralee, Co. Kerry, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slots beyond the 50% open position.	
Henley Druid 5 multifuel stove.	User manual reference "Version 2.0" dated May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Henley Stoves Ltd., Ard Ri Marble, Curraheen, Tralee, Co. Kerry, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slot beyond the 30% open position.	
Henley Druid 8 multifuel stove.	User manual reference "Version 2.0" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Henley Stoves Ltd., Ard Ri Marble, Curraheen, Tralee, Co. Kerry, Ireland.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control slot beyond the 40% open position.	
Herz BioFire BF 500, BF 600, BF 800, and BF 1000.	Instruction manual reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc".	Wood chips and pellets (1).
Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld, Austria.		
Herz Firematic 201, 249, 251, 299, 301 boilers.	Operating instructions manual reference "Betriebsanleitung_firematic_20-301_" V1 2 (2)" dated May 2013.	Wood pellets and Wood chips ⁽¹⁾ . Touch_Englisch

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld, Austria.		
Herz Firematic FM 80 and Herz Firematic FM 100. Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld, Austria.	Assembly and installation instructions "HERZ firematic 20 - 101 BioControl". Reference "04.001", installation instructions "Herz Firematic (1Ph) 20-101" and operating instructions "HERZ firematic 20 - 101 BioControl" reference "Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc".	Wood chips and pellets ⁽¹⁾ .
Hestia 5 EV-A5-CD1 wood burning stove. Manufactured by Broseley Fires Limited, First Floor Unit B, Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA.	Installation and operating instructions manual reference "Hestia EVA5/A7 Issue 1" dated 30th June 2014. The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 23mm open.	Wood logs ⁽¹⁾ .
Hestia 7 EV-A7-CD1 wood burning stove. Manufactured by Broseley Fires Limited, First Floor Unit B, Knights Court, Archers Way, Battlefield Enterprise Park, Shrewsbury, SY1 3GA.	Installation and operating instructions manual reference "Hestia EVA5/A7 Issue 1" dated 30th June 2014. The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 50mm open.	Wood logs ⁽¹⁾ .
Heta Inspire 40 and Heta Inspire 45 stoves. Manufactured by Heta A/S, Jupitervej	Operating and installation instruction manual reference "Pevex1020/AH/ver1: Jan 2013" dated January 2013. The appliance must be fitted with a permanent stop to fix the air control	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
22, 7620 Lemvig, Denmark.	valve at 41% open when in the fully closed position.	
Heta Scanline 500D, 510D, 520D and 530D wood burning stoves.	Instruction manual reference "Pevex1005/AH/ver2" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Heta Scanline 7D, 7AD, 7BD, 7CD and 7DD wood burning stoves.	Instruction manual reference "Pevex1006/AH/ver2" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Heta A/S, Jupitervej 22, 7620 Lemvig, Denmark.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Heta Scanline 800; Heta Scanline 810 standard;	Instruction manual reference "Pevex1019/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Heta Scanline 810 with high ash door and soapstone;	The appliance must be fitted with a permanent stop to fix the air control at 31% open when in the fully closed position.	
Heta Scanline 820 baking oven;		
Heta Scanline 820 with soapstone and baking oven;		
Heta Scanline 820 accumulation;		
Heta Scanline 820 soapstone and accumulation;		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heta Scanline 820		
with shelf;		
Heta Scanline 820 soapstone and shelf;		
Heta Scanline 830 extra accumulation;		
Heta Scanline 830 extra accumulation and soapstone;		
Heta Scanline 840 high ash door and shelf;		
Heta Scanline 840 high ash door, shelf and soapstone;		
Heta Scanline 840 high ash door and accumulation;		
Heta Scanline 840 high ash door, accumulation and soapstone;		
Heta Scanline 840 baking oven with high ash door;		
Heta Scanline 840 baking oven with high ash door and soapstone;		
Heta Scanline 850 on pedestal;		
Heta Scanline 850 soapstone on pedestal;		
Heta Scanline 80;		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heta Scanline 80 B;		
and		
Heta Scanline 80 BF wood burning stoves.		
Manufactured by Heta A/S,		
Jupitervej 22, 7620 Lemvig,		
Denmark.		
Heta Scanline 810 with high ash door and ceramic;	Instruction manual reference "Pevex1019/AH/ver1" dated January 2013.	Wood logs (1).
Heta Scanline 820 with baking oven and ceramic;	The appliance must be fitted with a permanent stop to fix the air control at 31% open when in the fully closed position.	
Heta Scanline 820 with thermastone and ceramic;	position.	
Heta Scanline 820 with shelf and top in sandstone;		
Heta Scanline 820 with shelf, ceramic;		
Heta Scanline 830 with extra thermastone and top in soapstone;		
Heta Scanline 830 with extra thermastone and ceramic;		
Heta Scanline 840 high ash door, shelf and ceramic;		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Heta Scanline 840 high ash door, thermastone and ceramic;		
Heta Scanline 840 high ash door, baking oven and ceramic;		
Heta Scanline 850 on column and ceramic; and		
Heta Scanline 850 on turntable column and ceramic wood burning stoves.		
Manufactured by Heta A/S,		
Jupitervej 22, 7620 Lemvig		
Denmark.		
Heta Scanline 800 Aqua and Heta Scanline 800 Aqua low boiler stoves.	Instruction manual reference "Pevex1018/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heta A/S,	The appliance must be fitted with a permanent stop to fix the air control at 52% open when in the fully closed position.	
Jupitervej 22, 7620 Lemvig,	position.	
Denmark.		
Hi-Flame Inset Convector model number HF 5902 4.9kW inset room heater.	Instruction manual reference "HF5902/UK-NI-ROI/V3.18-07-14" dated June 2014. The appliance must be fitted with a	Wood logs ⁽¹⁾ .
incutor.	mechanical stop to prevent secondary	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire CW4 8AF.	air control closure beyond the 5mm open position.	
Highland Biomass Solutions Bio-Flame 28 Wood Pellet Boiler.	Installation and operation manual reference "Version 2.1" dated July 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions, Donaskeigh, Co. Tipperary, Ireland.		
Highland Biomass Solutions Bio-Flame 55, 85, 100, 125, & 199 Wood Pellet Boilers.	Installation, operation and servicing instructions reference "Manual Edition: Bio-Flame Commercial Series" dated July 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Highlander 3 Enviroburn smoke exempt multi fuel stove.	Instruction manual reference "ENVIRO 3 DB005" dated 11th February 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	The appliance must be fitted with a system preventing closure of the secondary air control beyond the 3mm open position.	
Highlander 5 Clean Burn. Manufactured by Dunsley Heat	Instruction manual reference "Highlander. The Dunsley- Enviroburn-5. Clean Burn Stove Installation and operating	Wood logs conforming to BS EN 13240:2001 ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	instructions, D12-01-09, D060-01-09, D13-01-09, D12-12-08."	
Highlander 5 Enviroburn SOLO Slimline smoke exempt multi fuel stove.	Instruction manual reference "ENVIRO 5 DB002" dated 2nd February 2013.	Wood logs ⁽¹⁾ .
Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	The appliance must be fitted with a system preventing closure of the secondary air control beyond the 3mm open position.	
Highlander 7 Enviroburn Solo multi-fuel stove (product codes 00325, 00326 and 00327). Manufactured by Dunsley Heat Ltd., Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire, HD9 3TW.	Installation and operating instructions manual reference "ENVIRO 7 DB001" dated 15th June 2012. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air-wash beyond 2mm. Four fixed 5mm diameter air holes are provided for the tertiary air supply.	Dry wood logs ⁽¹⁾ .
Highlander 8 Enviro- burn Solo 8.1kW multifuel stove.	Installation and operating instructions manual reference "ENVIRO 8 DB010" dated 15th October 2014.	Wood logs ⁽¹⁾ .
Manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Huddersfield, HD9 3TW.	A mechanical stop to prevent closure beyond the 3mm open position must be implemented.	
Hillandale Silverdale 5SE, Amalia 5 and Oppdal 5 woodburning stoves.	Instruction manual reference "GB12A Version 1" dated February 2013. The appliance must be fitted with a permanent stop to prevent closure of	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	the secondary air slide beyond the 23mm open position.	
Hillandale Silverdale 7SE, Amalia 7 and Oppdal 7 woodburning stoves. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "GB12A Version 1" dated February 2013. The appliance must be fitted with a permanent stop to prevent closure of the secondary air slide beyond the 50mm open position.	Wood logs ⁽¹⁾ .
Hopwood Multifuel Stove Model HW1MF. Manufactured by ACR Heat Products Ltd., Unit 1, Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Instruction manual reference "HW1MF 0101" dated 17th July 2013. The appliance must be fitted with a permanent stop to the secondary air slider to prevent closure beyond the 5mm open position and the tertiary air openings at the rear of the appliance are fixed at 50% open.	Wood logs ⁽¹⁾ .
Horse Flame Little Artemis model number HF277-SE wood burning stove. Manufactured by Hi- Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	Instruction manual reference "AL905-SE/UK-NI-ROI/V2-D.18-07-12" dated July 2012. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.	Wood logs ⁽¹⁾ .
Horse Flame Precision 1 model number HF905-SE.	Instruction manual reference "HF905/ UK-NI-ROI/V2.1-06-11" dated June 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Manufactured by	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Henan Hi-Flame Metal Co. Ltd., Eastside, Yugang Avenue, Airport District, Zheng Zhou 451163, Henan, China.	mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Horse Flame Precision II model number HF907-SE wood burning stove.	Instruction manual reference "HF907-SE/UK-NI-ROI/V3-D. 14-07-12" dated July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hi- Flame Fireplace UK Ltd., Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air.	
Hothouse 4SE stove.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	"HH468SE" dated 25th July 2012. The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	
Hothouse 06C inset stove.	Instruction manual reference "HH06C" dated 26th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Hothouse 6SE stove.	Instruction manual reference "HH468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Estate, Naas Road, Dublin 12, Ireland.		
Hothouse 8SE stove. Manufactured by	Instruction manual reference "HH468SE" dated 25th July 2012.	Wood logs ⁽¹⁾ .
Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	
Hothouse 11C inset stove.	Instruction manual reference "HH11C" dated 26th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Hothouse Breeze 4SE Multi-fuel stove.	Installation and operating instruction manual reference "HHB468SE" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 5mm open position.	
Hothouse Breeze 5i Multi-fuel inset stove.	Installation and operating instruction manual reference "HHB5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
Hothouse Breeze 6SE Multi-fuel stove.	Installation and operating instruction manual reference "HHB468SE" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road,	The appliance must be fitted with a mechanical stop to prevent secondary	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Western Industrial Estate, Naas Road, Dublin 12, Ireland.	air control closure beyond the 25% open position.	
Hothouse Breeze 8SE Multi-fuel stove.	Installation and operating instruction manual reference "HHB468SE" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 75% open position.	
Hothouse HH5i Multifuel inset stove.	Installation and operating instruction manual reference "HH5i" dated 2nd May 2013.	Wood logs (1).
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
Hotpod Unlimited; Hotpod Limited Edition.	Instruction manual reference "Version 3" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Hotpod LLP, PO Box 137, St Ives, Cornwall, TR26 2WW.		
Hoval AgroLyt 20, 25, 35, 45 and 50.	Manufacturer's technical information and installation instructions reference "4 205 194/00" dated January 2006	Wood logs with less than 20% moisture ⁽¹⁾ .
Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	and reference "4 205 193/00" dated June 2006.	
Hoval BioLyt Wood Pellet Boiler. Manufactured by Hoval UK Ltd., Northgate, Newark,	Instruction manual reference "Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160)" dated 3rd July 2008 and reference "Technical	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nottinghamshire, NG24 1JN.	information assembly instructions" dated 3rd October 2009.	
Hoval BioLyt 50 Wood Pellet Boiler (49kW thermal output).	Manufacturer's technical information and installation instructions reference "4 204794/00" dated October 2005 and operating instructions reference "4 204 793/01" dated January 2006.	Wood pellets ⁽¹⁾ .
Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.		
Hoval BioLyt 50 and 70 models. Manufactured by	Manufacturer's technical information and installation instructions references "4 204 794/01" and "4 204 793/02" dated June 2007.	Wood pellets ⁽¹⁾ .
Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.		
Hoval BioLyt 160 pellet boiler. Manufactured by Hoval UK Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	Instruction manual reference "Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160)" dated 3rd July 2008 and reference "Technical information assembly instructions" dated 3rd October 2009.	Wood pellets ⁽¹⁾ .
Hoval BioLyt 8, 13, 15, 23, 25, 31 & 36 Wood Pellet Boiler.	Operating instructions reference "No: 4 211 326/01-10/13" dated October 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Hoval Limited,		
Northgate, Newark, Nottinghamshire, NG24 1JN.		
Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers.	Instruction manual reference "Hoval Forester MGS_MMXXXv1" (where XXX is the unit size for example 150) dated July 2011.	Wood pellets or wood chips following CEN/TS 14961 ⁽¹⁾ .
Manufactured by Schmid AG		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Woodfiring systems, PO Box 42, CH-8380 Eschikon, Switzerland.		
Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600.	Instruction manual reference "Forester UFS" dated November 2009.	Wood pellets or wood chips following CEN/TS 14961 ⁽¹⁾ .
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8360 Eschlikon, Switzerland.		
Hoval STU 150, 200, 250, 300, 350, 425 and 500. Manufactured by Hoval UK Ltd.,	Manufacturer's technical information and installation instructions reference "STUman/01" dated November 2007 or reference "STU/man/01/1" dated June 2008.	Wood pellets (1).
Northgate, Newark, Nottinghamshire, NG24 1JN.		
Hoval STU 600, 800 and 1000.	Installation and operation manual reference "STU/man/01" dated November 2007 or the installation	Wood pellets (1).
Manufactured by Hoval UK Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	and operation manual reference "STU/man/01/1" dated June 2008.	
HSV 50 + WTH 45, 49 or 55; HSV 80 + WTH 70 or 80; HSV 100 + WTH 100.	Manufacturer's installation manual version 44 reference "BA HSV30-100 RA/RAP V44 0608".	Wood chips or wood pellets (1).
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
8, A-4952, Weng, Austria.		
Hunter Avalon 5 Inset stove.	Instruction manual reference "JINAVI05 Rev B" dated 10th October 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The valve plate adjusted by the secondary air control must contain six 5mm holes.	
Hunter Hawk 4 multifuel stove.	Installation and operating instructions reference "JINHCR06 RevB" dated 20th June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Exeter, EX5 4RJ	The appliance must be fitted with a modified top air plate with an additional 9 x 5mm holes and the tertiary air aperture permanently fixed to the 60% open position.	
Hunter Herald 4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHH04 revC" dated 22nd September 2011 and "JINHH04&HHC05 Slider Stop revA" dated 22nd July 2011. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾ .
Hunter Herald 5 Compact. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHHC05 revC" dated 22nd September 2011 and "JINHH04&HHC05 Slider Stop revA" dated 22nd July 2011. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs ⁽¹⁾ .
Hunter Herald 5 Slimline.	Instruction manual reference "JINHHW05 revC" dated 22nd September 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.		
Hunter Herald 6.	Instruction manual reference "JINHH04 revC" dated 22nd	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	September 2011.	
Hunter Herald 8 slimline CE vII stove.	Instruction manual reference "JINHHW08 revB" dated 24th January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	January 2013.	
Hunter Herald i4.	Instruction manual reference "JINHVR04 Rev E" dated 2nd	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge,	December 2011 and instruction manual reference "JINHVR04SCK revB" dated 5th December 2011.	
Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with smoke control area kit JHVR0401.	
Hunter stoves Inset Avalon 8 multi-fuel inset stove.	Installation and operating instructions manual reference "JINAVI08 Rev B" dated 14th	Wood logs ⁽¹⁾ .
Manufactured by Hunter	February 2013 and modification instructions reference "JINAV108 Slider Stop Rev B" dated 25th	
Stoves Limited, Trevilla Park,	September 2013.	
Slaughterbridge, Camelford,	The appliance must be fitted with a mechanical stop to prevent secondary	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Cornwall, PL32 9TT.	air control closure beyond the 20% open position.	
Hunter stoves Inset Telford 8 multi-fuel inset stove. Manufactured by Hunter	Installation and operating instructions manual reference "JINTDI08 Rev B" dated 5th February 2013 and modification instructions "JINTD108 Slider Stop Rev B" dated 25th September 2013.	Wood logs ⁽¹⁾ .
Stoves Limited, Trevilla Park, Slaughterbridge, Camelford,	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Cornwall, PL32 9TT.		
Hunter Kestrel 5 multifuel stove.	Installation and operating instructions reference "JINHRR05 RevB" dated 20th June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited,	The appliance must be fitted with a modified top air plate with an additional 8 x 5mm holes.	
Unit 6,		
Old Mill Industrial Estate,		
Exeter,		
EX5 4RJ		
Hunter Telford 5 Inset stove.	Instruction manual reference "JINTDI05 rev B" dated 10th October 2012.	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The valve plate adjusted by the secondary air control must contain six 5mm holes.	
Huntingdon 25 clear door (model number 7057) and Huntingdon	Instruction manual reference "PM 249 Issue 1".	Untreated dry wood (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
25 tracery door (model	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
number 7058).	permanent stop on the secondary air inlet to prevent closure beyond the	
Manufactured by Stovax Ltd., Falcon Road, Sowerton Industrial Estate, Exeter, Devon EX2 7LF.	75% open position.	
Hwam Beethoven, Hwam Beethoven H, Hwam Mozart, Hwam Ravel, Hwam Vivaldi, Hwam 30 (4.5kW	Euroheat Distributors (HBS) Ltd.'s operational instructions reference "IN1 141 Ed B" dated November 2006.	Untreated dry wood (1).
nominal thermal output).	The appliance must be fitted with a mechanism to prevent closure of the air wash/secondary air control.	
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark.		
Ild 1 and Ild 4 stoves.	Instruction manual reference "11.1c" dated February 2012.	Wood logs ⁽¹⁾ .
Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Ild 2 and Ild 5 stoves.	Instruction manual reference "11-1d" dated February 2012.	Wood logs ⁽¹⁾ .
Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Ild 6 Insert stove. Manufactured by Color Email d.o.o.,	ILD 6 Insert stove Instruction manual reference "12-1b GB" dated 25th February 2013.	Wood logs ⁽¹⁾ .
Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a permanent stop preventing closure of	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	the secondary air control beyond 18% open.	
Ild 7 and Ild 8 woodburning stoves. Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	Instruction manual reference "Manual version. No. 13-1 GB 01.07.13" dated 1st July 2013. The appliance must be fitted with a permanent stop to fix the secondary air control at 7.5% open when in the fully closed position.	Wood logs ⁽¹⁾ .
Insert 50 Crystal, Insert 70 Crystal and Insert 80 Crystal.	Instruction manual reference "6096801-Rev.17" dated 22nd December 2010.	Wood logs ⁽¹⁾ .
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Insert 100 Crystal. Manufactured by, LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	Instruction manual reference "6096801-Rev.17" dated 22nd December 2010.	Wood logs ⁽¹⁾ .
Instyle 400; Instyle 550. Manufactured by Dik Geurts Haardkachels BV; Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands.	Instruction manual reference "Instruction_manual_Instyle_1209_EN	Wood logs ⁽¹⁾ . 'G".
Interra 60, 68, 74, 78 stoves. Manufactured by M-Design, M-Design, Torhoutsesteenweg 222A, 8210 Zedelgem,	Instruction manual reference "Interra 60-68-74-78 Instruction for Installation and use" dated August 2012. The units have a permanent stop fitted for use in UK smoke control areas.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Bruges, Belgium, 8210 Zedelgem.		
Italy Built In. Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	Instruction manual reference "7095401 Rev.02" dated 13th December 2010.	Wood logs ⁽¹⁾ .
Italy Imported wood burning ovens: Etna, Amiata, Stromboli and Vesuvius. Manufactured by Italy Imported Ltd., Avenue House, Southgate, Chichester, PO19 1ES.	Installation and operation manual reference "E.A.S.V. ISSUE 1" dated July 2013.	Wood logs ⁽¹⁾ .
Italy Termo Built- in DSA (back boiler cooker). Manufactured by La Nordica SPA, Via Summano, 104 Montecchio Precalcino, Vicenza, 36030, Italy.	Instructions for installation, use and maintenance manual reference "7095703 – IT-EN-DE-FR" dated July 2013.	Wood logs ⁽¹⁾ .
Italy Termo DSA; Termosuprema Compact DSA. Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	Instruction manual reference "7095802 Rev.06" dated 1st February 2011.	Wood logs ⁽¹⁾ .
Ivanhoe JS5000 multifuel. Manufactured by James Smellie Ltd.,	Instruction manual reference "Ivanhoe multi-fuel stove instruction manual Issue 1" dated June 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands, B62 9JQ.		
JC Bordelet EVA 992 Centrale Foyer Fermé (vitrée) enclosed wood-burning stove;	Instruction manual reference "Fireplaces Manual Installation – Use – 1/04/07	Wood logs ⁽¹⁾ .
JC Bordelet EVA 992 Murale (vitrée) enclosed wood- burning stove; and	Characteristics of the Fireplace" dated 1st April 2007.	
JC Bordelet EVA 992 Angle (vitrée) enclosed wood- burning stove.		
Manufactured by Groupe Seguin, Cheminees Seguin Duteriez, Zone Industrielle de Lhérat, 63310 France.		
JC Bordelet LEA 998 centrale foyer fermé (vitrée) enclosed wood-burning stove; and	Instruction manual reference "Fireplaces Manual Installation – Use – 1/04/07	Wood logs ⁽¹⁾ .
JC Bordelet LEA 998 Murale (vitrée) enclosed wood- burning stove.	Characteristics of the Fireplace" dated 1st April 2007.	
Manufactured by Groupe Seguin, Cheminees Seguin Duteriez, Zone Industrielle de Lhérat, 63310 France.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Jetmaster 18f stove. Manufactured by Jetmaster Fires Ltd., Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Instruction manual reference "106870/18f/60f/Issue No.5" dated June 2011.	Dry wood logs ⁽¹⁾ .
Jetmaster 18i stove. Manufactured by Jetmaster Fires Ltd., Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Installation and use instruction manual reference "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference "Part No 106872 Issue No. 1" dated May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position.	Wood logs ⁽¹⁾ .
Jetmaster 60i stove. Manufactured by Jetmaster Fires Ltd., Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Installation and use instruction manual reference "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference "Part No 106872 Issue No. 1" dated May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position.	Wood logs ⁽¹⁾ .
Jotul F100 Stove. Manufactured by Jotul UK Ltd., Unit 1, The IO Centre, Nash Road, Park Farm, Redditch, Worcestershire, B98 7AS.	Instruction manual reference "129980" dated September 2002 and smoke control area modification reference "UK F100 SC appendix" dated 2010. The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position.	Wood logs ⁽¹⁾ .
Jotul F162, F163, F262 and	Instruction manual reference "Jotul F162/F162C/F163 Manual Version	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
F263. Manufactured by Jotul UK Ltd., Unit 1, The IO Centre, Nash Road,	Po6" dated January 2011 and supplementary instruction manual reference "Jotul F162/F163/262/263 SMOKE" dated 1st January 2012.	
Park Farm, Redditch, Worcestershire, B98 7AS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Jotul I520FRL, I520F, I520FR and I520FL 7.8kW inset stoves.	Instruction manual reference "KIS-580 02 03 Version P02" dated November 2013 and "Jøtul I520 Series SMOKE" dated 3rd June 2014	Wood logs ⁽¹⁾ .
Manufactured by Jotul A.S, P.O. Box 1411, N-1602 Fredrikstad, Norway	The appliance must be fitted with a permanent stop to fix the secondary air control to 980mm2 in its minimum position.	
Jydepejsen Country 510 and 760 5kW stoves.	Instruction manual "Country001" reference "Jydepejsen A/S - June 2011" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark.	The appliance must be fitted with a permanent stop to the secondary air control such that it cannot be closed less than 35%.	
KARA KW990 woodchip boiler.	Instruction manual reference "Maintenance and Operation Guide KARA Wood Fired Boiler Version	Woodchip (1).
Manufactured by KARA Energy Systems B.V., P.O. Box 570, 7600 AN Almelo, Plesmanweg 27, 7602 PD Almelo, The Netherlands.	2012.02" dated 26th July 2012.	
Klover PFP18 and PFP18-B pellet insert appliances. Manufactured by Klover Limited,	Instruction manual reference "Installation. Use and Maintenance. Useful advice. Pellet Fire Place. User Guide" dated February 2009.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.		
Klover PFP22 and PFP22-B pellet insert appliances.	Instruction manual reference "Klover PFP22 insert Defra manual" dated 31st January 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.		
Klover Smart 80 central heating pellet stove models SM80, SM80-BP, SM80-P.	Instruction manual reference "Smart Pellet central heating Stove. Use and maintenance, Installation, Useful advice" dated March 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.		
Klover Smart 120 central heating pellet cooker stove models – SM120, SM120-BP, SM120-P.	Instruction manual reference "Klover. Pellet thermo cooker. Smart. Installation. Use and maintenance. Useful advice. User Guide" dated March 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy		
Klover Star 14 –ST14 pellet stove. Manufactured by	Instruction manual reference "Installation. Use and Maintenance. Useful advice. Star 14. User Guide" dated April 2011.	Wood pellets ⁽¹⁾ .
Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.		
Klover Star 18 – ST18 pellet stove.	Instruction manual reference "Star 18 Pellet Boiler Stove. Installation.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Manufactured by	The fireplace must be installed, maintained and operated in accordance with the following specifications: Use and Maintenance, Useful Tips	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Klover Limited, Klover s.r.l Via A. Volta, 8 - 37047 San Bonifacio (VR), Italy.	revision: 1.1" dated September 2013.	
Knightsbridge SE multifuel stove, Knightsbridge SE multifuel stove with stoveasy grate, Highgrove SE multifuel stove, Highgrove SE multifuel stove with stoveasy grate. Manufactured by Newman Fireplaces Limited, Unit 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	Instruction manual reference "NS 5-6 Issue 1" dated 8th January 2014. The tertiary air control must be fully open when burning wood.	Wood logs ⁽¹⁾ .
KÖB Pyromat-DYN (KPM-DYN) 45, 65, 85. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 103689-L English" dated 1st January 2005 and instruction manual reference "ID: 103708-G English".	Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets ⁽¹⁾ .
KÖB Pyromat-ECO (KPM-ECO) models 35, 45, 55, 65, 75, 85. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 104646-D English" dated 1st January 2005 and instruction manual reference "ID: 104642-B English".	Wood logs (up to 0.5m) and off cuts of natural timber ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
KÖB Pyromat-ECO (KPM-ECO) models 61, 81, 101, 151. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 104646-D English" dated 1st January 2005 and instruction manual reference "ID: 104642-B English".	Wood logs (up to 1.0m) and off cuts of natural timber ⁽¹⁾ .
KÖB Pyrot (KRT) models 100, 150, 220, 300, 400, 540. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 104654-H English" dated 1st January 2005 and instruction manual reference "ID: 106811-H English".	Wood chips or wood pellets ⁽¹⁾ .
KÖB Pyrtec (KPT) models 390, 530, 720, 950, 1250. Manufactured by Viessman Ltd., Hortonwood 30, Telford, Shropshire, TF1 7YP.	Instruction manual reference "ID 104661-F English" dated 1st January 2005 and instruction manual reference "ID: 105174-F English". The appliance must be fitted with multi-cyclone dedusters.	Wood chips or wood pellets (1).
Kooga Cleanburn Stove. Manufactured by Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.	Instruction manual reference "KCB 04/10A" dated April 2010.	Wood logs ⁽¹⁾ .
KOZ550, 639kW pellet boiler. Manufactured by Kayalioglu Kasabasi (Izmir-Istanbul Yolu	Owner/operator's manual reference "version 1A 2010" dated December 2010 and maintenance and instruction manual for Glosfume BMF Biomass filter units (50 to 1000kW) reference	6mm diameter wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Uzeri), PK23 Akhisar/ Manisa, Turkey.	"version AEE001-VER4" dated December 2010.	
	The appliance must be used with a Glosfume model BMF 208 ceramic particulate filter.	
KP12, KP22 and KP62 wood pellet boilers. Manufactured by PONAST spol. s r.o., Na Potůčkách 163, Valašské Meziříčí, 757 01, Czech Republic.	Service manual reference "QPP051-2" dated 25th May 2012 and instructions for operation manual reference "QPP049-3" dated 25th May 2012.	Wood pellets ⁽¹⁾ .
KWB Easyfire EF2 S/GS/V 8, 12, 15, 22, 25, 30 and 35 wood pellet boilers. Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.	Operation manual reference "B KWB Easyfire EN, 05.2011" dated May 2011 and installation manual reference "M KWB Easyfire, 05.2011" dated May 2011.	Wood pellets ⁽¹⁾ .
KWB Multifire 15, 25, 30, 40, 50, 60, 80, 99 and 100 wood-pellet and wood-chip fired boilers.	Manufacturer's instructions reference "BA-USV 0803" dated August 2003.	Wood chips and wood pellets (1).
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Margarethen an der Raab, Austria.		
KWB Multifire USV 49.5kW wood chip and wood pellet boiler.	Instruction manual reference "BA Multifire 06.2010" dated June 2010.	Wood chips and wood pellets (1).
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
KWB Powerfire TDS 200 199kW Boiler. Manufactured by KWB — Kraft und Wärme aus	Operation manual reference "B KWB Powerfire 200–300kW, EN, 09.2012" dated April 2013.	Wood pellets or Wood chips ⁽¹⁾ .
Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
KWB TDS Powerfire 130, 240 and 300. Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.	Manufacturer's instructions reference "BA TDS-05.2008" dated 14 May 2008, including specification of recommended fuels.	Wood pellets or wood chips (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
KWB TDS Powerfire 150.	Manufacturer's instructions reference "BA TDS – 0805" dated August	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.	2005.	
Lima B.11 wood burning stove	Instruction manual reference "Lima_R1" dated November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 42mm open position.	
Lindner & Sommerauer pellet boilers models: SL- P49, SL-P50, SL-P65, SL-P80, SL-P99, SL- P110, SL-P150, SL- P199, SL-P200 and SL-P250	Operating instructions and technical description – Rotary Grid system SL 25T/2R to SL250 T6R and SL-P30 to SL-P 250, reference "140304 ENG" dated 5th March 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Lindner & Sommerauer, SL- Technik GmbH, Trimmelkram 113 A-5120 St Pantaleon, Austria.		
Lindner & Sommerauer wood chip boilers models: SL49T4R, SL50T4R, SL65T4R, SL80T4R, SL99T4R, SL110T4R, SL150T4R, SL199T6R,	Operating instructions and technical description – Rotary Grid system SL 25T/2R to SL250 T6R and SL-P30 to SL-P 250, reference "140304 ENG" dated 5th March 2014.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
SL200T6R and SL250T6R		
Manufactured by Lindner & Sommerauer, SL- Technik GmbH, Trimmelkram 113 A-5120 St Pantaleon, Austria.		
Lin-ka H 1500 Hot Water Boiler fitted with either a mono- cyclone (type LIN- KA 2000) or a multi- cyclone (type LIN-KA 3x2).	Instruction manual reference "LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10" dated 27th January 2010.	Wood pellets of maximum 8mm diameter ⁽¹⁾ .
Manufactured by LIN- KA Maskinfabrik A/ S, Nylandsvej 38, DK-6940 Lem St. Denmark.		
Little Thurlow wood burning stove. Manufactured by Town and Country Fires Ltd., 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	Manufacturer's instructions reference "issue No. 3." dated 30th June 2007.	Seasoned logs of less than 20% moisture and of a maximum length of 350mm ⁽¹⁾ .
Little Wenlock Classic SE Wood Fuel Stove. Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ.	Operating instructions reference "N00471AXX Rev 001 DP 081219" dated 19th December 2008.	Dry and split wood logs of a maximum length of 25cm and a maximum diameter of 10cm ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
LogFire LF6cT Wood Burning Stove.	Instruction manual reference "LF6cT-1" dated 18th December 2012.	Wood logs ⁽¹⁾ .
Manufactured by LogFire Stoves Ltd., Britannia House, Junction Street, Darwen, Lancashire, BB3 2RB.	The appliance must be fitted with a mechanical stop to prevent closure of the air control slots beyond the 21mm open position.	
Lotus H370 Petite 6.6kW insert stove.	Instruction manual reference "Fireplace Insert, Lotus H370 Petite Version 1" dated 11th October 2012.	Wood logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S;	The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 5mm open	
Agertoften 6, 5550 Langeskov, Denmark.	position.	
Lotus Liva 1, Liva 2, Liva 3 and Liva 4G stoves. Manufactured by Lotus Heating Systems A/S;	Instruction manual reference "Mounting and User Instructions Lotus-Liva series Stoves Version 4" dated January 2010.	Wood logs ⁽¹⁾ .
Agertoften 6, 5550 Langeskov, Denmark.		
Lotus Sola, Sola S, Sola M and Sola MST stoves.	Instruction manual reference "Mounting and User Instructions Lotus-Sola series Stoves Version 2" dated January 2010.	Wood logs ⁽¹⁾ .
Manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark.	duted sundary 2010.	
Løvenholm. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge,	Manufacturer's installation and operation manual reference "version 07/08" dated July 2008.	Untreated wood with less than 20% moisture content ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Camelford, Cornwall, PL32 9TT.		
Løvenholm, Løvenholm Traditional, European and Pedestal Stoves. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Manufacturer's instructions "Løvenholm Multifuel stove installation and operating manual" reference "version 06/09" dated June 2009.	Untreated wood with less than 20% moisture content ⁽¹⁾ .
Loxton 3 stoves. Manufactured by Mendip Stoves Ltd., Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	Instruction manual reference "Mendip Stoves Ltd., 2012, ver 3" dated July 2012. The appliance must be fitted with a permanent stop to fix the secondary air control such that it cannot be closed more than 25% open.	Wood logs ⁽¹⁾ .
Loxton 5, Churchill 5 and Sqabox Uno stoves. Manufactured by Mendip Stoves Ltd., Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	Instruction manual reference "Mendip Stoves Ltd., 2012, ver 3" dated July 2012. The appliance must be fitted with a permanent stop such that the secondary air 'closed position' results in a 2.5mm gap in the two secondary air openings.	Wood logs ⁽¹⁾ .
Loxton 6, Loxton 8, Churchill 6, Churchill 8 and Sqabox Duo stoves. Manufactured by Mendip Stoves Ltd., Unit H1, Mendip Industrial Estate, Mendip	Instruction manual reference "Mendip Stoves Ltd., 2012, ver 3" dated July 2012. The appliance must be fitted with a permanent stop on the secondary air control such that it cannot be closed more than 35% open.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Road, Rooksbridge, Somerset, BS26 2UG.		
Love 7 5kW, 6kW, and 7kW Freestanding multifuel stoves	Installation and User Manual reference "LV567 v.2/10-2014" dated October 2014.	Wood logs ⁽¹⁾ .
Manufactured by De and Vi Commerce JSC, 3 Asen Zlatarov Str., 7150 Dve Mogili, Bulgaria.	The appliance must be fitted with smoke control kit DV6020400GB to prevent secondary air control closure beyond the 35% open position.	
Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE).	Instruction manual reference "N00529AXX REV:001" dated 13th July 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ.		
Luno B.13 wood burning stove	Instruction manual reference "Luno_R1" dated November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 33mm open position.	
Malvern Multifuel stove (Model MV1MF).	Technical manual reference "MV1MF 0101" dated 17th October 2013.	Wood logs ⁽¹⁾ .
Manufactured by	When the primary air control is in the closed position, it remains permanently open by 5mm and is	
ACR Heat Products Ltd, Unit 1, Weston Works, Weston Lane, Tyseley, Birmingham, West Midlands,	prevented from closing fully by a screw.	
B11 3RP.		
Marvic Multifuel Cassette (inset) roomheater.	Instruction manual reference "INK.00.7927" dated 20th December 2011.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Wanders Fires & Stoves, Amtweg 4, Netterden, NL-7077 AL, The Netherlands.	The appliance must be fitted with a modification to the secondary air control to ensure that the air supply holes remain 3mm open when the operator has nominally shut the control.	
Mazona Stoves Tuscon inset multi fuel stove	Instruction manual reference "Version A (MZSTUSE)" dated 17th December 2014.	Wood logs ⁽¹⁾ .
Manufactured by Micon Distribution Ltd, 1a Hallstown Road, Ballinderry Upper, Lisburn BT28 2NE	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 2mm open position.	
Meg 5.0 stove and Sirius 600 Inset stove.	Instruction manual reference "Manual Version 1.3" dated 27th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by F.E Robinson, (Hooton) Ltd., Station Works, Hooton Road, Hooton, South Wirral, CH66	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 10mm open position.	
7NF. MEG 7.5/Sirius 750 and MEG 4.5/Sirius	Instruction manual reference "Meg Solid Fuel Stoves Manual (107)"	Wood logs ⁽¹⁾ .
Manufactured by Meg Stoves, F.E. Robinson (Hooton) Ltd., Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	dated 28th January 2011.	
Mendip Burcott SE 4.1kW multi-fuel inset roomheater model No. M00401-00-00-00- Burcott SE, Manufactured by	Operation and installation manual reference "Mendip Stoves Ltd, 2013, Burcott v4" dated 9th August 2014. The appliance must be fitted with a stop to prevent closure of the	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG	secondary air control beyond 25% open.	
Mendip SE Wood Burning 5kW Space Heating Stove.	Instruction manual reference "700273 Iss. 2 Rev. 1" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Mendip SE Wood Burning 8kW Space Heating Stove.	Instruction manual reference "700275 Iss. 2 Rev. 1" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Mendip Stoves Christon Round D600 SE with 3 sided frame and Christon Round D600 SE with 4 sided frame wood-burning inset roomheaters	Instruction manual reference "Mendip Stoves Limited, 2014. Christon Insets v1 06.2014" dated June 2014. The appliance must be fitted with a permanent stop or other measure to prevent closure of the air control	Wood logs ⁽¹⁾ .
Manufactured by	beyond the 40% open position.	
Fogo Montanha (Solzaima, S.A.)		
Rua dos Outarelos,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
3750-362 Belazaima do Chão, Portugal		
Mendip Stoves Somerton 2 Standard SE, Somerton 2 Compact SE, Somerton 2 Pedestal SE 7kW wood burning stoves Manufactured by Mendip Stoves Ltd., Unit H1, Mendip, Industrial Estate, Rooksbridge, Somerset, BS26 2UG	Operation and installation manual reference "Mendip Stoves Ltd., Somerton 2. 2013. Ver.2" dated May 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	Wood logs ⁽¹⁾ .
Merlin Midline ST-C and Merlin Slimline ST-D multifuel stoves. Manufactured by Merlin Stoves Ltd., Foregates, Holmer,	Installation and operation instruction manual reference "MerlinST-C&D_v1" dated 16th July 2013. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 50mm	Wood logs ⁽¹⁾ .
Hereford, HR4 9RJ. Mescoli PB50, PB35, PB28. Manufactured by MESCOLI CALDAIE S.rI. Caldaie-Termocucine, Via del Commercio, 285 4 1058 Vignola, (MO) Italy.	open position. Instruction and installation manual reference "SY315EVO P,C,B-COMBIFIRE 2 PB28/35/50 BOILERS Edition 1.7" dated January 2006.	Wood pellets following ÖNORM M7 135 or DIN plus (DIN 51731) (1).
Micromet MEG 7.5 (also known as the Sirius 750); Micromet MEG 4.5 (also known as the Sirius 450). Manufactured by Micromet, 125 Bridge St, Birkenhead,	Instruction manual reference "Micromet Solid Fuel Stoves Manual (24)" dated 16th June 2010.	Dry wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Merseyside, CH41 1BD.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Milan Series 4. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH4K Milan-V2" dated 18th November 2010. The appliance must be fitted with a system to prevent closure of the air control beyond the 25mm open position.	Wood logs ⁽¹⁾ .
Milan Series 6. Manufactured by Chesneys Ltd., 194-200 Battersea Park Road, London, SW11 4ND.	Instruction manual reference "CH6K Milan-V2" dated 18th November 2010. The appliance must be fitted with a system to prevent closure of the air control beyond the 40mm open position.	Wood logs ⁽¹⁾ .
Monaco multifuel Stove, Staub Fonderie- Franco Belge model 1340605. Manufactured by Staub Fonderie-Franco Belge, Rue Orphee Variscotte, 59660, Merville, France.	Instruction manual reference "1303 - 1" dated 4th May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 4mm from closed.	Wood logs ⁽¹⁾ .
Mondo 1, Mondo 2 and Mondo Petite stoves. Manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550	Instruction manual reference "Lotus-Mondo Series Stoves Version 1" dated 15th October 2012. The appliance must be fitted with a mechanical stop to prevent closure of the air dampers beyond the 8mm open position.	Wood logs ⁽¹⁾ .
Langeskov, Denmark. Morsø-Ø4. Manufactured by Morsø Jernstoberi A/S, DK-7900	Instruction manual reference "Ø-Collection" dated 1st February 2010 and instruction manual reference "72000400" dated 1st February 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nykobing, Mors, Denmark.	Applies to units manufactured after 01/02/2010.	
The Morsø 1400 series consisting of the 1412 and 1442 models.	Manufacturer's instructions reference "72146800" dated 10th January 2008.	Wood logs with less than 20% moisture ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		
Morsø 1416, 1418, 1446 and 1448 4kW stoves.	Instruction manual reference "Morsø 1416, 1418, 1446 & 1448. Instruction for Installation and use Part No: 72150000" dated 31st January 2012.	Wood logs ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		
The Morsø 3100 series consisting of the 3112 and 3142 models.	Manufacturer's instructions reference "72311200" dated 4th February 2008.	Wood logs with less than 20% moisture ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		
The Morsø 6140 series consisting of the 6140 and 6148 models.	Manufacturer's instructions reference "72610400" dated 4th September 2007.	Wood logs with less than 20% moisture ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		
Morsø 7300 series 4.3kW wood burning stoves models 7340, 7342, 7343, 7348 &	Instructions for installation and use reference "72746400" dated August 2014.	Wood logs ⁽¹⁾ .
Manufactured by Morsø Jernstøberi A/S . DK-7900	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control inlet beyond 22mm open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nykøbing Mors, Denmark		
Morsø 7400 series 4.3kW wood-burning stoves models 7440, 7442, 7443, 7448 & 7470 Manufactured by Morsø Jernstøberi A/S . DK-7900 Nykøbing Mors, Denmark	Instructions for installation and use reference "72746400" dated August 2014. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control inlet beyond 22mm open.	Wood logs ⁽¹⁾ .
Morsø 7600 series including Model 7642, 7644 and 7648.	Instructions for installation and use reference "72762200" dated 14th July 2010.	Wood logs with less than 20% moisture (1).
Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.	The air control been altered such that this equates to an increased minimum open position. Reference drawings Morsø 7600-137, 7600-138, 7600-139, 7600-140 and 7600-141.	
Morsø 7800 series 7.3 kW wood-burning stoves models 7840, 7843, 7848, 7850, 7851, 7870, 7890 Manufactured by Morsø Jernstøberi A/S . DK-7900 Nykøbing Mors, Denmark	Instructions for installation and use reference "72797500" dated August 2014. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control inlet beyond 25% open	Wood logs ⁽¹⁾ .
Morsø 7900 series 7.3 kW wood-burning stoves models 7940, 7943, 7948, 7950, 7970, 7990 M Manufactured by Morsø Jernstøberi A/S . DK-7900	Instructions for installation and use reference "72797500" dated August 2014. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control inlet beyond 25% open.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nykøbing Mors, Denmark		
Morso DB15 central heating stove distributed by Morsø Jernstøberi A/S DK-7900 Nykøbing, Mors, Denmark.	Instruction manual reference "Solid Fuel Central Heating Stoves Manual Issued - 22/01/2014 (459)" dated 22nd January 2014 and reference "Soliftec Smoke Advice Sheet no1" dated 22nd January 2014.	Untreated dry wood. Peat or peat briquettes with, in either case, less than 25% moisture. Union Coal Brikettes, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 cm in length with square ends and with a sulphur content not exceeding 1% of the total weight. CPL Wildfire, manufactured by Coal Products Limited, Immingham, which comprise bituminous coal with a volatile content of 32-36 % (as to approximately 96% of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of either 80-90 grammes or 160-170 grammes; and have a sulphur content not exceeding 1.8% of the total weight (1).
Morsø Owl 3410, 3420 and 3440 for wood burning. Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.	Manufacturer's instructions reference "72345600" dated 1st January 2000.	Untreated dry wood which has been split, stacked and air dried; or air dried wood briquettes ⁽¹⁾ .
Morsø S10-40 5kW stove. Manufactured by Morsø Jernstøberi A/	Instruction manual reference "Morsø S10. Instruction for Installation and use. Part No: 72104000" dated 31st January 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
S DK-7900 Nykøbing, Mors, Denmark.		
Morsø S10-70 5kW stove. Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.	Instruction manual reference "Morsø S10-70. Instruction for Installation and use. Part No: 72103000" dated 31st January 2012.	Wood logs ⁽¹⁾ .
Morsø S11-40, S11-42, S11-43 and S11-90 4kW stoves. Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.	Instruction manual reference "Morsø S11. Instruction for Installation and use. Part No: 72114200" dated 31st January 2012.	Wood logs ⁽¹⁾ .
Morsø S81-90 4kW stove. Manufactured by Morsø Jernstøberi A/ S DK-7900 Nykøbing, Mors, Denmark.	Instruction manual reference "Morsø S81-90. Instruction for Installation and use" dated 30th January 2012.	Wood logs ⁽¹⁾ .
Multibio 49 pellet boiler. Manufactured by Ekoefekt Inc. Semecska 187, 411 15 Trebivlice, Czech Republic.	Instruction manual reference "MB49/IM/ISSUE 001" dated 4th July 2012.	Wood pellets or olive kernels ⁽¹⁾ .
Nero D, Nero M, Vecto D, Vecto M and Orbit 6kW free standing wood burning stoves Manufactured by Dan Skan GmbH, Burgwedeler Str. 7-8,	Instruction manual reference "DSB2-Defra/UK-NI-ROI/V1.11.14" dated November 2014. The appliance must be fitted with a modification to prevent closure of the air flow control valve below position 2.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
D-30657 Hannover, Germany.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nestor Martin C23 multifuel stove (7.7kW);	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1213 Edition B" dated June 2010.	Untreated dry wood (1).
Nestor Martin C33 multifuel stove (9.2kW);		
Nestor Martin D33 multifuel stove (8kW).		
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin 'Harmony' H13 multifuel stove (3.5kW nominal thermal output).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition D" dated January 2007.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin 'Harmony' H13 multifuel stove (5kW);	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition D5" dated June 2010.	Untreated dry wood (1).
Nestor Martin 'Stanford' S13 multifuel stove (3.5kW).	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nestor Martin 'Harmony' H23 (6kW) and H33 (8kW) multifuel stoves;	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition D5" dated June 2010.	Untreated dry wood (1).
Nestor Martin 'Stanford' S23 (6kW) SP23 (6kW) S33 (8kW) and SP33 (8kW) multifuel stoves.		
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin IN13 Insert multifuel stove (5kW).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1214 edition B" dated June 2010.	Untreated dry wood ⁽¹⁾ .
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin IT 13 multifuel stove (3.5kW).	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1180 Edition D1" dated June 2010.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin R23 multifuel stove (6kW). Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1141 Edition B" dated November 2006.	Untreated dry wood (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Nestor Martin R33 (8kW) multifuel stove.	Euroheat Distributors (HBS) Ltd.'s operation instructions reference "IN 1116 Edition D" dated January 2007.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	1110 Edition D. dated January 2007.	
Newark EGTL05.	Instruction manual reference "EGTL05 Version 1.4" dated 5th July	Wood logs ⁽¹⁾ .
Manufactured by Elite Group Trading Ltd., Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	
Newbourne 40 and Newbourne 50 Freestanding stoves.	Instruction manual reference "Pevex1012/AH/ver1" dated January	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	2013. The appliance must be fitted with a permanent stop ensuring a minimum opening area of 1cm² for the primary air slider when in the fully closed position and a tertiary air inlet area of 4cm².	
Newbourne 40 inset stove.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	"Pevex1015/AH/ver1" dated January 2013. The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	
Newton SE Wood Burning 5kW Space Heating Stove.	Instruction manual reference "700504 Iss. 2 Rev 1" dated January 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Newton SE Wood Burning 8kW Space Heating Stove.	Instruction manual reference "700506 Iss. 3 Rev. 2" dated January 2012.	Wood logs ⁽¹⁾ .
Manufactured by TR Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Nordic 350. Manufactured by C DE A Ingenieria Ltda, Jose Miguel Carrera 6, Colina, Santiago, 9361294, Chile.	Instruction manual reference number "1001" dated 20th July 2012.	Wood logs ⁽¹⁾ .
Nordpeis Bergen (NP-BERGEN) wood burning 5.4kW stove Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	Installation and user manual reference "PM1081 Issue 1" dated 1st January 2013 and additional installation and user instructions for use in Smoke Control Areas reference PM1066 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air vent control closure beyond 7mm open.	Wood logs ⁽¹⁾ .
Nordpeis Duo 1 (NP-DUO1STOVE), 2 (NP-DUO2STOVE), 4 (NP-DUO4STOVE), and 5 (NP-DUO5STOVE) wood burning 5kW stoves	Installation and user manual reference "PM1083 Issue 1" dated 13th May 2013 and additional installation and user instructions for use in Smoke Control Areas reference "PM1112 Issue 1" dated July 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Nordpeis Quadro 1 (NP-QUAD1P) and 2 (NP-QUAD2B) wood burning 6.2kW stoves Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	User manual reference "PM1084 Issue 1" dated 3rd September 2012 and additional installation and user instructions for use in Smoke Control Areas reference "PM1068 Issue 1" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond 8mm open.	Wood logs ⁽¹⁾ .
Nordpeis S-31A(S31-A) wood burning 6.2kW inset roomheater Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	User manual reference "PM1089 Issue 1" dated 15th January 2013 and additional installation and user instructions for use in Smoke Control Areas reference "PM1068 Issue 1" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond 8mm open.	Wood logs ⁽¹⁾ .
Nordpeis Uno 1 (NP-UNO1), 2 (NP-UNO2), and 4 (NP-UNO4) wood burning 4.2kW stoves Manufactured by Nordpeis AS, Gjellebekkstubben 11, N-3420 LIERSKOGEN, Norway.	Installation and user manual reference "PM1082 Issue 1" dated 14th May 2013 and additional installation and user instructions for use in Smoke Control Areas reference "PM1111 Issue 1" dated July 2014. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 38% open position.	Wood logs ⁽¹⁾ .
Nørreskoven MkII.	Instruction manual reference "Cleanburn, Nørreskoven MkII, Multifuel Stove. Installation and	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Operating Instructions, v01.11" dated January 2011. The appliance must have a factory fitted stop to prevent closure of secondary air control beyond 40%.	
Norvik 5. Manufactured by Elite Group Trading Ltd., Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	Instruction manual reference "EGTL05A Version 1.5" dated 12th September 2011. The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	Wood logs ⁽¹⁾ .
Octoplus 10 and Octoplus 15 Boiler. Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions reference "Version 1.1" dated 19th April 2010 and operating manual reference "Version 10.051" dated 10th May 2010.	Wood pellets ⁽¹⁾ .
ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PEK32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25, and PESK32.	Manufacturer's instructions reference "PE/HB/001.E" dated February 2007.	Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm ⁽¹⁾ .
ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
ÖkoFEN Pellematic PE36, PE48, PE56, PEK36, PEK48, PEK56, PES36, PES48, PES56, PESK36, PESK48, PESK56.	Manufacturer's instructions reference "PBV 2000 CMP 1.4 (V2.31)" dated March 2008.	Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm ⁽¹⁾ .
Manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria.		
Olymberyl Baby Gabriel model number HF217-SE.	Instruction manual reference "HF217-SE/UK-NI-ROI/V2.16-06-11" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Henan Hi-Flame Metal Co. Ltd., Eastside, Yugang Avenue, Airport District, Zheng Zhou 451163, Henan, China.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.	
Optifire 800 Green, Infire 800 Green, wood burning stoves.	Instruction manual reference "07DH8000A" dated November 2011.	Wood logs ⁽¹⁾ .
Manufactured by Bodart & Gonay Ltd., Rue De Lambinon, 3 Harze, Belgium, 4920.	The appliance must be fitted with a "UK kit for smokeless areas OPTI IF 800".	
Orchard Ovens models: FVR Speciale	Manufacturer's instructions dated 25th October 2004 references:	Untreated dry wood (1).
80, 100, 110, 110 x 160 and 120; TOP	Instruction Model	
Superiore 100 and 120; GR 100, 120,	OOL inst.1 FVR 80	
140, 120 x 160, 140	OOL inst.2 FVR100	
x 160, 140 x 180 and 180; OT 100, 120,	OOL inst.3 FVR 110	
140, 120 x 160, 140 x 160, 140 x 180 and	OOL inst.4 FVR 120	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
180; the Valoriani Piccolo.	OOL inst.5 FVR 110x160	
i iccolo.	OOL inst.6 TOP 100	
Manufactured by Valoriani of Via	OOL inst.7 TOP 120	
Caselli alla Fornace,	OOL inst.8 GR 100 and	
213 50066 Reggello, Firenze, Italy.	OT 100	
	OOL inst.9 GR 120 and	
	OT 120	
	OOL inst.10 GR 140 and	
	OT 140	
	OOL inst.11 GR 120x160 and OT 120x160	
	OOL inst.12 GR 140x160 and OT 140x160	
	OOL inst.13 GR 140x180 and OT 140x180	
	OOL inst.14 GR 180 and	
	OT 180	
	OOL inst.15 Valoriani Piccolo	
Oregon EGTL03. Manufactured by Elite Group Trading Ltd., Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	Instruction manual reference "EGTL03 Version 1.3" dated 5th July 2011.	Wood logs ⁽¹⁾ .
Osby Parca P500 Type 30 wood pellet boiler using Bioline 300 pellet burner. Manufactured by Enertech AB, Osby	Instruction manual reference "Osby Parca P500 Type P30 biomass O & M: Version 1" dated 18th July 2013. The appliance must have a management system designed so that	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Parca Division, PO Box 93, SE-283 22 Osby, Sweden. The burner is manufactured by Ecotec varmesystem AB Hedbovagen 42, PO Box 2103, S-511 02 Skene, Sweden.	the boiler will only operate at 100% Maximum Continuous Rating.	
Osby Parca PB2 2000kW boiler. Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.	Operating & Maintenance manual, PB2 boiler reference "manual PB2_ENG_Rev2_JAN2012" dated January 2012.	Wood pellets ⁽¹⁾ .
Osby Parca PB2 3000kW boiler. Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.	Operating & Maintenance manual, PB2 boiler reference "manual PB2_ENG_Rev2_JAN2012" dated January 2012.	Wood pellets, wood chips, wood briquettes ⁽¹⁾ .
Ottawa B.12 wood burning stove	Instruction manual reference "Ottawa_R1" dated November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Hase Kaminofenbau GmbH, Niederkircher Strasse 14, D-54294 Trier	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 42mm open position.	
Parkray Caprice 4. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAP04 Rev E" dated 2nd December 2011 and instruction manual reference "JINCAP04SCK revB" dated 5th December 2011. The appliance must be fitted with smoke control area kit JCAP0401.	Wood logs ⁽¹⁾ .
Parkray Caprice 5 inset stove.	Instruction manual reference "JINCAP05 Rev B" dated 10th December 2012 and instruction	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	manual reference "JINCAP05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit JCAP0501.	
Parkray Caprice 6 inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCAP06 Rev B" dated 10th December 2012 and instruction manual reference "JINCAP05SCK Rev A" dated 6th July 2012. The appliance must be fitted with smoke control area kit JCAP0501.	Wood logs ⁽¹⁾ .
Parkray Chevin 5 Inset stove. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCHI05 Rev B" dated 10th October 2012. The valve plate adjusted by the secondary air control must contain six 5mm holes.	Wood logs ⁽¹⁾ .
Parkray Consort 4 multifuel stove Manufactured by Parkray Limited, Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT	Installation and operating instructions reference "JINCNS04 RevB" dated 20th June 2014. The appliance must be fitted with a modified top air plate with an additional 9 x 5mm holes, and the tertiary air aperture permanently fixed to the 60% open position.	Wood logs ⁽¹⁾ .
Parkray Consort 5. Manufactured by Hunter Stoves	Instruction manual reference "JINCND05 revC" dated 22nd September 2011 and	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Ltd., Trevilla Park,	The fireplace must be installed, maintained and operated in accordance with the following specifications: "JINCND05&CNC05 Slider Stop	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	revA" dated 22nd July 2011. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Parkray Consort 5 Compact. Manufactured by Hunter Stoves Ltd., Trevilla Park,	Instruction manual reference "JINCNC05 revC" dated 22nd September 2011 and "JINCND05&CNC05 Slider Stop revA" dated 22nd July 2011.	Wood logs ⁽¹⁾ .
Slaughterbridge, Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Parkray Consort 5 Slimline. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINHHW05 revC" dated 22nd September 2011.	Wood logs ⁽¹⁾ .
Parkray Consort 7. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JNCS07 revC" dated 22nd September 2011.	Wood logs ⁽¹⁾ .
Parkray Consort slimline 9. Manufactured by Hunter Stoves Ltd., Trevilla Park, Slaughterbridge, Camelford, Cornwall, PL32 9TT.	Instruction manual reference "JINCSS09 revC" dated 14th December 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Parkray Derwent 5 multifuel stove	Installation and operating instructions reference "JINDER05 RevB" dated 20th June 2014.	Wood logs ⁽¹⁾ .
Manufactured by Parkray Limited, Unit 6,	The appliance must be fitted with a modified top air plate with an additional 8 x 5mm holes.	
Old Mill Industrial Estate,		
Exeter,		
EX5 4RJ		
Parkray Inset Chevin 8 multi-fuel inset stove.	Installation and operating instructions manual reference "JINCHI08 Rev B" dated 7th February 2013 and	Wood logs ⁽¹⁾ .
Manufactured by Hunter Stoves Limited, Trevilla Park, Slaughterbridge,	modification instructions reference "JINCH108 Slider Stop Rev B" dated 25th September 2013.	
Camelford, Cornwall, PL32 9TT.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
PCE 50 500kW wood chip boiler.	Instruction manual reference "PCE50 rev00" dated 29th January 2013.	Wood chips (1).
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.		
PCE 70 700kW wood chip boiler.	Instruction manual reference "PCE70 rev00" dated 29th January 2013.	Wood chips (1).
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.		
PCE 90 900kW wood chip boiler.	Instruction manual reference "PCE90 rev00" dated 29th January 2013.	Wood chips (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.		
PCE 120 1200kW wood chip boiler.	Instruction manual reference "PCE120 rev00" dated 29th January 2013.	Wood chips (1).
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.		
PCE 150 1500kW boiler.	Instruction manual reference "PCE150 rev00" dated 29th January 2013.	Wood chips (1).
Manufactured by Groupe Compte, R, Zl de Vaureil, F – 63220 Arlanc, France.		
Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove.	Instruction manual reference "8900009004" dated July 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), the Netherlands.		
Pelletmaster PM15, 15kW wood pellet boiler.	Manufacturer's operating instructions reference "HDG Pelletmaster Version V1" dated October 2006.	Wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.		
Pelletstar 10, 20, 30, 45 and 60.	Manufacturer's operating instructions reference "V2.2" dated November 2007.	Wood pellets corresponding to ÖNORM M7135 of 6mm diameter ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Straße 22,		
A-1230 Wien, Austria.		
PelletTop 15 and PelletTop 25 Boiler. Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Installation instructions reference "Version 020905" dated 2nd September 2005 and operating manual reference "Version 270906" dated 27th September 2006.	Wood pellets ⁽¹⁾ .
Pellettop 35, Pellettop 49 and Pellettop 70 wood pellet boilers. Manufactured by SOLARFOCUS GmbH, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Operating manual dated August 2012 reference "pellettop_operating_manual_201209v	Wood pellets ⁽¹⁾ . 1".
Penman Heritage 100M, Mode 100M, Heritage 200M and Mode 200M multifuel stoves. Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	Installation and operating instructions manual reference "Her/Mod M&W Version 1" dated May 2013. The appliance must be fitted with the manufacturer's smoke control kit.	Wood logs ⁽¹⁾ .
Penman Heritage 100W and Mode 100W wood-burning stoves.	Installation and operating instructions manual reference "Her/Mod M&W Version 1" dated May 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Penman Heritage 200W and Mode 200W wood-burning stoves. Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	Installation and operating instructions manual reference "Her/Mod M&W Version 1" dated May 2013. The appliance must be fitted with the manufacturer's smoke control kit.	Wood logs ⁽¹⁾ .
Pevex 60 convector stove. Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	Instruction manual reference "Pevex1016/AH/ver1" dated January 2013. The appliance must be fitted with a permanent stop to the secondary air supply to prevent the slider from being closed beyond the 40% open position. The tertiary air supply must remain 100% open.	Wood logs ⁽¹⁾ .
Pevex Bohemia X30,X40, X40 Cube, X50 and X60 multifuel stoves. Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	Manufacturer's instruction manual reference "AH/Ver3" dated July 2010.	Dry wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Pevex Bohemia X40 Inset multi-fuel appliance.	Instruction manual reference "Pevex1004/AH/ver2/" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2cm open positions respectively.	
Pevex Serenity 40D inset multi-fuel appliance.	Instruction manual reference "Pevex1003/AH/ver2" dated June 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	
PONAST KP 12S, KP 22S, KP 52S and KP 62S automatic pellet boilers.	Automatic boiler service and operation manual reference "Version 1.1" dated 29th July 2013.	Wood pellets (1).
Manufactured by PONAST spol. s r. o., Na Potůčkách 163, Valašské Meziříčí, 757 01, Czech Republic.		
Portway 1. Manufactured by BFM Europe Ltd., Trentham Lakes, Stoke on Trent, Staffordshire, ST4	Instruction manual reference "Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2"dated 20th August 2009. The appliance must be used with a	Wood logs ⁽¹⁾ .
4TJ.	modification to the secondary air slide which inhibits closure further than the 25mm from the left position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Portway 2; Portway 3. Manufactured by BFM Europe Ltd., Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.	Instruction manual reference "Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2" dated 20th August 2009. The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20mm from the left position.	Wood logs ⁽¹⁾ .
Portway Deepwood No 2. Manufactured by BFM Europe Limited, Gordon Banks Drive, Trentham Lakes North, Stoke-on-Trent, Staffordshire, ST4 4TJ.	Instruction manual reference "Portway solid fuel heating stoves wood burning models. Wood Fuel Stoves Manual v1" and "Soliftec Smoke Advice Sheet no1" dated 22nd January 2014 All appliances will be fitted with a mechanical stop to prevent closure beyond the 7mm closed position on the secondary air control.	Wood logs ⁽¹⁾ .
Portway Inset. Manufactured by BFM Europe Ltd., Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.	Instruction manual reference "Solid Fuel Stoves Manual issued - 20/08/2009 (291) 2" dated 20th August 2009. The secondary air control must be modified such that the 20mm from left position is maintained during use. The primary air control must also be modified such that the minimum setting allows a bleed of air to pass through.	Wood logs ⁽¹⁾ .
Potterton Commercial BBS 199 199kW wood pellet boiler when fitted with a WVT multi-cyclone MK02. Manufactured by WVT - Wirtschaftliche Verbrennungs-Technik GmbH	Instruction manual reference "Rev 1.1" dated July 2013.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Bahnhofstrasse 55-59, D-51491 Overath- Untereschbach, Germany.		
Pyroclassic IV.	Instruction manual reference "PYROS 04" dated August 2011.	Wood logs ⁽¹⁾ .
Manufactured by Pyroclassic Fires Ltd., PO Box 28150, Havelock North 4157,		
Hawke Bay, New Zealand.		
PZ 65 RL and PZ 100 RL pellet boilers.	Instruction manual reference "Assembly instruction – Instruction manual – servicing & cleaning	Wood pellets ⁽¹⁾ .
Manufactured by Biotech Energietechnik GmbH, Furtmühlstrasse 32, A-5101, Bergheim bei Salzburg, Austria.	PZ65RL/PZ100RL/PZ101RL" reference "BTMoBeWe ENG" dated July 2012.	
Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove.	Manufacturer's instructions reference "250-6931B" dated 9th October 2003.	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm ⁽¹⁾ .
Manufactured by Hearth & Home Technologies, 1445 North Highway, Colville, WA 99114, USA.		
Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove.	Manufacturer's instructions reference "7006-186" dated 8th July 2003.	Dry cured untreated wood of maximum size 43.18 cm x 10.16 cm x 5.08 cm ⁽¹⁾ .
Manufactured by Hearth & Home Technologies, 1445 North Highway,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Colville, WA 99114, USA.		
Quadra-Fire Yosemite Freestanding Wood Burning Stove. Manufactured by Hearth & Home Technologies, 1445 North Highway, Colville, WA 99114, USA.	Manufacturer's instructions reference "7004-187" dated 4th June 2003.	Dry cured untreated wood of maximum size 38.1 cm x 10.16 cm x 5.08 cm ⁽¹⁾ .
Rais 2:1 inset stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "USER MANUAL Rais 2:1 Revision 2" dated December 2009. Part number 9106510.	Wood logs ⁽¹⁾ .
Rais 500, 500-1G, 500-1SG, 500-2G, 500-2SG, 500-3G, & 500-3SG Woodburning stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual references "Instructions for installation, use and maintenance Rais 500 Revision 5" dated January 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 15% open position.	Wood logs ⁽¹⁾ .
Rais 700 inset stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "USER MANUAL Rais 700 Revision 0" dated 2010.	Wood logs ⁽¹⁾ .
Rais 900 woodburning stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais 900 Revision 1" dated January 2014. The appliance must be fitted with a mechanical stop to prevent secondary	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications: air control closure beyond the 5%	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	open position.	
Rais Bionic woodburning stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual references "Instructions for installation, use and maintenance Rais Bionic Fire Revision 1" dated January 2014.	Wood logs ⁽¹⁾ .
Rais Epoca, Rais Poleo 95 and Rais Poleo 106 stoves. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "User Manual Rais Poleo 95 & Rais Poleo 106 Rais Epoca Revision 1" dated December 2009. Part number 2106510.	Wood logs ⁽¹⁾ .
Rais Epoca II, Rais Poleo II 106 SST & Rais Poleo II 128 SST woodburning stoves. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais Poleo 2 & Rais Epoca 2 Revision 1" dated January 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	Wood logs ⁽¹⁾ .
Rais Juno & Rais Juno G Woodburning stoves. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais Rina, Rais Viva & Rais Juno Rev 6" dated January 2014. The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5 mm open position.	Wood logs ⁽¹⁾ .
Rais Pilar 13L & 13H Wood Burning Stoves. Manufactured by Rais A/S, Industrivej 20,	Instruction manual reference "Instructions for installation, use and maintenance Rais Pilar 13 L & Pilar 13 H Revision 2" dated January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
9900, Frederikshavn, Denmark.		
Rais Q-Tee II woodburning stove. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Instructions for installation, use and maintenance Rais Q-Tee 2 Revision 1" dated January 2014. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 48% open position.	Wood logs ⁽¹⁾ .
Rais Q-Tee 57, 65 and 85. Manufactured by Rais A/S Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Manual for Rais Q-Tee Revision 1" dated 28th June 2011 and supplementary instructions reference "Rais Q-Tee" dated 7th July 2011. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	Dry wood logs ⁽¹⁾ .
Rais Q-Tee Wall 57, Rais Q-Tee Wall 65 and Rais Q-Tee Inset. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Manual for Rais Q-Tee Revision 2" dated 7th December 2012 and supplementary instructions reference "Supplementary Instructions Rais Rev.3" dated 31st January 2013. The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	Dry wood logs ⁽¹⁾ .
Rais Rondo 92 and Rais Rondo 120 stoves. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "User Manual Rais Rondo 92 & Rais Rondo 120 revision 2" dated December 2009. Part number 4076510.	Wood logs ⁽¹⁾ .
Rais Rondo Classic and Rais Mino II stoves.	Instruction manual reference "User Manual Rais Rondo & Rais Mino II	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Manufactured by Rais A/S, Industrivej 20,	The fireplace must be installed, maintained and operated in accordance with the following specifications: revision 2" dated March 2008. Part number 5056510.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
9900, Frederikshavn, Denmark.		
Rais Viva 98, Rais Viva 98G, Rais Viva 120, Rais Viva 120G and Rais Rina 90 wood burning stoves. Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	Instruction manual reference "Manual for Rais Rina, Rais Viva" dated 29th August 2011 and instruction manual reference "Supplementary Instructions Rais" dated 27th September 2011. The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5mm open position.	Wood logs ⁽¹⁾ .
Red Compact 14 wood pellet boiler. Manufactured by MCZ GROUP SpA, Via La Croce, 8 Vigonovo di Fontanafredda (PN) Italy, 33074.	Instruction manual reference "8901310800 Revision 0" dated 19th December 2013.	Wood pellets ⁽¹⁾ .
Red Compact 18 and Red Compact 24 wood pellet boilers. Manufactured by MCZ GROUP SpA, Via La Croce, 8 Vigonovo di Fontanafredda (PN) Italy, 33074.	Instruction manual reference "8901232500 Revision 2" dated 8th January 2014.	Wood pellets ⁽¹⁾ .
Red Compact 35 wood pellet boiler. Manufactured by MCZ GROUP SpA, Via La Croce, 8 Vigonovo di Fontanafredda (PN) Italy, 33074.	Instruction manual reference "8901238400 Revision 1" dated 8th January 2014.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Redfyre Kensal 20 flat top (product code RF-EN20M), Redfyre Kensal 33 flat top (product code RF-KEN33M and RF-KEN33W). Manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG.	Manufacturer's instruction manual reference "PM247 issue 1" dated July 2008 and instruction manual reference "PM280 issue 1" dated January 2009. The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood ⁽¹⁾ .
Rika Como pellet stove. Manufactured by RIKA Innovative Ofentechnik GmbH	Instruction manual reference "IN1226 Edition 1" dated June 2011.	6 mm wood pellets ⁽¹⁾ .
Müllerviertel 20 AT - 4563 Micheldorf, Austria.		
Rika Evo Aqua 9 and 15.	Instruction manual reference "J18/HB" dated 27th February 2009.	6mm wood pellets ⁽¹⁾ .
Manufactured by SHT Heiztechnik aus Salzburg GmbH, Rechtes Salzachufer 40 A-5101, Salzburg- Bergheim, Austria.		
Rika Memo pellet stove.	Instruction manual reference "IN1228 Edition 1" dated June 2011.	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.		
Rika Pico pellet stove.	Instruction manual reference "IN1230 Edition 1" dated June 2011.	6 mm wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.		
Rika Revo pellet stove.	Instruction manual reference "IN1229 Edition 1" dated June 2011.	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.		
Rika Tema 6kW stove. Manufactured by RIKA Innovative Ofentechnik GmbH, Müllerviertel 20, AT - 4563 Micheldorf, Austria.	Instruction manual reference "IN1218 Edition 2" dated January 2012.	Wood logs ⁽¹⁾ .
Rika Topo pellet stove.	Instruction manual reference "IN1227 Edition 1" dated June 2011.	6 mm wood pellets ⁽¹⁾ .
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT - 4563 Micheldorf, Austria.		
Riva 40 Cassette 4.9kW stoves. Manufactured by Stovax Ltd., Falcon	Instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated January 2010.	Wood logs ⁽¹⁾ .
Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi, And Riva 40 Avanti Highline 4.9kW stoves. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated January 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
Riva 45 Cassette (model numbers RV45 & RV45B) wood burning stoves.	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
Riva 50 Cassette (model numbers RV50 & RV50B) wood burning stoves.	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva 55 Cassette, Riva 66 Cassette, and Riva 66 Avanti Cassette stoves.	Instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated January 2010.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton	The appliance must be fitted with a permanent stop to prevent closure of	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Industrial Estate, Exeter, Devon, EX2 7LF.	The fireplace must be installed, maintained and operated in accordance with the following specifications: the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Riva 55 Avanti Midi and Riva 66 Freestanding 8kW stoves.	Instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual reference "PM375 Issue 2" dated January 2010.	Wood logs ⁽¹⁾ .
Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva Plus Small (5kW), Riva Plus Midi (6.5kW) and Riva Plus Medium (8kW) stoves.	Instruction manual reference "PM231 Issue 3" dated June 2009 and smoke control kit instruction manual reference "PM402 Issue 1" dated November 2009.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position.	
Riva Studio 1 (5kW) freestanding wood stove. Manufactured by Stovay Ltd. Falcon	Instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM400 Issue 3" dated June 2010.	Wood logs ⁽¹⁾ .
Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Riva Studio 2 (8kW) freestanding wood stove. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM400 Issue 3" dated June 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾ .
Riva Studio 1 Cassette (5kW). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual reference "PM400 Issue 1" dated November 2009. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾ .
Riva Studio 2 Cassette (8kW). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual reference "PM400 Issue 1" dated November 2009. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	Wood logs ⁽¹⁾ .
Riva Studio Cassette 500 RVS-500 Wood Burning Stove.	Instruction manual reference "PM400 Issue 4" dated October 2012 and instruction manual reference "PM274 Issue 9" dated August 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by	The appliance must be fitted with	
Stovax Ltd.,	Smoke Control Kit RVS500SCKIT to prevent secondary air closure beyond	
Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	the 50% open position.	
Riva Studio Duplex RVS-2DS Wood Burning Stove.	Instruction manual reference "PM935 Issue 1" dated October 2012 and instruction manual reference "PM904 – Issue 1" dated August 2012.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with Smoke Control Kit RVS-2DSSCKIT to prevent secondary air closure beyond the 91mm open position.	
Riva Studio Freestanding 500 RVFS-500 Wood Burning Stove.	Instruction manual reference "PM400 Issue 4" dated October 2012 and instruction manual reference "PM452 Issue 3" dated August 2012.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with Smoke Control Kit RVS500SCKIT to prevent secondary air closure beyond the 50% open position.	
Riva Vision Small (5kW) – Multifuel; Riva Vision Midi (6.5kW) - Multifuel.	Instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke control kit instruction manual reference "PM401 Issue 1" dated January 2010.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
Riva Vision Medium (8kW) – Multifuel.	Instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke control kit instruction manual	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Stovax Ltd., Falcon Road, Sowton	reference "PM401 Issue 1" dated January 2010.	
Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 25% open position.	
Robus Black Star 10, 14, 24 and 45 comfort wood pellet boilers.	Instruction manual reference "MCS 0001RE Issue 1" dated May 2013.	Wood pellets ⁽¹⁾ .
Manufactured by OPOP spol s.r.o, Zašovská 750, Valašské Meziříčí, Czech Republic and the pellet burners by NBE Productions A/S, Kjeldgaardsvej 2, 9300 Saeby, Denmark.		
Robus Black Star BS100 105kW and Robus Black Star BS200 196kW wood pellet boilers.	Instruction manual reference "Robus Black Star 100 and 200: Version 1.0" dated September 2014.	Wood pellets ⁽¹⁾ .
Manufactured by OPOP spol s.r.o. Zasovska 750, Valasske Mezirici, Czech Republic and the pellet burners by NBE Productions A/S, Kjeldgaardsvej 2, 9300 Saeby, Denmark.		
Robus RTB 10, RTB 16, RTB 30, RTB 50, Robus RTB 10 Vac, 16 Vac, 30 Vac, and 50 Vac wood pellet boilers.	Instruction manual reference "Ready to Burn: Version 1.1: Version 1.0" dated November 2014.	Wood pellets ⁽¹⁾ .
Manufactured by NBE Productions A/		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
S, Kjeldgaardsvej 2, 9300 Saeby, Denmark.		
Rosedale Inset Smoke Control inset roomheater. Manufactured by Town and Country Fires Ltd., Unit 1Enterprise Way, Thornton Road Industrial Estate,	Instruction manual reference "Issue No. 04" dated 11th January 2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	Wood logs ⁽¹⁾ .
Pickering, North Yorkshire, YO18 7NA.		
Rosedale SC Multifuel Stove. Manufactured by Town & Country Fires Ltd., 1 Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	"Rosedale Smoke Control Stove Installation and User Instructions Issue 1" dated 01/05/2010. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position.	Wood logs with a maximum of 20% moisture ⁽¹⁾ .
Royal Klima 18 Idro wood pellet stove boiler. Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual reference "cod. 0047700880" dated September 2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference "004723000" dated January 2012.	Wood pellets ⁽¹⁾ .
Salamander Hobbit SE stove Model 0901. Manufactured by Salamander Stoves Ltd., Cosemount	Instruction manual reference "Ref 0901SE" dated March 2013. The secondary air rotating plate must be modified such that it cannot be closed further than 4mm open.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Cottage, Canada Hill, East Ogwell, Newton Abbot, Devon, TQ12 6AF.	The primary air spin wheel must be modified such that it is fixed at a minimum of 1 half turn open.	
Saltfire Aquaburn 20 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions reference "Saltfire Aquaburn 20 Boiler Wood Version, Manual Version 1.1" dated 22nd January 2014. The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 25mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	Wood logs ⁽¹⁾ .
Saltfire Aquaburn 30 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions reference "Saltfire Aquaburn 30 Boiler Wood Version, Manual Version 1.1" dated 22nd January 2014. The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 30mm open position and a stop preventing manual primary air control closure beyond the 2mm open position.	Wood logs ⁽¹⁾ .
Saltfire Double Sided DS1 wood-burning stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and operating instructions manual reference "Saltfire Double Sided DS1 Manual 1.0" dated 4th July 2013. The appliance must be modified so that when the primary and secondary air controls are in the fully closed position they will be fixed at 3.5mm open. A tertiary air control system comprising two 7mm holes on each side of the appliance and a fixed opening of 4 cm ² on the underside of the stove must be implemented.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Saltfire Ecoview 5, Fireglow Eco 5, and Ecowarm Crystal 5 stoves. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Instruction manual reference "Evoview5 Manual 1.0" dated 15th December 2011. The appliance must be fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4mm open position.	Wood logs ⁽¹⁾ .
Saltfire Ecoview 12, Fireglow Eco 12, and Ecowarm Crystal 12 stoves. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Instruction manual reference "Evoview12 Manual 1.0" dated 15th December 2011. The appliance must be fitted with a mechanical stop to prevent closure of the tertiary air beyond the 4mm open position.	Wood logs ⁽¹⁾ .
Saltfire Oslo-Eco, Fireglow Eco 7 and Ecowarm Crystal 6. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Instruction manual reference "ECO7operation-Revision 2A" dated 24th January 2011.	Wood logs ⁽¹⁾ .
Saltfire ST1, Fireglow ST1, & Ultimo ST1 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	Installation and Operating Instructions reference "Saltfire ST1, A.K.A Fireglow ST1, A.K.A. Ultimo ST1, Manual Version 1.1" dated 22nd January 2014. The appliance must be fitted with mechanical stop to prevent air wash control closure beyond the 22mm open position and a stop to prevent secondary air control closure beyond the 50% open position.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Saltfire ST2, Fireglow ST2, & Ultimo ST2 Wood Burning Stove. Manufactured by Saltfire Stoves Ltd, Station Works, Johns Road, Wareham, BH20 4BG.	Installation and Operating Instructions reference "Saltfire ST2, A.K.A Fireglow ST2, A.K.A. Ultimo ST2, Manual Version 1.1" dated 22nd January 2014. The appliance must be fitted with a mechanical stop to prevent air wash control closure beyond the 7mm open position and a stop to prevent tertiary air control closure beyond the 20% open position.	Wood logs ⁽¹⁾ .
Saltfire Sturminster Inset wood-burning stove. Manufactured by Saltfire Stoves Ltd., Station Works, Johns Road, Wareham, BH20 4BG.	Installation and Operating Instruction manual reference "Saltfire Sturminster Manual 1.0" dated 4th July 2013.	Wood logs ⁽¹⁾ .
San Remo 4SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "SR468SE" dated 25th July 2012. The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	Wood logs ⁽¹⁾ .
San Remo 6SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	Instruction manual reference "SR468SE" dated 25th July 2012. The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	Wood logs ⁽¹⁾ .
San Remo 8SE stove. Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial	Instruction manual reference "SR468SE" dated 25th July 2012. The appliance must be fitted with a system to prevent closure of the	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Estate, Naas Road, Dublin 12, Ireland.	The fireplace must be installed, maintained and operated in accordance with the following specifications: secondary air control beyond 25% from closed.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
San Remo SR5i Multi- fuel inset stove.	Installation and Operating Instruction manual reference "SR5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
SASP 1000 675 kW Biomass Boiler when fitted with a multi- cyclone	Instruction manual assembly and operation manual reference "Version TOP/SASP/V.1.1" dated 12th December 2013.	Woodchips of maximum 25% moisture content (1).
Manufactured by Topling d.o.o. Magistraini put BB, 78430 Prnjavor. The Republic of Srpska, Bosnia and Herzegovina.		
Scan Anderson 4-5. Manufactured by Krog Iversen 7 Co., A/S DK-5492 Vissenbjerg, Denmark.	Manufacturer's instructions entitled "Scan Andersen 4-5" reference "09/05-GB" dated 15th November 2007. The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond 20mm.	Untreated dry wood ⁽¹⁾ .
Scan Andersen 8-2 wood-burning 7 kW stove Manufactured by Jøtul A.S, P.O. Box 1411, N-1602 Fredrikstad,	Installation and operating instructions manual reference "10026402 -P01" dated October 2012 and addendum to installation and operating instructions manual reference "SMOKEA8-2" dated 5th June 2014.	Wood logs ⁽¹⁾ .
Norway.	The appliance must be fitted with Smoke control kit SMOKEA8-2 to prevent closure of the air control beyond 25% open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Scan 58-1, Scan 58-1 Wall;	Instruction manual reference "GB 90358500-5" dated 24th March 2011	Wood logs ⁽¹⁾ .
Scan 58-2, Scan 58-2 Wall;	and supplementary instructions for UK Smoke Control Areas reference "SCAN58SCA" dated 1st March 2013.	
Scan 58-3, Scan 58-3 Wall;	The appliance must be fitted with a mechanical stop to prevent closure of	
Scan 58-4, Scan 58-4 Wall;	the secondary air control beyond the 1/3rd open position.	
Scan 58-5, Scan 58-5 Wall;		
Scan 58-6, Scan 58-6 Wall;		
Scan 58-7, Scan 58-7 High Top;		
Scan 58-8, Scan 58-8 High Top;		
Scan 58-9, Scan 58-9 High Top;		
Scan 58-10, Scan 58-10 High Top.		
Manufactured by Scan A/S, Glasvænget 3-9, 5492 Vissenbjerg, Denmark.		
Scan 66-1, 66-3, 66-4 stoves	Assembly and instructions manual reference "GB 90066500" dated 27th October 2014.	Wood logs ⁽¹⁾ .
Manufactured by Scan A/S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 35mm open position.	
Scan 83-1 stove, Scan 83-2 stove, Scan 83-3	Instruction manual reference "UK 90583500" dated 15th January 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Maxi stove, Scan 83-4 Maxi stove, Scan 83-5 stove, Scan 83-6 stove, Scan 83-7 Maxi stove, Scan 83-8 Maxi stove.		
Manufactured by Scan A/S, Glasvaenget 3-9, 5492 Vissenbjerg, Denmark.		
Scan DSA 7-5 wood-burning Inset roomheater. Manufactured by Scan A/S, Glasvænget 3-9, 5492 Vissenbjerg, Denmark.	Instruction manual "Instructions for installation and use: SCAN DSA 6 & DSA 7-5" reference "Edition 17.09.2010 – GB", supplement "DSA 7-5 – UK smoke control areas" reference "DSA 7-5 SMOKE" dated 1st January 2012 and instructions for installation (including directions for use and stoking) reference "Edition 05.10.2010 – GB" dated 5th October 2010.	Wood logs ⁽¹⁾ .
	The appliance must be fitted with a mechanical stop to prevent closure of the air wash control lever beyond the 50% open position.	
Scan ILD 7 and ILD 8 wood-burning stoves Manufactured by Color Emajl d.o.o. Alaginci 87/a, HR-34000 Pozega, Croatia.	Instruction manual reference "Manual version. No. 13-1 GB 01.07.13" dated 1st July 2013. The appliance must be fitted with a permanent stop to fix the secondary air control 7.5% open in the fully closed position.	Wood logs ⁽¹⁾ .
Scandian 5MF Traditional, Scandian 5MF Modern, Scandian 8MF Traditional and Scandian 8MF Modern multifuel stoves.	Installation and operating instructions manual reference "Scandian MF&WD Version 1" dated June 2013. The appliance must be fitted with the manufacturer's smoke control kit.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Scandian 5WD Traditional and Scandian 5WD Modern wood-burning stoves.	Installation and operating instructions manual reference "Scandian MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.		
Scandian 8WD Traditional and Scandian 8WD Modern wood-burning stoves.	Installation and operating instructions manual reference "Scandian MF&WD Version 1" dated June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	The appliance must be fitted with the manufacturer's smoke control kit.	
Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600kW.	Manufacturer's instruction manual reference "UTSK-ABC.22-AME-S-PPU" dated 25/09/2008 (where ABC is model number i.e. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600).	Wood pellets or wood chips following CEN/TS 14961:2005
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Schmid UTSL 30, 40, 50, 65, 80, 110, 150kW. Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	Manufacturer's instruction manual reference "Operating Manual Wooden Chips and Pellets Plant. Lignumat UTSL" dated 23rd December 2004.	Wood pellets or wood chips following CEN/TS 14961:2005
Schmid UTSP 180, 240, 300kW. Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	Manufacturer's instruction manual reference "UTSK – ABC22-AME-S-PPU" (where ABC is model number i.e. 180, 240, 300) dated 25th September 2008.	Wood pellets following CEN/TS 14961:2005 ⁽¹⁾ .
Schmid UTSR 150, 180, 240, 300, 360, 450, 550, 700, 900kW. Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	Manufacturer's instruction manual reference "UTSR – ABC22-AME-S-PPV" (where ABC is model number i.e. 150, 180, 240, 300, 360, 450, 550, 700, 900) dated 25th September 2008.	Wood pellets or wood chips following CEN/TS 14961:2005
Schmid UTSR 1200. Manufactured by Schmid AG Energy Solutions, PO Box 42, CH-8380 Eschikon, Switzerland.	Instruction manual reference "60110797.doc" dated 24th April 2012.	Wood chips and wood pellets (1).
Schmid UTSW 900.32. Manufactured by Schmid AG Woodfiring Systems, PO Box 42,	Instruction manual reference "Instruction manual. Wood chip furnace with boiler type Schmid Pyrotroinc Modular issue 1" dated 7th January 2013 and instruction manual reference "PersonalTouch Version	Wood chips and wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
CH-8380 Eschikon,	The fireplace must be installed, maintained and operated in accordance with the following specifications: 2010 EVO10 V531\PT 2010 C3."	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Switzerland.	dated 2010.	
Seguin Jade woodburning stove.	Instruction manual reference "Wood Stoves Manual	Wood logs ⁽¹⁾ .
Manufactured by Groupe Seguin, Cheminees Seguin Duteriez, Zone Industrielle de Lhérat, 63310 France.	Installation – Use 1/1/2013 Characteristics of the Stove" dated 1st January 2013. The appliance must be fitted with a	
000101144400	permanent stop to prevent closure of the secondary air control beyond the 40% open position.	
Seguin Saphir woodburning stove.	Instruction manual reference "Wood Stoves Manual	Wood logs ⁽¹⁾ .
Manufactured by Groupe Seguin, Cheminees Seguin Duteriez, Zone Industrielle de Lhérat,	Installation – Use 1/1/2013 Characteristics of the Stove" dated 1st January 2013.	
63310 France.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond the 15mm open position.	
Senza UK w/o sideglass and Senza UK w/ sideglass 5kW wood burning stoves	Instruction manual reference "User's manual Revision 1, 27.11.2014" dated 27th November 2014.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr. Felding, DK-7500 Holstebro, Denmark.	The appliance must be fitted with a modification to fix the secondary air control to 1300mm ² in its minimum position.	
Serenity 40 FS, Serenity 40 LS and Serenity 40 FW stoves.	Instruction manual reference "Pevex1014/AH/ver1" dated January 2013.	Wood logs ⁽¹⁾ .
Manufactured by Pevex Enterprises	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	do not close beyond 1.1cm open and 2cm open positions respectively.	
Serenity 50FS, Serenity 50LS, Serenity 50FW, Serenity 50 Ped and Serenity 50 Inset stoves. Manufactured by Pevex Enterprises Ltd., Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS.	Instruction manual reference "Pevex1014/AH/ver1" dated January 2013. The secondary air slider must have a built in stop to prevent the slider from being shut off completely and remains open by 40% of its full travel. The tertiary air control must not have a slider and it must be factory designed with a 2cm open slot that remains 100% open.	Wood logs ⁽¹⁾ .
Serrano 5, York Midi; Monterrey 6 Stoves. Manufactured by Broseley Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "09TJD" dated January 2010. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	Wood logs ⁽¹⁾ .
Serrano 5 Multi Fuel and Monterrey 6 Multi Fuel Stoves. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "TJ09C" dated 21st December 2009. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	Wood logs ⁽¹⁾ .
Serrano 7 Multi Fuel stove.	Instruction manual reference "TJ09C" dated 21st December 2009.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by	The appliance must be fitted with a	
Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	system that prevents the closure of the secondary air flaps to less than 10mm open position.	
Sherborne SE NS-3C,	Installation and user instruction manual reference "NS-3A - NS-3B -	Wood logs (1).
Chesham SE NS-3B,	NS-3C" dated 4th June 2014.	
Burford SE NS-3A 4.9kW multi-fuel stoves.	The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position and the tertiary	
Manufactured by Newman Fireplaces Ltd	air beyond the 50% open position.	
Units 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.		
Short Penguin and Penguin 8 multifuel stoves.	Instruction manual reference "Penguin Manual Version 1 Issue 1" dated 17th December 2013.	Wood logs ⁽¹⁾ .
Manufactured by Chilli Penguin Stoves Limited, Castell Bach, Mynydd Nefyn, Pwllheli, LL53 6TL.	The appliance must be fitted with a modification to fix the secondary air control to 1cm open in the fully closed position.	
SHT TDA Thermodual 15 and 25 log and pellet burning boilers.	Installation servicing instructions reference "In1233 Edition 1a" dated January 2014, operating instructions reference "M21/HB M27/GB" dated 28th January 2014 and supplementary	Wood logs or wood pellets ⁽¹⁾ .
Manufactured by Lohberger Heiztechnik GmbH,	installation instructions reference "IN1241 Edition 1a" dated January 2014.	
Rechtes Salzachufer 40,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
A-5020 Salzburg, Austria.		
SHT TDA Thermodual 30 and 40 log and pellet burning boilers. Manufactured by Lohberger Heiztechnik GmbH,	Installation servicing instructions reference "In2015 Edition 1" dated January 2014, operating instructions reference "M21/HB M27/GB dated 28th January 2014 and supplementary installation instructions reference "IN1241 Edition 1a" dated January 2014.	Wood logs or wood pellets ⁽¹⁾ .
Rechtes Salzachufer 40,		
A-5020 Salzburg, Austria.		
Silverdale 5SE, Amalia 5, Oppdal 5 and Hestia 5 multifuel stoves Manufactured by Broseley Fires, Knights Way, Battlefield Enterprise Park, Shrewsbury, SY1 3AB. NB: these are the same as the wood burning versions, with an alternative grate to allow use of other authorised fuels.	Instruction manual reference "GB14A-issue 5" dated December 2014. The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 23mm open.	Wood logs ⁽¹⁾ .
Silverdale 7SE, Amalia 7, Oppdal 7 and Hestia 7 multifuel stoves Manufactured by Broseley Fires, Knights Way, Battlefield Enterprise	Instruction manual reference "GB14A-issue 5" dated December 2014. The appliance must be fitted with a permanent stop to fix the secondary air slide at a minimum of 50mm open.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Park, Shrewsbury, SY1 3AB.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
NB: these are the same as the wood burning versions, with an alternative grate to allow use of other authorised fuels.		
Sirius 490 Sigma MF, Sirius 490 Scene MF, Sirius 790 Sigma MF and Sirius 790 Scene MF multifuel stoves. Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	Installation and Operating Instructions manual reference "Sirius MF&WD Version 1" dated May 2013. The appliance must be fitted with the manufacturer's smoke control kit.	Wood logs ⁽¹⁾ .
Sirius 490 Sigma WD and Sirius 490 Scene WD wood-burning stoves. Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	Installation and operating Instructions manual reference "Sirius MF&WD Version 1" dated May 2013.	Wood logs ⁽¹⁾ .
Sirius 790 Sigma WD and Sirius 790 Scene WD wood-burning stoves. Manufactured by Capital Fireplaces Ltd., 12-17 Henlow Trading Estate, Henlow Camp, Hitchin, SG16 6DS.	Installation and operating instructions manual reference "Sirius MF&WD Version 1" dated May 2013. The appliance must be fitted with the manufacturer's smoke control kit.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Sirius Traditional Stove. Manufactured by Tianjin Focus Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tianjin, P.R. China 300350.	Instruction and operating instruction manual reference "v173 of 09/11/2010" dated 9th November 2010.	Wood logs ⁽¹⁾ .
Smart 150, Smart 199, Smart 250, Smart 300, Smart 350, Smart 400, Smart 450 and Smart 500 boilers all fitted with cyclones. Manufactured by Smart Heating Technology s.r.o, U Statku 653/24, 717 00 Ostrava-Bartovice, Czech Republic.	Operation manual reference "BO4CD35 Issue No: 02" dated January 2014.	6mm wood pellets or 30mm wood chips at maximum 30% moisture ⁽¹⁾ .
Spartherm Arte U-50h - P3, U-90h - P3 and U-70h - P3 insert stoves Manufactured by Spartherm Feuerungstechnik GmbH Maschweg 38, Melle, Germany.	Instruction manual reference "Version 06/2014" dated June 2014.	Wood logs ⁽¹⁾ .
Spartherm Linear Cassette XS500-P3 insert stove Manufactured by Spartherm Feuerungstechnik GmbH Maschweg 38, Melle, Germany.	Instruction manual reference "Version 06/2014" dated June 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Spartherm Linear cassette model S 600 P3 inset stove. Manufactured by	Installation and operating instructions reference "Spatherm_AA_BA_Kaminkassette_L 01-2014" dated January 2014.	Dry wood logs ⁽¹⁾ . inear_GB_Stand
Spartherm Feuerungstechnik GmbH, Maschweg 38,Melle, Germany.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 25% open position.	
Spartherm Mini 2LRh-4S P3, Mini 2L-4S P3 and Mini 2R-4S P3 wood-burning inset roomheaters Manufactured by Spartherm Feuerungstechnik GmbH Maschweg 38, Melle, 49324, Germany.	Instruction manual reference "Instruction Manual Fireplace Inserts Version 06/2014" dated June 2014. The appliance must be fitted with a system to prevent closure of the air controls beyond the 3mm open position.	Wood logs ⁽¹⁾ .
Spartherm Stovo S, M, & L Wood burning stoves.	Installation and operating instructions reference "Version 07/2013" dated July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Spartherm, Feuerungstechnik GmbH, Maschweg 38, Melle, Germany.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 13% open position.	
Spatherm Varia ASh2L – P3, Varia ASh2R – p3, Varia ASh2LX – P3, Varia Ash2R X – P3 wood burning inset roomheaters.	Instruction manual reference 'Instruction Manual Fireplace Inserts Version 06/2014' dated June 2014. A system to prevent closure of the air controls beyond the 7mm open position must be implemented.	Wood logs ⁽¹⁾ .
Manufactured by Spatherm Feuerungstechnik GmbH, Maschweg	halogenated organic compounds or heavy metals as	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
38, D-49324 Melle,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Germany.		
Stockton 3 flat top (product code 7118), Stockton 4 flat top (product code 7101 and 7102), Stockton 5 flat top (product code 7127), Stockton 5 midline (product code 7130), Stockton 6 flat top (product codes 7100 and 7162), Stockton 6 Highline (product code 7117), and Stockton 7 flat top (product codes 7120 and 7163).	Instruction manual reference "PM227 ENG Issue 2" dated July 2008 and instruction manual reference "PM271 Issue 2" dated January 2009. The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood (1).
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.		
Stockton 5 flat top (model number 7119), Stockton 5 Canopy (model number 7160), and Stockton 5 Midline (model number 7133). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2	Manufacturer's instructions reference "PM176 – issue 4". The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood ⁽¹⁾ .
7LF. Stockton 7 Inset	Manufacturer's instruction manual	Untreated dry wood ⁽¹⁾ .
Convector (product codes 7125F and 7125C).	reference "PM230 Issue 1" dated May 2008 and instruction manual reference "PM281 Issue 1" dated January 2009.	Onucated dry wood

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	
Stockton Milner (4.6kW) inset stove – smoke control version. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM416 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM501 Issue 1" dated June 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
Stoven Mayfair SE & Stoven Kensington SE 5kW Wood Burning Stoves. Manufactured by Ciang Stoves Ltd., South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China 455000.	Instruction manual reference "3-4" dated 27th November 2011. The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 25% open position and the tertiary air beyond the 1mm open position.	Wood logs ⁽¹⁾ .
Strebel Biotec 25 and 40 boilers Manufactured by Topling d.o.o. Magistralni put BB, 78430 Prnjavor, The Republic of Srpska, Bosnia and Herzegovina.	Instruction manual reference "Version BIOTEC 122013" dated December 2013.	Wood pellets ⁽¹⁾ .
Strebel SRP TR 90, 90kW output pellet boiler.	Installation manual reference "Installation and operation	6mm diameter wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Strebel Ltd., 1F Albany Park Industrial Estate, Frimley Road, Camberley, Surrey, GU15 7P.	instructions for special pellet-furnace version 09:2010".	
Strebel Taurus XL 145, Strebel Taurus XL	Instruction manual reference "Manual Version XL145 to 290" dated December 2013.	Wood pellets and wood chips (1).
Strebel Taurus XL 240 and		
Strebel Taurus XL 290 boilers.		
Manufactured by KSM Stoker, Naessundvej 440, 7960 Karby, Denmark.		
Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE).	Instruction manual reference "N00530AXX REV:001" dated 12th July 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Aga, Station Road, Ketley Telford, Shropshire, TF1 5AQ.		
STU 195 and STU 975.	Instruction manual reference "Installation, Operation and Maintenance Instructions. STU	Wood pellets (1).
Manufactured by Hoval Ltd., Northgate, Newark, Nottinghamshire, NG24 1JN.	wood-pellet fired hot water boiler skid assembly STUman CAA (SM)" dated May 2011.	
Stuv 30 Compact H. Manufactured by Stuv Sa, Rue Jules	Instruction manual reference "SN 131766" dated January 2013 and installation instruction manual	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Borbouse 4, B-5170 Bois-de-Villers, Belgium.	reference "SN 131766" dated January 2013.	
Beigium.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	
Stuv 30 Compact IN and Stuv 30 Compact R. Manufactured by Stuv Sa, Rue Jules	Instruction manual reference "SN 112787" dated January 2013 and installation instruction manual reference "112787" dated January 2013.	Wood logs ⁽¹⁾ .
Borbouse 4, B-5170 Bois-de-Villers, Belgium.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	
Stuv 30 Compact.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Stuv Sa, Rue Jules Borbouse 4, B-5170 Bois-de-Villers, Belgium.	"SN 94770" dated January 2013 and installation instruction manual reference "SN 94770" dated January 2013.	
	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the positions between settings 3 and 4.	
Suprema, Mamy and Italy Hard Top.	Instruction manual reference "7095701 Rev.09" dated 13th December 2010.	Wood logs ⁽¹⁾ .
Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Talbott 150-CMH 150kW output Biomass Air Heater.	Instruction manual reference "OM-150-CMH version.1" dated January 2011.	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts ⁽¹⁾ .
Manufactured by Talbott's Biomass Energy Systems		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's Automatic Biomass Air Heaters, models T1.5/A, T3/A, T5/A and TM/A.	Manufacturer's instructions reference "T/A JANUARY 1990".	Hardwood or softwood shavings or sawdust ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's Biomass Energy Models C1, C2, C3 and C4.	Manufacturer's instructions reference "Issue C1000/C/Range" dated August 1995.	Chipboard or wood shavings, forestry chips ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's model T75, T150, T300 Biomass Air Heaters.	Manufacturer's instructions reference "models T75, T150 and T300: "gen/sttech" dated 1st January 1995.	Wood offcuts, wood-waste, pellets, chipboard ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's T500 Biomass Air heater (afterburn model). Formerly manufactured by Talbott's Heating Ltd., and now manufactured by Talbott's Biomass Energy Systems Ltd., Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.	Manufacturer's instructions reference "A10000" dated 1st January 1983. The afterburn cycle must last not less than 25 minutes and must come into operation each time the loading door is opened.	Wood offcuts, wood-waste, pellets, chipboard ⁽¹⁾ .
Termatech TT20, TT20Bazic, TT20R, TT20S, TT20RS and TT20SA woodburning stoves Manufactured by TermaTech A/S, Jegstrupvej 60, DK-8361 Hasselager, Denmark	User and mounting manual reference "99-275 UK version" dated July 2014. The appliance must be fitted with the damper control unit referenced in the manufacturer's manual.	Wood logs ⁽¹⁾ .
Termatech TT22 and TT22S convection wood-burning stoves	User and mounting manual reference "99-234 UK version" dated July 2014.	Wood logs ⁽¹⁾ .
Manufactured by TermaTech A/S, Jegstrupvej 60, DK-8361 Hasselager, Denmark	The appliance must be fitted with a smoke control kit to ensure the primary and secondary air controls are 25% open in their minimum position.	
Therminator II 22 and Therminator II 30 Boiler. Manufactured by Solarfocus Ltd.,	Installation instructions reference "Version: 11/08/06" dated July 2006, operating manual reference "V8.051" dated September 2009 and maintenance instructions reference "Ver.:01/09/06" dated 2006.	Wood pellets ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.		
Therminator II 27 and Therminator II 36 Boiler.	Installation instructions reference "Version:11/08/06" dated July 2006, operating manual reference "V8.051" dated September 2009 and	Wood logs ⁽¹⁾ .
Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	maintenance instructions reference "Ver.:01/09/06" dated 2006.	
Therminator II 40 Boiler.	Installation instructions reference "Version: 11/08/06" dated July 2006, operating manual reference	Wood pellets or wood chips (1).
Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	"V8.051" dated September 2009 and maintenance instructions reference "Ver.:01/09/06" dated 2006.	
Therminator II 49 and Therminator II 60 Boiler.	Installation instructions reference "Version: 11/08/06" dated July 2006, operating manual reference "V8.051" dated September 2009 and	Wood logs or wood pellets or wood chips ⁽¹⁾ .
Manufactured by Solarfocus Ltd., Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	maintenance instructions reference "Ver.:01/09/06" dated 2006.	
Thornhill T3 small.	Instruction manual reference "ED/11/05" dated January 2011.	Wood logs ⁽¹⁾ .
Manufactured by Thornhill Eco Design Ltd., 58-60 Wincheap, Canterbury, Kent, CT1 3RS.	The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	
Tiger GH-T Insert Stove.	Instruction manual reference "Tiger solid fuel heating stoves inset multifuel models incorporating GH-T	Wood logs ⁽¹⁾ .
Manufactured by Hughes Design Limited, Denver House, Winster,	Firebox. Solid Fuel Stoves Manual v12" dated 22nd January 2014 and "Soliftee Smoke Advice Sheet no1" dated 22nd January 2014.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Derbyshire, DE4 2DH.	The fireplace must be installed, maintained and operated in accordance with the following specifications: The appliance must be fitted with a mechanical stop to prevent closure beyond the 5mm closed position on the secondary air control.	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Tiger SuperClean.	Instruction manual reference	Wood logs ⁽¹⁾ .
Manufactured by Tiger stoves, Focus Arts & Crafts Co., Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tainjin, P. R. China 300350.	"Installation and Operating Instructions document v.148" dated April 2010.	
Trianco Greenflame 15 wood pellet boiler.	Instruction manual reference "Item No. 400001 Iss. 2" dated 25th June 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by T.R Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Trianco Greenflame 18 Slim Wood Pellet Boiler	Installation and operating manual reference "V.1.1" dated June 2014.	Wood pellets (1).
Manufactured by T.R Engineering Ltd., Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Trianco Greenflame 55, 85, 100, 125, & 199 Wood Pellet Boilers.	Installation, operation and servicing instructions reference "Manual Edition: Greenflame Commercial Series" dated May 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd.,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Tripp TR5i Multi-fuel inset stove.	Installation and operating instruction manual reference "TR5i" dated 2nd May 2013.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design Ltd., 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 3.5mm open position.	
Turbhogar Alfa 80T and 65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lambda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T and Turbhogar Tau 80T and 65T fireplace inserts.	Manual of assembly and use reference "RR100920" dated 20th September 2010 and supplementary instruction manual reference "UK100920" dated 20th September 2010. The appliance must be fitted with a system that prevents the full closure of the air control opening so that the air openings remain 3mm (30%) open at the minimum setting.	Wood logs ⁽¹⁾ .
Manufactured by Rofer & Rodi UK Ltd., Rofer & Rodi UK Ltd., Unit 10, Millennium Road, Airedale Business Centre, Skipton, North Yorkshire, BD23 2TZ.		
Turco Woodsman 18 Slim Wood Pellet Boiler	Installation and operation manual reference "V.1.1" dated June 2014.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Turkington Engineering Woodlander 28 Wood Pellet Boiler; and Highland Biomass Solutions Bio-Flame 28 Wood Pellet Boiler. Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	Installation and operation manual reference "Version 2.1" dated July 2013.	Wood pellets ⁽¹⁾ .
Turkington Engineering Woodlander 55, 85, 100, 125, & 199 Wood Pellet Boilers. Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.	Installation, operation and servicing instructions reference "Manual Edition: Woodlander Commercial Series" dated July 2013.	Wood pellets ⁽¹⁾ .
Twin Heat CS 150i. Manufactured by TWIN HEAT A/ S, Nørrevangen 7, DK-9631 Gedsted, Denmark.	Manufacturer's operating instructions reference "version 6.0.03." dated 17th December 2008.	Wood pellets of a maximum length of 30mm and diameter of 6mm and conforming to CEN/TS 14961:2005 (1).
Type USV wood pellet and wood chip fired boilers, model numbers USV-15, 25, 30, 40, 50, 60, 80 and 100.	Manufacturer's instructions reference "BA-USV 0803" dated August 2003.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by KWB – Kraft und Wärme aus		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
Type USP wood pellet fired boilers, model numbers USP-10, 15, 20, 25 and 30.	Manufacturer's instructions reference "BA-USP 0703" dated 28th July 2003.	Wood pellets ⁽¹⁾ .
Manufactured by KWB – Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
Uniconfort EOS 45, EOS 50, EOS 55, EOS 65, EOS 70, EOS 75, EOS 80, EOS 85 fitted with a multi-cyclone.	Instruction manual reference "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.		
Uniconfort EOS 90 fitted with a multicyclone.	Instruction manual reference "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Varde Aura Ovne 1 (VD-AURA1), 2 (VD-AURA2), 3 (VD-AURA3), and 11 (VD-AURA11) wood burning 5kW stoves Manufactured by Varde Ovne A/ S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "FOR-177 GB2 edition" dated 26th July 2010 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Aura 2. Edition FOR-177 GB PM1053 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position.	Wood logs ⁽¹⁾ .
Varde Ovne Fuego 1 (VD-FUEGO1) and 2 (VD-FUEGO2) wood burning 5kW stoves Manufactured by Varde Ovne A/ S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "Varde Fuego Revision 2" dated 15th May 2013 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Fuego – Revision 02 Installation and User Guide PM1062 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position.	Wood logs ⁽¹⁾ .
Varde Ovne Shape 1 (VD-SHAPE1B) and 2 (VD-SHAPE2B) wood burning 5kW stoves Manufactured by Varde Ovne A/ S, Kongevej 246, DK-6510 Gram, Denmark.	Installation and user guide reference "FOR – 176 GB1 edition" dated 18th June 2009 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Shape 1. Edition FOR-176 GB PM 1054 Issue 2" dated July 2014. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 37.5% open position.	Wood logs ⁽¹⁾ .
Varde Ovne Uniq 1 (VD-UNIQ1) wood burning 5.4kW stove Manufactured by Varde Ovne A/	Installation and user guide reference "Revision 6" dated 3rd June2014 and additional installation and user instructions for use in Smoke Control Areas reference "Varde Uniq – Revision 4 Installation and User	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
S, Kongevej 246, DK-6510 Gram, Denmark.	Guide PM1055 Issue 2" dated July 2014.	
Definition.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 30% open position.	
VarioWIN VA 120 12kW wood pellet boiler.	Installation instruction manual reference "092947/00" dated January 2010 and operating instruction manual reference "092945/00" dated	Wood pellets, 6mm diameter, length 80% between 15-30mm and a density of at least 1.1kg/dm ³⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str.20, A-5201 Seerkirchen bei Salzburg, Austria.	January 2010.	
Vega 100 Clean Burn II. Manufactured by	Instruction manual reference "Vega 100 Clean Burn II Installation and Operation Instructions REV: D" dated January 2013.	Wood logs ⁽¹⁾ .
Percy Doughty & Co Ltd., Imperial Point, Express Trading Estate, Stonehill Road, Farnworth	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	
Bolton, BLA 9TN.		
Vega 200 Clean Burn. Manufactured by Percy Doughty & Co Ltd., Imperial	Instruction manual reference "Vega 200 Clean Burn Installation and Operation Instructions REV: D" dated January 2013.	Wood logs ⁽¹⁾ .
Point, Express Trading Estate, Stonehill Road, Farnworth Bolton, BLA 9TN.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 50% open position.	
Vega Amor 100 4.9kW multi-fuel stove	Instruction manual reference "AMOR 100 REV:B" dated December 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Percy Doughty & Co. Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton BL4 9TN	The appliance must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	
Vega Edge 100 4.9kW multi-fuel stove	Instruction manual reference "VEGA EDGE 100 INSTRUCTION – REV. B" dated December 2014.	Wood logs ⁽¹⁾ .
Manufactured by Percy Doughty & Co. Limited, Imperial Point, Express Trading Estate, Stone Hill Road, Farnworth, Bolton BL4 9TN	The appliance must be fitted with a permanent stop to modify the secondary air control closure to a minimum of 7mm open.	
Vermont Castings Defiant model 1975 catalytic wood- burning stove.	Homeowner's installation and operating manual reference "30005554 7/13 Rev. 10" dated July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Vermont Castings Group, 62 Vermont Castings Road, Bethel, Vermont, 05032, USA.	The appliance must be operated with the catalyst and fitted with a system that prevents closure of the air control lever beyond the 25mm (5 o'clock) open position.	
Vermont Castings Encore model 2040 catalytic wood- burning stove.	Homeowner's installation and operating manual reference "30005552 7/13 Rev. 9" dated July 2013.	Wood logs ⁽¹⁾ .
Manufactured by Vermont Castings Group, 62 Vermont Castings Road, Bethel, Vermont, 05032, USA.	The appliance must be operated with the catalyst.	
Vesuvio 400kW automatic pizza oven. Manufactured by CLM srl, Via I	CLM Vesuvio oven instruction manual reference "Instruction and maintenance manual ENGLISH version Review 0.1" dated 29th November 2011.	'CalorPan' 100% beech briquette, octagonal section, length 260-300mm, width and height 75-90mm manufactured from dried beech sawdust (1).
Maggio 35, 31043,	The term of Early	from aried beech sawaust \(\cdot \).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fontanelle (Treviso), Italy.		
View 3 (3.8kW) and View 5 (4.9kW) multifuel stoves; View 5 (4.9kW) wood stove. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM485 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM490 Issue 1" dated June 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
View 7 (7kW) inset appliance Product code VW-7NMF. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM552 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM490 Issue 2" dated July 2011. The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	Wood logs ⁽¹⁾ .
Vista Magnifico SE & Vista Perfetto SE 4.9kW wood burning stoves. Manufactured by Ciang Stoves Ltd., South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China 455000.	Newman Fireplaces Ltd.'s Instruction manual reference "1-2" dated 24th October 2011. The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position and the tertiary air beyond the 50% open position.	Wood logs ⁽¹⁾ .
Vista Magnifico SE NS-1 and Vista Perfetto SE NS-2	Installation and user instruction manual reference "NS-1, NS-2 Edition: 2" dated 3rd June 2014.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
4.9kW multi-fuel	The appliance must be fitted with	
stoves	mechanical stops to prevent closure	
Manufactured by	of the secondary air control beyond the 30% open position and the tertiary air beyond the 50% open position.	
Newman Fireplaces Ltd		
Units 6 & 7 Rawreth Barns, Dollymans Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD		
Vitae 06C inset stove.	Instruction manual reference "VIT06C" dated 26th July 2012.	Wood logs ⁽¹⁾ .
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Vitae 11C inset stove.	Instruction manual reference "VIT11C" dated 26th July 2012.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Vitoligno 300-P models 12, 18, 24, 32, 40 and 48 pellet boilers.	Operating instructions reference "5592 617 GB" dated January 2014 and Vitoligno 300-P Technical guide reference "5414 644 GB" dated January 2014.	Wood pellets (1).
Manufactured by Viessmann Limited, Hortonwood 30, Telford, TF1 7YP.		
Warm 1 and 4 stoves. Manufactured by Color Emajl d.o.o.,	Instruction manual reference "11-1a" dated February 2012.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Alaginci 87/a, HR-34000 Požega, Croatia.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	
Warm 2 and 5 stoves. Manufactured by Color Emajl d.o.o., Alaginci 87/a, HR-34000 Požega, Croatia.	Instruction manual reference "11-1b" dated February 2012. The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 83mm open position.	Wood logs ⁽¹⁾ .
Warmflow WS18 and WP 18 Pellet Boilers Manufactured by Warmflow Engineering Co Limited, Lissue Industrial Estate, Moira Road, Lisburn, Northern Ireland, BT28 2RF.	Boiler Manual for Wood Pellet Boiler WS18/WP18 reference "CODE 4220 Issue 1." dated May 2014.	Wood pellets ⁽¹⁾ .
Warmington SE multi- fuel stove Manufactured by Newman Fireplaces Ltd, Units 6&7, Rawreth Barns, Dollyman's Farm, Doublegate Lane, Rawreth, Wickford, Essex, SS11 8UD.	Instruction manual reference "NS-10 Edition 1" dated 17th September 2014. The appliance must be fitted with the manufacturer's smoke control kit (Newman fireplaces part number 59) to prevent closure of the secondary air control beyond the 30% open position.	Wood logs ⁽¹⁾ .
Westcott 5SE. Manufactured by Dimplex, GDC Group Ltd., Millbrook House, Grange Drive, Hedge End Southampton, SO30 2DF.	The instruction manual reference "08/51351/0 - Issue 0" dated 7th September 2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Westfire Series One stove and Westfire Series Two stove. Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of	Wood logs ⁽¹⁾ .
	the secondary air control less than 50% open.	
Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20).	Manufacturer's instructions reference "WF15 – WF16 – WF20" dated 2007 and supplementary instructions reference "01 wfuk.2207" dated 2007.	Untreated dry wood (1).
Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond 50mm.	
Westfire Uniq 17, Westfire Uniq 18, Westfire Uniq 19, Westfire Uniq 23, Westfire Uniq 23 side Glass and Westfire Uniq 23 Inset.	Instruction manual reference "Westfire Supplementary Instructions June 2010" dated June 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 30mm open position.	Wood logs ⁽¹⁾ .
Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	position.	
Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Westfire APS, Tømrervej 3,	The appliance must be fitted with a permanent stop to prevent closure of	

The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives
or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
DK-6800 Varde, Denmark.	the secondary air control less than 60% open.	
Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove. Manufactured by Westfire APS,	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011.	Wood logs ⁽¹⁾ .
Tømrervej 3, DK-6800 Varde, Denmark.	The appliance must be fitted with a permanent stop to the secondary air slider control to prevent closure more than 20mm from the fully closed position.	
Westfire Uniq 32 Inset stove and Westfire Uniq 32 Freestanding stove. Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	Installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	Wood logs ⁽¹⁾ .
Westfire Uniq 33 SE Westfire Uniq 33 side glass SE Westfire Uniq 34 SE Westfire Uniq 34 side glass SE multi-fuel 6.1 kW stoves Manufactured by Westfire ApS, Tømrervej 3, VARDE, DK-6800, Denmark.	Installation manual and operating instructions reference "UNIQ33/34V1" dated 2012.	Wood logs ⁽¹⁾ .
Westfire Uniq 35 SE Freestanding multi- fuel 4.3 kW stove,	Installation manual and operating instructions reference "WF35" dated 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Westfire Uniq 35 SE Pedestal multi-fuel 4.3kW stove, Westfire Uniq 35 SE Inset with 3 sided frame multi- fuel 4.3kW stove and Westfire Uniq 35 SE Inset with 4 sided frame multi-fuel 4.3kW stove.	The appliance must be fitted with the manufacturer's smoke reduction kit to prevent closure of the secondary air control beyond 25% open.	
Manufactured by Westfire ApS, Tomrervej 3, VARDE, DK-6800, Denmark.		
Windhager BioWin 90 and 120.	Manufacturer's instructions reference "092125/00" dated August 2008.	Wood pellets ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.		
Windhager BioWin 100, 150, 210 and 260. Manufactured by Windhager	Manufacturer's instruction manual reference "0916197/00" dated May 2008.	Wood pellets ⁽¹⁾ .
Zentralheizung GmbH, Anton- Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.		
Windhager Bio Win 350, 450 and 600 35, 45 and 60kW pellet boilers.	Operating manual reference "093209/02" dated July 2013 and installation instructions manual reference "093212/04" dated July 2013.	Wood pellets ⁽¹⁾ .
Manufactured by Windhager Zentralheizung GmbH, Anton-		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Windhager-Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.		
Windhager FireWyn 90 and 120.	Instruction manual reference "092125/00" dated August 2007.	Wood pellets (1).
Manufactured by Windhager Zentralheizung GmbH, Anton- Windhager-Str.20, A-5201 Seekirchen bei Salzburg, Austria.		
Wood Energy Solutions E-Compact 15 Slim and 18 Slim Wood Pellet Boilers.	Installation and operation manual reference "V.1.1" dated June 2014.	Wood pellets (1).
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Wood Energy Solutions E-Compact 55 Wood Pellet Boiler.	Installation and operating manual reference "Manual Edition: E-COMPACT 55_December 2012 Issue 1" dated December 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Wood Energy Solutions E-Compact 85, 100, & 125 Wood Pellet Boilers.	Installation and operating manual reference "Manual Edition: E-COMPACT Commercial Series_85-125" dated May 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Tipperary, Co. Tipperary, Ireland.		
Wood Energy Solutions E-Compact 199 Wood Pellet Boiler.	Installation and operating manual reference "Manual Edition: E-COMPACT Commercial Series_199" dated May 2012.	Wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Ltd., Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 100; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 100.	Instruction manual reference "OOLinst.8 GR 100 and OT 100 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 120; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 120.	Instruction manual reference "OOLinst.9 GR 120 and OT 120 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 140; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 140.	Instruction manual reference "OOLinst.10 GR 140 and OT 140 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 120x160; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 120x160.	Instruction manual reference "OOLinst.11 GR 120x160 and OT 120x160 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 140x160; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 140x160.	Instruction manual reference "OOLinst.12 GR 140x160 and OT 140x160 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 140x180; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 140x180.	Instruction manual reference "OOLinst.13 GR 140x180 and OT 140x180 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s GR Valoriani Ristorante 180; Wood Fired Ovens by Jamie Oliver Ltd.'s OT Valoriani Ristorante 180.	Instruction manual reference "OOLinst.14 GR 180 and OT 180 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 80.	Instruction manual reference "OOLinst.1 FVR 80 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 100.	Instruction manual reference "OOLinst.2 FVR 100 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
213, 50066 Reggello, Firenze, Italy.	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 110.	Instruction manual reference "OOLinst.3 FVR 110 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 110x160.	Instruction manual reference "OOLinst.5 FVR 110x160 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Casa 120.	Instruction manual reference "OOLinst.4 FVR120 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Piccolo.	Instruction manual reference "OOLinst.15 Valoriani Piccolo v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Villa 100.	Instruction manual reference "OOLinst.6 TOP 100 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd.'s Valoriani Villa 120.	Instruction manual reference "OOLinst.7 TOP 120 v2" dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Woodpecker 15, 25 and 45 wood pellet boilers.	Installation and operating manual reference "Issue 6" dated May 2012.	Wood pellets conforming to CEN TS 14961 (1).
Formerly manufactured by Garranlea Renewables Ltd., and now manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.		
Woodpecker 50kW wood pellet boilers.	Instruction manual reference "Installation and Operating Manual Woodpecker 50 Model Wood Pellet Poilor System Version 2" deted May	Wood pellets conforming to CEN TS 14961 (a) (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	Boiler System Version 2" dated May 2012.	
Woodpecker Thermon 150 boiler.	Instruction manual reference "Installation and Operating manual Issue 2" dated February 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
Business Centre,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Preston Road, Yeovil, BA20 2EN.		
Woodpecker Thermon 199kW pellet boiler.	Instruction manual reference "Issue 2.0" dated February 2012.	6mm wood pellets (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.		
Woodpecker Thermon 200 boiler.	Instruction manual reference "Installation and Operating manual Issue 2" dated February 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	issue 2 dated rebluary 2012.	
Woodpecker Thermon 250 boiler.	Instruction manual reference "Installation and Operating manual Issue 2" dated February 2012.	6mm wood pellets (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	issue 2 dated restainly 2012.	
Woodpecker Thermon 300 boiler.	Instruction manual reference "Installation and Operating manual Legue 2" dated February 2012	6mm wood pellets ⁽¹⁾ .
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	Issue 2" dated February 2012.	
Woodwarm stoves Firebright SE multifuel insert stove.	Installation and operating instructions manual reference "Version INSSE" dated 1st June 2013.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Metal Developments Ltd., The Workshop, Wheatcroft Farm, Cullompton, Devon, EX15 1RA.	The appliance must be modified to prevent closure of the existing secondary air slide plate, located beneath the appliance, beyond the 3mm open position.	
Woodwarm stoves Firegem, Firewren and Fireblaze SE.	Installation and operating instructions manual reference "Version FSSE" dated 1st June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Metal Developments Ltd., The Workshop, Wheatcroft Farm, Cullompton, Devon, EX15 1RA.	The appliance must be fitted with a system that prevents closure of the secondary air control beyond the 5mm open position.	
Woodwarm stoves Foxfire SE woodburning stove.	Installation and operating instructions manual reference "Version FFSE" dated 1st June 2013.	Wood logs ⁽¹⁾ .
Manufactured by Metal Developments Ltd., The Workshop, Wheatcroft Farm, Cullompton, Devon, EX15 1RA.	The appliance must be modified to fix the secondary bleed hole at a minimum of 75% open.	
Wood Waste Technology Ltd. WT5.	Manufacturer's instructions reference "WT5_v2" dated 16th February 2009.	Medium density fibreboard, chipboard, hardwood or softwood offcuts ⁽¹⁾ .
Manufactured by Wood Waste Technology Ltd., Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.		Softwood offcuts V.
Wood Waste Technology Heater, models WT10 and WT15.	Manufacturer's instructions reference "WT10" and "WT15" dated 19th January 2005.	Medium density fibreboard, chipboard, hardwood or softwood offcuts ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Wood Waste Technology Ltd., Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.		
Wood Waste Technology WW199 (199kW output) biomass boiler and cyclone Manufactured by Wood Waste Technology Limited, Units 1,2 and 3 Drummond Road, Astonfields Industrial Estate, Stafford, ST16 3HJ	Instruction manual reference "WW199 Biomass Water Heating O&M Manual Revision C" dated 11th July 2014.	Chipboard, medium density fibreboard, softwood and hardwood. All fuels to be chipped to a maximum size of 15mm with a maximum moisture content of 30% Maximum fines (sawdust) content 50% (1).
WTA WT Auto 200kW Airheater. Manufactured by Wood Waste Technology Ltd., Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.	Instruction manual reference "WTA Installation Operation & Maintenance Instructions WTA v1 Issue A" dated April 2011.	Chipboard, medium density fibreboard, softwood, hardwood. All fuels to be chipped to a maximum size of 25mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5%. (1).
WTH 150 and WTH 200 boilers. Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding	Installation manual "version 91 for Large Capacity Boiler WTH 150-200" reference "BA GK V90b 0309".	Wood chips or wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
8, A-4952, Weng, Austria.		
Xeoos 5kW stove Versions: Natur, Style, Harmony, Pur, Classic, Elegance and Stone;	Operating and installation instructions reference "Revisions – Index 01/08 Fassung Januar 2008" dated January 2008.	Wood logs conforming to DIN 51731 ⁽¹⁾ .
Xeoos 8kW stove Versions: Basic, Pur, Classic, Elegance Stone and Air.		
Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V. Dipl Ing. Frank Werner Projektmanagement Bahnhofstr, 2 D 35116 Hatzfeld.		
Yeoman CL3 (3.8kW) and CL5 (4.9kW) multifuel stoves; Yeoman CL5 (4.9kW) wood Stove.	Instruction manual reference "PM489 Issue 1" dated June 2010 and smoke control kit instruction manual "PM491 Issue 1" dated 5th April 2010.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
Yeoman CL 7 (7kW) inset appliance Product code YM- CL7NMF.	Instruction manual reference "PM553 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop on the secondary air inlet to prevent closure beyond the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Yeoman CL Milner Stove Product code YM-CLMB. Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM559 - Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	Wood logs ⁽¹⁾ .
Yeoman Devon - Multifuel, flat top, 1 door (9kW); Yeoman Devon - Multifuel, flat top, 2 door (9kW); Yeoman Devon - Multifuel, low canopy, 1 door (9kW); Yeoman Devon - Multifuel, low canopy, 2 door (9kW); Yeoman Devon - Multifuel, high canopy, 1 door (9kW); Yeoman Devon - Multifuel, high canopy, 2 door (9kW); Yeoman Devon - Multifuel, high canopy, 2 door (9kW). Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	Instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position and a system must be fitted that ensures a gap of 1mm for bleed of primary air when the spin wheels are rotated to their closed positions must be fitted.	Wood logs ⁽¹⁾ .
Yeoman Exmoor - Multifuel, flat top (4.9kW); Yeoman Exmoor - Multifuel, low canopy (4.9kW); Yeoman Exe - Multifuel, flat top, 1 door (4.9kW); Yeoman Exe -	Instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 60% open position and a system that	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Fireplace	Conditions	
M. Idi C. al. Classes	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Multifuel, flat top, 2 door (4.9kW); Yeoman Exe - Multifuel, low canopy, 1 door (4.9kW); Yeoman Exe - Multifuel, low canopy, 2 door (4.9kW);	prevents full closure of the primary air controls must be fitted.	
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.		
York Grande SE, Serrano 7SE, Monterrey 7SE and Monroe 7SE Multi Fuel stoves. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "GB12A Version 1" dated February 2013. The appliance must be fitted with a system that prevents the closure of the secondary air slider beyond the 10mm open position.	Wood logs ⁽¹⁾ .
York Midi SE, Serrano 5 SE, Monterrey 5 SE and Monroe 5 SE Multi Fuel stoves. Manufactured by Broseley Fires Ltd., Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	Instruction manual reference "GB12A Version 1" dated February 2013. The appliance must be fitted with a system that prevents the closure of the secondary air slider beyond the 8mm open position.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

EXPLANATORY NOTE

(This note is not part of the Order)

This Order revokes and replaces with amendments the Smoke Control Areas (Exempted Fireplaces) (Wales) Order 2014 (S.I. 2014/694) (W.75).

Section 20 of the Clean Air Act 1993 ("the 1993 Act") places a general prohibition on the emission of smoke in smoke control areas.

The Welsh Ministers may, by order made under section 21 of the 1993 Act, exempt, in relation to Wales, specified classes of fireplace from the provisions of section 20, if they are satisfied that such fireplaces can be used for burning fuel other than authorised fuels without producing any smoke or a substantial quantity of smoke.

Article 2 of this Order exempts the fireplaces listed in the first column of the Schedule to this Order from the provisions of section 20 of the 1993 Act, subject to the conditions in the second and third columns of that Schedule.

The Welsh Ministers' Code of Practice on the carrying out of Regulatory Impact Assessments was considered in relation to this Order. As a result, it was not considered necessary to carry out a regulatory impact assessment as to the likely costs and benefits of complying with this Order.