Council Directive 92/58/EEC of 24 June 1992 on the minimum requirements for the provision of safety and /or health signs at work (ninth individual Directive within the meaning of Article 16 (1) of Directive 89/391/EEC)

#### SECTION I

#### GENERAL PROVISIONS

- Article 1 Object
- Article 2 Definitions

#### SECTION II

#### **EMPLOYERS' OBLIGATIONS**

- Article 3 General rules
- Article 4 Safety and/or health signs used for the first time
- Article 5 Safety and/or health signs already in use
- Article 6 Exemptions
- Article 7 Information and instruction for workers
- Article 8 Consultation of workers and workers' participation

## SECTION III

#### MISCELLANEOUS PROVISIONS

- Article 9 Adaptation of the Annexes
- Article 10 (1) Directive 77/576/EEC shall be repealed on the date referred...
- Article 11 Final provisions
- Article 12 This Directive is addressed to the Member States. Signature

#### ANNEX I

### GENERAL MINIMUM REQUIREMENTS CONCERNING SAFETY AND/OR HEALTH SIGNS AT WORK

#### 1. Preliminary remarks

- 1.1. Where health and/or safety signs are required by the general...
- 1.2. This Annex introduces those requirements, describes the different uses of...
- 1.3. Health and/or safety signs must be used only to convey...
- 2. Types of signs
  - 2.1. Permanent signs
    - 2.1.1. Permanent signboards must be used for signs relating to prohibitions,...
    - 2.1.2. Signboards on containers and pipes must be placed as laid...

- 2.1.3. Places where there is a risk of colliding with obstacles...
- 2.1.4. Traffic routes must be permanently marked with a safety colour....
- 2.2. Occasional signs
  - 2.2.1. Illuminated signs, acoustic signals and/or verbal communication must be used...
  - 2.2.2. Hand signals and/or verbal communication must be used where the...
- 3. Interchanging and combining signs
  - 3.1. Any one of the following may be used if equally...
  - 3.2. Some types of signs may be used together:
- 4. The instructions in the table below apply to all signs...
- 5. The effectiveness of a sign must not be adversely affected...
  - 5.1. the presence of another emission source of the same type...
  - 5.2. poor design, insufficient number, incorrect positioning, poor state of repair...
- 6. Depending on requirements, signs and signalling devices must be cleaned,...
- 7. The number and positioning of signs or signalling devices to...
- 8. Signs requiring some form of power must be provided with...
- 9. The triggering of an illuminated sign and/or acoustic signal indicates...
- 10. Illuminated signs and acoustic signals must be checked to ensure...
- 11. If the hearing or the sight of the workers concerned...
- 12. Areas, rooms or enclosures used for the storage of significant...

### ANNEX II

### MINIUM GENERAL REQUIREMENTS CONCERNING SIGNBOARDS

- 1. Intrinsic features
  - 1.1. The shape and colours of signboards are set out in...
  - 1.2. Pictograms must be as simple as possible and should contain...
  - 1.3. The pictograms used may be slightly different from or more...
  - 1.4. Signboards are to be made of shock and weather-resistant material...
  - 1.5. The dimensions and colorimetric and photometric features of signoboards must...
- 2. Conditions of use
  - 2.1. Signboards are in principle to be installed at a suitable...
  - 2.2. The signboard must be removed when the situation to which...
- 3. Signboards to be used
  - 3.1. Prohibitory signs
  - 3.2. Warning signs
  - 3.3. Mandatory signs
  - 3.4. Emergency escape or first-aid signs

# 3.5. Fire-fighting signs

## ANNEX III

## MINIMUM REQUIREMENTS GOVERNING SIGNS ON CONTAINERS AND PIPES

- 1. Containers used at work for dangerous substances or preparations defined...
- 2. Signs must be mounted as follows:
- 3. Where appropriate, the signs referred to in section 1 of...
- 4. Without prejudice to sections 1,2 and 3, the labels used...
- 5. Areas, rooms or enclosures used for the storage of significant...

### ANNEX IV

### MINIMUM REQUIREMENTS FOR THE IDENTIFICATION AND LOCATION OF FIRE-FIGHTING EQUIPMENT

- 1. Preliminary remark
- 2. Fire-fighting equipment must be identified by using a specific colour...
- 3. The colour for identifying this equipment is red.
- 4. The signboards provided for in section 3.5 of Annex Ii...

### ANNEX V

### MINIMUM REQUIREMENTS GOVERNING SIGNS USED FOR OBSTACLES AND DANGEROUS LOCATIONS, AND FOR MARKING TRAFFIC ROUTES

- 1. Signs for obstacles and dangerous locations
  - 1.1. Places where there is a risk of colliding with obstacles,...
  - 1.2. The dimensions of the markings must be commensurate with the...
  - 1.3. The yellow and black or red and white stripes must...
  - 1.4. Example:
- 2. Marking of traffic routes
  - 2.1. Where the use and equipment of rooms so requires for...
  - 2.2. The stripes must be located so as to indicate the...
  - 2.3. Permanent traffic routes in built-up areas outdoors should, as far...

### ANNEX VI

### MINIMUM REQUIREMENTS FOR ILLUMINATED SIGNS

- 1. Intrinsic features
  - 1.1. The light emitted by a sign must produce a luminous...

- 1.2. The luminous area emitting a sign may be of a...
- 1.3. The single colour must correspond to the table of colours...
- 1.4. Likewise, when the sign contains a pictogram, the latter must...
- 2. Specific rules governing use
  - 2.1. If a device can emit both continuous and intermittent signs,...
  - 2.2. If a flashing sign is used instead of or...
  - 2.3. Devices for emitting flashing signs in the event of grave...

# ANNEX VII

## MINIMUM REQUIREMENTS FOR ACOUSTIC SIGNS

- 1. Intrinsic features
  - 1.1. Acoustic signals must:
  - 1.2. If a device can emit an acoustic signal at variable...
- 2. Code

# ANNEX VIII

## MINIMUM REQUIREMENTS FOR VERBAL COMMUNICATION

- 1. Intrinsic features
  - 1.1. Verbal communication between a speaker or emitter and one or...
  - 1.2. Spoken messages are to be as short, simple and clear...
  - 1.3. Verbal communication is direct (by means of the human voice)...
- 2. Specific rules governing use
  - 2.1. The persons involved must have a good knowledge of the...
  - 2.2. If verbal communication is used instead of or together...

# ANNEX IX

# MINIMUM REQUIREMENTS FOR HAND SIGNALS

- 1. Features
- 2. Specific rules governing use
  - 2.1. The person giving the signs, hereinafter referred to as the...
  - 2.2. The signalman must be able to monitor all manoeuvres visually...
  - 2.3. The signalman's duties must consist exclusively of directing manoeuvres and...
  - 2.4. If the conditions described in point 2.2 are not fulfilled,...
  - 2.5. The operator must interrupt the ongoing manoeuvre in order to...
  - 2.6. Accessories:
- 3. Coded signals to be used Preliminary remark:

Status: This is the original version (as it was originally adopted).

- (1) OJ NoC 53,28. 2.1991, p. 46 and OJ No C 279, 26.10.1991, p. 13.
- (2) OJ No C 240, 16. 9. 1991, p. 102 and OJ No C 150, 15. 6. 1992.
- (**3**) OJ No C 159, 17. 6. 1991, p. 9.
- (4) OJ No C 28, 3. 2. 1988, p. 3.
- (5) OJ No L 229, 7. 9. 1977, p. 12. Last amended by Commission Directive 79/640/EEC. (OJ No L 183, 19. 7. 1979, p. 11.)
- (6) OJ No C 28, 3. 2. 1989, p. 1.
- (7) OJ No L 183, 29. 6. 1989, p. 1.
- (8) OJ No L 185, 9. 7. 1974, p. 15.