Council Regulation (EC) No 2187/2005 of 21 December 2005 for the conservation of fishery resources through technical measures in the Baltic Sea, the Belts and the Sound, amending Regulation (EC) No 1434/98 and repealing Regulation (EC) No 88/98 (repealed)

CHAPTER I

SCOPE AND DEFINITIONS

- Article 1 Subject matter and scope
- Article 2 Definitions

CHAPTER II

NETS AND CONDITIONS FOR THEIR USE

SECTION I

Target species

Article 3 Target species and minimum mesh sizes Article 4 Calculation of percentages of target species

SECTION II

Active gear

Article 5 Structure of fishing gear Article 6 Specific prohibited structures Selectivity in trawl fisheries for cod Article 7

SECTION III

Passive gear

- Article 8 Dimensions and immersion time Article 9 Restrictions on driftnets Article 10 Conditions for driftnets

SECTION IV

Common provisions on gear and its use

- Article 11 Determination of mesh size and twine thickness
- Article 12 Reaching of required catch percentages
- Conditions for use of gear Article 13

Status: Point in time view as at 01/06/2015.

CHAPTER III

MINIMUM LANDING SIZE OF FISH

Article 14	Measurement of fish
Article 14a	Procedure for establishing minimum conservation reference sizes
	in the context of discard plans
Article 15	Retention on board of undersized fish
Article 15a	Prohibition of highgrading

CHAPTER IV

RESTRICTIONS RELATING TO CERTAIN AREAS, TYPES OF FISHERIES OR LIVING AQUATIC RESOURCES

- Article 16 Prohibited areas
- Article 17 Restrictions on fishing for salmon and sea trout
- Article 18 Restrictions on fishing for eel
- Article 18a Restrictions on fishing for flounder and turbot
- Article 19 Restrictions on unsorted landings

CHAPTER V

SPECIFIC MEASURES FOR THE GULF OF RIGA

- Article 20 Special fishing permit
- Article 21 Replacement of vessels or engines
- Article 22 Trawling prohibition

CHAPTER VI

GENERAL PROVISIONS

- Article 23 Prohibited fishing gear and practices
- Article 24 Scientific research
- Article 25 Artificial restocking and transplantation
- Article 26 Measures taken by Member States applying solely to fishing
- vessels flying their flag
- Article 27 Scientific assessment of gear types

CHAPTER VII

FINAL PROVISIONS

Article 28	Implementing rules
Article 28a	Procedure for adopting technical measures in the context of
	discard plans
Article 28b	Exercise of delegation
Article 29	Amendments to the Annexes
Article 30	Amendments to Regulation (EC) No 1434/98
Article 31	Repeal
Article 32	Entry into force
	Signature

ANNEX I

Subdivisions of the geographical area referred to in Article 1 to be measured according to the WGS84 coordinate system

Subdivision 22

Subdivision 23

Subdivision 24

Subdivision 25

Subdivision 26

Subdivision 27

Subdivision 28-1

Subdivision 28-2

Subdivision 29

Subdivision 30

Subdivision 31

Subdivision 32

ANNEX II

Appendix 1

Specifications of Bacoma codends

Description

- (a) Size of the codend, extension piece and the rear end...
 - (i) The codend shall be constructed of two panels, joined together...
 - (ii) The minimum mesh size of the diamond meshes shall be...
 - (iii) The use of codends and extension pieces which are made...
 - (iv) The number of open diamond meshes, excluding those in the...
- (b) Location of window
 - (i) The window shall be inserted into the top panel of...
 - (ii) The window shall terminate not more than four meshes from...

(c) Size of window

- (i) The width of the window, expressed in number of mesh...
- (ii) The length of the window shall be at least 5,5...

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 2187/2005 (repealed). (See end of Document for details)

- (iii) By way of derogation from point (ii) the length of...
- (d) Netting of window
 - (i) The meshes shall have a minimum mesh opening of 120...
 - (ii) The netting shall be mounted such that the bars run...
 - (iii) The diameter of the single yarn shall be at least...
- (e) Other specifications
 - (i) A back strap shall not encircle the Bacoma exit window....
 - (ii) A codend buoy shall be spherical in shape and have...
 - (iii) A flapper shall not overlap the Bacoma exit window.
 - Appendix 2

SPECIFICATIONS OF THE T90 TRAWL

- (a) Definition
 - 1. T90 trawls are defined as trawls, Danish seines and similar...
 - 2. The direction of run of the netting twine in a...
- (b) Mesh size and measurement
- (c) Twine thickness
- (d) Construction
 - 1. A codend and extension of turned meshes (T90) shall be...
 - 2. The number of open meshes in any circumference must be...
 - 3. At the point of attachment of the codend or extension...
 - 4. A codend and extension piece is illustrated in Figure 2...
- (e) Circumference
- (f) Joining rounds
- (g) Codend buoy

ANNEX III

ANNEX IV

ANNEX V

- (1) OJ C 125, 24.5.2005, p. 12.
- (2) Opinion delivered on 13 October 2005 (not yet published in the Official Journal).
- (**3**) OJ L 358, 31.12.2002, p. 59.
- (**4**) OJ L 237, 26.8.1983, p. 4.
- (5) OJ L 9, 15.1.1998, p. 1. Regulation as last amended by Regulation (EC) No 289/2005 (OJ L 49, 22.2.2005, p. 1).
- (**6**) OJ L 171, 6.7.1994, p. 7.
- (7) OJ L 191, 7.7.1998, p. 10.
- (8) OJ L 184, 17.7.1999, p. 23.

Status:

Point in time view as at 01/06/2015.

Changes to legislation:

There are currently no known outstanding effects for the Council Regulation (EC) No 2187/2005 (repealed).