

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

[^{F1}ANNEX IV

(List referred to in Article 22(1) of this Regulation)

Textual Amendments

- F1** Substituted by Commission Delegated Regulation (EU) 2020/1749 of 7 October 2020 amending Council Regulation (EC) No 428/2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

The entries do not always cover the complete description of the item and the related notes in Annex I⁽¹⁾. Only Annex I provides for the complete description of the items.

The mention of an item in this Annex does not affect the application of the provisions concerning mass-market products in Annex I.

The terms appearing in straight double quotes are defined terms in the global definitions list of Annex I

PART I

(possibility of National General Authorisation for intra-Community trade) Items of stealth technology

1C001	Materials specially designed for use as absorbers of electromagnetic waves, or intrinsically conductive polymers. <i>N.B. SEE ALSO 1C101</i>
1C101	Materials and devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures, other than those specified in 1C001, usable in ‘missiles’, ‘missile’ subsystems or unmanned aerial vehicles specified in 9A012. <i>Note: 1C101 does not control materials if such goods are formulated solely for civil applications.</i> <i>Technical Note:</i> <i>In 1C101 ‘missiles’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>
1D103	‘Software’ specially designed for analysis of reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures.
1E101	‘Technology’ according to the GTN for the ‘use’ of goods specified in 1C101 or 1D103.

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

1E102	'Technology' according to the GTN for the 'development' of 'software' specified in 1D103.
6B008	Pulse radar cross-section measurement systems having transmit pulse widths of 100 ns or less and specially designed components therefor. <i>N.B. SEE ALSO 6B108</i>
6B108	Systems specially designed for radar cross section measurement usable for 'missiles' and their subsystems.

Items of the Community strategic control

1A007	Equipment and devices, specially designed to initiate charges and devices containing 'energetic materials', by electrical means, as follows: <i>N.B. SEE ALSO MILITARY GOODS CONTROLS, 3A229 AND 3A232.</i> a. Explosive detonator firing sets designed to drive multiple controlled detonators specified in 1A007.b. below ; b. Electrically driven explosive detonators as follows: 1. Exploding bridge (EB); 2. Exploding bridge wire (EBW); 3. Slapper; 4. Exploding foil initiators (EFI). <i>Note: 1A007.b. does not control detonators using only primary explosives, such as lead azide.</i>
1C239	High explosives, other than those specified in the Military Goods Controls, or substances or mixtures containing more than 2 % by weight thereof, with a crystal density greater than 1,8 g/cm ³ and having a detonation velocity greater than 8 000 m/s.
1E201	'Technology' according to the General Technology Note for the 'use' of goods specified in 1C239.
3A229	High-current pulse generators, as follows ... <i>N.B. SEE ALSO MILITARY GOODS CONTROLS</i>
3A232	Multipoint initiation systems, other than those specified in 1A007 above , as follows...

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	<i>N.B. SEE ALSO MILITARY GOODS CONTROLS</i>
3E201	‘Technology’ according to the General Technology Note for the ‘use’ of equipment specified in 3A229 or 3A232.
6A001	Acoustics, limited to the following:
6A001.a.1.b.	Object detection or location systems having any of the following: 1. A transmitting frequency <i>below 5 kHz</i> ; 6. Designed to withstand ...;
6A001.a.2.a.2.	Hydrophones ... Incorporating ...
6A001.a.2.a.3.	Hydrophones ... Having any ...
6A001.a.2.a.6.	Hydrophones ... Designed for ...
6A001.a.2.b.	Towed acoustic hydrophone arrays ...
6A001.a.2.c.	Processing equipment, specially designed for real time application with towed acoustic hydrophone arrays, having ‘user-accessible programmability’ and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;
6A001.a.2.e.	Bottom or bay-cable hydrophone arrays, having any of the following: 1. Incorporating hydrophones ..., <i>or</i> 2. Incorporating multiplexed hydrophone group signal modules ...;
6A001.a.2.f.	Processing equipment, specially designed for real time application with bottom or bay cable systems, having ‘user-accessible programmability’ and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;
6D003.a.	‘Software’ for the ‘real-time processing’ of acoustic data;
8A002.o.3.	Noise reduction systems designed for use on vessels of 1 000 tonnes displacement or more, as follows: b. Active noise reduction or cancellation systems, or magnetic bearings, specially designed for power transmission systems,

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	and incorporating electronic control systems capable of actively reducing equipment vibration by the generation of anti-noise or anti-vibration signals directly to the source;
8E002.a.	‘Technology’ for the ‘development’, ‘production’, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction.

Items of the Community strategic control — Cryptanalysis — Category 5 Part 2

5A004.a.	Equipment designed or modified to perform ‘cryptanalytic functions’. <i>Note: 5A004.a. includes systems or equipment, designed or modified to perform ‘cryptanalytic functions’ by means of reverse engineering.</i> <i>Technical Note:</i> <i>‘Cryptanalytic functions’ are functions designed to defeat cryptographic mechanisms in order to derive confidential variables or sensitive data, including clear text, passwords or cryptographic keys.</i>
5D002.a.	‘Software’ specially designed or modified for the ‘development’, ‘production’ or ‘use’ of any of the following: 3. Equipment specified in 5A004;
5D002.c.	‘Software’ having the characteristics of, or performing or simulating the functions of, any of the following: 3. Equipment specified in 5A004;
5E002.a.	Only ‘technology’ for the ‘development’, ‘production’ or ‘use’ of the goods specified in 5A004.a, 5D002.a.3. or 5D002.c.3. above.

Items of the MTCR technology

7A117	‘Guidance sets’, usable in ‘missiles’ capable of achieving system accuracy of 3,33 % or less of the range (e.g., a ‘Circle of Equal Probability’ of 10 km or less at a range of 300 km), except ‘guidance sets’ designed for missiles with a range under 300 km or manned aircraft. <i>Technical Note:</i> <i>In 7A117 ‘Circle of Equal Probability’ is a measure of accuracy, defined as the radius of</i>
-------	--

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	<i>the circle centred at the target, at a specific range, in which 50 % of the payloads impact.</i>
7B001	Test, calibration or alignment equipment specially designed for equipment specified in 7A117 above. <i>Note: 7B001 does not control test, calibration or alignment equipment for 'Maintenance Level I' or 'Maintenance Level II'.</i>
7B003	Equipment specially designed for the 'production' of equipment specified in 7A117 above.
7B103	'Production facilities' specially designed for equipment specified in 7A117 above .
7D101	'Software' specially designed for the 'use' of equipment specified in 7B003 or 7B103 above .
7E001	'Technology' according to the General Technology Note for the 'development' of equipment or 'software' specified in 7A117, 7B003, 7B103 or 7D101 above .
7E002	'Technology' according to the General Technology Note for the 'production' of equipment specified in 7A117, 7B003 and 7B103 above .
7E101	'Technology' according to the General Technology Note for the 'use' of equipment specified in 7A117, 7B003, 7B103 and 7D101 above .
9A004	Space launch vehicles capable of delivering at least a 500 kg payload to a range of at least 300 km. <i>N.B. SEE ALSO 9A104.</i> <i>Note 1: 9A004 does not control payloads.</i>
9A005	Liquid rocket propulsion systems containing any of the systems or components specified in 9A006 usable for space launch vehicles specified in 9A004 above or sounding rockets specified in 9A104 below. <i>N.B. SEE ALSO 9A105 and 9A119.</i>
9A007.a.	Solid rocket propulsion systems, usable for space launch vehicles specified in 9A004 above or sounding rockets specified in 9A104 below , with any of the following: <i>N.B. SEE ALSO 9A119.</i> a. Total impulse capacity exceeding 1,1 MNs;

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

9A008.d.	<p>Components, as follows, specially designed for solid rocket propulsion systems: <i>N.B. SEE ALSO 9A108.c.</i></p> <p>d. Movable nozzle or secondary fluid injection thrust vector control systems, usable for space launch vehicles specified in 9A004 above or sounding rockets specified in 9A104 below, capable of any of the following:</p> <ol style="list-style-type: none"> 1. Omni-axial movement exceeding $\pm 5^\circ$; 2. Angular vector rotations of $20^\circ/\text{s}$ or more; <i>or</i> 3. Angular vector accelerations of $40^\circ/\text{s}^2$ or more.
9A104	<p>Sounding rockets, capable of delivering at least a 500 kg payload to a range of at least 300 km. <i>N.B. SEE ALSO 9A004.</i></p>
9A105.a.	<p>Liquid propellant rocket engines, as follows: <i>N.B. SEE ALSO 9A119.</i></p> <p>a. Liquid propellant rocket engines usable in ‘missiles’, other than those specified in 9A005, integrated, or designed or modified to be integrated, into a liquid propellant propulsion system which has a total impulse capacity equal to or greater than 1,1 MNs having a total impulse capacity equal to or greater than 1,1 MNs; except liquid propellant apogee engines designed or modified for satellite applications and having all of the following:</p> <ol style="list-style-type: none"> 1. nozzle throat diameter of 20 mm or less; and 2. 2. combustion chamber pressure of 15 bar or less.
9A106.c.	<p>Systems or components, other than those specified in 9A006, usable in ‘missiles’, as follows, specially designed for liquid rocket propulsion systems:</p> <p>c. Thrust vector control sub-systems, except those designed for rocket systems that are not capable of delivering at least a 500 kg payload to a range of at least 300 km.</p> <p><i>Technical Note:</i></p>

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	<p><i>Examples of methods of achieving thrust vector control specified in 9A106.c. are:</i></p> <ol style="list-style-type: none">1. <i>Flexible nozzle;</i>2. <i>Fluid or secondary gas injection;</i>3. <i>Movable engine or nozzle;</i>4. <i>Deflection of exhaust gas stream (jet vanes or probes); or</i>5. <i>Thrust tabs.</i>
9A108.c.	<p>Components, other than those specified in 9A008, usable in ‘missiles’ as follows, specially designed for solid rocket propulsion systems:</p> <ol style="list-style-type: none">c. Thrust vector control sub-systems, except those designed for rocket systems that are not capable of delivering at least a 500 kg payload to a range of at least 300 km. <p><i>Technical Note:</i> <i>Examples of methods of achieving thrust vector control specified in 9A108.c. are:</i></p> <ol style="list-style-type: none">1. <i>Flexible nozzle;</i>2. <i>Fluid or secondary gas injection;</i>3. <i>Movable engine or nozzle;</i>4. <i>Deflection of exhaust gas stream (jet vanes or probes); or</i>5. <i>Thrust tabs.</i>
9A116	<p>Reentry vehicles, usable in ‘missiles’, and equipment designed or modified therefor, as follows, except for reentry vehicles designed for non-weapon payloads:</p> <ol style="list-style-type: none">a. Reentry vehicles;b. Heat shields and components therefor fabricated of ceramic or ablative materials;c. Heat sinks and components therefor fabricated of light-weight, high heat capacity materials;d. Electronic equipment specially designed for reentry vehicles.
9A119	<p>Individual rocket stages, usable in complete rocket systems or unmanned aerial vehicles, capable of delivering at least a 500 kg payload to a range of 300 km, other than those specified in 9A005 or 9A007.a. above</p>
9B115	<p>Specially designed ‘production equipment’ for the systems, sub-systems and components specified in 9A005, 9A007.a., 9A008.d., 9A105.a., 9A106.c., 9A108.c., 9A116 or 9A119 above.</p>

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

9B116	Specially designed ‘production facilities’ for the space launch vehicles specified in 9A004, or systems, sub-systems, and components specified in 9A005, 9A007.a., 9A008.d., 9A104, 9A105.a., 9A106.c., 9A108.c., 9A116 or 9A119 <i>above</i> .
9D101	‘Software’ specially designed for the ‘use’ of goods specified in 9B116 <i>above</i> .
9E001	‘Technology’ according to the General Technology Note for the ‘development’ of equipment or ‘software’ specified in 9A004, 9A005, 9A007.a., 9A008.d., 9B115, 9B116 or 9D101 <i>above</i> .
9E002	‘Technology’ according to the General Technology Note for the ‘production’ of equipment specified in 9A004, 9A005, 9A007.a., 9A008.d., 9B115 or 9B116 <i>above</i> . <i>Note: For ‘technology’ for the repair of controlled structures, laminates or materials, see 1E002.f.</i>
9E101	‘Technology’ according to the General Technology Note for the ‘development’ or ‘production’ of goods specified in 9A104, 9A105.a., 9A106.c., 9A108.c., 9A116 or 9A119 <i>above</i> .
9E102	‘Technology’ according to the General Technology Note for the ‘use’ of space launch vehicles specified in 9A004, 9A005, 9A007.a., 9A008.d., 9A104, 9A105.a., 9A106.c., 9A108.c., 9A116, 9A119, 9B115, 9B116 or 9D101 <i>above</i> .

Exemptions:

Annex IV does not control the following items of the MTCR technology:

1. that are transferred on the basis of orders pursuant to a contractual relationship placed by the European Space Agency (ESA) or that are transferred by ESA to accomplish its official tasks;
2. that are transferred on the basis of orders pursuant to a contractual relationship placed by a Member State's national space organisation or that are transferred by it to accomplish its official tasks;
3. that are transferred on the basis of orders pursuant to a contractual relationship placed in connection with a Community space launch development and production programme signed by two or more European governments;
4. that are transferred to a State-controlled space launching site in the territory of a Member State, unless that Member State controls such transfers within the terms of this Regulation.

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

PART II

(no National General Authorisation for intra-Community trade) Items of the CWC (Chemical Weapons Convention)

1C351.d.4.	Ricin
1C351.d.5.	Saxitoxin

Items of the NSG technology

All Category 0 of Annex I is included in Annex IV, subject to the following:

- 0C001: this item is not included in Annex IV;
- 0C002: this item is not included in Annex IV, with the exception of special fissile materials as follows:
 - (a) separated plutonium;
 - (b) 'uranium enriched in the isotopes 235 or 233' to more than 20 %.
- 0C003 only if for use in a 'nuclear reactor' (within 0A001.a);
- 0D001 (software) is included in Annex IV except insofar as it relates to 0C001 or to those items of 0C002 that are excluded from Annex IV;
- 0E001 (technology) is included in Annex IV except insofar as these related to 0C001 or to those items of 0C002 that are excluded from Annex IV.

1B226	Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater. <i>Note: 1B226 includes separators:</i> <ul style="list-style-type: none">a. <i>Capable of enriching stable isotopes;</i>b. <i>With the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.</i>
1B231	Tritium facilities or plants, and equipment therefor, as follows: <ul style="list-style-type: none">a. Facilities or plants for the production, recovery, extraction, concentration, or handling of tritium;b. Equipment for tritium facilities or plants, as follows:<ul style="list-style-type: none">1. Hydrogen or helium refrigeration units capable of cooling to 23 K (– 250 °C) or less, with heat removal capacity greater than 150 W;2. Hydrogen isotope storage or purification systems using metal hydrides as

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	the storage or purification medium.
1B233	<p>Lithium isotope separation facilities or plants, and equipment therefor, as follows:</p> <ol style="list-style-type: none"> a. Facilities or plants for the separation of lithium isotopes; b. Equipment for the separation of lithium isotopes, as follows: <ol style="list-style-type: none"> 1. Packed liquid-liquid exchange columns specially designed for lithium amalgams; 2. Mercury or lithium amalgam pumps; 3. Lithium amalgam electrolysis cells; 4. Evaporators for concentrated lithium hydroxide solution.
1C012	<p>Materials as follows:</p> <p><i>Technical Note:</i> <i>These materials are typically used for nuclear heat sources.</i></p> <ol style="list-style-type: none"> b. 'Previously separated' neptunium-237 in any form. <p><i>Note: 1C012.b. does not control shipments with a neptunium-237 content of 1 g or less.</i></p>
1C233	<p>Lithium enriched in the lithium-6 (⁶Li) isotope to greater than its natural isotopic abundance, and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><i>Note: 1C233 does not control thermoluminescent dosimeters.</i></p> <p><i>Technical Note:</i> <i>The natural isotopic abundance of lithium-6 is approximately 6,5 weight % (7,5 atom %).</i></p>
1C235	<p>Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1 000, and products or devices containing any of the foregoing.</p> <p><i>Note: 1C235 does not control a product or device containing less than $1,48 \times 10^3$ GBq (40 Ci) of tritium.</i></p>
1E001	'Technology' according to the General Technology Note for the 'development'

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	or 'production' of equipment or materials specified in 1C012.b.
1E201	'Technology' according to the General Technology Note for the 'use' of goods specified in 1B226, 1B231, 1B233, 1C233 or 1C235.
3A228	Switching devices, as follows: a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics: 1. Containing three or more electrodes; 2. Anode peak voltage rating of 2,5 kV or more; 3. Anode peak current rating of 100 A or more; <i>and</i> 4. Anode delay time of 10 µs or less; <i>Note: 3A228 includes gas krytron tubes and vacuum sprytron tubes.</i> b. Triggered spark-gaps having both of the following characteristics: 1. An anode delay time of 15 µs or less; <i>and</i> 2. Rated for a peak current of 500 A or more;
3A231	Neutron generator systems, including tubes, having both of the following characteristics: a. Designed for operation without an external vacuum system; <i>and</i> b. Utilizing electrostatic acceleration to induce a tritium-deuterium nuclear reaction
3E201	'Technology' according to the General Technology Note for the 'use' of equipment specified in 3A228 or 3A231.
6A203	Cameras and components, other than those specified in 6A003, as follows: a. Mechanical rotating mirror streak cameras, as follows, and specially designed components therefor: 1. Streak cameras with writing speeds greater than 0,5 mm per microsecond; b. Mechanical rotating mirror framing cameras, as follows, and specially designed components therefor:

Status: Point in time view as at 31/12/2019.

Changes to legislation: There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)

	<p>1. Framing cameras with recording rates greater than 225 000 frames per second;</p> <p><i>Note: In 6A203.a. components of such cameras include their synchronizing electronics units and rotor assemblies consisting of turbines, mirrors and bearings.</i></p>
6A225	<p>Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 microseconds.</p> <p><i>Note: 6A225 includes velocity interferometers such as VISARs (Velocity interferometer systems for any reflector) and DLIs (Doppler laser interferometers).</i></p>
6A226	<p>Pressure sensors, as follows:</p> <p>a. Manganin gauges for pressures greater than 10 GPa;</p> <p>b. Quartz pressure transducers for pressures greater than 10 GPa.]</p>

Status: Point in time view as at 31/12/2019.

*Changes to legislation: There are currently no known outstanding effects for the
Council Regulation (EC) No 428/2009, ANNEX IV. (See end of Document for details)*

- (1) [^{F1}The differences in the wordings/scopes between Annex I and Annex IV are indicated with bold italic text.]

.....
Textual Amendments

- F1** Substituted by Commission Delegated Regulation (EU) 2020/1749 of 7 October 2020 amending Council Regulation (EC) No 428/2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Status:

Point in time view as at 31/12/2019.

Changes to legislation:

There are currently no known outstanding effects for the Council Regulation (EC) No 428/2009, ANNEX IV.