

Status: This is the original version (as it was originally adopted).

ANNEX I

SCOPE OF APPLICATION OF THE REQUIREMENTS REFERRED TO IN ARTICLE 5(1) AND (2)

Subject	Applicability									
	M ₁	M ₂	M ₃	N ₁	N ₂	N ₃	O ₁	O ₂	O ₃	O ₄
Fuel tanks/ rear protective devices	X	X	X	X	X	X	X	X	X	X
Rear registration plate	X	X	X	X	X	X	X	X	X	X
Steering effort	X	X	X	X	X	X	X	X	X	X
Door latches and hinges	X			X	X	X				
Audible warning	X	X	X	X	X	X				
Indirect vision devices	X	X	X	X	X	X				
Braking	X	X	X	X	X	X	X	X	X	X
Radio interference (electromagnetic compatibility)	X	X	X	X	X	X	X	X	X	X
Interior fittings	X									
Anti- theft and immobiliser	X	X	X	X	X	X				

a Vehicles of this category shall be fitted with an adequate windscreen defrosting and demisting device.

b Vehicles of this category shall be fitted with adequate windscreen washing and wiping devices.

c Only if the vehicle is fitted with couplings.

d Not exceeding 2,5 tonnes technically permissible maximum laden mass.

e Only applicable to vehicles where the 'Seating reference point ("R" point)' of the lowest seat is not more than 700 mm above ground level. The 'R' point is defined in UNECE Regulation 95.

f Only when the manufacturer applies for type-approval of a vehicle intended for the transport of dangerous goods.

Status: This is the original version (as it was originally adopted).

Protective steering	X			X						
Seat strength	X	X	X	X	X	X				
Exterior projections	X									
Speedometer	X	X	X	X	X	X				
Plates (statutory)	X	X	X	X	X	X	X	X	X	X
Seat belt anchorages	X	X	X	X	X	X				
Installation of lighting and light signalling devices	X	X	X	X	X	X	X	X	X	X
Retro reflectors	X	X	X	X	X	X	X	X	X	X
End-outline, front-position (side), rear-position (side), stop, side marker, daytime running lamps	X	X	X	X	X	X	X	X	X	X
Direction indicators	X	X	X	X	X	X	X	X	X	X
Rear registration	X	X	X	X	X	X	X	X	X	X

a Vehicles of this category shall be fitted with an adequate windscreen defrosting and demisting device.

b Vehicles of this category shall be fitted with adequate windscreen washing and wiping devices.

c Only if the vehicle is fitted with couplings.

d Not exceeding 2,5 tonnes technically permissible maximum laden mass.

e Only applicable to vehicles where the 'Seating reference point ("R" point)' of the lowest seat is not more than 700 mm above ground level. The 'R' point is defined in UNECE Regulation 95.

f Only when the manufacturer applies for type-approval of a vehicle intended for the transport of dangerous goods.

Status: This is the original version (as it was originally adopted).

plate lamps										
Headlamps (including bulbs)	X	X	X	X	X	X				
Front fog lamps	X	X	X	X	X	X				
Towing hooks	X	X	X	X	X	X				
Rear fog lamps	X	X	X	X	X	X	X	X	X	X
Reversing lamps	X	X	X	X	X	X	X	X	X	X
Parking lamps	X	X	X	X	X	X				
Seat belts and restraint systems	X	X	X	X	X	X				
Forward vision	X									
Identification of controls, tell-tales and indicators	X	X	X	X	X	X				
Defrost/demist	X	a	a	a	a	a				
Wash/wipe	X	b	b	b	b	b				
Heating systems	X	X	X	X	X	X	X	X	X	X

a Vehicles of this category shall be fitted with an adequate windscreen defrosting and demisting device.

b Vehicles of this category shall be fitted with adequate windscreen washing and wiping devices.

c Only if the vehicle is fitted with couplings.

d Not exceeding 2,5 tonnes technically permissible maximum laden mass.

e Only applicable to vehicles where the 'Seating reference point ("R" point)' of the lowest seat is not more than 700 mm above ground level. The 'R' point is defined in UNECE Regulation 95.

f Only when the manufacturer applies for type-approval of a vehicle intended for the transport of dangerous goods.

Status: This is the original version (as it was originally adopted).

Wheel guards	X									
Head restraints	X									
Lateral protection					X	X			X	X
Spray-suppression systems					X	X			X	X
Safety glazing	X	X	X	X	X	X	X	X	X	X
Tyres	X	X	X	X	X	X	X	X	X	X
Speed limitation devices		X	X		X	X				
Masses and dimensions	X	X	X	X	X	X	X	X	X	X
External projections of cabs				X	X	X				
Couplings	X ^c	X ^c	X ^c	X ^c	X ^c	X ^c	X	X	X	X
Flammability			X							
Buses and coaches		X	X							
Frontal impact	X ^d									
Side impact	X ^e			X ^e						
Vehicles intended for the transportation of				X ^f	X ^f	X ^f	X ^f	X ^f	X ^f	X ^f

a Vehicles of this category shall be fitted with an adequate windscreen defrosting and demisting device.

b Vehicles of this category shall be fitted with adequate windscreen washing and wiping devices.

c Only if the vehicle is fitted with couplings.

d Not exceeding 2,5 tonnes technically permissible maximum laden mass.

e Only applicable to vehicles where the 'Seating reference point ("R" point)' of the lowest seat is not more than 700 mm above ground level. The 'R' point is defined in UNECE Regulation 95.

f Only when the manufacturer applies for type-approval of a vehicle intended for the transport of dangerous goods.

Status: This is the original version (as it was originally adopted).

dangerous goods									
Front underrun protection				X	X				
a	Vehicles of this category shall be fitted with an adequate windscreen defrosting and demisting device.								
b	Vehicles of this category shall be fitted with adequate windscreen washing and wiping devices.								
c	Only if the vehicle is fitted with couplings.								
d	Not exceeding 2,5 tonnes technically permissible maximum laden mass.								
e	Only applicable to vehicles where the 'Seating reference point ("R" point)' of the lowest seat is not more than 700 mm above ground level. The 'R' point is defined in UNECE Regulation 95.								
f	Only when the manufacturer applies for type-approval of a vehicle intended for the transport of dangerous goods.								