Changes to legislation: There are outstanding changes not yet made to Commission Regulation (EU) No 109/2011. Any changes that have already been made to the legislation appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes



PART 2 U.K.

## Tests on spray-suppression devices of the energy-absorber type

## 4. PROCEDURE U.K.

- 4.1. Secure a 500 (+ 0/- 5) mm wide 750 mm high sample of the equipment to be tested to the vertical plate of the testing equipment, making sure that the sample lies well within the limits of the collector, and that no obstacle is able to deflect the water, either before or after its impact.
- 4.2. Set the water flow rate at 0,675 (+/-0,01) l/s and direct at least 90 l, at most 120 l on to the sample from a horizontal distance of 500 (+/-2) mm (Figure 8 of Annex VI).
- 4.3. Allow the water to trickle from the sample into the collector. Calculate the percentage of water collected versus the quantity of water sprayed.
- 4.4. Carry out the test five times on the sample according to points 4.2 and 4.3. Calculate the average percentage of the series of five tests.

## **Changes to legislation:**

There are outstanding changes not yet made to Commission Regulation (EU) No 109/2011. Any changes that have already been made to the legislation appear in the content and are referenced with annotations.

View outstanding changes

## Changes and effects yet to be applied to the whole legislation item and associated provisions

- Signature words omitted by S.I. 2022/1273 reg. 63(8)
- Annex 2 Pt. 2 s. 1 point 000.7 words substituted by S.I. 2022/1273 reg. 63(10)(c)(ii)
- Art. 2(11) words substituted by S.I. 2022/1273 reg. 63(3)(a)
- Art. 2(12) words substituted by S.I. 2022/1273 reg. 63(3)(b)
- Art. 2(13) words substituted by S.I. 2022/1273 reg. 63(3)(c)
- Art. 2(15) words substituted by S.I. 2022/1273 reg. 63(3)(d)
- Art. 2(16) words substituted by S.I. 2022/1273 reg. 63(3)(e)