Document Generated: 2024-05-16

Changes to legislation: There are outstanding changes not yet made to Regulation (EU) No 540/2014 of the European Parliament and of the Council. Any changes that have already been made to the legislation appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

# [F1ANNEX VIII U.K.

# MEASURES CONCERNING THE ACOUSTIC VEHICLE ALERTING SYSTEM (AVAS)

#### **Textual Amendments**

**F1** Substituted by Commission Delegated Regulation (EU) 2017/1576 of 26 June 2017 amending Regulation (EU) No 540/2014 of the European Parliament and of the Council as regards the Acoustic Vehicle Alerting System requirements for vehicle EU-type approval (Text with EEA relevance).

## [F2Section I

This Annex sets out measures concerning the AVAS for hybrid electric and pure electric vehicles.

- I.1. Notwithstanding points I.2(a), I.2(b), I.3(a) and I.3(b), the provisions of section II shall apply to an AVAS installed:
- (a) in any vehicle type-approved before 1 July 2019;
- (b) in any new vehicle based on the type referred to in point (a) registered before 1 July 2021.
- I.2. Notwithstanding points I.3(a) and (b), the provisions of section III shall apply to an AVAS installed:
- in any vehicle type-approved before 1 July 2019, where the manufacturer so chooses;
- (b) in any new vehicle based on the type referred to in point (a);
- (c) in any vehicle type-approved as from 1 July 2019 and before 1 September 2021;
- in any new vehicle based on the type referred to in point (c) registered before 1 September 2023.
- I.3. The provisions of section IV shall apply to an AVAS installed:
- in any vehicle type-approved before 1 September 2021, where the manufacturer so chooses;
- (b) in any new vehicle based on the type referred to in point (a);
- in any vehicle type-approved on or after 1 September 2021;
- (d) in any new vehicle based on the type referred to in point (c);
- (e) in all new vehicles registered on or after 1 September 2023.

#### SECTIONI.1.System performance

- II If AVAS is installed on a vehicle, it shall comply with the requirements referred to in points II.2 and II.3.
- II.2. Operation conditions U.K.
- (a) Sound generation method

The AVAS shall automatically generate a sound in the minimum range of vehicle speed from start up to approximately 20 km/h and during reversing. Where the vehicle is equipped with an internal combustion engine that is in operation within the vehicle speed range defined above, the AVAS shall not generate a sound.

For vehicles having a reversing sound warning device, it is not necessary for the AVAS to generate a sound whilst reversing.

### (b) Switch

The AVAS shall be fitted with a switch which is easily accessible by the vehicle driver in order to allow engaging and disengaging. Upon restarting the vehicle, AVAS shall default to the switched on position.

(c) Attenuation

The AVAS sound level may be attenuated during periods of vehicle operation.

- II.3. Sound type and volume U.K.
- (a) The sound to be generated by the AVAS shall be a continuous sound that provides information to the pedestrians and other road users of a vehicle in operation. The sound should be easily indicative of vehicle behaviour and should sound similar to the sound of a vehicle of the same category equipped with an internal combustion engine.
- (b) The sound to be generated by the AVAS shall be easily indicative of vehicle behaviour, for example, through the automatic variation of sound level or characteristics in synchronisation with vehicle speed.
- (c) The sound level generated by the AVAS shall not exceed the approximate sound level of a vehicle of the M1 category equipped with an internal combustion engine and operating under the same conditions.

## SECTIONII.1.System performance

The AVAS shall comply with the requirements set out in points III.2 to III.6.

- III.2. Operation conditions U.K.
- (a) Sound generation method

The AVAS shall automatically generate a sound in the minimum range of vehicle speed from start up to approximately 20 km/h and during reversing. Where the vehicle is equipped with an internal combustion engine that is in operation within that vehicle speed range, the AVAS shall not generate a sound.

Vehicles having overall sound levels complying with the requirements in paragraph 6.2.8 of UNECE Regulation No 138<sup>(1)</sup> with a margin of +3 dB(A), are not required to be equipped with AVAS. The requirements laid down in paragraph 6.2.8 of UNECE Regulation No 138 for one-third octave bands and the requirements laid down in paragraph 6.2.3 of UNECE Regulation No 138 for the frequency shift as defined in paragraph 2.4 of the same UNECE Regulation ('frequency shift') shall not apply to those vehicles.

For vehicles having a reversing sound warning device, it is not necessary for the AVAS to generate a sound whilst reversing, on condition that the reversing sound of the

warning device complies with the requirements laid down in the second subparagraph of paragraph 6.2 and in paragraph 6.2.2 of UNECE Regulation No 138.

The sound generated by the vehicle type submitted for approval shall be measured in accordance with the methods set out in Annex 3 and subparagraphs 6.2.1.3 and 6.2.2.2 of UNECE Regulation No 138.

#### (b) Switch

The AVAS may be fitted with a mechanism to enable the driver to halt the operation of an AVAS ('pause function'), which is easily accessible by the vehicle driver in order to allow engaging and disengaging. Where a pause function is fitted, the AVAS shall default to the switched on position upon restarting of the vehicle.

In addition, the pause function shall comply with the requirements laid down in paragraph 6.2.6 of UNECE Regulation No 138.

#### (c) Attenuation

The AVAS sound level may be attenuated during periods of vehicle operation. In those cases, the AVAS sound level shall comply with the requirements laid down in paragraph 6.2.8 of UNECE Regulation No 138.

## III.3. Sound type and volume U.K.

(a) The sound to be generated by the AVAS shall be a continuous sound that provides information to the pedestrians and other road users of a vehicle in operation. The sound shall be easily indicative of vehicle behaviour, for example, through the automatic variation of sound level or characteristics in synchronisation with vehicle speed. The sound shall be similar to the sound of a vehicle of the same category equipped with an internal combustion engine.

The following rules shall apply:

- (i) where it is generated when the vehicle is in motion, the AVAS sound shall comply with the requirements laid down in paragraphs 6.2.1.1, 6.2.1.2, 6.2.1.3, 6.2.2.1, 6.2.2.2 and 6.2.3 of UNECE Regulation No 138, as applicable;
- (ii) the vehicle may emit a sound when stationary, as set out in paragraph 6.2.4 of UNECE Regulation No 138.
- (b) The vehicle manufacturer may provide for the possibility for the driver to select from among different sounds, which shall comply with the requirements laid down in paragraph 6.2.5 of UNECE Regulation No 138.
- (c) The sound level generated by the AVAS shall not exceed the approximate sound level of a vehicle of the M<sub>1</sub> category equipped with an internal combustion engine and operating under the same conditions. In addition, the requirements in paragraph 6.2.7 of UNECE Regulation No 138 shall apply.
- (d) The overall sound level emitted by a vehicle complying with the second subparagraph of point 2(a) shall not exceed the approximate sound level of a vehicle of the M<sub>1</sub> category equipped with an internal combustion engine and operating under the same conditions.
- III.4. Test track requirements U.K.

Until 30 June 2019, the standard ISO 10844:1994 may be applied as an alternative to the standard ISO 10844:2014 to check compliance of the test track as described in Annex 3, paragraph 2.1.2, of UNECE Regulation No 138.

# III.5. Type-approval certificate U.K.

The vehicle manufacturer shall provide, as an attachment to the EU type-approval certificate, any of the following documents:

- a) the communication referred to in paragraph 5(3) of UNECE Regulation No 138, in accordance with the model set out in Annex 1 to that Regulation;
- b) the test results of AVAS sound emission levels, measured in accordance with this Regulation.

# III.6. Markings U.K.

Each component of the AVAS shall bear the following markings:

- (a) the trade name or mark of the manufacturer;
- (b) a designated identification number.

The markings shall be indelible and clearly legible.

[F3SECTION provisions of section III shall apply, with the exception of point III.2.(b). In IV addition, the following shall apply:

Switch

Any mechanism to enable the driver to halt the operation of an AVAS ('pause function') shall comply with the requirements of paragraph 6.2.6 of UNECE Regulation No 138, Supplement 1 to the original version of the Regulation, 01 series of amendments (OJ L 204, 5.8.2017, p.112).]]

#### **Textual Amendments**

**F3** Inserted by Commission Delegated Regulation (EU) 2019/839 of 7 March 2019 amending Regulation (EU) No 540/2014 of the European Parliament and of the Council on the sound level of motor vehicles and of replacement silencing systems (Text with EEA relevance).

# (1) [F1OJ L 9, 13.1.2017, p. 33.]

#### **Textual Amendments**

F1 Substituted by Commission Delegated Regulation (EU) 2017/1576 of 26 June 2017 amending Regulation (EU) No 540/2014 of the European Parliament and of the Council as regards the Acoustic Vehicle Alerting System requirements for vehicle EU-type approval (Text with EEA relevance).

#### **Changes to legislation:**

There are outstanding changes not yet made to Regulation (EU) No 540/2014 of the European Parliament and of the Council. Any changes that have already been made to the legislation appear in the content and are referenced with annotations.

View outstanding changes

# Changes and effects yet to be applied to the whole legislation item and associated provisions

- Signature words omitted by S.I. 2022/1273 reg. 75(10)
- Annex 7 s. 1 words substituted by S.I. 2022/1273 reg. 76(7)
- Annex 8 s. 3.5 words substituted by S.I. 2022/1273 reg. 76(8)
- Annex 4 s. 1 words substituted by S.I. 2022/1273 reg. 76(5)
- Annex 9 Appendix 3 image substituted by S.I. 2022/1273 reg. 76(9)(n)(i)
- Annex 9 Appendix 1 point 1.5 word substituted by S.I. 2022/1273 reg. 76(9)(k)
- Annex 9 Appendix 2 Addendum word substituted by S.I. 2022/1273 reg. 76(9)(1)
- Annex 9 Appendix 3 image words omitted by S.I. 2022/1273 reg. 76(9)(n)(ii)
- Annex 9 Appendix 2 notes words substituted by S.I. 2022/1273 reg. 76(9)(m)
- Annex 6 s. 3 words substituted by S.I. 2022/1273 reg. 76(6)
- Annex 1 Appendix 2 heading word substituted by S.I. 2022/1273 reg. 76(2)(j)(i)
- Annex 1 Appendix 2 Addendum word substituted by S.I. 2022/1273 reg. 76(2)(1)
- Annex 1 Appendix 2 words inserted by S.I. 2022/1273 reg. 76(2)(j)(ii)
- Annex 1 Appendix 1 heading words substituted by S.I. 2022/1273 reg. 76(2)(i)(i)
- Annex 1 Appendix 1 point 9(1) words substituted by S.I. 2022/1273 reg. 76(2)(i)(ii)
- Annex 1 Appendix 2 notes words substituted by S.I. 2022/1273 reg. 76(2)(k)(i)
- Annex 1 Appendix 2 notes words substituted by S.I. 2022/1273 reg. 76(2)(k)(ii)
- Art. 3(1) words substituted by S.I. 2022/1273 reg. 75(4)(b)
- Art. 3(5) words substituted by S.I. 2022/1273 reg. 75(4)(c)
- Art. 3(21) word substituted by S.I. 2022/1273 reg. 75(4)(d)