Commission Regulation (EU) 2019/2020 of 1 October 2019 laying down ecodesign requirements for light sources and separate control gears pursuant to Directive 2009/125/EC of the European Parliament and of the Council and repealing Commission Regulations (EC) No 244/2009, (EC) No 245/2009 and (EU) No 1194/2012 (Text with EEA relevance)

Article 1

Subject matter and scope

- 1 This Regulation establishes ecodesign requirements for the placing on the market of
 - a light sources;
 - b separate control gears.

The requirements also apply to light sources and separate control gears placed on the market in a containing product.

2 This Regulation shall not apply to light sources and separate control gears specified in points 1 and 2 of Annex III.

3 Light sources and separate control gears specified in point 3 of Annex III shall comply only with the requirements of point 3(e) of Annex II.

Article 2

Definitions

For the purpose of this Regulation, the following definitions shall apply:

- (1) 'light source' means an electrically operated product intended to emit, or, in the case of a non-incandescent light source, intended to be possibly tuned to emit, light, or both, with all of the following optical characteristics:
 - (a) chromaticity coordinates x and y in the range

0,27 < x < 0,53 and

 $2,3172 x^{2} + 2,3653 x - 0,2199 < y < -2,3172 x^{2} + 2,3653 x - 0,1595;$

- (b) a luminous flux < 500 lumen per mm² of projected light-emitting surface area as defined in Annex I;
- (c) a luminous flux between 60 and 82 000 lumen;
- (d) a colour rendering index (CRI) > 0;

using incandescence, fluorescence, high-intensity discharge, inorganic light emitting diodes (LED) or organic light emitting diodes (OLED), or their combinations as lighting technology, and that can be verified as a light source according to the procedure of Annex IV.

High-pressure sodium (HPS) light sources that do not fulfil condition (a) are considered light sources for the purposes of this Regulation.

Light sources do not include:

- (a) LED dies or LED chips;
- (b) LED packages;
- (c) products containing light source(s) from which these light source(s) can be removed for verification;
- (d) light-emitting parts contained in a light source from which these parts cannot be removed for verification as a light source;
- (2) 'control gear' means one or more devices, that may or may not be physically integrated in a light source, intended to prepare the mains for the electric format required by one or more specific light sources within boundary conditions set by electric safety and electromagnetic compatibility. It may include transforming the supply and starting voltage, limiting operational and preheating current, preventing cold starting, correcting the power factor and/or reducing radio interference.

The term 'control gear' does not include power supplies within the scope of Commission Regulation (EC) No 278/2009⁽¹⁾. The term also does not include lighting control parts and non-lighting parts (as defined in Annex I), although such parts may be physically integrated with a control gear or marketed together as a single product.

A Power over Ethernet (PoE) switch is not a control gear in the sense of this Regulation. 'Power-over-Ethernet switch' or 'PoE switch' means equipment for power-supply and data-handling that is installed between the mains and office equipment and/or light sources for the purpose of data transfer and power supply;

- (3) 'separate control gear', means a control gear that is not physically integrated with a light source and is placed on the market as a separate product or as a part of a containing product;
- (4) 'containing product' means a product containing one or more light sources, or separate control gears, or both. Examples of containing products are luminaires that can be taken apart to allow separate verification of the contained light source(s), household appliances containing light source(s), furniture (shelves, mirrors, display cabinets) containing light source(s). If a containing product cannot be taken apart for verification of the light source and separate control gear, the entire containing product is to be considered a light source;
- (5) 'light' means electromagnetic radiation with a wavelength between 380 nm and 780 nm;
- (6) 'mains' or 'mains voltage' (MV) means the electricity supply of $230 (\pm 10 \%)$ volt of alternating current at 50 Hz;
- (7) 'LED die' or 'LED chip' means a small block of light-emitting semiconducting material on which a functional LED circuit is fabricated;
- (8) 'LED package' means a single electric part comprising principally at least one LED die. It does not include a control gear or parts of it, a cap or active electronic components and is not connected directly to the mains voltage. It can include one or more of the following: optical elements, light converters (phosphors), thermal, mechanical and electric interfaces or parts to address electrostatic discharge concerns.

Any light-emitting devices that are intended to be used directly in an LED luminaire, are considered to be light sources;

- (9) 'chromaticity' means the property of a colour stimulus defined by its chromaticity coordinates (x and y);
- (10) 'luminous flux' or 'flux' (Φ) , expressed in lumen (lm), means the quantity derived from radiant flux (radiant power) by evaluating the electromagnetic radiation in accordance with the spectral sensitivity of the human eye. It refers to the total flux emitted by a light source in a solid angle of 4π steradians under conditions (e.g. current, voltage, temperature) specified in applicable standards. It refers to the initial flux for the undimmed light source after a short operating period, unless it is clearly specified that the flux in a dimmed condition or the flux after a given period of operation is intended. For light sources that can be tuned to emit different light spectra and/ or different maximum light intensities, it refers to the flux in the 'reference control settings' as defined in Annex I;
- (11) 'colour rendering index' (CRI) means a metric quantifying the effect of an illuminant on the colour appearance of objects by conscious or subconscious comparison with their colour appearance under the reference illuminant and is the average Ra of the colour rendering for the first 8 test colours (R1-R8) defined in standards;
- (12) 'incandescence' means the phenomenon where light is produced from heat, in light sources typically produced through a threadlike conductor ('filament') which is heated by the passage of an electric current;
- (13) 'halogen light source' means an incandescent light source with a threadlike conductor made from tungsten surrounded by gas containing halogens or halogen compounds;
- (14) 'fluorescence' or 'fluorescent light source' (FL) means the phenomenon or a light source using an electric gas discharge of the low-pressure mercury type in which most of the light is emitted by one or more layers of phosphors excited by the ultraviolet radiation from the discharge. Fluorescent light sources may have one ('single-capped') or two ('double-capped') connections ('caps') to their electricity supply. For the purposes of this Regulation, magnetic induction light sources are also considered as fluorescent light sources;
- (15) 'high intensity discharge' (HID) means an electric gas discharge in which the light-producing arc is stabilised by wall temperature and the arc chamber has a bulb wall loading in excess of 3 watts per square centimetre. HID light sources are limited to metal halide, high-pressure sodium and mercury vapour types, as defined in Annex I;
- (16) 'gas discharge' means a phenomenon where light is produced, directly or indirectly, by an electric discharge through a gas, plasma, metal vapour or mixture of gases and vapours;
- (17) 'inorganic light emitting diode' (LED) means a technology in which light is produced from a solid state device embodying a p-n junction of inorganic material. The junction emits optical radiation when excited by an electric current;
- (18) 'organic light emitting diode' (OLED) means a technology in which light is produced from a solid state device embodying a p-n junction of organic material. The junction emits optical radiation when excited by an electric current;
- (19) 'high-pressure sodium light source' (HPS) means a high intensity discharge light source in which the light is produced mainly by radiation from sodium vapour

operating at a partial pressure of the order of 10 kilopascals. HPS light sources may have one ('single-ended') or two ('double-ended') connectors to their electricity supply.

- (20) 'equivalent model' means a model with the same technical characteristics relevant for the ecodesign requirements, but that is placed on the market or put into service by the same manufacturer or importer as another model with a different model identifier;
- (21) 'model identifier' means the code, usually alphanumeric, which distinguishes a specific product model from other models with the same trade mark or the same manufacturer's or importer's name;
- (22) 'end-user' means a natural person buying or expected to buy a product for purposes which are outside his trade, business, craft or profession.

For the purposes of the Annexes, additional definitions are set out in Annex I.

Article 3

Ecodesign requirements

The ecodesign requirements set out in Annex II shall apply from the dates indicated therein.

Article 4

Removal of light sources and separate control gears

1 Manufacturers, importers or authorised representatives of containing products shall ensure that light sources and separate control gears can be replaced with the use of common available tools and without permanent damage to the containing product, unless a technical justification related to the functionality of the containing product is provided in the technical documentation explaining why the replacement of light sources and separate control gear is not appropriate.

The technical documentation shall also provide instructions on how light sources and separate control gears can be removed without being permanently damaged for verification purposes by market surveillance authorities.

2 Manufacturers, importers or authorised representatives of containing products shall provide information about the replaceability or non-replaceability of light sources and control gears by end-users or qualified persons without permanent damage to the containing product. Such information shall be available on a free-access website. For products sold directly to endusers, this information shall be on the packaging, at least in the form of a pictogram, and in the user instructions.

3 Manufacturers, importers or authorised representatives of containing products shall ensure that light sources and separate control gears can be dismantled from containing products at end of life. Dismantling instructions shall be available on a free access website.

Article 5

Conformity assessment

1 The conformity assessment procedure referred to in Article 8 of Directive 2009/125/ EC shall be the internal design control system set out in Annex IV to that Directive or the management system set out in Annex V to that Directive.

2 For the purposes of the conformity assessment pursuant to Article 8 of Directive 2009/125/EC, the technical documentation shall contain the information set out in point 3(d) of Annex II to this Regulation and the details and the results of the calculations in accordance with points 1 and 2 of Annex II, and Annex V to this Regulation.

3 Where the information included in the technical documentation for a particular model has been obtained:

- a from a model that has the same technical characteristics relevant for the technical information to be provided but is produced by a different manufacturer, or
- b by calculation on the basis of design or extrapolation from another model of the same or a different manufacturer, or both,

the technical documentation shall include details of such calculations or extrapolations, the assessment carried out by the manufacturer to verify the accuracy of the calculations and, where appropriate, the declaration of identity between the models of different manufacturers.

The technical documentation shall include a list of all equivalent models, including the model identifiers.

4 The technical documentation shall include the information in the order and as set out in Annex VI of Regulation (EU) 2019/2015. For market surveillance purposes, manufacturers, importers or authorised representatives may, without prejudice to Annex IV, point 2(g) of Directive 2009/125/EC, refer to the technical documentation uploaded to the product database which contains the same information laid down in Regulation (EU) 2019/2015.

Article 6

Verification procedure for market surveillance purposes

Member States shall apply the verification procedure laid down in Annex IV to this Regulation when performing the market surveillance checks referred to in point 2 of Article 3 of Directive 2009/125/EC.

Article 7

Circumvention

The manufacturer, importer or authorised representative shall not place on the market products designed to be able to detect they are being tested (e.g. by recognising the test conditions or test cycle), and to react specifically by automatically altering their performance during the test with the aim of reaching a more favourable level for any of the parameters declared by the manufacturer, importer or authorised representative in the technical documentation or included in any of the documentation provided. Status: Point in time view as at 01/10/2019. Changes to legislation: There are outstanding changes not yet made to Commission Regulation (EU) 2019/2020. Any changes that have already been made to the legislation appear in the content and are referenced with annotations. (See end of Document for details)

The energy consumption of the product and any of the other declared parameters shall not deteriorate after a software or firmware update when measured with the same test standard originally used for the declaration of conformity, except with explicit consent of the end-user prior to the update.

Article 8

Indicative benchmarks

The indicative benchmarks for the best-performing products and technologies available on the market at the time of adopting this Regulation are set out in Annex VI.

Article 9

Review

The Commission shall review this Regulation in the light of technological progress and shall present the results of this review, including, if appropriate, a draft revision proposal, to the Consultation Forum no later than 25 December 2024.

This review shall in particular assess the appropriateness of:

- (a) setting more stringent energy efficiency requirements for all light source types, in particular for non-LED light source types, and for separate control gears;
- (b) setting requirements on lighting control parts;
- (c) setting more stringent requirements on flicker and stroboscopic effects, while extending them to separate control gears;
- (d) setting requirements on dimming, including the interaction with flicker;
- (e) setting more stringent requirements on (networked) standby power;
- (f) lowering or abolishing the power bonus for colour-tuneable light sources and removing the exemption for high colour purity;
- (g) setting lifetime requirements;
- (h) setting improved information requirements concerning lifetime, including for control gears;
- (i) substituting the CRI colour rendering metric by a more adequate metric;
- (j) verifying the adequacy of lumen as a stand-alone metric for the quantity of visible light;
- (k) the exemptions;
- (l) setting additional resource efficiency requirements for products in accordance with the principles of the circular economy, especially concerning the removability and exchangeability of light sources and control gears.

Status: Point in time view as at 01/10/2019. Changes to legislation: There are outstanding changes not yet made to Commission Regulation (EU) 2019/2020. Any changes that have already been made to the legislation appear in the content and are referenced with annotations. (See end of Document for details)

Article 10

Repeal

Regulations (EC) No 244/2009, (EC) No 245/2009 and (EU) No 1194/2012 are repealed with effect from 1 September 2021.

Article 11

Entry into force and application

This Regulation shall enter into force on the twentieth day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 September 2021. However, Article 7 shall apply from 25 December 2019.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 1 October 2019.

For the Commission The President Jean-Claude JUNCKER Status: Point in time view as at 01/10/2019. Changes to legislation: There are outstanding changes not yet made to Commission Regulation (EU) 2019/2020. Any changes that have already been made to the legislation appear in the content and are referenced with annotations. (See end of Document for details)

Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power consumption and average active efficiency of external power supplies (OJ L 93, 7.4.2009, p. 3).

Status:

Point in time view as at 01/10/2019.

Changes to legislation:

There are outstanding changes not yet made to Commission Regulation (EU) 2019/2020. Any changes that have already been made to the legislation appear in the content and are referenced with annotations.