

---

STATUTORY RULES OF NORTHERN IRELAND

---

**2004 No. 294**

**ROAD AND RAILWAY TRANSPORT**

**Level Crossing (Trooperslane) Order (Northern Ireland) 2004**

*Made* - - - - - *7th July 2004*

*Coming into operation* *5th August 2004*

**LEVEL CROSSING (TROOPERSLANE)  
ORDER (NORTHERN IRELAND) 2004**

1. Citation, commencement and interpretation
  2. Suspension of statutory provisions
  3. Provision of equipment
  4. Revocation
- Signature

---

SCHEDULE	PARTICULARS OF THE BARRIERS, LIGHTS, TRAFFIC SIGNS AND OTHER DEVICES
1	AND OTHER DEVICES
1.	Cattle-cum-trespass guards of standard railway design shall be provided adjacent...
2.	A barrier shall be pivoted as close to the railway...
3.	It shall be possible to raise and lower the barriers....
4.	When the barriers are fully lowered their uppermost surfaces shall...
5.	When in the fully raised position the barriers shall be...
6.	The barriers shall be as light as possible but shall...
7.	The barriers shall be fitted with skirts so arranged that...
8.	Two electric lamps, each of not less than 5 watts...
9.	The barriers shall display on both front and rear faces...
10.	Suitable screening shall be provided for each barrier machine to...
11.	A traffic light signal as prescribed by diagram 3014 of...
12.	An audible warning device shall be provided on or adjacent...
13.	A reflectorised stop line of the size and type shown...
14.	Where the road passes over the crossing, reflectorised edge of...
15.	The centre line of the carriageway shall be marked on...
16.	A traffic sign of the size, colour and type shown...
17.	There shall be a signal box at Belfast Central. A...
18.	The control point shall have push-buttons to –

*Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.*

19. Facilities shall be provided at the crossing to operate the...
  20. Lighting shall be provided as necessary so that during the...
  21. Protecting railway signals shall be provided and these shall be...
  22. In this Schedule – “the Regulations” means the Traffic Signs...
- SCHEDULE
- 2
- CONDITIONS AND REQUIREMENTS TO BE COMPLIED WITH BY THE RAILWAY UNDERTAKING
1. The carriageway shall be at least 6.3 metres wide at...
  2. The ground at the two edges of the carriageway over...
  3. The surface of the carriageway over the crossing shall be...
  4. The barriers shall be kept in the fully raised position...
  5. The electric lamps on each barrier mentioned in Schedule I...
  6. If the road approaches to the crossing are lit the...
  7. The protecting signals shall be controlled from the signal box...
  8. The picture of the crossing shall be exhibited on the...
  9. Visual indicators and an audible alarm shall be provided at...
  10. The audible alarm shall sound if –
  11. When the ‘lower’ push-button is pressed or the train occupies...
  12. The arrangements shall be such that the protecting railway signals...
  13. If a train overruns a protecting signal the arrangements shall...
  14. The intermittent red lights shall continue to show until the...
  15. If any barrier fails to rise from the lowered position...
  16. Should automatic lowering or raising take an abnormally long time...
- Explanatory Note