STATUTORY RULES OF NORTHERN IRELAND

2015 No. 13

ROAD AND RAILWAY TRANSPORT

The Level Crossing (Cullybackey South) Order (Northern Ireland) 2015

Made - - - - 21st January 2015

Coming into operation 16th February 2015

THE LEVEL CROSSING (CULLYBACKEY SOUTH) ORDER (NORTHERN IRELAND) 2015

- 1. Citation, commencement and interpretation
- 2. Suspension of statutory provisions
- 3. Provision of automatic equipment
- 4. Revocation Signature

SCHEDULE PARTICULARS OF THE BARRIERS, LIGHTS, TRAFFIC SIGNS

- AND OTHER DEVICES
- 1. Cattle-cum-trespass guards of standard railway design shall be provided adjacent...
- 2. A barrier shall be pivoted as close to the railway...
- 3. It shall be possible to raise and lower the barriers....
- 4. When barriers are fully lowered their uppermost surfaces shall be...
- 5. When in the fully raised position the barriers shall be...
- 6. The barriers shall be as light as possible but shall...
- 7. Two electric lamps or equivalent (light emitting diodes), each of...
- 8. The barriers shall display on both front and rear faces...
- 9. Suitable screening shall be provided for each barrier machine to...
- 10. A traffic light signal of the size, colour and type...
- 11. An audible warning device shall be provided on or adjacent...
- 12. A reflectorised stop line of the size and type shown...
- 13. A reflectorised pedestrian stop line of the size and type...
- 14. Where the road passes over the crossing, reflectorised edge of...
- 15. (a) The centre line of the carriageway shall be marked...
- 16. A traffic sign of the size, colour and type shown...

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

- 17. A traffic sign of the size, colour and type shown...
- 18. A traffic sign of the size, colour and type shown...
- 19. A traffic sign of the size, colour and type shown...
- 20. A telephone mounted in a weather-proof box connected to the...
- 21. A level crossing speed restriction board for 40 miles per...
- 22. Two independent power supplies shall be provided at the crossing,...
- 23. In this Schedule "the Regulations" means the Traffic Signs Regulations...

SCHEDULE CONDITIONS AND REQUIREMENTS TO BE COMPLIED

- 2 WITH BY THE RAILWAY UNDERTAKING
- 1. The carriageway shall be approximately 6.5 metres wide at the...
- 2. The ground shall be made up to the level of...
- 3. The surface of the carriageway over the crossing shall be...
- 4. The barriers shall be kept in the fully raised position...
- 5. The electric lamps or equivalent (light emitting diodes) on each...
- 6. If the road approaches to the crossing are lit the...
- 7. Visual indicators and an audible alarm shall be provided in...
- 8. The barriers, the audible warning devices and the traffic light...
- 9. When the train either occupies a track circuit or operates...
- 10. In the event of the failure of both intermittent red...
- 11. Should a total power failure occur both barriers shall descend...
- 12. If either barrier fails to rise from the lowered position... Explanatory Note