

SCHEDULE 1

Regulations 2, 3, 8(2), 9(1), 11(5)

LIMIT VALUES, MARGINS OF TOLERANCE ETC.

PART I
SULPHUR DIOXIDE

Limit values for sulphur dioxide**1.1**

	<i>Averaging Period</i>	<i>Limit value</i>	<i>Margin of Tolerance</i> <i>M1</i>	<i>Date by which limit value is to be met</i>
1.Hourly limit value for the protection of human health	1 hour	350µg/m ³ , not to be exceeded more than 24 times a calendar year	470µg/m ³ on 19th July 2001 reducing on 1st January of each following year by 30µg/m ³ to reach 350µg/m ³ by 1st January 2005	1st January 2005
2.Daily limit value for the protection of human health	24 hours	125µg/m ³ , not to be exceeded more than 3 times a calendar year	None	1st January 2005
3.Limit value for the protection of ecosystems	Calendar year and winter (1st October to 31st March)	20µg/m ³	None	19th July 2001

Marginal Citations

M1 The figures for Margins of Tolerance for each of the relevant pollutants given in this Schedule are calculated from those given in Annex I of Directive 99/30/EC (O.J. No. L 163, 22.4.99, p.41). This gave a figure above the limit value for each relevant pollutant, reducing by equal percentages from the date of entry into force of that Directive in 1999.

Alert threshold for sulphur dioxide

1.2 500µg/m³ measured over three consecutive hours at locations representative of air quality over at least 100 km² or an entire zone or agglomeration, whichever is the smaller.

Minimum Details to be made available to the public when the alert threshold for sulphur dioxide is exceeded

1.3 Details to be made available to the public should include at least:

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- the date, hour and place of the occurrence and the reasons for the occurrence, where known;
- any forecasts of:
 - changes in concentration (improvement, stabilisation, or deterioration), together with the reasons for those changes,
 - the geographical area concerned,
 - the duration of the occurrence,
 - the type of population potentially sensitive to the occurrence,
 - the precautions to be taken by the sensitive population concerned.

PART II

NITROGEN DIOXIDE (NO₂) AND OXIDES OF NITROGEN (NO_x)

Limit values for nitrogen dioxide and oxides of nitrogen

2.1

	<i>Averaging Period</i>	<i>Limit value</i>	<i>Margin of tolerance</i>	<i>Date by which limit value is to be met</i>
1.Hourly limit value for the protection of human health	1 hour	200µg/m ³ NO ₂ not to be exceeded more than 18 times a calendar year	290µg/m ³ on 19th July 2001, reducing on 1st January of each following year by 10µg/m ³ to reach 200µg/m ³ by 1st January 2010	1st January 2010
2.Annual limit value for the protection of human health	Calendar year	40µg/m ³ NO ₂	58µg/m ³ on 19th July 2001 reducing on 1st January of each following year by 2µg/m ³ to reach 40µg/m ³ by 1st January 2010	1st January 2010
3.Annual limit value for the protection of vegetation	Calendar year	30µg/m ³ NO _x	None	19th July 2001

Alert threshold for nitrogen dioxide

2.2 400µg/m³ measured over three consecutive hours at locations representative of air quality over at least 100 km² or an entire zone or agglomeration, whichever is the smaller.

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Minimum Details to be made available to the public when the alert threshold for nitrogen dioxide is exceeded

2.3 Details to be made available to the public should include at least:

- the date, hour and place of the occurrence and the reasons for the occurrence, where known;
- any forecasts of:
 - changes in concentration (improvement, stabilisation, or deterioration), together with the reasons for those changes,
 - the geographical area concerned,
 - the duration of the occurrence,
- the type of population potentially sensitive to the occurrence,
- the precautions to be taken by the sensitive population concerned.

PART III

PARTICULATE MATTER (PM₁₀)

	<i>Averaging Period</i>	<i>Limit value</i>	<i>Margin of tolerance</i>	<i>Date by which limit value is to be met</i>
1.24-hour limit value for the protection of human health	24 hours	50µg/m ³ PM ₁₀ not to be exceeded more than 35 times a calendar year	70µg/m ³ on 19th July 2001, reducing on 1st January of each following year by 5µg/m ³ to reach 50µg/m ³ by 1st January 2005	1st January 2005
2. Annual limit value for the protection of human health	Calendar year	40µg/m ³ PM ₁₀	46.4µg/m ³ on 19th July 2001, reducing on 1st January of each following year by 1.6µg/m ³ to reach 40µg/m ³ by 1st January 2005	1st January 2005

PART IV

LEAD

	<i>Averaging Period</i>	<i>Limit value</i>	<i>Margin of tolerance</i>	<i>Date by which limit value is to be met</i>
Annual limit value for the	Calendar year	0.5µg/m ³	0.9µg/m ³ on 19th July 2001,	1st January 2005

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

protection of human health

reducing on 1st January of each following year by $0.1\mu\text{g}/\text{m}^3$ to reach $0.5\mu\text{g}/\text{m}^3$ by 1st January 2005

SCHEDULE 2

Regulations 5(5) and 6

UPPER AND LOWER ASSESSMENT THRESHOLDS AND EXCEEDANCES

PART I

UPPER AND LOWER ASSESSMENT THRESHOLDS

The following upper and lower assessment thresholds will apply:

(a) SULPHUR DIOXIDE

	<i>Health protection</i>	<i>Ecosystem protection</i>
Upper assessment threshold	60% of 24-hour limit value ($75\mu\text{g}/\text{m}^3$, not to be exceeded more than 3 times in any calendar year)	60% of winter limit value ($12\mu\text{g}/\text{m}^3$)
Lower assessment threshold	40% of 24-hour limit value ($50\mu\text{g}/\text{m}^3$, not to be exceeded more than 3 times in any calendar year)	40% of winter limit value ($8\mu\text{g}/\text{m}^3$)

(b) NITROGEN DIOXIDE AND OXIDES OF NITROGEN

	<i>Hourly limit value for the protection of human health (NO_2)</i>	<i>Annual limit value for the protection of human health (NO_2)</i>	<i>Annual limit value for the protection of Vegetation (NO_x)</i>
Upper assessment threshold	70% of limit value ($140\mu\text{g}/\text{m}^3$, not to be exceeded more than 18 times in any calendar year)	80% of limit value ($32\mu\text{g}/\text{m}^3$)	80% of limit value ($24\mu\text{g}/\text{m}^3$)
Lower assessment threshold	50% of limit value ($100\mu\text{g}/\text{m}^3$, not to be exceeded more than 18 times in any calendar year)	65% of limit value ($26\mu\text{g}/\text{m}^3$)	65% of limit value ($19.5\mu\text{g}/\text{m}^3$)

(c) PARTICULATE MATTER ^{M2}

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

	24-hour average	Annual average
Upper assessment threshold	60% of limit (30µg/m ³ , not to be exceeded more than seven times in any calendar year)	70% of limit value (14µg/m ³)
Lower assessment threshold	40% of limit value (20µg/m ³ , not to be exceeded more than seven times in any calendar year)	50% of limit value (10µg/m ³)

(d) LEAD

	Annual average
Upper assessment threshold	70% of limit value (0.35µg/m ³)
Lower assessment threshold	50% of limit value (0.25µg/m ³)

Marginal Citations

M2 The upper and lower assessment thresholds for PM

¹⁰

are based on the following indicative limit values for 1st January 2010, which will be reviewed in the light of further information on health and environmental effects, technical feasibility and experience in the application of the existing "Stage 1" limit values: (See the following table)

Marginal Citations

M2 The upper and lower assessment thresholds for PM

¹⁰

are based on the following indicative limit values for 1st January 2010, which will be reviewed in the light of further information on health and environmental effects, technical feasibility and experience in the application of the existing "Stage 1" limit values: (See the following table)

	Averaging period	Limit value	Margin of tolerance	Date by which limit value is to be met
1.24-hour limit value for the production of human health	24 hours	50µg/m ³ PM ₁₀ not to be exceeded more than 7 times a calendar year	To be derived from date and to be equivalent to Stage 1 limit value	1st January 2010
2. Annual limit value for the protection of human health	Calendar year	20µg/m ³ PM ₁₀	50% on 1st January 2005 reducing every 12 months thereafter by	1st January 2010

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

equal percentages
to reach 0% by
1st January 2010

PART II

DETERMINATION OF EXCEEDANCES OF UPPER AND LOWER ASSESSMENT THRESHOLDS

Exceedances of upper and lower assessment thresholds must be determined on the basis of concentrations during the previous five years where sufficient data are available. An assessment threshold will be deemed to have been exceeded if during those five years the total number of exceedances of the numerical concentration of the threshold is more than three times the number of exceedances allowed each year.

Where fewer than five years' data are available, measurement campaigns of short duration during the period of the year and at locations likely to be typical of the highest pollution levels may be combined with results obtained from information from emission inventories and modelling to determine exceedances of the upper and lower assessment thresholds.

SCHEDULE 3

Regulation 7(3)

LOCATION OF SAMPLING POINTS FOR THE MEASUREMENT OF SULPHURDIOXIDE, NITROGEN DIOXIDE AND OXIDES OF NITROGEN, PARTICULATE MATTER AND LEAD IN AMBIENT AIR.

The following considerations will apply to fixed measurement.

PART I

MACROSCALE SITING

Protection of human health

- (a) Sampling points directed at the protection of human health should be sited:
- (i) to provide data on the areas within zones and agglomerations where the highest concentrations occur to which the population is likely to be directly or indirectly exposed for a period which is significant in relation to the averaging period of the limit value(s);
 - (ii) to provide data on levels in other areas within the zones and agglomerations which are representative of the exposure of the general population.

Sampling points should in general be sited to avoid measuring very small micro-environments in their immediate vicinity. As a guideline, a sampling point should be sited to be representative of air

Changes to legislation: *The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes*

quality in a surrounding area of no less than 200 m² at traffic-orientated sites and of several square kilometres at urban-background sites.

Sampling points should also, where possible, be representative of similar locations not in their immediate vicinity.

Account should be taken of the need to locate sampling points on islands, where that is necessary for the protection of human health.

Protection of ecosystems and vegetation

- (b) Sampling points targeted at the protection of ecosystems or vegetation should be sited more than 20 km from agglomerations or more than 5 km from other built-up areas, industrial installations or motorways. As a guideline, a sampling point should be sited to be representative of air quality in a surrounding area of at least 1 000 km². A sampling point may be sited at a lesser distance or to be representative of air quality in a less extended area, taking account of geographical conditions.

Account should be taken of the need to assess air quality on islands.

PART II

MICROSCALE SITING

The following guidelines should be met as far as practicable:

- the flow around the inlet sampling probe should be unrestricted without any obstructions affecting the airflow in the vicinity of the sampler (normally some metres away from buildings, balconies, trees, and other obstacles and at least 0.5 m from the nearest building in the case of sampling points representing air quality at the building line);
- in general, the inlet sampling point should be between 1.5 m (the breathing zone) and 4 m above the ground. Higher positions (up to 8 m) may be necessary in some circumstances. Higher siting may also be appropriate if the station is representative of a large area;
- the inlet probe should not be positioned in the immediate vicinity of sources in order to avoid the direct intake of emissions unmixed with ambient air;
- the sampler's exhaust outlet should be positioned so that recirculation of exhaust air to the sampler inlet is avoided;
- location of traffic-oriented samplers:
 - for all pollutants, such sampling points should be at least 25 m from the edge of major junctions and at least 4 m from the centre of the nearest traffic lane,
 - for nitrogen dioxide, inlets should be no more than 5 m from the kerbside,
 - for particulate matter and lead, inlets should be sited so as to be representative of air quality near to the building line.

The following factors may also be taken into account:

- interfering sources;
- security;
- access;
- availability of electrical power and telephone communications;

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- visibility of the site in relation to its surroundings;
- safety of public and operators;
- the desirability of co-locating sampling points for different pollutants;
- planning requirements.

PART III

DOCUMENTATION AND REVIEW OF SITE SELECTION

The site-selection procedures should be fully documented at the classification stage by such means as compass-point photographs of the surrounding area and a detailed map. Sites should be reviewed at regular intervals with repeated documentation to ensure that selection criteria remain valid over time.

SCHEDULE 4

Regulation 7(4)

CRITERIA FOR DETERMINING MINIMUM NUMBERS OF SAMPLING POINTS FOR FIXED MEASUREMENT OF CONCENTRATIONS OF RELEVANT POLLUTANTS IN AMBIENT AIR

PART I

MINIMUM NUMBER OF SAMPLING POINTS FOR FIXED MEASUREMENT TO ASSESS COMPLIANCE WITH LIMIT VALUES FOR THE PROTECTION OF HUMAN HEALTH AND ALERT THRESHOLDS IN ZONES AND AGGLOMERATIONS WHERE FIXED MEASUREMENT IS THE SOLE SOURCE OF INFORMATION

Diffuse sources

(a)

<i>Population of agglomeration or zone (thousands)</i>	<i>If concentrations exceed the upper assessment threshold</i>	<i>If maximum concentrations are between the upper and lower assessment thresholds</i>	<i>For SO₂ and NO₂ in agglomerations where maximum concentrations are below the lower assessment threshold</i>
0–249	1	1	not applicable
250–499	2	1	1
500–749	2	1	1
750–999	3	1	1

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

1 000–1 499	4	2	1
1 500–1 999	5	2	1
2 000–2 749	6	3	2
2 750–3 749	7	3	2
3 750–4 749	8	4	2
4 750– 5 999	9	4	2
6 000	10	5	3

For NO₂ and particulate matter: to include at least one urban-background station and one traffic-orientated station

Point sources

- (b) For the assessment of pollution in the vicinity of point sources, the number of sampling points for fixed measurement should be calculated taking into account emission densities, the likely distribution patterns of ambient-air pollution and the potential exposure of the population.

PART II

MINIMUM NUMBER OF SAMPLING POINTS FOR FIXED MEASUREMENTS TO ASSESS COMPLIANCE WITH LIMIT VALUES FOR THE PROTECTION OF ECOSYSTEMS OR VEGETATION IN ZONES OTHER THAN AGGLOMERATIONS

If maximum concentrations exceed the upper assessment threshold

1 station every 20 000 km²

If maximum concentrations are between the upper and lower assessment thresholds

1 station every 40 000 km²

In island zones the number of sampling points for fixed measurement should be calculated taking into account the likely distribution patterns of ambient air pollution and the potential exposure of ecosystems or vegetation.

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

SCHEDULE 5

Regulation 7(5), (8)

DATA-QUALITY OBJECTIVES AND COMPILATION
OF RESULTS OF AIR QUALITY ASSESSMENT

PART I

DATA-QUALITY OBJECTIVES

The following data-quality objectives for the required accuracy of assessment methods, of minimum time coverage and of data capture of measurement are laid down to guide quality assurance programmes.

	<i>Sulphur dioxide, nitrogen dioxide and oxides of nitrogen</i>	<i>Particulate matter and lead</i>
Continuous measurement		
Accuracy	15%	25%
Minimum data capture	90%	90%
Indicative measurement		
Accuracy	25%	50%
Minimum data capture	90%	90%
Minimum time coverage	14% (One measurement a week at random, evenly distributed over the year, or eight weeks evenly distributed over the year.)	14% (One measurement a week at random, evenly distributed over the year, or eight weeks evenly distributed over the year.)
Modelling		
Accuracy:		
Hourly averages	50%–60%	
Daily averages	50%	
Annual averages	30%	50%
Objective estimation		
Accuracy:	75%	100%

The accuracy of the measurement is defined as laid down in the “Guide to the Expression of Uncertainty of Measurements” (ISO 1993) ^{M3} or in ISO 5725-1 “Accuracy (trueness and precision) of measurement methods and results” (ISO 1994) ^{M4}. The percentages in the table are given for individual measurements averaged, over the period considered, by the limit value, for a 95% confidence interval (bias + two times the standard deviation). The accuracy for continuous measurements should be interpreted as being applicable in the region of the appropriate limit value.

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Marginal Citations

- M3** Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.
- M4** Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

Marginal Citations

- M3** Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.
- M4** Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

The accuracy for modelling and objective estimation is defined as the maximum deviation of the measured and calculated concentration levels, over the period considered by the limit value, without taking into account the timing of the events.

The requirements for minimum data capture and time coverage do not include losses of data due to the regular calibration or the normal maintenance of the instrumentation.

The Scottish Ministers may allow for random measurements to be made instead of continuous measurements for particulate matter and lead by methods for which accuracy within the 95% confidence interval with respect to continuous monitoring has been demonstrated to be within 10%. Random sampling must be spread evenly over the year.

PART II

RESULTS OF AIR QUALITY ASSESSMENT

The following information should be compiled for zones or agglomerations within which sources other than measurement are employed to supplement information from measurement or as the sole means of air quality assessment:

- a description of assessment activities carried out;
- the specific methods used, with references to descriptions of the method;
- the sources of data and information;
- a description of results, including accuracies and, in particular, the extent of any area or, if relevant, the length of road within the zone or agglomeration over which concentrations exceed limit value(s) or, as may be, limit value(s) plus applicable margin(s) of tolerance and of any area within which concentrations exceed the upper assessment threshold or the lower assessment threshold;

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

– for limit values the object of which is the protection of human health, the population potentially exposed to concentrations in excess of the limit value.

Where possible maps shall be compiled showing concentration distributions within each zone and agglomeration.

SCHEDULE 6

Regulation 7(6)

REFERENCE METHODS FOR ASSESSMENT OF CONCENTRATIONS OF SULPHUR DIOXIDE, NITROGEN DIOXIDE AND OXIDES OF NITROGEN, PARTICULATE MATTER (PM₁₀ AND PM_{2.5}) AND LEAD

PART I

REFERENCE METHOD FOR THE ANALYSIS OF SULPHUR DIOXIDE:

ISO/FDIS 10498 (Standard in draft) Ambient air – determination of sulphur dioxide – ultraviolet fluorescence method ^{M5}.

Marginal Citations

M5 Copies of these International Standards Organisation publications can be purchased from the British Standards Institution “BSI” sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

Marginal Citations

M5 Copies of these International Standards Organisation publications can be purchased from the British Standards Institution “BSI” sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

PART II

REFERENCE METHOD FOR THE ANALYSIS OF NITROGEN DIOXIDE AND OXIDES OF NITROGEN:

ISO 7996: 1985 Ambient air – determination of the mass concentrations of nitrogen oxides – chemiluminescence method ^{M6}.

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Marginal Citations

M6 Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

Marginal Citations

M6 Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

PART IIIA

REFERENCE METHOD FOR THE SAMPLING OF LEAD:

The reference method for the sampling of lead will be that described in the Annex to Directive [82/884/EEC](#)^{M7} until such time as the limit value in Schedule 1 to these Regulations is to be met, when the reference method will be that for PM₁₀ as laid down in Part IV of this Schedule.

Marginal Citations

M7 O.J. No. L 378, 31.12.82, p.15.

Marginal Citations

M7 O.J. No. L 378, 31.12.82, p.15.

PART IIIB

REFERENCE METHOD FOR THE ANALYSIS OF LEAD:

ISO 9855: 1993 Ambient air – Determination of the particulate lead content of aerosols collected in filters. Atomic absorption spectroscopy method ^{M8}.

Marginal Citations

M8 Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Marginal Citations

M8 Copies of these International Standards Organisation publications can be purchased from the British Standards Institution "BSI" sales department either by telephone on 020-8996-9001 or by post from the BSI, Standards House, 389 Chiswick High Road, London W4 4AL.

PART IV

REFERENCE METHOD FOR THE SAMPLING AND MEASUREMENT OF PM₁₀

The reference method for the sampling and measurement of PM₁₀ will be that described in EN 12341 "Air Quality – Field Test Procedure to Demonstrate Reference Equivalence of Sampling Methods for the PM₁₀ fraction of particulate matter"^{M9}. The measurement principle is based on the collection on a filter of the PM₁₀ fraction of ambient particulate matter and the gravimetric mass determination.

Marginal Citations

M9 European Standards Institute "CEN" publication reference BSEN 12341, obtainable from the British Standards Institute "BSI" as for footnote (a) above

Marginal Citations

M9 European Standards Institute "CEN" publication reference BSEN 12341, obtainable from the British Standards Institute "BSI" as for footnote (a) above

SCHEDULE 7

Regulation 9(1), (3), (4)

INFORMATION TO BE INCLUDED IN THE PLAN OR PROGRAMME FOR IMPROVEMENT OF AMBIENT AIR QUALITY

Localization of excess pollution

- region
- city (map)
- measuring station (map, geographical coordinates).

General information

- type of zone (city, industrial or rural area)
- estimate of the polluted area (km²) and of the populations exposed to the pollution
- useful climatic data
- relevant data on topography
- sufficient information on the type of targets requiring protection in the zone.

Changes to legislation: The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

Responsible authorities

3. Names and addresses of persons responsible for the development and implementation of improvement plans.

Nature and assessment of pollution

- concentrations observed over previous years (before the implementation of the improvement measures)
- concentrations measured since the beginning of the project
- techniques used for the assessment.

Origin of pollution

- list of the main emission sources responsible for pollution (map)
- total quantity of emissions from these sources (tonnes/year)
- information on pollution imported from other regions.

Analysis of the situation

- details of those factors responsible for the excess (transport, including cross-border transport, formation)
- details of possible measures for improvement of air quality.

Details of those measures or projects for improvement which existed prior to 21st November 1996 i.e.

- local, regional, national, international measures
- observed effects of these measures.

Details of those measures or projects adopted with a view to reducing pollution following 21st November 1996

- listing and description of all the measures set out in the project
- timetable for implementation
- estimate of the improvement of air quality planned and of the expected time required to attain these objectives.

Details of the measures or projects planned or being researched for the long term.

9.

List of the publications, documents, work etc. used to supplement information requested in this Schedule.

10.

Changes to legislation:

The Air Quality Limit Values (Scotland) Regulations 2001 is up to date with all changes known to be in force on or before 23 May 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations.

[View outstanding changes](#)

Changes and effects yet to be applied to :

- Instrument rev by [S.S.I. 2003/428 reg 16\(1\)](#)
- Sch 1 Pt I para 1.1 am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(8\)\(a\)](#)
- Sch 1 Pt II para 2.1 am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(8\)\(b\)](#)
- Sch 1 Pt III am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(8\)\(c\)](#)
- Sch 1 Pt IV am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(8\)\(d\)](#)
- Sch 2 Pt I am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(9\)](#)
- Sch 2 Pt II am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(10\)](#)
- Sch 3 Pt II am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(11\)](#)
- Sch 4 Pt I am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(12\)](#)
- Sch 5 Pt I am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(13\)](#)
- reg 2 defn(s) am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(2\)\(i\)](#)
- reg 2 defn(s) rev in pt (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(2\)\(ii\)](#)
- reg 5 am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(4\)](#)
- reg 7 am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(5\)\(a\)\(i\)reg 2\(5\)\(b\)\(ii\)reg 2\(5\)\(b\)\(iii\)\(c\)](#)
- reg 7 rev in pt (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(5\)\(a\)\(ii\)reg 2\(5\)\(b\)\(i\)](#)
- reg 11 am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(6\)](#)
- reg 12 am (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(7\)](#)

Changes and effects yet to be applied to the whole Instrument associated Parts and Chapters:

Whole provisions yet to be inserted into this Instrument (including any effects on those provisions):

- Sch 1 PtsVVI added (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)reg 2\(8\)\(e\)](#)
- Sch 6 PtsVVI added (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(14\)](#)
- reg 2A added (19.1.2003) by [S.S.I. 2002/556 reg 2\(1\)\(3\)](#)