

## 1973 No. 1381

## CUSTOMS AND EXCISE

## The Import Duties (Temporary Exemptions) (No. 19) Order 1973

<i>Made</i>	<i>3rd August 1973</i>
<i>Laid before the House of Commons</i>	<i>6th August 1973</i>
<i>Coming into Operation</i>	<i>8th August 1973</i>

The Lords Commissioners of Her Majesty's Treasury, by virtue of the powers conferred on them by sections 1, 3(6) and 13 of the Import Duties Act 1958(a) as amended by paragraph 1 of Schedule 4 to the European Communities Act 1972(b) and of all other powers enabling them in that behalf, on the recommendation of the Secretary of State(c), hereby make the following Order:

1.—(1) This Order may be cited as the Import Duties (Temporary Exemptions) (No. 19) Order 1973 and shall come into operation on 8th August 1973.

(2) The Interpretation Act 1889(d) shall apply for the interpretation of this Order as it applies for the interpretation of an Act of Parliament.

2.—(1) Up to and including 31st December 1973 any import duty which is for the time being chargeable on goods of a heading of the Customs Tariff 1959 specified in the Schedule hereto shall not be chargeable in respect of goods of any description there specified in relation to that heading.

(2) Any entry in the second column in the Schedule to this Order shall be taken to comprise all goods which would be classified under an entry in the same terms constituting a subheading (other than the final subheading) of the relevant heading in the Customs Tariff 1959.

(3) For the purposes of classification under the Customs Tariff 1959, insofar as that depends on the rate of duty, any goods to which paragraph (1) or (2) above applies shall be treated as chargeable with the same duty as if this Order had not been made.

*Tim Fortescue,*

*Oscar Murton,*

Two of the Lords Commissioners  
of Her Majesty's Treasury.

3rd August 1973.

(a) 1958 c. 6.

(c) See S.I. 1970/1537 (1970 III, p. 5293).

(b) 1972 c. 68

(d) 1889 c. 63.

## SCHEDULE

## GOODS TEMPORARILY EXEMPT FROM IMPORT DUTY

<i>Tariff Heading</i>	<i>Description</i>
05.08	Bones and horn-cores, unworked, defatted, simply prepared (but not cut to shape)
73.10	Bars and rods of iron or steel, not further worked than hot-rolled or extruded, in straight lengths and having a rectangular cross-section of which the width is not less than 10 millimetres nor more than 210 millimetres and the thickness is not less than 6 millimetres  Bars and rods of iron or steel, not further worked than hot-rolled or extruded, in straight lengths or in coils, of circular, square or hexagonal cross-section, or ribbed and of which the greatest cross-sectional dimension does not exceed 156 millimetres; in the case of square cross-section the corners may be either square or rounded
73.13	Sheets and plates of iron or steel, hot-rolled, but not coated or otherwise worked
73.15	Alloy steel billets, containing not less than 0.50 per cent. nor more than 0.60 per cent. by weight of carbon, not less than 0.70 per cent. nor more than 1.00 per cent. by weight of manganese and not less than 1.50 per cent. nor more than 2.00 per cent. by weight of silicon as the alloying elements; having a cross-section of which neither width nor thickness is less than 55 millimetres nor more than 80 millimetres  Alloy steel coils for re-rolling, containing not less than 16.0 per cent. nor more than 26.0 per cent. by weight of chromium, and not less than 6.0 per cent. nor more than 22.0 per cent. by weight of nickel as the major alloying elements, and having a width exceeding 500 millimetres but not more than 1,372 millimetres, and a thickness of not less than 2.5 millimetres nor more than 6 millimetres  Bars and rods of alloy steel, not further worked than hot-rolled or extruded and in coils, having a circular, square or hexagonal cross-section of which no cross-sectional dimension exceeds 46 millimetres and containing either (a) not less than 0.10 per cent. lead; or (b) not less than 0.10 per cent. sulphur as the major alloying element other than carbon  Bars and rods of alloy steel, not further worked than hot-rolled or extruded and in straight lengths, having a circular, square or hexagonal cross-section of which no cross-sectional dimension exceeds 156 millimetres and containing either (a) not less than 0.10 per cent. lead; or (b) not less than 0.10 per cent. sulphur as the major alloying element other than carbon  Hot rolled alloy steel strip in coils, containing not less than 16.0 per cent. nor more than 26.0 per cent. by weight of chromium, and not less than 6.0 per cent. nor more than 22.0 per cent. by weight of nickel as the major alloying elements, and not less than 0.5 per cent. nor more than 2.0 per cent. by weight of manganese; of a width of not less than 400 millimetres nor more than 500 millimetres and of a thickness of not less than 3 millimetres nor more than 6 millimetres
73.18	Spirally double welded steel linepipe in lengths of not less than 8.0 metres and not more than 16.0 metres with an outside diameter of not less than 1216 millimetres and not more than 1223 millimetres and a wall thickness

*Tariff  
Heading**Description*

of not less than 15.0 millimetres and not more than 18.0 millimetres, containing not more than 0.20 per cent. by weight of carbon, not more than 1.50 per cent. by weight of manganese, not more than 0.05 per cent. by weight of sulphur; with a yield strength of not less than 36 Kg/mm<sup>2</sup> and not more than 57 Kg/mm<sup>2</sup> in a direction transverse to the pipe axis and a Charpy V notch value at minus 10°C of not less than 20 joule with the specimen length orientated in a direction perpendicular to the spiral weld

Spirally double welded steel linepipe in lengths of not less than 8.0 metres and not more than 16.0 metres with an outside diameter of not less than 1216 millimetres and not more than 1223 millimetres and a wall thickness not less than 12.0 millimetres and not more than 14.0 millimetres, containing not more than 0.20 per cent. by weight of carbon, not more than 1.50 per cent. by weight of manganese, not more than 0.05 per cent. by weight of sulphur; with a yield strength of not less than 36 Kg/mm<sup>2</sup> and not more than 57 Kg/mm<sup>2</sup> in a direction transverse to the pipe axis and a Charpy V notch value at minus 10°C of not less than 20 joule with the specimen length orientated in a direction perpendicular to the spiral weld

Spirally double welded steel linepipe in lengths of not less than 8.0 metres and not more than 16.0 metres with an outside diameter of not less than 758 millimetres and not more than 766 millimetres and a wall thickness of not less than 12.0 millimetres and not more than 14.0 millimetres, containing not more than 0.20 per cent. by weight of carbon, not more than 1.50 per cent. by weight of manganese, not more than 0.05 per cent. by weight of sulphur; with a yield strength of not less than 36 Kg/mm<sup>2</sup> and not more than 57 Kg/mm<sup>2</sup> in a direction transverse to the pipe axis and a Charpy V notch value at minus 10°C of not less than 20 joule with the specimen length orientated in a direction perpendicular to the spiral weld

---

**EXPLANATORY NOTE**

*(This Note is not part of the Order.)*

This Order provides that the goods listed in the Schedule shall be temporarily exempt from import duty up to and including 31st December 1973.

SI 1973/1381  
ISBN 0-11-031381-X



780110 313818