#### STATUTORY INSTRUMENTS

## 1975 No. 330

# The Fishing Vessels (Safety Provisions) Rules 1975

### **PART III**

#### **RULES FOR LIFE-SAVING APPLIANCES**

#### Α

#### LIFE-SAVING APPLIANCES AND EQUIPMENT

#### General requirements for lifeboats

- **82.**—(1) Lifeboats carried in any vessel to which these Rules apply shall comply with the requirements specified in Schedule 4 to these Rules.
- (2) Subject to the provisions of paragraphs (3) and (4) below, the number of persons which such a lifeboat shall be deemed fit to accommodate shall be equal to the greatest whole number obtained by the formula v/x where "v" is the cubic capacity of the lifeboat in cubic metres determined in accordance with the provisions of Schedule 5 to these Rules and "x" is the volume in cubic metres for each person and which shall be 0.283 for a lifeboat of 7.3 metres in length or over and 0.453 for a lifeboat of 3.65 metres in length. For intermediate lengths of lifeboats the value of "x" shall be determined by interpolation.
- (3) The number of persons which such a lifeboat is deemed fit to accommodate shall not exceed the number of adult persons wearing lifejackets for which there is proper seating accommodation arranged in such a way that the persons when seated do not interfere in any way with the use of the oars or the operation of other propulsion equipment.
- (4) No such lifeboat shall be deemed fit to accommodate more than 60 persons unless it is a motor lifeboat.
- (5) Every such lifeboat being a motor lifeboat shall in addition to complying with the requirements of Schedule 4 to these Rules comply with the following requirements:—
  - (a) it shall be fitted with a compression ignition engine and such engine and its accessories shall comply with the requirements of Schedule 6 to these Rules and shall be kept so as to be at all time ready for use;
  - (b) it shall be provided with sufficient fuel for 24 hours continuous operation at the speed and under the conditions specified in sub paragraph (d) below;
  - (c) it shall be capable of going astern;
  - (d) it shall be capable of going ahead in smooth water when loaded with its full complement of persons and equipment at a speed of 4 knots.