STATUTORY INSTRUMENTS

1988 No. 918

HIGHWAYS, ENGLAND AND WALES

The (A41) East of Birmingham to Birkenhead and the (A49) Shrewsbury to Warrington Trunk Roads (Whitchurch Bypass) Order 1988

 Made
 13th May 1988

 Coming into force
 29th July 1988

THE (A41) EAST OF BIRMINGHAM TO BIRKENHEAD AND THE (A49) SHREWSBURY TO WARRINGTON TRUNK ROADS (WHITCHURCH BYPASS) ORDER 1988

- 1. The new highway which the Secretary of State proposes to...
- 2. The centre line of the new trunk road is indicated...
- 3. The Secretary of State directs as respects any part of...
- 4. The lengths of trunk roads described in Schedule 2 and...
- 5. The Secretary of State is authorised to construct the bridge...
- 6. The Secretary of State is authorised to construct the bridge...
- 7. In this Order:—(1) all measurements of distance are measured...
- 8. This Order shall come into force on 29th July 1988... Signature

SCHEDULE 1 — ROUTE OF THE NEW TRUNK ROAD

The route of the new trunk road is at Whitchurch...

SCHEDULE 2 — LENGTHS OF THE TRUNK ROAD CEASING TO BE TRUNK ROAD

The A41 (which includes Heath Road (part) Prees Road, Sedgeford,...

SCHEDULE 3 —

SPECIFICATION

Points of comencement and Termination

To a point 102 metres east of the boundary between fields...

Headroom(Canal) not less than 2.6 metres above normal canal retention...

Headroom(North Bank) not less than 2.2 metres above bank, to...

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Headroom(South Bank) not less than 2.4 metres above bank to...

Waterwaywidth of canal is reduced to 6.0 metres at water...

Length of Watercourse to be Diverted

Length of Towing Path to be Diverted and New Length...

SCHEDULE 4 —
— SPECIFICATION
— Terminat Points of comencement and Termination

Toa point 294 metres south-east of the existing Dansons Bridge....

Headroom(Canal) not less than 2.6 metres above normal canal retention...

Headroom(North Bank) not less than 3.0 metres above bank to...

Headroom(South Bank) not less than 2.6 metres above bank to...

Waterwaywidth of canal is reduced to 6.0 metres at water...

Length of Watercourse to be Diverted

Length of Towing Path to be Diverted and New Length to be Provided