

## SCHEDULE 2

### RESCUE BOATS

#### PART III

#### INFLATED RESCUE BOATS

##### **Boat Equipment**

**6.2** The equipment of every boat shall consist of:

(6.2.1) sufficient buoyant oars or paddles to make headway in calm seas; thole pins, crutches or equivalent arrangements shall be provided for each oar; thole pins or crutches shall be attached to the boat by lanyards or chains;

(6.2.2) a buoyant bailer;

(6.2.3) a sea-anchor complying with the requirements of Part I of Schedule 7;

(6.2.4) a painter of sufficient length and strength, attached to the release device complying with the requirements of paragraph 4.6 and replaced at the forward end of the boat;

(6.2.5) one buoyant line, not less than 50 metres in length, of sufficient strength to tow a liferaft as required by paragraph 2.14;

(6.2.6) one waterproof electric torch suitable for Morse signalling, together with one spare set of batteries and one spare bulb in a waterproof container;

(6.2.7) one whistle or equivalent sound signal;

(6.2.8) a first-aid outfit complying with the requirements of Part II of Schedule 7 in a waterproof case capable of being closed tightly after use;

(6.2.9) two buoyant rescue quoits, attached to not less than 30 metres of buoyant line with a breaking strain of at least 1.0kN;

(6.2.10) a buoyant safety knife;

(6.2.11) two sponges;

(6.2.12) an efficiently manually operated bellows or pump;

(6.2.13) a repair kit in a suitable container for repairing punctures;

(6.2.14) a safety boat hook; and

(6.2.15) a portable fire extinguisher.