

SCHEDULE 1

RENDERING REQUIREMENTS

PART II

METHODS OF RENDERING

METHOD 3

ADDED FAT BATCH ATMOSPHERIC (30 MM PARTICLE SIZE)

Equipment

1. The premises shall be equipped with apparatus to crush specified bovine material to the appropriate particle size, at least one cooker to cook the specified bovine material, sufficient capacity of hot water and steam production to render specified bovine material in accordance with this method, and equipment to separate protein from tallow and store those products.

Crushing

2. The raw material shall be reduced in size by crushing so that the particle size does not exceed 30 mm. Final reduction equipment shall be checked daily and its condition recorded. Any broken equipment shall be repaired without delay to ensure that the final particle size is achieved.

Cooking

3. Crushed material shall then be heated with added tallow in a steam jacketed vessel to remove the inherent moisture at atmospheric pressure. The times and temperatures achieved during the cooking process must be recorded on a permanent recording system. During the course of cooking, the material shall be maintained at a temperature in excess of 100°C for at least 16 minutes, a temperature in excess of 110°C for at least 13 minutes, and a temperature in excess of 130°C for at least 3 minutes. Material may be cooked so that two or more time/temperature requirements are carried out at the same time.

Separation and storage of final products

4. After cooking, the material shall be discharged from the cookers and separated into its tallow and protein components. Protein and tallow shall be stored separately.

Records

5. All records shall be kept for one year.