

SCHEDULE 4

METHOD OF DISPATCH AND RESTRICTIONS ON FORWARDING OF CERTAIN DANGEROUS GOODS

Flammable solids

5. For the following goods—

UN 3233	SELF-REACTIVE LIQUID TYPE C, TEMPERATURE CONTROLLED*
UN 3234	SELF-REACTIVE SOLID TYPE C, TEMPERATURE CONTROLLED*
UN 3235	SELF-REACTIVE LIQUID TYPE D, TEMPERATURE CONTROLLED*
UN 3236	SELF-REACTIVE SOLID TYPE D, TEMPERATURE CONTROLLED*
UN 3237	SELF-REACTIVE LIQUID TYPE E, TEMPERATURE CONTROLLED*
UN 3238	SELF-REACTIVE SOLID TYPE E, TEMPERATURE CONTROLLED*
UN 3239	SELF-REACTIVE LIQUID TYPE F, TEMPERATURE CONTROLLED*
UN 3240	SELF-REACTIVE SOLID TYPE F, TEMPERATURE CONTROLLED*

the methods of temperature control specified below shall be used—

- (a) where the maximum ambient temperature to be expected during carriage is at least 10°C below the control temperature, any of the methods specified in paragraph 3(5);
- (b) where the maximum ambient temperature to be expected during carriage does not exceed the control temperature by more than 30°C, one of the methods specified in paragraph 3(5)(b) to (e);
- (c) in all other cases, one of the methods specified in paragraph 3(5)(c) to (e).