SCHEDULE 2

Article 3

PART I

ENGLAND AND WALES

- **1.** In Column (2) of the Schedule to the Smoke Control Areas (Exempted Fireplaces) (No. 3) Order 1983(1), at the end of condition 2 there shall be added:
 - "or Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent."
- **2.**—(1) The Smoke Control Areas (Exempted Fireplaces) Order 1984(2) shall be amended as follows.
 - (2) After article 2(2) there shall be added the following paragraph:
 - "(3) For the purpose of the conditions set out in paragraph (2), Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent, shall be treated as a fuel which may be used in accordance with the relevant manufacturer's instructions for the Parkray Coalmaster II fireplace, the SE60 Coalburner Stove fireplace and the Worcester Centair 40 Solid Fuel Warm Air Heater fireplace."
- (3) In the second column in the Schedule to that Order, for "operating instructions and installation and maintenance instructions: reference" BC40.1.1. July 1982" (manufacturer's instructions for the Worcester Centair 40 Solid Fuel Warm Air Heater fireplace) there shall be substituted:
 - "(a) installation instructions: reference "BC40.1.2 July 1983";
 - (b) operating and maintenance instructions: reference "BC40.OM2 July 1983"."

PART II

SCOTLAND

- **3.** In Column (2) of Schedule 1 to the Smoke Control Areas (Exempted Fireplaces) (Scotland) Order 1983(3), at the end of condition 2 there shall be added:
 - "or Union Coal Briketts, manufactured by Rheinbraun of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent."
- **4.** In Column (2) of the Schedule to the Smoke Control Areas (Exempted Fireplaces) (Scotland) Order 1984(4), at the end of condition 2 of the conditions specified against the second class of fireplace listed in Column (1) (the Parkray Coalmaster II fireplace) there shall be added:
 - "or Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent."

⁽¹⁾ S.I.1983/1018.

⁽²⁾ S.I. 1984/1649, amended by S.I. 1985/864.

⁽³⁾ S.I. 1983/1573.

⁽⁴⁾ S.I. 1984/1805, amended by S.I. 1985/315.

- **5.**—(1) Schedule 1 to the Smoke Control Areas (Exempted Fireplaces) (Scotland) Order 1985(**5**) shall be amended as follows.
- (2) At the end of condition 1 specified in Column (2) of Schedule 1 against the first class of fireplace described in Column (1) (the SE Coalburner Stove fireplace), there shall be added: ", and, for the purpose of this condition, Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent, shall be treated as a fuel which may be used in accordance with those manufacturer's instructions."
 - (3) The following entry shall be added to Schedule 1:

$\overline{(1)}$	(2)
Class of fireplace	Conditions
The Worcester Centair 40 Solid Fuel Warm Air Heater manufactured by Worcester Engineering Co. Limited	1. The fireplace shall be installed, maintained and operated so as to minimise the emission of smoke at all times and in accordance with the manufacturer's instructions which—
	(a) in the case of installation instructions bear the reference "BC40.1.2 July 1983"; and
	(b) in the case of operating and maintenance instructions, bear the reference "BC40.OM2 July 1983",
	and, for the purpose of this condition, Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent, shall be treated as a fuel which may be

instructions.

used in accordance with those manufacturer's