SCHEDULE Article 2

Class of fireplace

Conditions

The Dunsley Yorkshire Stove manufactured by Dunsley Heat Limited.

- **1.** The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 5th August 1998 and bearing the reference "A/22160".
 - 2. No fuel shall be used other than—
 - (a) untreated dry wood;
 - (b) peat or peat briquettes with, in either case, less than 25 per cent moisture;
 - (c) Union Coal Briketts, manufactured by Rheinbraun AG of Germany and comprising lignite compressed into briquettes of approximately 15 centimetres in length with square ends and with a sulphur content not exceeding 1 per cent of the total weight;
 - (d) CPL Wildfire, manufactured by Coal Products Limited, Coventry, which comprise bituminous coal with a volatile content of 32 per cent to 36 per cent (as to approximately 96 per cent of the total weight) and a cold cure resin binder (as to the remaining weight); are manufactured from those constituents by a process involving roll-pressing; have an average weight of between 80 and 90 grammes or between 160 and 170 grammes; and have a sulphur content not exceeding 1.8 per cent of the total weight.

The I.D.L, M and H incinerators, manufactured by the Incinerator Doctor.

- **1.** The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions dated February 1999 and bearing the reference "I.D.E.I".
- 2. No fuel shall be used other than paper, cardboard, untreated dry wood, foliage, floor sweepings, and other waste containing no more than 20 per cent by weight of restaurant and cafeteria waste and less than 5 per cent by weight of coated paper, plastic or rubber waste.
- The Osier wood burning stove, manufactured by Reinhart von Zschock.
- **1.** The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 30th September 1997 and bearing the reference "CSC/OS/001".

1

α_1	c	A 1	
Class	ot	fireplace	

Corporation, USA.

Conditions

2. No fuel shall be used other than untreated dry wood.

The Trash X Incinerator, models TX25, TX35, TX50, TX35L and TX50L, manufactured by Roscoe Fabrications Limited.

1. The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 1998 and bearing the reference "TX/1998".

The Wood Stone Ovens, models WS-MS-4-W (Mt. Chuckanut), WS-MS-5-W (Mt. Adams), WS-MS-6-W (Mt. Baker) and WS-MS-7-W (Mt. Rainier), manufactured by the Wood Stone

- **2.** No fuel shall be used other than paper, card, untreated dry wood and cotton waste.
- **1.** The fireplaces shall be installed, maintained and operated in accordance with the manufacturer's instructions dated 8 September 1998 and bearing the reference "BPWS version 1".
- **2.** No fuel shall be used other than untreated dry wood.