

SCHEDULE 4

CORDLESS TELEPHONE APPARATUS

PART III

DESCRIPTIONS OF THE PRESCRIBED APPARATUS

Analogue Cordless Telephone Apparatus (CT1)

1. Apparatus consisting of a base station and one or more portable stations designed or adapted in accordance with MPT 1322–

- (a) to be used to send and receive voice or data messages to be conveyed over a telecommunication system to which the base station is connected; and
- (b) so as not to operate on more than one of the pairs of frequencies set out below at any one time–

<i>Channel No.</i>	<i>Base station transmission frequency</i>	<i>Portable station transmission frequency</i>
1	1642.00 kHz	47.45625 MHz
2	1662.00 kHz	47.46875 MHz
3	1682.00 kHz	47.48125 MHz
4	1702.00 kHz	47.49375 MHz
5	1722.00 kHz	47.50625 MHz
6	1742.00 kHz	47.51875 MHz
7	1762.00 kHz	47.53125 MHz or 47.44375 MHz
8	1782.00 kHz	47.54375 MHz

2. Apparatus consisting of a base station and one or more portable stations designed or adapted in accordance with MPT 1384–

- (a) to be used to send and receive voice or data messages to be conveyed over a telecommunication system to which the base station is connected; and
- (b) so as not to operate on more than one of the pair of frequencies set out below at any one time–

<i>Channel No.</i>	<i>Base station transmission frequency</i>	<i>Portable station transmission frequency</i>
1	31.0375 MHz	39.9375 MHz
2	31.0625 MHz	39.9625 MHz
3	31.0875 MHz	39.9875 MHz
4	31.1125 MHz	40.0125 MHz
5	31.1375 MHz	40.0375 MHz
6	31.1625 MHz	40.0625 MHz

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

<i>Channel No.</i>	<i>Base station transmission frequency</i>	<i>Portable station transmission frequency</i>
7	31.1875 MHz	40.0875 MHz
8	31.2125 MHz	40.1125 MHz

Analogue Cordless Telephone Extended Range Apparatus (Extended Range CT1)

3. Apparatus consisting of a base station and one or more portable stations designed or adapted in accordance with MPT 1371–

- (a) to be used to send and receive voice or data messages to be conveyed over a telecommunication system to which the base station is connected; and
- (b) so as to operate on either of the pairs of frequencies set out below–

<i>Channel No.</i>	<i>Base station transmission frequency</i>	<i>Portable station transmission frequency</i>
1	47.43125 MHz	77.51250 MHz
2	47.41875 MHz	77.55000 MHz

Digital Cordless Telephone Apparatus (CT2)

4. Apparatus conforming, at the time it is manufactured, to MPT 1334 or the Interim European Telecommunications Standard I-ETS 300 131 referred to in Part IV and consisting of one or more base stations and one or more portable stations designed or adapted–

- (a) to be used to send and receive voice or data messages or visual images in digitised packets in time division duplex mode bi-directionally to be conveyed over a telecommunication system to which the base station is connected; and
- (b) so as to operate in a 100 kHz channel within the frequency band 864.1–868.1 MHz.

Digital European Cordless Telecommunications Apparatus (DECT, also known as Digital Enhanced Telecommunications Apparatus)

5. Apparatus conforming, at the time it is manufactured, to the ETSI Technical Basis for Regulation TBR 006 referred to in Part IV(1) and consisting of one or more base stations, repeater stations and portable stations designed or adapted–

- (a) to be used to send and receive voice or data messages or visual images either directly between a base station and a portable station or between a base station and a portable station by relay through a repeater station in digitised packets in time division duplex mode bi-directionally to be conveyed over a telecommunication system to which the base station is connected; and
- (b) so as to operate within the frequency band 1880–1900 MHz(2).

For the purposes of this paragraph, “repeater station” means a station which relays the voice or data message or visual image between the base station and one or more portable stations.

(1) Council Recommendation 91/288/EEC of 3rd June 1991 (OJ No. L144, 8.6.91, p. 47) referred to the co-ordinated introduction of DECT into the European Community.

(2) Council Directive 91/287/EEC of 3rd June 1991 (OJ No. L144, 8.6.91, p. 45) designated the frequency band for the co-ordinated introduction of DECT into the European Community.

Document Generated: 2023-08-13

Status: *This is the original version (as it was originally made). This item of legislation is currently only available in its original format.*