## SCHEDULE 1

Regulations 4(1) and 6(5)

## Hand-Arm Vibration

#### **Commencement Information**

I1 Sch. 1 in force at 6.7.2005, see reg. 1

# Part I-Daily exposure to vibration

The daily exposure to vibration (A(8)) of a person is ascertained using the formula:

$$A(8) = a_{hv} \sqrt{\frac{T}{T_0}}$$

where:

 $a_{\rm hv}$  is the vibration magnitude, in metres per second squared (m/s<sup>2</sup>;);

T is the duration of exposure to the vibration magnitude  $a_{hv}$ ; and

 $T_0$  is the reference duration of 8 hours (28,800 seconds).

To avoid confusion between vibration magnitude and daily exposure to vibration, it is conventional to express daily exposure to vibration in  $m/s^2$  A(8).

The vibration magnitude,  $a_{hv}$ , is ascertained using the formula:

$$a_{\text{hv}} = \sqrt{a_{\text{hwx}}^2 + a_{\text{hwy}}^2 + a_{\text{hwz}}^2}$$

where:

 $a_{\text{hwx}}$ ,  $a_{\text{hwy}}$  and  $a_{\text{hwz}}$  are the root-mean-square acceleration magnitudes, in m/s<sup>2</sup>, measured in three orthogonal directions, x, y and z, at the vibrating surface in contact with the hand, and frequency-weighted using the weighting W<sub>h</sub>.

The definition for the frequency weighting W<sub>h</sub> is given in British Standard BS EN ISO 5349-1:2001.

Where both hands are exposed to vibration, the greater of the two magnitudes  $a_{\rm hv}$  is used to ascertain the daily exposure.

If the work is such that the total daily exposure consists of two or more operations with different vibration magnitudes, the daily exposure (A(8)) for the combination of operations is ascertained using the formula:

$$A(8) = \sqrt{\frac{1}{T_0} \sum_{i=1}^{n} a_{hvi}^2 T_i}$$

where:

*n* is the number of individual operations within the working day;

 $a_{\text{hvi}}$  is the vibration magnitude for operation i; and

 $T_i$  is the duration of operation i.

## Part II-Exposure to vibration averaged over one week

The exposure to vibration averaged over one week  $(A(8)_{\text{week}})$  is the total exposure occurring within a period of seven consecutive days, normalised to a reference duration of five 8-hour days (40 hours). It is ascertained using the formula:

$$A(8)_{\text{week}} = \sqrt{\frac{1}{5} \sum_{j=1}^{7} A(8)_{j}^{2}}$$

where:

A(8)j is the daily exposure for day j.

The exposure to vibration averaged over one week is for use only for the purposes of Regulation 6(5).

## SCHEDULE 2

Regulations 4(2) and 6(5)

## Whole-Body Vibration

## **Commencement Information**

I2 Sch. 2 in force at 6.7.2005, see reg. 1

# Part I-Daily exposure to vibration

The daily exposure to vibration (A(8)) of a person is ascertained using the formula:

$$A(8) = k \, a_{\rm w} \sqrt{\frac{T}{T_0}}$$

where:

 $a_{\rm w}$  is the vibration magnitude (root-mean-square frequency-weighted acceleration magnitude) in one of the three orthogonal directions, x, y and z, at the supporting surface;

T is the duration of exposure to the vibration magnitude  $a_{\rm w}$ ;

 $T_0$  is the reference duration of 8 hours (28,800 seconds); and

*k* is a multiplying factor.

To avoid confusion between vibration magnitude and daily exposure to vibration, it is conventional to express daily exposure to vibration in  $m/s^2$  A(8).

Daily exposure to vibration (A(8)) is evaluated separately for the x, y and z directions of vibration.

For horizontal vibration (x and y directions), k = 1.4 and  $a_w$  is obtained using the W<sub>d</sub> frequency weighting. For vertical vibration (z direction), k = 1.0 and  $a_w$  is obtained using the W<sub>k</sub> frequency weighting.

Definitions for the frequency weightings are given in International Standard ISO 2631-1:1997.

If the work is such that the total daily exposure consists of two or more operations with different vibration magnitudes, the daily exposure (A(8)) for the combination of operations is ascertained using the formula:

Changes to legislation: There are currently no known outstanding effects for the The Control of Vibration at Work Regulations 2005. (See end of Document for details)

$$A(8) = \sqrt{\frac{1}{T_0} \sum_{i=1}^{n} a_{wi}^2 T_i}$$

where:

n is the number of individual operations within the working day;  $a_{wi}$  is the vibration magnitude for operation i; and  $T_i$  is the duration of operation i.

# Part II-Exposure to vibration averaged over one week

The exposure to vibration averaged over one week  $(A(8)_{\text{week}})$  is the total exposure occurring within a period of seven consecutive days, normalised to a reference duration of five 8-hour days (40 hours). It is ascertained using the formula:

$$A(8)_{\text{week}} = \sqrt{\frac{1}{5} \sum_{j=1}^{7} A(8)_{j}^{2}}$$

where:

A(8)j is the daily exposure for day j.

The exposure to vibration averaged over one week is for use only for the purposes of Regulation 6(5).

**Changes to legislation:**There are currently no known outstanding effects for the The Control of Vibration at Work Regulations 2005.