

## SCHEDULE 2

### CLASSIFICATION AND MARKING OF AIRCRAFT AND DEALER CERTIFICATION Article 5(2)

#### **PART B**

##### Nationality and registration marks of aircraft registered in the United Kingdom

###### **General**

1.—(1) The nationality mark of the aircraft shall be the capital letter “G” in Roman character and the registration mark shall be a group of four capital letters in Roman character assigned by the CAA on the registration of the aircraft. The letters shall be without ornamentation and a hyphen shall be placed between the nationality mark and the registration mark.

(2) The nationality and registration marks shall be displayed to the best advantage, taking into consideration the constructional features of the aircraft and shall always be kept clean and visible.

(3) The letters constituting each group of marks shall be of equal height and they, and the hyphen, shall all be of the same single colour which shall clearly contrast with the background on which they appear.

(4) The nationality and registration marks shall also be inscribed on a fire-proof metal plate affixed in a prominent position—

- (a) in the case of a microlight aeroplane, either in accordance with sub-paragraph (c) or on the wing;
- (b) in the case of a balloon, on the basket or envelope; or
- (c) in the case of any other aircraft on the fuselage or car as the case may be.

(5) The nationality and registration marks shall be painted on the aircraft, or shall be affixed thereto by any other means ensuring a similar degree of permanence, in the manner specified in paragraphs 2 and 3 of this Part.

###### **Position and size of marks**

2.—(1) The position and size of marks on heavier than air aircraft (excluding kites) shall be as follows—

- (a) on the horizontal surfaces of the wings—
  - (i) on aircraft having a fixed wing surface, the marks shall appear on the lower surface of the wing structure and shall be on the port wing unless they extend across the whole surface of both wings. So far as is possible the marks shall be located equidistant from the leading and trailing edges of the wings. The tops of the letters shall be towards the leading edge of the wing;
  - (ii) the height of the letters shall be—
    - (aa) subject to sub-paragraph (bb), at least 50 centimetres;
    - (bb) if the wings are not large enough for the marks to be 50 centimetres in height, marks of the greatest height practicable in the circumstances;
- (b) on the fuselage (or equivalent structure) and vertical tail surfaces—
  - (i) the marks shall also appear either—

**Changes to legislation:** The Air Navigation Order 2005, PART B is up to date with all changes known to be in force on or before 06 June 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes

- (aa) on each side of the fuselage (or equivalent structure), and shall, in the case of fixed wing aircraft be located between the wings and the horizontal tail surface; or
  - (bb) on the vertical tail surfaces;
  - (ii) when located on a single vertical tail surface, the marks shall appear on both sides. When located on multi-vertical tail surfaces, the marks shall appear on the outboard sides of the outer-surfaces. Subject to sub-paragraphs (iv) and (v), the height of the letters constituting each group of marks shall be at least 30 centimetres;
  - (iii) if one of the surfaces authorised for displaying the required marks is large enough for those marks to be 30 centimetres in height (whilst complying with sub-paragraph (v)) and the other is not, marks of 30 centimetres in height shall be placed on the largest authorised surface;
  - (iv) if neither authorised surface is large enough for marks of 30 centimetres in height (whilst complying with sub-paragraph (v)), marks of the greatest height practicable in the circumstances shall be displayed on the larger of the two authorised surfaces;
  - (v) marks on the vertical tail surfaces shall be such as to leave a margin of at least 5 centimetres along each side of the vertical tail surface;
  - (vi) on rotary wing aircraft where owing to the structure of the aircraft the greatest height practicable for the marks on the side of the fuselage (or equivalent structure) is less than 30 centimetres, the marks shall also appear on the lower surface of the fuselage as close to the line of symmetry as is practicable, and shall be placed with the tops of the letters towards the nose. The height of the letters constituting each group of marks shall be:
    - (aa) subject to sub-paragraph (bb), at least 50 centimetres; or
    - (bb) if the lower surface of the fuselage is not large enough for the marks to be of 50 centimetres in height, marks of the greatest height practicable in the circumstances;
  - (c) wherever in this paragraph marks of the greatest height practicable in the circumstances are required, that height shall be such as is consistent with compliance with paragraph 3 of this Part.
- (2) The position and size of marks on airships and free balloons shall be as follows—
- (a) in the case of airships the marks shall be placed on each side of the airship. They shall be placed horizontally either on the hull near the maximum cross-section of the airship or on the lower vertical stabiliser;
  - (b) in the case of free balloons, the marks shall be in two places on diametrically opposite sides of the balloon;
  - (c) in the case of both airships and free balloons the side marks shall be so placed as to be visible from the sides and from the ground. The height of the letters shall be at least 50 centimetres.

### **Width, spacing and thickness of marks**

- 3.—(1) For the purposes of this paragraph—
- (a) “standard letter” shall mean any letter other than the letters I, M and W;
  - (b) the width of each standard letter and the length of the hyphen between the nationality mark and the registration mark shall be two thirds of the height of a letter;

**Changes to legislation:** *The Air Navigation Order 2005, PART B is up to date with all changes known to be in force on or before 06 June 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations. (See end of Document for details) View outstanding changes*

- (c) the width of the letters M and W shall be neither less than two thirds of their height nor more than their height; and
  - (d) the width of the letter I shall be one sixth of the height of the letter.
- (2) The thickness of the lines comprising each letter and hyphen shall be one sixth of the height of the letters forming the marks.
- (3) Each letter and hyphen shall be separated from the letter or hyphen which it immediately precedes or follows by a space equal to either one quarter or one half of the width of a standard letter. Each such space shall be equal to every other such space within the marks.

**Changes to legislation:**

The Air Navigation Order 2005, PART B is up to date with all changes known to be in force on or before 06 June 2024. There are changes that may be brought into force at a future date. Changes that have been made appear in the content and are referenced with annotations.

[View outstanding changes](#)

**Changes and effects yet to be applied to :**

- Instrument by [S.I. 2006/1384 reg 16](#)
- Instrument by [S.I. 2006/1384 reg 17](#)
- Instrument appl in pt (mod) by [S.I. 2008/25 art 4 schedule](#)
- Part 10 (arts 107 - 120) subst by [S.I. 2009/1742 arts 23](#)

**Changes and effects yet to be applied to the whole Instrument associated Parts and Chapters:**

Whole provisions yet to be inserted into this Instrument (including any effects on those provisions):

- art 28A added (31.1.2008) by [S.I. 2007/3467 arts 25](#)
- art 31A added (31.1.2008) by [S.I. 2007/3467 arts 25](#)
- arts 32A - 32C added (31.1.2008) by [S.I. 2007/3467 arts 25](#)
- art 52A added by [S.I. 2007/274 art 4](#)
- art 54A added by [S.I. 2007/274 art 4](#)
- art 61A added (31.1.2008) by [S.I. 2007/3467 arts 211](#)
- art 62A added by [S.I. 2007/274 art 5](#)
- art 72A added by [S.I. 2007/274 art 4](#)
- art 141A added by [S.I. 2006/2316 art 2](#)
- arts 144A-144C added by [S.I. 2006/1384 reg 14](#)