

SCHEDULE 5

Regulation 14(d) and (e)

MAXIMUM PERMISSIBLE ERRORS APPLICABLE TO AN
AUTOMATIC CATCHWEIGHER FOR USE FOR TRADE

Table 1

Maximum permissible errors for automatic operation

<i>Net Load (m) in verification scale intervals (e)</i>				<i>Maximum permissible errors</i>
Y(I)	Y(II)	Y(a)	Y(b)	
$0 < m \leq 50\,000$	$0 < m \leq 5\,000$	$0 < m \leq 500$	$0 < m \leq 50$	$\pm 2 e$
$50\,000 < m \leq 200\,000$	$5\,000 < m \leq 20\,000$	$500 < m \leq 2000$	$50 < m \leq 200$	$\pm 3 e$
$200\,000 < m$	$20\,000 < m \leq 100\,000$	$2\,000 < m \leq 10\,000$	$200 < m \leq 1\,000$	$\pm 4 e$

Table 2

Maximum permissible errors for static weighing in non-automatic operation

<i>Net Load (m) in verification scale intervals (e)</i>				<i>Maximum permissible errors</i>
Y(I)	Y(II)	Y(a)	Y(b)	
$0 < m \leq 50\,000$	$0 < m \leq 5\,000$	$0 < m \leq 500$	$0 < m \leq 50$	$\pm 1 e$
$50\,000 < m \leq 200\,000$	$5\,000 < m \leq 20\,000$	$500 < m \leq 2000$	$50 < m \leq 200$	$\pm 2 e$
$200\,000 < m$	$20\,000 < m \leq 100\,000$	$2\,000 < m \leq 10\,000$	$200 < m \leq 1\,000$	$\pm 3 e$