

SCHEDULE 8

Product information

Product information sheet

1. The product information sheet must contain the information set out in Table 6.

Table 6

Product information sheet

Supplier's name or trade mark:			
Supplier's address:			
Model identifier:			
Type of light source:			
Lighting technology used:	[HL/LFL T5 HE/LFL T5 HO/CFLni/other FL/HPS/MH/other HID/LED/OLED/mixed/other]	Non-directional or directional:	[NDLS/DLS]
Light source cap-type (or other electric interface)	[Free text]		
Mains or non-mains:	[MLS/NMLS]	Connected light source (CLS):	[yes/no]
Colour-tuneable light source:	[yes/no]	Envelope:	[no/second/non-clear]
High luminance light source:	[yes/no]		
Anti-glare shield:	[yes/no]	Dimmable:	[yes/only with specific dimmers/no]
Product parameters			
Parameter	Value	Parameter	Value
General product parameters			
Energy consumption in on-mode (kWh/1,000 h) rounded up to the nearest integer	x	Energy efficiency class	[A/B/C/D/E/F/G]
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	x in [sphere/wide cone/narrow cone]	Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the	[x/x...x/x or x (or x...)]

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

		nearest 100K, that can be set	
On-mode power (P_{on}), expressed in W	x.x	Standby power (P_{sb}), expressed in W and rounded to the second decimal point	x.xx
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal point	x.xx	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	[x/x...x]
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	x	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	x	
	Depth	x	
Claim of equivalent power (see paragraph [2(1) and (2)])	[yes/-]	If yes, equivalent power (W)	x
		Chromaticity coordinates (x and y)	0.xxx 0.xxx
Parameters for directional light sources:			
Peak luminous intensity (cd)	x	Beam angle in degrees, or the range of beam angles that can be set	[x/x...x]
Parameters for LED and OLED light sources:			
R9 colour rendering index value	x	Survival factor	x.xx
The lumen maintenance factor	x.xx		
Parameters for LED and OLED mains light sources:			
Displacement factor ($\cos \phi_1$)	x.xx	Colour consistency in McAdam ellipses	x
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2(3)]).	[yes/-]	If yes then replacement claim (W)	x

Status: This is the original version (as it was originally made). This item of legislation is currently only available in its original format.

Flicker metric (Pst LM)	x.x	Stroboscopic effect metric (SVM)	x.x
-------------------------	-----	----------------------------------	-----