



CYNULLIAD CENEDLAETHOL CYMRU

OFFERYNNAU STATUDOL

2006 Rhif 2979 (Cy.270)

AER GLÂN, CYMRU

Rheoliadau Ardaloedd Rheoli Mwg
(Tanwyddau Awdurdodedig)
(Cymru) 2006

NODYN ESBONIADOL

(Nid yw'r nodyn hwn yn rhan o'r Rheoliadau)

Mae adran 20 o Ddeddf Aer Glân 1993 ("Deddf 1993") yn darparu, pan fo simnai naill ai-

- (a) yn simnai adeilad; neu
- (b) yn simnai sy'n gwasanaethu ffwrnais bwyler sefydlog neu beiriannau diwydiannol,

fod meddiannydd yr adeilad, neu (yn ôl y digwydd) y person sy'n meddu ar y bwyler neu'r peiriannau yn euog o dramgydd os yw'r simnai mewn ardal rheoli mwg ac yn gollwng mwg. Er hynny, mae'n amddiffyniad os gellir profi yr achoswyd y gollyngiad honedig drwy ddefnyddio tanwydd awdurdodedig yn unig a dim byd arall.

Yng Nghymru, ystyr "tanwydd awdurdodedig" yw tanwydd y datgenir ei fod wedi'i awdurdodi drwy Reoliadau a wnaed gan Gynulliad Cenedlaethol Cymru.

Mae'r rheoliadau hyn yn pennu pob tanwydd sydd ar hyn o bryd wedi'i awdurdodi i'w ddefnyddio yng Nghymru at ddibenion adran 20 o Ddeddf 1993. Maent yn cydgrynhoi ac yn disodli Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2001 (OS 2001/3762 (Cy.311)), Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Diwygio) (Cymru) 2001 (OS 2001/3996 (Cy.327)) a Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Diwygio) (Cymru) 2002 (OS 2002/3160) (Cy.295)).

NATIONAL ASSEMBLY FOR WALES

STATUTORY INSTRUMENTS

2006 No. 2979 (W.270)

CLEAN AIR, WALES

The Smoke Control Areas
(Authorised Fuels) (Wales)
Regulations 2006

EXPLANATORY NOTE

(This note is not part of the Regulations)

Section 20 of the Clean Air Act 1993 ("the 1993 Act") provides that where a chimney is either-

- (a) a chimney of a building; or
- (b) a chimney serving the furnace of a fixed boiler or industrial plant,

then the occupier of the building or (as the case may be) the person having possession of the boiler or plant is guilty of an offence if the chimney is in a smoke control area and emits smoke. However, it is a defence to prove that the alleged emission was caused solely by the use of an authorised fuel.

In Wales, an authorised fuel means a fuel declared to be authorised by Regulations made by the National Assembly for Wales.

These regulations specify all fuels which are currently authorised for use in Wales for the purposes of Section 20 of the 1993 Act. They consolidate and replace the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2001 (SI 2001/3762 (W.311)), Smoke Control Areas (Authorised Fuels) (Amendment) (Wales) Regulations 2001 (SI 2001/3996 (W.327)) and Smoke Control Areas (Authorised Fuels) (Amendment) (Wales) Regulations 2002 (SI 2002/3160) (W.295)).

Mae'r rhan fwyaf o'r tanwyddau yn y Rheoliadau hyn wedi bod yn danwyddau awdurdodedig o'r blaen. Serch hynny, mae'r disgrifiad o frics glo Ancit, brics glo Phurnacite a brics glo Taybright wedi'i ddiwygio i adlewyrchu newidiadau yn y modd y maent yn cael eu gweithgynhyrchu.

Mae brics glo Briteflame, Duraflame Firelogs, brics glo Multiheat, brics glo Stoveheat Premium, boncyffion tân ZIP Cracklelog, boncyffion tân ZIP Crackle-log, boncyffion tân ZIP Crackling Log, a ZIP Firelogs a weithgynhyrchir gan Allspan B.V. a Woodflame Moerdijk B.V. wedi'u hawdurdodi i'w defnyddio am y tro cyntaf.

Mae darpariaeth arbed (gweler Rheoliad 3(2)) yn sicrhau y bydd stociau tanwyddau awdurdodedig a weithgynhyrchwyd cyn y dyddiad y daeth y Rheoliadau hyn i rym yn parhau i fod yn danwyddau awdurdodedig. Bydd defnyddio'r tanwyddau hyn yn parhau i fod yn amddiffyniad felly yn erbyn unrhyw honiad bod mwg wedi'i ollwng yn anghyfreithlon, hynny yw, yn groes i adran 20 o Ddeddf 1993.

Most of the fuels in these Regulations have previously been authorised fuels. However, the description of Ancit briquettes, Phurnacite briquettes and Taybright briquettes has been revised to reflect changes in their manufacture.

Briteflame briquettes, Duraflame Firelogs, Multiheat briquettes, Stoveheat Premium briquettes, ZIP Cracklelog firelogs, ZIP Crackle-log firelogs, ZIP Crackling Log firelogs, and ZIP Firelogs manufactured by Allspan B.V. and Woodflame Moerdijk B.V. are authorised for use for the first time.

A savings provision (see Regulation 3(2)) ensures that stocks of authorised fuels manufactured before these Regulations came into force will continue to be authorised fuels. Use of such fuels will therefore continue to provide a defence to any allegation of an unlawful emission of smoke contrary to Section 20 of the 1993 Act.

2006 Rhif 2979 (Cy.270)**AER GLÂN, CYMRU****Rheoliadau Ardaloedd Rheoli Mwg
(Tanwyddau Awdurdodedig)
(Cymru) 2006***Wedi'u gwneud**14 Tachwedd 2006**Yn dod i rym**24 Tachwedd 2006*

Mae Cynulliad Cenedlaethol Cymru ("y Cynulliad Cenedlaethol"), drwy arfer y pwerau a roddwyd i'r Ysgrifennydd Gwladol gan adrannau 20(6) a 63(1) o Ddeddf Aer Glân 1993⁽¹⁾ ac a freiniwyd bellach yn y Cynulliad Cenedlaethol⁽²⁾, drwy hyn yn gwneud y Rheoliadau a ganlyn:

Enwi, cychwyn a chymhwysyo

1.-(1) Enw'r Rheoliadau hyn yw Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2006 a deuant i rym ar 24 Tachwedd 2006.

(2) Mae'r Rheoliadau hyn yn gymwys o ran Cymru.

Tanwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993

2. Datgenir bod glo caled, glo lled-galed, trydan, nwy, gloeau stêm isel eu hanweddolrwydd a'r tanwyddau a ddisgrifir yn Atodlen 1 yn danwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993.

Dirymiadau ac arbedion

3.-(1) Mae'r Rheoliadau a restrir yn Atodlen 2 wedi'u dirymu.

(2) Bydd unrhyw danwydd a weithgynhyrchwyd cyn i'r Rheoliadau hyn ddod i rym, ac a oedd yn danwydd awdurdodedig adeg ei weithgynhyrchu, yn parhau i fod yn danwydd awdurdodedig er bod y Rheoliadau a restrir yn Atodlen 2 wedi'u dirymu.

2006 No. 2979 (W.270)**CLEAN AIR, WALES****The Smoke Control Areas
(Authorised Fuels) (Wales)
Regulations 2006***Made**14 November 2006**Coming into force**24 November 2006*

The National Assembly for Wales ("the National Assembly") in exercise of the powers conferred upon the Secretary of State by sections 20(6) and 63(1) of the Clean Air Act 1993⁽¹⁾ and now vested in the National Assembly⁽²⁾ hereby makes the following Regulations:

Title, commencement and application

1.-(1) The title of these Regulations is the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2006 and they come into force on 24 November 2006.

(2) These Regulations apply in relation to Wales.

Authorised fuels for the purposes of Part III of the Clean Air Act 1993

2. Anthracite, semi-anthracite, electricity, gas, low volatile steam coals and the fuels described in Schedule 1 are declared to be authorised fuels for the purposes of Part III of the Clean Air Act 1993.

Revocations and savings

3.-(1) The Regulations listed in Schedule 2 are revoked.

(2) Any fuel manufactured before the coming into force of these Regulations which was an authorised fuel when it was manufactured will continue to be an authorised fuel notwithstanding the revocation of the Regulations listed in Schedule 2.

(1) 1993 p.11.

(2) Trosglwyddwyd swyddogaethau perthnasol yr Ysgrifennydd Gwladol i'r Cynulliad Cenedlaethol gan erthygl 2 o Orchymyn Cynulliad Cenedlaethol Cymru (Trosglwyddo Swyddogaethau) 1999, ac Atodlen 1 iddo (O.S. 1999/672).

(1) 1993 c.11.

(2) The relevant powers of the Secretary of State were transferred to the National Assembly by Article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672).

Llofnodwyd ar ran Cynulliad Cenedlaethol Cymru o dan adran 66(1) o Ddeddf Llywodraeth Cymru 1998(1)

14 Tachwedd 2006

D. Elis-Thomas

Llywydd y Cynulliad Cenedlaethol

Signed on behalf of the National Assembly for Wales under section 66(1) of the Government of Wales Act 1998(1)

14 November 2006

The Presiding Officer of the National Assembly

(1) 1998 p.38.

(1) 1998 c.38.

ATODLEN 1

Rheoliad 2

TANWYDDAU AWDURDODEDIG

1. Brics glo Aimcor Excel, a weithgynhyrchrir gan Applied Industrial Materials UK Limited yn Newfield, County Durham-

- (a) sy'n cynnwys golosg petrolewm (sef 60 i 75 y cant o'r cyfanswm pwysau), glo isel ei anweddolwydd a golosg adweithiol (sef 20 i 25 y cant o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu pan fo'n oer (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwys 73 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

2. Brics glo Aimcor Pureheat, a weithgynhyrchrir gan Applied Industrial Materials UK Limited yn Immingham, North East Lincolnshire -

- (a) sy'n cynnwys glo caled (sef rhyw 60 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 25 y cant o'r cyfanswm pwysau) a rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 250°C;
- (c) yn frics glo ar siâp gobennydd gydag un llinell wedi'i hindentio ar un ochr a dwy linell wedi'u hindentio ar yr ochr arall ac sy'n pwys 75 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

3. Brics glo Ancit, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire -

- (a) sy'n cynnwys glo caled (sef rhyw 60 i 95 y cant o'r cyfanswm pwysau), golosg petrolewm (hyd at ryw 30 y cant o'r cyfanswm pwysau), glo meddal (hyd at ryw 15 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp clustog heb eu marcio ac sy'n pwys 48 gram ar gyfartaledd; ac

SCHEDULE 1

Regulation 2

AUTHORISED FUELS

1. Aimcor Excel briquettes, manufactured by Applied Industrial Materials UK Limited at Newfield, County Durham, which-

- (a) comprise petroleum coke (as to 60 to 75 per cent of the total weight), low volatile coal and reactive coke (as to 20 to 25 per cent of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 73 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

2. Aimcor Pureheat briquettes, manufactured by Applied Industrial Materials UK Limited at Immingham, North East Lincolnshire, which-

- (a) comprise anthracite (as to approximately 60 per cent of the total weight), petroleum coke (as to approximately 25 per cent of the total weight) and binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are pillow-shaped briquettes with a single line indentation on one side and a double line indentation on the reverse side and have an average weight of 75 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

3. Ancit briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite (as to approximately 60 to 95 per cent of the total weight), petroleum coke (up to approximately 30 per cent of the total weight), bituminous coal (up to approximately 15 per cent of the total weight) and a molasses and phosphoric acid binder or an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked cushion-shaped briquettes with an average weight of 48 grammes; and

(ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

4. Brics glo Black Diamond Gem, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys llwch glo caled (sef 20 i 30 y cant o'r cyfanswm pwysau), golosg petrolewm (sef 40 i 45 y cant o'r cyfanswm pwysau), glo meddal (sef 12 i 22 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp gobennydd wedi'u marcio â dwy linell gyfochrog sydd wedi'u hindentio ac yn rhedeg yn lledredol o amgylch y fricsen ac sy'n pwysu 160 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

5. Bord na Móna Firelogs, a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Gweriniaeth Iwerddon-

- (a) sy'n cynnwys cwyr hydrin (sef rhyw 55 y cant o'r cyfanswm pwysau) a blawd llif pren caled (sef rhyw 45 y cant o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses triniaeth wres ac allwthio;
- (c) sy'n fonyffion tân, rhyw 255 milimetru eu hyd a 75 milimetru eu diamedr, a chyda rhigolau ar hyd un wyneb hydredol, ac sy'n pwysu 1.3 cilogram (net) ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 0.1 y cant o sylffwr o'r cyfanswm pwysau.

6. Brics glo Bord na Móna Firepak (sy'n cael eu marchnata hefyd fel brics glo Arigna Special) a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Gweriniaeth Iwerddon-

- (a) sy'n cynnwys glo caled (sef rhyw 50 y cant o'r cyfanswm pwysau), golosg petrolewm (sef 20 i 40 y cant o'r cyfanswm pwysau), glo meddal (sef 10 i 30 y cant o'r cyfanswm pwysau) a rhwymwr sydd wedi'i seilio ar starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwysu 50 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

(d) have a sulphur content not exceeding 2 per cent of the total weight.

4. Black Diamond Gem briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite duff (as to 20 to 30 per cent of the total weight), petroleum coke (as to 40 to 45 per cent of the total weight), bituminous coal (as to 12 to 22 per cent of the total weight) and molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with two parallel indented lines running latitudinally around the briquette and have an average weight of 160 grammes; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

5. Bord na Móna Firelogs, manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Republic of Ireland, which-

- (a) comprise slack wax (as to approximately 55 per cent of the total weight) and hardwood sawdust (as to approximately 45 per cent of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs, approximately 255 millimetres in length and 75 millimetres in diameter, and with grooves along one longitudinal face, and have an average weight of 1.3 kilogrammes (net); and
- (d) have a sulphur content not exceeding 0.1 per cent of the total weight.

6. Bord na Móna Firepak briquettes (also marketed as Arigna Special coal briquettes), manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Republic of Ireland, which-

- (a) comprise anthracite (as to approximately 50 per cent of the total weight), petroleum coke (as to 20 to 40 per cent of the total weight), bituminous coal (as to 10 to 30 percent of the total weight) and starch based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 50 grammes; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

7. Brics glo Briteflame, a weithgynhyrchir gan Maxibrite Limited ar Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf-

- (a) sy'n cynnwys 10 i 15 y cant o lo meddal, 10 i 15 y cant o olosg petrolewm, 70 i 80 y cant o lwch glo caled a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 260°C;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwysgo 140 gram ar gyfartaledd fesul bricsen; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.9 y cant o sylffwr pan fyddant yn sych.

8. Bryant and May Firelogs a weithgynhyrchir gan Swedish Match yn Kostenetz, Bwgaria-

- (a) sy'n cynnwys cwyr paraffin (sef rhyw 50 y cant o'r cyfanswm pwysau), pren poplys mäl (sef rhyw 25 y cant o'r cyfanswm pwysau), blawd gwenith (sef rhyw 15 y cant o'r cyfanswm pwysau), solidau cyneudwy ar wasgar mewn cwyr paraffin ar ffurf jel (sef rhyw 1 y cant o'r cyfanswm pwysau) a dŵr, cyfryngau chwyddo a chadwolyn (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys eu hallwthio;
- (c) y mae iddynt drawstoriadau cwadrant o ryw 80 milimetatr o radiws, ac sy'n rhyw 265 milimetatr o hyd gyda stribyn cynnau ar hyd un ymyl, ac sy'n pwysgo rhyw 1.15 cilogram; ac
- (ch) nad ydynt yn cynnwys mwy na 0.1 y cant o sylffwr o'r cyfanswm pwysau.

9. Brics glo Charglow, a weithgynhyrchir gan Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Gwlad Pwyl-

- (a) sy'n cynnwys golosg glo meddal (sef rhyw 45 i 95 y cant o'r cyfanswm pwysau), glo caled (sef rhyw 0 i 20 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 0 i 20 y cant o'r cyfanswm pwysau), glo meddal (sef rhyw 0 i 10 y cant o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 110°C;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwysgo 100 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

7. Briteflame briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taff, which-

- (a) comprise 10 to 15 per cent bituminous coal, 10 to 15 per cent petroleum coke, 70 to 80 per cent anthracite duff and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260 degrees C;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 140 grammes per briquette; and
- (d) have a sulphur content not exceeding 1.9 per cent sulphur on a dry basis.

8. Bryant and May Firelogs manufactured by Swedish Match at Kostenetz, Bulgaria, which-

- (a) comprise paraffin wax (as to approximately 50 per cent of the total weight), ground poplar wood (as to approximately 25 per cent of the total weight), wheatflour (as to approximately 15 per cent of the total weight), ignitable solids dispersed in gelled paraffin wax (as to approximately 1 per cent of the total weight) and water, swelling agents and preservative (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are of quadrant cross sections with a radius of approximately 80 millimetres, and length approximately 265 millimeteres with an ignition strip along one edge, and having an approximate weight of 1.15 kilogrammes; and
- (d) have a sulphur content not exceeding 0.1 per cent of the total weight.

9. Charglow briquettes, manufactured by Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Poland, which-

- (a) comprise bituminous coal char (as to approximately 45 per cent to 95 per cent of the total weight), anthracite (as to approximately 0 per cent to 20 per cent of the total weight), petroleum coke (as to approximately 0 per cent to 20 per cent of the total weight), bituminous coal (as to approximately 0 per cent to 10 per cent of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing and heat treatment at about 110° C;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 100 grammes; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

10. Coalite a weithgynhyrchrir gan Coalite Products Limited yn Bolsover, yn ymyl Chesterfield, Derbyshire ac yn Grimethorpe, South Yorkshire drwy ddefnyddio proses carboneiddio tymheredd isel.

11. Golosg a weithgynhyrchrir gan-

- (a) Coal Products Limited yn Cwm Coking Works, Llanilltud Faerdref, Pontypridd, Rhondda Cynon Taf, a'i werthu fel "Sunbrite";
- (b) Monckton Coke & Chemical Company Limited yn Royston, yn ymyl Barnsley, South Yorkshire a'i werthu fel "Sunbrite" neu "Monckton Boiler Beans";
- (c) Corus UK Limited yn Teesside Works, Redcar & Cleveland a'i werthu fel "Redcar Coke Nuts (Doubles)"; a
- (ch) Coal Products Limited yn Cwm Coking Works, Llanilltud Faerdref, Pontypridd, Rhondda Cynon Taf a'i werthu fel "Cwm Coke Doubles".

12. Cosycoke (sy'n cael ei farchnata hefyd fel Lionheart Crusader neu Sunbrite Plus) a weithgynhyrchrir gan Monckton Coke & Chemical Company Limited yn Royston, yn ymyl Barnsley, South Yorkshire ac Aimcor Supercoke (sydd hefyd yn cael ei farchnata fel Supercoke), a weithgynhyrchrir gan M & G Fuels Limited yn Hartlepool Docks, Hartlepool, sydd ym mhob achos-

- (a) yn cynnwys golosg caled o faint penodol (sef rhyw 45 i 65 y cant o'r cyfanswm pwysau) a golosg petrolewm o faint penodol (sef gweddill y pwysau);
- (b) wedi'i weithgynhyrchu o'r cyfansoddion hynny drwy eu cyfuno;
- (c) o hapsiapiau heb eu marcio; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

13. Brics glo Dragonbrite, a weithgynhyrchrir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf-

- (a) sy'n cynnwys llwch y tŵr (sef rhyw 95 y cant o gyfanswm y pwysau) a rhwymwr wedi ei seilio ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo siâp gobennydd wedi eu marcio â'r llythyren "T" ar un ochr ac sy'n pwysu 50 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1 y cant o sylffwr o'r cyfanswm pwysau.

14. Brics glo Dragonbrite, a weithgynhyrchrir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf-

- (a) sy'n cynnwys llwch y tŵr (sef rhyw 95 y cant

10. Coalite manufactured by Coalite Products Limited at Bolsover, near Chesterfield, Derbyshire and at Grimethorpe, South Yorkshire using a low temperature carbonisation process.

11. Coke manufactured by-

- (a) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taff, and sold as "Sunbrite";
- (b) Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire and sold as "Sunbrite" or "Monckton Boiler Beans";
- (c) Corus UK Limited at Teesside Works, Redcar & Cleveland and sold as "Redcar Coke Nuts (Doubles)"; and
- (d) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taff and sold as "Cwm Coke Doubles".

12. Cosycoke (also marketed as Lionheart Crusader or Sunbrite Plus) manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire and Aimcor Supercoke (also marketed as Supercoke), manufactured by M & G Fuels Limited at Hartlepool Docks, Hartlepool, which in each case-

- (a) comprise sized hard coke (as to approximately 45 to 65 per cent of the total weight) and sized petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by blending;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

13. Dragonbrite briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taff which-

- (a) comprise tower duff (as to approximately 95 per cent of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are pillow-shaped briquettes marked with the letter "T" on one side and have an average weight of 50 grammes; and
- (d) have a sulphur content not exceeding 1 per cent of the total weight.

14. Dragonglow briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf, which-

- (a) comprise tower duff (as to approximately 95

- (o) gyfanswm y pwysau) a rhwymwr wedi ei seilio ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwysu 100 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1 y cant o sylffwr o'r cyfanswm pwysau.

15. Duraflame Firelogs, a weithgynhyrchir gan Paramelt B.V., Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, Yr Iseldiroedd-

- (a) sy'n cynnwys cwyd petrolewm sydd wedi'i seilio ar fwynau (sef rhyw 55 y cant o'r cyfanswm pwysau) a ffibr pren caled mât (sef rhyw 45 y cant o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses triniaeth wres ac allwthio;
- (c) sy'n fonyffion tân rhyw 320 milimetru eu hyd, 90 milimetru eu huchder a 85 milimetru eu lled, yn pwysu 1.45 cilogram ar gyfartaledd fesul boncyff tân; ac
- (ch) nad ydynt yn cynnwys mwy na 0.1 y cant o sylffwr o'r cyfanswm pwysau.

16. Brics glo Ecobrite, a weithgynhyrchir gan Arigna Fuels Limited yn Arigna, Carrick-on-Shannon, County Roscommon, Gweriniaeth Iwerddon-

- (a) sy'n cynnwys gronynnau glo caled (sef rhyw 96 y cant o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 250°C;
- (c) sy'n frics glo siâp gobennydd heb eu marcio mewn dau faint sydd, ar gyfartaledd, yn pwysu 37 gram yn achos y maint lleiaf a 48 gram yn achos y maint mwyaf; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

17. Brics glo Extracite, a weithgynhyrchir gan Sophia-Jacoba Handelsgesellschaft mbH yn Hückelhoven, Yr Almaen-

- (a) sy'n cynnwys llwch glo caled (sef rhyw 95.5 y cant o'r cyfanswm pwysau) a lleisw amoniwm lignosylffonad yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 260°C;
- (c) sy'n frics glo ariannaidd siâp clustog â'r llythrennau "S" a "J" wedi'u marcio arnynt ac sy'n pwysu 40 gram ar gyfartaledd; ac

per cent of the total weight) and a resin-based binder (as to the remaining weight);

- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 100 grammes; and
- (d) have a sulphur content not exceeding 1 per cent of the total weight.

15. Duraflame Firelogs, manufactured by Paramelt B.V., Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, The Netherlands, which-

- (a) comprise mineral-based petroleum wax (as to approximately 55 per cent of the total weight) and ground hardwood fibre (as to approximately 45 per cent of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs approximately 320 millimetres in length, 90 millimetres high and 85 millimetres wide and have an average weight of 1.45 kilogrammes per firelog; and
- (d) have a sulphur content not exceeding 0.1 per cent of the total weight.

16. Ecobrite briquettes, manufactured by Arigna Fuels Limited at Arigna, Carrick-on-Shannon, County Roscommon, Republic of Ireland, which-

- (a) comprise anthracite fines (as to approximately 96 per cent of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are unmarked pillow-shaped briquettes in two sizes having an average weight of 37 grammes for the smaller size and 48 grammes for the larger size; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

17. Extracite briquettes, manufactured by Sophia-Jacoba Handelsgesellschaft mbH at Hückelhoven, Germany, which-

- (a) comprise anthracite duff (as to approximately 95.5 per cent of the total weight) and ammonium lignosulphonate lye as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are cushion-shaped briquettes with a silvery appearance and are marked with the letters "S" and "J" and have an average weight of 40 grammes; and

(ch) sy'n cynnwys rhyw 1.2 y cant o sylffwr o'r cyfanswm pwysau.

18. Brics glo Fireglo, a weithgynhyrchrir gan Les Combustibles de Normandie yn Caen, Ffrainc, a chan La Société Rouennaise de Défumage yn Rouen, Ffrainc-

- (a) sy'n cynnwys llychau Cymreig wedi'u golchi (sef rhyw 92 y cant o'r cyfanswm pwysau) a rhwymwr pyg glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyt o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 330°C;
- (c) sy'n siâp ofoid â thair llinell ar un ochr a'r ochr arall yn llyfn ac sy'n pwysu 30 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 0.8 y cant o sylffwr o'r cyfanswm pwysau.

19. Brics glo Homefire, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys gronynnau glo caled (sef rhyw 40 i 70 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 20 i 45 y cant o'r cyfanswm pwysau), cols (sef rhyw 0 i 10 y cant o'r cyfanswm pwysau), glo meddal (sef rhyw 5 i 30 y cant o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyt o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sydd, fel brics glo gorffenedig, yn cynnwys nid llai na 9 y cant ac nid mwy na 15 y cant o fater anwedol o'r cyfanswm pwysau pan fyddant yn sych;
- (ch) sy'n frics glo chweochrog heb eu marcio ac sy'n pwysu 140 gram ar gyfartaledd; a
- (d) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

20. Homefire Ovals, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys llwch glo caled (sef rhyw 57 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 17 y cant o'r cyfanswm pwysau), glo meddal (sef rhyw 13 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyt o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp gobennydd wedi'u marcio â dwy linell gyfochrog sydd wedi'u hindentio ac

(d) have a sulphur content of approximately 1.2 per cent of the total weight.

18. Fireglo briquettes, manufactured by Les Combustibles de Normandie at Caen, France, and by La Société Rouennaise de Défumage at Rouen, France, which-

- (a) comprise washed Welsh duffs (as to approximately 92 per cent of the total weight) and coal pitch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 330°C;
- (c) are ovoids with three lines on one side and are smooth on the other side and have an average weight of 30 grammes; and
- (d) have a sulphur content not exceeding 0.8 per cent of the total weight.

19. Homefire briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite fines (as to approximately 40 to 70 per cent of the total weight), petroleum coke (as to approximately 20 to 45 per cent of the total weight), char (as to approximately 0 to 10 per cent of the total weight), bituminous coal (as to approximately 5 to 30 per cent of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) have a volatile matter content in the finished briquette of neither less than 9 nor more than 15 per cent of the total weight on a dry basis;
- (d) are unmarked hexagonal briquettes and have an average weight of 140 grammes; and
- (e) have a sulphur content not exceeding 2 per cent of the total weight.

20. Homefire ovals, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite duff (as to approximately 57 per cent of the total weight), petroleum coke (as to approximately 17 per cent of the total weight), bituminous coal (as to approximately 13 per cent of the total weight) and molasses and phosphoric acid as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the

yn rhedeg yn lledredol o amgylch y fricsen ac sy'n pwysu 135 gram ar gyfartaledd; ac

- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

21. Homefire Ovals (R), a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys gronynnau glo caled (sef rhyw 50 i 75 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 20 i 45 y cant o'r cyfanswm pwysau), glo meddal (sef rhyw 5 i 17 y cant o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo siâp gobennydd wedi'u marcio â dwy linell gyfochrog sydd wedi'u hindentio ac yn rhedeg yn lledredol o amgylch y fricsen ac sy'n pwysu 130 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

22. Island Lump ac Island Nuts, a weithgynhyrchrir gan Unocal Refinery, California, Unol Daleithiau America-

- (a) sy'n cynnwys golosg petrolewm;
- (b) a weithgynhyrchwyd o'r golosg petrolewm drwy broses sy'n cynnwys triniaeth wres a chwistrellu stêm;
- (c) sy'n hapsiapiau heb eu marcio ac sy'n pwysu 80 gram ar gyfartaledd (Island Lump) neu 30 gram ar gyfartaledd (Island Nuts); ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

23. Brics glo Jewel, a weithgynhyrchrir gan Eldon Colliery Limited yn Newfield Works, Bishop Auckland, County Durham-

- (a) sy'n cynnwys glo caled (sef rhyw 30 i 50 y cant o'r cyfanswm pwysau) a golosg petrolewm Long Beach (sef rhyw 50 i 70 y cant o'r cyfanswm pwysau) a rhwymwr carbohydrate (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 150°C;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwysu 33 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

24. Long Beach Lump nuts (a elwir fel arall yn LBL nuts), a weithgynhyrchrir gan Aimcor Carbon Corporation yn Long Beach, California, Unol Daleithiau America-

briquette and have an average weight of 135 grammes; and

- (d) have a sulphur content not exceeding 2 per cent of the total weight.

21. Homefire Ovals (R), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite fines (as to approximately 50 to 75 per cent of the total weight), petroleum coke (as to approximately 20 to 45 per cent of the total weight), bituminous coal (as to approximately 5 to 17 per cent of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette and have an average weight of 130 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

22. Island Lump and Island Nuts, manufactured by Unocal Refinery, California, the United States of America, which-

- (a) comprise petroleum coke;
- (b) were manufactured from the petroleum coke by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes and have an average weight of 80 grammes (Island Lump) or 30 grammes (Island Nuts); and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

23. Jewel briquettes, manufactured by Eldon Colliery Limited at Newfield Works, Bishop Auckland, County Durham, which-

- (a) comprise anthracite (as to approximately 30 to 50 per cent of the total weight) and Long Beach petroleum coke (as to approximately 50 to 70 per cent of the total weight) and a carbohydrate binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 150°C;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 33 grammes; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

24. Long Beach Lump nuts (otherwise known as LBL nuts), manufactured by Aimcor Carbon Corporation at Long Beach, California, the United States of America, which-

- (a) sy'n cynnwys golosg petrolewm (sef rhyw 85 i 100 y cant o'r cyfanswm pwysau), calchfaen (sef rhyw 0 i 10 y cant o'r cyfanswm pwysau) a phyg tar glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys triniaeth wres a chwistrellu stêm;
- (c) o hapsiapiau heb eu marcio; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

25. Brics glo Maxibrite, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf-

- (a) sy'n cynnwys gronynnau glo caled (sef rhyw 84 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 12 y cant o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 250°C;
- (c) sy'n frics siâp clustog wedi'u marcio â'r llythyren "M" ac sy'n pwys 35 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

26. Brics glo Multiheat, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys glo caled (sef rhyw 60 i 80 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 10 i 30 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwys 55 neu 80 gram ar gyfartaledd fesul bricsen; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

27. Brics glo Newflame, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf-

- (a) sy'n cynnwys gronynnau glo caled (sef rhyw 84 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 12 y cant o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 260°C;

- (a) comprise petroleum coke (as to approximately 85 to 100 per cent of the total weight), limestone (as to approximately 0 to 10 per cent of the total weight) and coal tar pitch (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

25. Maxibrite briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which-

- (a) comprise anthracite fines (as to approximately 84 per cent of the total weight), petroleum coke (as to approximately 12 per cent of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are cushion-shaped briquettes marked with the letter "M" and have an average weight of 35 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

26. Multiheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite (as to approximately 60 to 80 per cent of the total weight), petroleum coke (as to approximately 10 to 30 per cent of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked pillow-shaped briquettes and have average weights per briquette of either 55 or 80 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

27. Newflame briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which-

- (a) comprise anthracite fines (as to approximately 84 per cent of the total weight), petroleum coke (as to approximately 12 per cent of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;

- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwys 78 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

28. Brics glo Phurnacite, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys llwch glo caled (sef rhyw 65 i 85 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 20 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp ofoid â dwy linell gyfochrog yn rhedeg yn hydredol o amgylch y fricsen ac sy'n pwys 40 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

29. Safelight Firelogs, a weithgynhyrchrir gan Advanced Natural Fuels Limited, yn Pocklington, East Riding of Yorkshire-

- (a) sy'n cynnwys sglodion pren (sef rhyw 40 i 55 y cant o'r cyfanswm pwysau) a rhwymwr cwyr palmwydden (sef rhyw 45 i 60 y cant o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys gwasgu' cynhwysion, ar ôl eu cymysgu, ar ryw 40°C i 50°C;
- (c) sy'n fonyffion Tân petryal caled â dwy agen ddfon sy'n gorgyffwrdd yn yr wyneb uchaf, un agen ddi-dor yn yr wyneb isaf, ac sy'n pwys 1.8 cilogram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

30. Brics glo Sovereign, a weithgynhyrchrir gan Monckton Coke & Chemical Company Limited yn Royston, yn ymwl Barnsley, South Yorkshire-

- (a) sy'n cynnwys glo caled (sef rhyw 75 y cant o'r cyfanswm pwysau), glo a golosg adweithiol (sef rhyw 21 y cant o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu pan fo'n oer (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys eu hallwthio;
- (c) sy'n frics glo chweochrog heb eu marcio ac sy'n pwys 130 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

- (c) are unmarked pillow-shaped briquettes and have an average weight of 78 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

28. Phurnacite briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite duff (as to approximately 65 to 85 per cent of the total weight), petroleum coke (as to approximately 20 per cent of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette and have an average weight of 40 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

29. Safelight Firelogs, manufactured by Advanced Natural Fuels Limited, at Pocklington, East Riding of Yorkshire, which-

- (a) comprise woodchip (as to approximately 40 to 55 per cent of the total weight) and palm wax binder (as to approximately 45 to 60 per cent of the total weight);
- (b) were manufactured from those constituents by a process involving pressing of the mixed ingredients at about 40°C to 50°C;
- (c) are rectangular hard finish Firelogs with two deep overlapping slots in the top surface, a single continuous slot in the base surface, and have an average weight of 1.8 kilogrammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

30. Sovereign briquettes, manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire which-

- (a) comprise anthracite (as to approximately 75 per cent of the total weight), coal and reactive coke (as to approximately 21 per cent of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are unmarked hexagonal briquettes and have an average weight of 130 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

31. Brics glo Stoveheat Premium, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys llwch glo caled (sef rhyw 65 i 85 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 20 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp ofoidau heb eu marcio ac sy'n pwys 40 gram ar gyfartaledd fesul bricsen; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

32. Supabrite Coke Doubles, a weithgynhyrchir gan H. J. Banks and Company Limited yn Inkerman Road Depot, Tow Law, County Durham-

- (a) sy'n cynnwys golosg metelegol (sef rhyw 40 i 60 y cant o'r cyfanswm pwysau) a golosg petrolewm (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys eu cyfuno a'u sgrinio;
- (c) sy'n hapsiapiau heb eu marcio; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.95 y cant o sylffwr o'r cyfanswm pwysau.

33. Brics glo Supacite, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf-

- (a) sy'n cynnwys gronynnau glo caled (sef rhyw 84 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 12 y cant o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 240°C;
- (c) sy'n siâp ofoid heb eu marcio ac sy'n pwys 45 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

34. Brics glo Supertherm, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys cyfuniad (mewn cyfrannedd o 19:1) o lo caled a glo canolig ei anweddolrwydd (sef rhyw 93 y cant o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu pan fo'n oer neu rwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;

31. Stoveheat Premium briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite duff (as to approximately 65 to 85 per cent of the total weight), petroleum coke (as to approximately 20 per cent of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing and heat treatment at about 300°C;
- (c) are unmarked ovoid-shaped briquettes and have an average weight of 40 grammes per briquette; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

32. Supabrite Coke Doubles, manufactured by H. J. Banks and Company Limited at Inkerman Road Depot, Tow Law, County Durham, which-

- (a) comprise metallurgical coke (as to approximately 40 to 60 per cent of the total weight) and petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving blending and screening;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 1.95 per cent of the total weight.

33. Supacite briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taff, which-

- (a) comprise anthracite fines (as to approximately 84 per cent of the total weight), petroleum coke (as to approximately 12 per cent of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 240°C;
- (c) are unmarked ovoids and have an average weight of 45 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

34. Supertherm briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise a blend (in the proportion of 19:1) of anthracite and medium volatile coal (as to approximately 93 per cent of the total weight) and cold-setting organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;

- (c) sy'n siâp ofoid heb eu marcio ac sy'n pwys o 160 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

35. Brics glo Supertherm II, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys glo caled (sef rhyw 36 i 51 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 40 i 55 y cant o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n siâp ofoid heb eu marcio ac sy'n pwys o 140 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

36. Brics glo Taybrite (a elwir fel arall yn frics glo Surefire), a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys glo caled (sef rhyw 60 i 80 y cant o'r cyfanswm pwysau), golosg petrolewm (sef rhyw 10 i 30 y cant o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thriniaeth wres ar ryw 300°C;
- (c) sy'n frics glo siâp gobennydd sydd wedi'u marcio ag un llinell wedi'i hindentio yn rhedeg yn hydredol ar hyd pob wyneb yn gorwedd 10 milimetru oddi wrth y llinell gyfatebol, neu heb eu marcio, ac sydd yn y naill achos a'r llall yn pwys o 80 gram ar gyfartaledd; ac
- (ch) nad ydynt yn cynnwys mwy na 2 y cant o sylffwr o'r cyfanswm pwysau.

37. Brics glo Thermac, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire-

- (a) sy'n cynnwys glo caled (sef rhyw 90 y cant o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu pan fo'n oer (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo siâp gobennydd heb eu marcio ac sy'n pwys o 48 gram ar gyfartaledd; ac
- (d) nad ydynt yn cynnwys mwy nag 1.5 y cant o sylffwr o'r cyfanswm pwysau.

- (c) are unmarked ovoids and have an average weight of 160 grammes; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

35. Supertherm II briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite (as to approximately 36 to 51 per cent of the total weight), petroleum coke (as to approximately 40 to 55 per cent of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked ovoids and have an average weight of 140 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

36. Taybrite briquettes (otherwise known as Surefire briquettes), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite (as to approximately 60 to 80 per cent of the total weight), petroleum coke (as to approximately 10 to 30 per cent of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with a single indented line running longitudinally along each face offset from its counterpart by 10 millimetres, or unmarked, and in either case have an average weight of 80 grammes; and
- (d) have a sulphur content not exceeding 2 per cent of the total weight.

37. Thermac briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which-

- (a) comprise anthracite (as to approximately 90 per cent of the total weight) and cold-setting organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes and have an average weight of 48 grammes; and
- (d) have a sulphur content not exceeding 1.5 per cent of the total weight.

38. Bonyffion tân ZIP Cracklelog, bonyffion tân ZIP Crackle-log a bonyffion tân ZIP Crackling Log, a weithgynhyrchir gan Allspan B.V., Macroweg 4, 5804 CL Venray, Yr Iseldiroedd-

- (a) sy'n cynnwys cwyr hydrin (sef rhyw 55 y cant o'r cyfanswm pwysau), blawd llif pren caled (sef rhyw 42 y cant o'r cyfanswm pwysau) a hadau clecian (sef rhyw 3.2 y cant o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses triniaeth wres ac allwthio;
- (c) sy'n foncyffion tân, rhyw 235 milimetru eu hyd a 80 milimetru eu diamedr, gyda rhigolau ar hyd yr wynebau, ac sy'n pwysu 1.1 cilogram ar gyfartaledd fesul bonyff tân; ac
- (ch) nad ydynt yn cynnwys mwy na 0.1 y cant o sylffwr o'r cyfanswm pwysau.

39. ZIP Firelogs, a weithgynhyrchir gan Allspan B.V., Macroweg 4, 5804 CL Venray, Yr Iseldiroedd-

- (a) sy'n cynnwys cwyr hydrin (sef rhyw 58 i 59 y cant o'r cyfanswm pwysau) a blawd llif pren caled (sef rhyw 41 i 42 y cant o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses triniaeth wres ac allwthio;
- (c) sy'n foncyffion tân, rhyw 265 milimetru eu hyd a 80 milimetru eu dyfnder, gyda rhigolau ar hyd yr wynebau, ac sy'n pwysu 1.3 cilogram ar gyfartaledd fesul bonyff tân; ac
- (ch) nad ydynt yn cynnwys mwy na 0.1 y cant o sylffwr o'r cyfanswm pwysau.

40. ZIP Firelogs, a weithgynhyrchir gan Woodflame Moerdijk B.V., Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, Yr Iseldiroedd-

- (a) sy'n cynnwys cwyr hydrin (sef rhyw 55 i 60 y cant o'r cyfanswm pwysau) a blawd llif pren caled (sef rhyw 40 i 45 y cant o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses triniaeth wres ac allwthio;
- (c) sy'n foncyffion tân rhyw 255 milimetru eu hyd a 75 milimetru eu diamedr, gyda rhigolau ar hyd un wyneb hydredol, ac sy'n pwysu 1.3 cilogram ar gyfartaledd fesul bonyff tân; ac
- (ch) nad ydynt yn cynnwys mwy na 0.1 y cant o sylffwr o'r cyfanswm pwysau.

38. ZIP Cracklelog firelogs, ZIP Crackle-log firelogs and ZIP Crackling Log firelogs, manufactured by Allspan B.V., Macroweg 4, 5804 CL Venray, The Netherlands, which-

- (a) comprise slack wax (as to approximately 55 per cent of the total weight), hardwood sawdust (as to approximately 42 per cent of the total weight) and crackle seeds (as to approximately 3.2 per cent of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs approximately 235 millimetres in length and 80 millimetres in diameter, with grooves along the faces and have an average weight of 1.1 kilogrammes per firelog; and
- (d) have a sulphur content not exceeding 0.1 per cent of the total weight.

39. ZIP Firelogs, manufactured by Allspan B.V., Macroweg 4, 5804 CL Venray, The Netherlands, which-

- (a) comprise slack wax (as to approximately 58 to 59 per cent of the total weight) and hardwood sawdust (as to approximately 41 to 42 per cent of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs approximately 265 millimetres in length and 80 millimetres in depth, with grooves along the faces and have an average weight of 1.3 kilogrammes per firelog; and
- (d) have a sulphur content not exceeding 0.1 per cent of the total weight.

40. ZIP Firelogs, manufactured by Woodflame Moerdijk B.V., Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, The Netherlands, which-

- (a) comprise slack wax (as to approximately 55 to 60 per cent of the total weight) and hardwood sawdust (as to approximately 40 to 45 per cent of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs approximately 255 millimetres in length and 75 millimetres in diameter, with grooves along one longitudinal face and have an average weight of 1.3 kilogrammes per firelog; and
- (d) have a sulphur content not exceeding 0.1 per cent of the total weight.

ATODLEN 2

Rheoliad 3(1)

DIRYMIADAU

Y rheoliadau a ddirymwyd:-

Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2001 (O.S. 2001/3762 (Cy.311))

Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Diwygio) (Cymru) 2001 (O.S. 2001/3996 (Cy.327))

Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Diwygio) (Cymru) 2002 (O.S. 2002/3160 (Cy.295))

SCHEDULE 2

Regulation 3(1)

REVOCATIONS

Regulations revoked:-

The Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2001 (S.I. 2001/3762 (W.311))

The Smoke Control Areas (Authorised Fuels) (Amendment) (Wales) Regulations 2001 (S.I. 2001/3996 (W.327))

The Smoke Control Areas (Authorised Fuels) (Amendment) (Wales) Regulations 2002 (S.I. 2002/3160 (W.295))

2006 Rhif 2979 (Cy.270)

AER GLÂN, CYMRU

Rheoliadau Ardaloedd Rheoli Mwg
(Tanwyddau Awdurdodedig)
(Cymru) 2006

2006 No. 2979 (W.270)

CLEAN AIR, WALES

The Smoke Control Areas
(Authorised Fuels) (Wales)
Regulations 2006

© Hawlfraint y Goron 2006

Argraffwyd a chyhoeddwyd yn y Deyrnas Unedig gan The Stationery Office Limited o dan awdurdod ac arolygiaeth Carol Tullo, Rheolwr Gwasg Ei Mawrhydi ac Argraffydd Deddfau Seneddol y Frenhines.

© Crown copyright 2006

Printed and Published in the UK by the Stationery Office Limited under the authority and superintendence of Carol Tullo, Controller of Her Majesty's Stationery Office and Queen's Printer of Acts of Parliament.

£3.50

W429/11/06

ON