SCHEDULE

Article 2

EXEMPTED FIREPLACES

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Jetmaster Fires Ltd, Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Installation and use instruction manual reference: "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference: "Part No 106872 Issue No. 1" dated May 2010. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 40% open position.	Wood logs ⁽¹⁾ .
Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC, Hamlet Solution 5 SC and Villager Espirit 5 SC. Manufactured by Arada Ltd, The Fire Works, Millwey Industrial Estate, Axminster, Devon, EX13 5HU.	Instruction manual reference "Rev 02" dated April 2010. All the appliances must be fitted with a mechanical stop to prevent closure of the air control beyond 20mm from the closed position and 50 mm beyond the fully open position.	Wood logs ⁽¹⁾ .
Acquisitions Bloomsbury 5kW stove. Manufactured by Esse Engineering Limited, Ouzedale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	Instruction manual reference "01/12 (PP)" dated January 2012. The appliance must be fitted with a system that prevents the closure of the air controls beyond the 50% open position.	Wood logs (1).
Acquisitions Cannonbury 4 and 5. Manufactured by Esse Engineering Ltd, Ouzledale	Installation and operating instruction manual reference "v71 of 09/11/2010" dated 09/11/2010.	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.		
Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves. Distributed by Pevex Enterprises Ltd, Unit 16, Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS.	Instruction manual reference "Pexex1001/AH/ver1" and dated June 2011 It must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	Dry wood logs (1).
Aduro 9D wood burning stove.	Instruction manual reference "Pevex1002/AH/ver1" and dated June 2011.	Dry wood logs (1).
Distributed by Pevex Enterprises Ltd, Unit 16, Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS.	It must be fitted with permanent stops to ensure that ensure the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Alberg 7. Manufactured by Elite Group Trading Ltd, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	The instruction manual reference "EGTL03A Version 1.4" dated 21 December 2012.	Wood logs (1).
Alpha I model number AL905-SE Wood Burning Stove. Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel	Instruction manual reference "HF277-SE/UK-NI-ROI/V2D.18-07-12" dated July 2012. The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.		
Alpha II model number AL907-SE Wood Burning Stove.	Instruction manual reference "AL907-SE/UK-NI-ROI/V3-D.14-07-12" dated July 2012.	Wood logs (1).
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air.	
Angus Orligno 200 18kW and 25kW gasification boilers.	Instruction manual reference "EV-20111002" dated October 2011.	Wood logs (1).
Manufactured by Eko-Vimar Orlanski Spólka z ograniczona odpowiedzialnoscia, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Orligno 200 40kW, 60kW and 80kW gasification boilers.	Instruction manual reference "EV- 20111002" dated October 2011.	Wood logs (1).
Manufactured by Eko-Vimar Orlanski Spólka z ograniczona odpowiedzialnoscia, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Angus Super 18, 25, 40, 60 and 80kW gasification boilers.	Instruction manual reference "EV- 20111001" dated October 2011.	Wood logs (1).
Manufactured by Eko-Vimar Orlanski		

(1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	C to:	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Spólka z ograniczona odpowiedzialnoscia, ul. Nyska 17 b, 48-385 Otmuchów, Poland.		
Apollo 8 inset stove.	Instruction manual reference "CH8K Apollo — V2" dated 31 October 2011.	Wood logs (1).
Manufactured by Chesneys Limited, 194-200 Battersea Park Road, London, SW11 4ND.	The appliance must be fitted with a system that prevents closure of the air controls further than 40mm from open.	
Arimax Bio 300kW, Arimax Bio 400kW and Arimax Bio 500kW.	Instruction manual reference "INSTALLATION AND OPERATION MANUAL Arimax Bio 120-3000 kW" dated 30/03/2010.	6-8mm wood pellets with a moisture content less than 10%
Manufactured by Artierm Oy, Kimmo Kantalainen; PO Box 59; Fin — 43101; Saarijärvi, Finland.		
Ariterm Ekerum 6kW pellet stove and Neptuni 6kW pellet stove.	Instruction manual reference "ARITERM-SP-PX26868-B.2" dated 15/12/2011.	Wood pellets (1).
Manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Ariterm Mysinge 6kW pellet stove.	Instruction manual reference "ARITERM-SP-PX26868-B.1" dated 15/12/2011.	Wood pellets (1).
Manufactured by Ariterm Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Ashwell Green-Tec 150 boiler.	Instruction manual reference "ASH-gt150/101 Version 1.2" dated 06/2009.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Ashwell Biomass Ltd, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.		
Ashwell Green-Tec 195 boiler.	Instruction manual reference "ASH-gt195/102 Version 1.2" dated 06/2009.	Wood pellets (1).
Manufactured by Ashwell Biomass Ltd, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.		
Ashwell Green-Tec 300 boiler.	Instruction manual reference "ASH-gt300/103 Version 1.2" dated 06/2009.	Wood pellets (1).
Manufactured by Ashwell Biomass Ltd, Unit 12, 35 Pinfold Road, Thurmaston, Leicester, LE4 8AT.		
Barbas ECO 40, 5 kW wood burning roomheater.	ECO 40 instruction manual, document Version 01-327332 dated October 2009.	Wood logs (1).
Manufactured by Interfocos BV; Hallenstraat 17, NL-5531 AB, BLADEL, The Netherlands.		
Barbas ECO 52 Stove.	Instruction manual reference "02 — 327332" dated March 2010.	Wood logs (1).
Manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.	dated March 2010.	
Barbas Unilux — 3 40, 5kW wood burning insert.	Unilux — 3 40 instruction manual, document Version 01 — 326587 dated August 2009.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Interfocos BV, Hallenstraat 17, NL — 5531 AB, BLADEL, The Netherlands.		
Barbas Unilux 3- 52 Stove.	Instruction manual reference "03 — 326587" dated March 2010.	Wood logs (1).
Manufactured by Interfocos, Hallenstraat 17, 5531 AB Bladel, The Netherlands.		
Baxi Bioflo.	Operating instruction manual reference "720574401" dated 2010 and installation	Wood pellets (1).
Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.	and servicing instruction manual reference "720574501" dated 2010.	
Be Modern Monroe 5, Monroe 5, Be Modern Monterrey 5, Monterrey 5 and York Midi Multi Fuel Stoves.	Instruction manual reference "OCT10/GB" dated 6th October 2010. The appliance must be fitted with a system that prevents the closure of the secondary air flaps to less than 8mm open position.	Wood logs (1).
Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.		
Be Modern Monterrey 7, Monterrey 7, Be Modern Monroe 7 and	Instruction manual reference "OCT10/GB" dated 6th October 2010.	Wood logs (1).
Monroe 7 Multi Fuel Stoves.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 10mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained	No fuel is to be used
	and operated in accordance with the following specifications:	in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.		·
The Binder Wood Fired Boiler models RRK 22 — 49 (49 kW output).	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler models RRK 80 — 175 (75 — 149 kW output) with cyclone models ZA 80 — 175.	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 130 — 250 (185 — 230 kW output) 200-350 (250-300kW output) 400-600 (350-500 kW output) 640-850 (650-840kW output)	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fivonlago	Conditions	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
with cyclone (model type ZA).		
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 1000 (1200 kW output) with multi- cyclone (model MZA).	The manufacturer's and Wood Energy Limited's instructions entitled "Binder Equipment Installation, Commissioning and Maintenance" dated 17 May 2005, reference WELBinderManual rev0.doc, revision 0.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 1200-1650 with Binder model MZA multi-cyclone and automatic ignition.	The manufacturer's and Wood Energy Limited's operating instructions for Binder appliances reference "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8", dated 15 July 2009.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 1800-2300 with Binder model MZA	The manufacturer's and Wood Energy Limited's Operating instructions for Binder appliances reference: "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8", dated 15 July 2009.	Wood pellets or wood chips ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
multi-cyclone and automatic ignition.		
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
The Binder Wood Fired Boiler model RRK 2500-3000 with Binder model MZA multi-cyclone and automatic ignition.	The manufacturer's and Wood Energy Limited's Operating instructions for Binder appliances reference: "2009 July Binder O&M revision 8.doc Operation and Maintenance Manual, revision 8", dated 15 July 2009.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Binder Gesellschaft mit beschränkter Haftung (GmbH) Mitterdorfer Strasse 5, A-8572 Barnbach, Austria.		
Biomatic +20 boiler.	Instruction manual reference "ARITERM-VTT-S-07229-11.1" dated 21/05/2012.	Wood pellets (1).
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.	V11-3-07229-11.1 dated 21/03/2012.	
Biomatic +20 light boiler and Biomatic +20 ultra light boiler.	Instruction manual reference "ARITERM-VTT-S-07229-11.2" dated 21/05/2012.	Wood pellets (1).
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Biomatic +40 boiler.	Instruction manual reference "ARITERM-VTT-S-06765-11.1" dated 21/05/2012.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
Biomatic +40 light boiler and Biomatic +40 ultra light boiler.	Instruction manual reference "ARITERM-VTT-S-06765-11.2" dated 21/05/2012.	Wood pellets (1).
Manufactured by Ariterm, Sweden AB, Flottiljvägen 15, 392 41 Kalmar, Sweden.		
The Biomatic 220 and 250 fitted with Zyklovent 220-250 cyclone separator.	The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc.	Wood chips, wood pellets, or planed wood shavings (1).
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Strasze 22,A-1230 Wien, Austria.		
The Biomatic 300, 350, 400 and 500 fitted with Zyklovent 300-500 cyclone separator.	The manufacturer's instructions dated April 2005, reference Bedienungsanleitung Englisch v2.0 doc.	Wood chips, wood pellets, or planed wood shavings (1).
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Strasze 22,A-1230 Wien, Austria.		
Boru 4.9kW Stove.	The Instruction manual reference "BFF010" dated 26/01/2011.	Wood logs (1)
Manufactured by	uaica 20/01/2011.	
Righpur Ltd, T/A Boru Stoves, The	The air controls must be fixed such they cannot be closed more than:	
	— Primary air slide 2mm;	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hive, Ballydine, Gooldscross, Ireland.	— Secondary air slide 2mm;— Tertiary air slide 30%.	
Burley Brampton 8 kW stove.	Instruction manual reference "BUR/11/10" dated October 2011.	Wood logs (1).
Manufactured by Burley Appliances, Lands' End Way, Oakham, Rutland, LE15 6RB.		
Burley Debdale 4 kW stove.	Instruction manual reference "BUR/11/10" dated October 2011.	Wood logs (1).
Manufactured by Burley Appliances, Lands' End Way, Oakham, Rutland, LE15 6RB.	The radius of the air inlet hole must be 19mm.	
Burley Hollywell SE.	The instruction manual reference "BUR/11/05" dated January 2011.	Wood logs (1).
Manufactured by Burley Appliances Ltd., Lands' End Way, Oakham, Rutland, LE15 6RB.	The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	
Bushman Large Commercial Pizza Oven.	The Instruction manual reference "LCOINST" dated 01/2011.	Wood logs (1).
Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE.		
Bushman Large Domestic Pizza Oven.	The instruction manual reference "LDOINST" dated 01/2011.	Wood logs (1).
Manufactured by Dingley Dell		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE.		
Bushman Medium Commercial Pizza Oven.	The instruction manual reference "MCOINST" dated 01/2011.	Wood logs (1).
Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE.		
Bushman Medium Domestic Pizza Oven.	The instruction manual reference "MDOINST" dated 01/2011.	Wood logs (1).
Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE.		
Bushman Small Commercial Pizza Oven.	The instruction manual reference "SCOINST" dated 01/2011.	Wood logs (1).
Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE.		
Bushman Small Domestic Pizza Oven.	The instruction manual reference "SDOINST" dated 01/2011.	Wood logs (1).

(1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Dingley Dell Enterprises Ltd, PO Box 3534, Kidderminster Worcestershire, DY14 9ZE.		
Carillon 4:3.	The instruction manual reference "7196755-Rev.09" dated 22nd December 2010.	Wood logs (1).
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Carillon 16:9 Crystal.	The instruction manual reference "7196755-Rev.09" dated 22nd December 2010.	Wood logs (1).
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Carron Dante SE.	The instruction manual reference "BHC401-406" dated 12th January 2011.	Wood logs (1)
Manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 14mm.	
Carron Stove.	The instruction manual reference "91-62351"	Dry and split wood
Manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL	dated July 2009.	logs of a maximum length of 23cm ⁽¹⁾ .
Carron Stove SE.	Instruction manual reference "BHC501-506" dated 12th January 2011.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

 Fireplace	Conditions	
•	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by JIG UK Ltd, Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	The appliance must be fitted with a system preventing the closure of the secondary air control openings beyond 3mm.	
Carron 11kW SE Stove.	Instruction manual reference "Carron 11kW Stove model September 2012 (Smoke Exempt)".	Wood logs (1).
Manufactured by JIG UK Ltd Hurlingham Business Park, Fulbeck Heath, Grantham, Lincolnshire, NG32 3HL.	The appliance must be fitted with a modification to the secondary air control preventing closure beyond 4mm.	
CB800 Skagen.	Instruction manual reference "JINHCE08 revE" dated 06/12/11 and instruction manual	Wood logs (1).
Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	"JINHCE08SCK revB" dated 06/12/11. The appliance must be fitted with smoke control area kit JHCE0801.	
Charnwood C-Four stove.	Instruction manual reference "CFOUR V1" dated 08/2011.	Wood logs (1).
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.		
Charnwood C-Five wood burning stove.	Instruction manual reference "C-series v2" dated 09/12.	Wood logs (1).
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 58mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Charnwood C-Six stove.	Instruction manual reference "Ref. C-4 C-6 v1" dated March 2012.	Wood logs (1).
Manufactured by A.J Wells and Sons Limited, Bishops Way, Newport, Isle of Wight PO30 5WS.	The appliance must be fitted with a system that prevents the closure of the air control opening beyond 58mm of the open position.	
Charnwood C-Seven wood burning stove.	Instruction manual reference "C-series v2" dated 09/12.	Wood logs (1).
Manufactured by A.J Wells and Sons Limited, Bishops Way, Newport, Isle of Wight PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 64mm open position.	
Charnwood C-Eight wood burning stove.	Instruction manual reference "C-series v2" dated 09/12.	Wood logs (1).
Manufactured by A.J Wells and Sons Limited, Bishops Way, Newport, Isle of Wight PO30 5WS.	The appliance must be fitted with a mechanical stop that prevents the closure of the air control opening beyond the 64mm open position.	
Charnwood Country 4 wood burning stove.	The modification instruction manual reference "TIS.95" dated 01/2011 and instruction manual "Country 4 MKII" dated 01/2011.	Wood logs (1).
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.	The appliance must be fitted with the manufacturer's smoke reduction kit to fix the minimum aperture of the secondary air inlets to a minimum of 21mm open.	
Charnwood Cove 1SR.	Installation and use instruction manual reference "COVE1SR01.10 Issue A".	Wood logs (1).
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.	The air control must be adjusted such that the minimum closure of the air control is equivalent to that found with the control pushed in 15mm from the fully open position.	
Charnwood Island 1.	The instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.	It must be fitted with a stop bracket (Kit No. 010/AY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Island 2.	The instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010.	Wood logs (1).
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	It must be fitted with a stop bracket (Kit No. 010/BY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Island 3.	The instruction manual reference "Island I.II.III 12.10 IssueB" dated December 2010.	Wood logs (1).
Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	It must be fitted with a stop bracket (Kit No. 010/CY83/S) to prevent the airwash flaps at the back of the stove from being closed beyond 2mm.	
Charnwood Tor stove. Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS.	Installation and use instruction manual reference "Tor 02.10 Issue A".	Wood logs (1).
Charnwood Tor Pico. Manufactured by A.J Wells and Sons Ltd, Bishops Way, Newport, Isle of Wight, PO30 5WS	The instruction manual reference "Tor & Tor Pico 12.10 IssueB" dated December 2010.	Wood logs (1).
Chesneys 4 Series (4.6kW) Stoves: Flatford 4; Hampstead 4, Alpine 4 also sold as: Sunbeam 4, Dakota 4, Providence 4, Pacific 4 also sold as: Milan 4,	The Chesneys 4 series instruction manual reference "CH4K-V4" dated 7 December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 34mm open position.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	~ 1	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Murano 4, Apollo 4, Chelsea 4 also sold as: Wellington 4, Guernsey 4, Belgravia 4.		
Manufactured by Chesneys Ltd, 194-200 Battersea Park Road, London, SW1 14ND.		
Chesneys Series 6 (7kW) Stoves: Flatford 6, Petworth 6, Barrington 6, Hampstead 6, Alpine 6 also sold as: Sunbeam 6, Dakota 6, Providence 6; Chelsea 6 also sold as: Wellington 6, Guernsey 6, Belgravia 6.	The Chesneys 6 series instruction manual reference "CH6K-V4" dated 7 December 2009. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 10mm open position.	Wood logs ⁽¹⁾ .
Manufactured by Chesneys Ltd, 194-200 Battersea Park Road, London, SW1 14ND.		
Classic model 25, 35, 40, 49 and 60 wood pellet boilers.	The manufacturer's installation manual for the Classic Pellet Boilers reference "No. 22, Pellet Boilers, Type Classic 25, 31, 35, 40, 49, 60, reference BA Classic 25L-60L Nr 21 0508".	Wood pellets (1).
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.		
Clean Air Systems CAS 200, 400 and 600 hand-fed airheaters.	The Handbook for CAS hand fired airheater range reference 24600H version 1 dated January 2011.	Softwood, hardwood, medium density fibreboard (MDF) or chipboard offcuts (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	a . t	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.		
Clean Air Systems CAS 300 Max airheater and cyclone.	The Handbook for CAS 300 Max airheater range reference 300A version 1 dated January 2011.	Chipped or sawdust softwood, hardwood, medium density fibreboard (MDF) or
Manufactured by Inventair Ltd, Lancaster Road, Carnaby Industrial Estate, Bridlington, East Yorkshire, YO15 3QY.		chipboard (1).
Cleanburn CB900 Inset & Cleanburn CB900 Sonderskoven Inset wood burning stoves.	Instruction manual reference "JINHCN09 Slider Stop Rev A" dated 17/01/12 and instruction manual "JINHCN09 Rev F" dated 24/01/12.	Wood logs (1).
Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position.	
Cleanburn R4.	Instruction manual reference "JINCLR04 Rev	Wood logs (1).
Manufactured by Hunter Stoves Limited, Unit 6, Old	E" dated 02/12/11 and instruction manual "JINCLR04SCK revB" dated 05/12/11. The appliance must be fitted with "smoke	
Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	control area kit JCLR0401".	
Clearburn Junior SE.	Instruction manual reference "JRSE Issue 1" dated March 2012.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Dean Forge Limited, Dean Prior, Buckfastleigh, Devon, TQ11 0LS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 83mm open position.	
The Clearview Pioneer 400, Solution 400 and Pioneer Oven wood burning stoves.	The manufacturer's instructions entitled "Operating Instructions Clearview Vision/ Vision Inset/Pioneer & Solution" dated 1 July 2006, reference V1/42, stamped and signed "Smoke Control".	Air-dried wood logs (1).
Manufactured by Clearview Stoves, More Works, Bishops Castle, Shropshire, SY9 5HH.	The appliance must be fitted with a tamperproof mechanical stop on the air slide/damper.	
Contura 510, 520T, 550, 550A, 550W, 560T, 560K, 570, 580, 585, 590 and Contura	The manufacturer's installation instructions IAV SE/EX 0726-6 611821 Lighting instruction BAV SA/EX 0717-2 611820.	Untreated dry wood with less than 20% moisture (1).
T. Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden.	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	
Contura 580W.	The manufacturer's installation instructions IAV SE/EX 0740-1 511911.	Untreated dry wood with less than 20%
Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden.	A permanent stop must be in place on the air inlet to prevent closure beyond the 20% open position.	moisture (1).
Contura 750, 750A and 780.	Instruction manual reference "811064 BAV SE-EX C750/780-1".	Wood logs (1).
Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Contura 810, Contura 820 T, Contura 850, Contura 860 T and Contura 880.	Instruction manual reference "811118 BAV SE-EX C800-1" dated 28/06/2011 and supplementary operating instructions "811142 BAV GB-2" dated June 2011.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by NIBE Stoves, Box 134, SE-285 23 Markaryd, Sweden.	The appliance must be fitted with a mechanical stop to prevent air control closure beyond the 38% open position.	
Contura i4 Modern and Contura i4 Classic.	The instruction manual reference "811136 BAV C i4 GB-1" dated 04-07-2011 and supplementary operating instructions "811142 BAV GB-2" dated June 2011.	Dry wood logs (1).
Manufactured by Nibe AB, Box 134, 285 23 Markaryd, Sweden.	It must be fitted with a mechanical stop to prevent closure beyond the 28% open position.	
Cove 2 SR. Manufactured by A.J Wells and Son Ltd. Of Bishops Way, Newport, Isle of Wight, PO30 5WS	The manufacturer's instruction manual reference "Cove2SR 07.09 IssB" dated July 2009. A permanent stop must be in place on air control to prevent closure beyond 14mm from the fully closed position.	Dry and split wood logs of a maximum length of 23cm (1).
Crator JS5500 multi- fuel stove. Manufactured by James Smellie Limited, Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands, B62 9JQ.	Instruction manual reference "Crator multi-fuel stove instruction manual Issue 1" dated June 2012.	Wood logs ⁽¹⁾ .
CTC Ecoflex 15 and 20. Manufactured by	The manufacturer's instructions dated 20 February 2007, reference 161 505 27 06/1.	Wood pellets (1).
Enertech AB, Box 313, S-341 26 Ljungby, Sweden.		
D'Alessandro GSA 130.	Instruction manual reference "2.0-1-QGSA130XEN0612" dated 26/06/2012.	Wood chips (1).
Manufactured by D'Alessandro		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.		
D'Alessandro Termomeccanica CS and CSA boilers 40, 60, 80 and 100kW.	Instruction manual reference "Ver. 2.0 — QCSA100XXIT0209 [UK SMOKE CONTROL]" dated 02/2009.	Wood pellets (1).
Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.		
D'Alessandro Termomeccanica CS and CSA 130, 180, 230, 300 and 2000kW.	Instruction manual reference "Ver. 2.0 — QCSA2000XEN0209 [UK SMOKE CONTROL]" dated 02/2009.	Wood pellets (1).
Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.		
D'Alessandro Termomeccanica CS and CSA 400, 500, 650, 800, 950, 1300, 1650 and 2000kW.	Instruction manual reference "Ver. 2.0 — QCSA2000XEN0209 [UK SMOKE CONTROL]" dated 02/2009. The appliance must be fitted with the optional multi-avalone.	Wood pellets (1).
Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.	multi-cyclone.	
D'Alessandro Termomeccanica CSI 20kW.	Instruction manual reference "Ver. 2.0 - QCSI100XXIT0209" dated 02/2009.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by D'Alessandro Termomeccanica, Contrada Cerreto, 55, 66010 Miglianico, Chieti, Italy.		
Dartmoor 5 SE.	Instruction manual reference "DM5 Issue 1" dated March 2012.	Wood logs (1).
Manufactured by Dean Forge Limited, Dean Prior, Buckfastleigh, Devon, TQ11 0LS.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	
Design 800 Green wood burning stove.	Instruction manual reference "07DH8000A" dated 11/11.	Wood logs (1).
Manufactured by Bodart & Gonay Limited, Rue De Lambinon, 3 Harze, Belgium, 4920.	The appliance must be fitted with a "UK kit for smokeless areas Design 800".	
Di Lusso R4.	Instruction manual reference "JINDLU04 Rev E" dated 02/12/11 and instruction manual	Wood logs (1).
Manufactured by Hunter Stoves	"JINDLU04SCK revB" dated 05/12/11.	
Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	The appliance must be fitted with smoke control area kit JDLU0401.	
Dimplex SE Selbourne 5.	The instruction manual reference "SE Selbourne 5 Issue 1" dated 08 2009.	Wood logs (1).
Manufactured by ESSE Engineering Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	All appliances must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	
Dovre Vintage 30 (DV-VIN30, DV- VIN30WH, DV-	Instruction manual reference 03.27681.100 dated April 2011 and PM813 Issue 1 dated May 2012.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
TBVIN30 and DV-TBVIN30WH), Dovre Vintage 35 (DV-VIN35, DV-VIN35WH, DV-TBVIN35 and DV-TBVIN35WH) and Dovre Vintage 50 (DV-VIN50, DV-VIN50WH, DV-TBVIN50WH, DV-TBVIN50 and DV-TBVIN50WH) stoves.	The appliance must be fitted with a permanent stop preventing closure of the secondary air supply beyond 50%.	
Manufactured by Dovre N.V., Nijverheidsstraat 18, B-2381 Weelde, Belgium.		
The Dovre 250 (model DV-250).	The manufacturer's instructions, reference "PM250 Issue 1".	Untreated dry wood (1).
Manufactured by Dovre NV, Nijverheidsstraat 18, BE-2381 Weelde, Belgium.	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position.	
The Dunsley Yorkshire Stove.	The manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those	Untreated dry wood (1);
Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road,	dated 4 December 2004, reference D13.	Peat or peat briquettes with, in either case, less than 25% moisture;
Holmfirth, Yorkshire HD9 3TW.		Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the	No fuel is to be used in the fireplace other
	following specifications:	than authorised fuels and the following fuel or fuels:
		not exceeding 1% of the total weight;
		CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.
Multifuel Stove. Manufactured by Dunsley Heat Ltd, Bridge Mills,	The manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those dated 4 December 2004, reference D13.	Untreated dry wood (1); Peat or peat briquettes with, in either case, less than 25% moisture;
Huddersfield Road, Holmfirth, Yorkshire HD9 3TW.		Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight;

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	CPL Wildfire, manufactured by Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile
The Dunsley Yorkshire Multifuel Stove and Boiler. The manufacturer's instructions dated 5 August 1998, reference A/22160 as amended by those dated 4 October 2004, reference GHD/DUN4B/1. Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW.	content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight. Untreated dry wood (1); Peat or peat briquettes with, in either case, less than 25% moisture; Union Coal Briketts, manufactured by Rheinbraun AG of Germany comprising lignite compressed into briquettes of approx. 15cm in length with square ends and with a sulphur content not exceeding 1% of the total weight; CPL Wildfire, manufactured by

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
		Coal Products Ltd., Immingham, which comprise bituminous coal with a volatile content of 32-36% (as to approx. 96% of the total weight) and a cold cure resin binder (as to the remaining weight) are manufactured from those constituents by a process involving roll pressing, have an average weight of either 80-90 grams or 160-170 grams, and have a sulphur content not exceeding 1.8% of the total weight.
The Dunsley Yorkshire Woodburning Stove.	The manufacturer's instructions dated 4 December 2004, reference D13W.	Untreated dry wood (1).
Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW.		
The Dunsley Yorkshire Woodburning Stove and Boiler.	The manufacturer's instructions dated 4 December 2004, reference D13W together with the manufacturer's instructions dated 4 October 2004, reference GHD/DUN4B/1.	Untreated dry wood (1).
Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield Road, Holmfirth, Yorkshire HD9 3TW.	2007, Telefelice OHD/DUN4D/1.	
E-Compact 15 wood pellet stove boiler.	Instruction manual reference "E-COMPACT 15 Outdoor Pellet Boiler v1.5" dated 05/ 2012.	6mm wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
•	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Wood Energy Solutions, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
E-Compact 28 Pellet Boiler.	Instruction manual reference "Installation & Operation Manual V.2.1" dated 07/12.	6mm wood pellets ⁽¹⁾ .
Manufactured by Wood Energy Solutions Limited, Donaskeigh, Tipperary, Co. Tipperary, Ireland.		
Earlswood.	The instruction manual reference "EW1MF technical manual" dated 02 2009.	Wood logs (1).
Manufactured by ACR Heat Products Ltd, Unit One Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	When the primary air control is in the closed position, it must remain permanently open by 5mm and be prevented from closing fully by a screw.	
Ecco Stove E580.	Instruction manual reference "Ecco Stove 580 manual" dated 12/12/11.	Wood logs (1).
Manufactured by Landy Vent UK Limited, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.		
Ecco Stove E678.	The instruction manual reference "01/11/3" dated 28/01/2011.	Wood logs (1).
Manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	The appliance must be fitted with a system to fix the secondary air (airwash) to a 4mm open position.	
Ecco Stove E850.	The instruction manual reference "02/10" dated 10th October 2010.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Landy Vent UK Ltd, Foster House, 2 Redditch Road, Studley, Warwickshire, B80 7AX.	The appliance must be fitted with a system that prevents closure of the secondary air flaps beyond 4mm (3 turns).	
Ecofire Barbara wood pellet stove boiler. Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Instruction manual reference "cod. 004770900" dated 10/2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference 004723000 dated 01/2012.	Wood pellets ⁽¹⁾ .
Ecofire Giulia Idro, Ecofire Kelly Idro Plus and Ecofire Tania Idro wood pellet stove boilers.	Instruction manual reference "cod. 004770432" dated 02/2011 and supplementary information "Clean Air Act 1993 and Smoke Control Areas" reference 004723000 dated 01/2012.	Wood pellets ⁽¹⁾ .
Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.		
Eco-Ideal Eco 1 Stove.	The instruction manual reference "JINECO01 revC" dated 20/07/11.	Dry wood logs (1).
Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	It must be fitted with a permanent stop that prevents closure of the secondary air slider	
Eco-Ideal Eco 2 Stove.	The instruction manual reference "JINECO02 revC" dated 20/07/11.	Dry wood logs (1).
Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	It must be fitted with a permanent stop that prevents closure of the secondary air slider	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	Conditions	
Тиерисе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Eco-Ideal Eco 4 Stove. Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	The instruction manual reference "JINEC004 revC" dated 20/07/11.	Dry wood logs (1).
Eco-Ideal Eco 6 Stove. Manufactured by Hunter Stoves Ltd., Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	The instruction manual reference "JINEC006 revC" dated 20/07/11.	Dry wood logs (1).
Ellipse. Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The instruction manual reference "7196901-Rev.09" dated 22nd December 2010. It must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	Wood logs (1).
En-tech model ENP 10, 15, 18, 25 and 35 boilers.	The manufacturer's installation manual dated 11/2009, reference IMENP 10-35 11/2009 for the Firefox pellet boiler.	Wood pellets (1).
Manufactured by En-tech Energietechnikpprodukt Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria.	tion,	
En-tech model PK15 and 25 boilers. Manufactured by En-tech	The manufacturer's installation manual dated 11/2009, reference IMPK PK 15/25 11/2009 EN for the Firefox pellet boiler.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

 Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Energietechnikpproduk Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria.	tion,	
En-tech model PK45 boilers.	The manufacturer's installation manual dated 11/2009, reference IMPK PK 45 11/2009 EN for the Firefox pellet boiler.	Wood pellets (1).
Manufactured by En-tech Energietechnikpproduk Gesellschaft mit beschränkter Haftung (GmbH), Gewerbezone 3, A-9300 St Veit, Glan- Hunnenbrunn, Austria.	•	
Endress USF-W 250.	The instruction manual reference "Operating and Maintenance manual Endress USF -	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	W250" dated 03/2010. Reference EMAN — USFW250.	
Endress USF-W 350.	The instruction manual references "Operating and Maintenance manual Endress USF –	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	W350" dated 03/2010. Reference EMAN — USFW350.	··.
Endress USF-W 500. Manufactured by Endress	The instruction manual references "Operating and Maintenance manual Endress USF - W500" dated 03/2010. Reference EMAN — USFW500.	Wood chips and pellets (1).

30

(1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained	No fuel is to be used
	and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.		
Endress USF-W 800.	The instruction manual references "Operating and Maintenance manual Endress USF –	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	W800" dated 03/2010. Reference EMAN — USFW800.	
Endress USF-W 1000.	The instruction manual reference "Operating and Maintenance manual Endress USF –	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	W1000" dated 03/2010. Reference EMAN — USFW1000.	
Endress VR-S 300.	The instruction manual reference "Operating and Maintenance manual Endress VR-S300"	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	dated 03/2010. Reference EMAN — VRS300.	
Endress VR-W 400.	The instruction manual reference "Operating and Maintenance manual Endress VR –W400"	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	dated 03/2010. Reference EMAN — VRW400.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The Grandes around he installed an aintained	No final in to be used
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Endress VR-W 600.	The instruction manual reference "Operating and Maintenance manual Endress VR-W600"	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	dated 03/2010. Reference EMAN — VRW600.	
Endress VR-W 900.	The instruction manual reference "Operating and Maintenance manual Endress VR-W900"	Wood chips and pellets
Manufactured by Endress Holzfeuerungsanlagen GmbH, Industriestrasze 18, D-91593 Burgbernheim.	dated 03/2010. Reference EMAN — VRW900.	
-	The use and maintenance manual reference "Uniconfort EOS30 Manual v1" dated July 2011.	Wood pellets (1).
Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.		
	The use and maintenance manual reference "Uniconfort EOS35 Manual v1" dated July 2011.	Wood pellets (1).
Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.		
EOS 40 464kW output wood pellet boiler with multicyclone.	The use and maintenance manual reference "Uniconfort EOS40 Manual v1" dated July 2011.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Einanlaga	Conditions	
Fireplace	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Uniconfort srl, Via dell'Industria 21, 35018, San Martino Di Lupari (PD) Italy.		
EOS 60 700 kW output wood pellet boiler with multicyclone.	The installation instruction manual reference "K135-07332 Uniconfort MUN v 2" dated September 2010.	6mm diameter wood pellets ⁽¹⁾ .
Manufactured by Uniconfort srl. Via dell'Industria 21, 35018, San Martino Di Lupari, (PD) Italy.		
ESSE 100 SE Smoke Exempt woodburning stove.	Manufacturer's instruction manual dated February 2009, reference 100 SE Issue 1.	Untreated dry wood with a maximum moisture content of 20% maximum
Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswisk, Lancashire, BB18 6BN.		length of 200 mm and maximum width or diameter of 120 mm ⁽¹⁾ .
Esse 100DD SE 5kW stove.	Instruction manual reference "10/11 (PP) INSTR.ST-100DDSE/u" dated October 2011.	Wood logs (1).
Manufactured by ESSE Engineering Limited, Ouzedale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a system to prevent closure of the air controls beyond the 50% open position.	
ESSE 125 SE.	Instruction manual reference "Esse 125SE Issue 1" dated 08 2009.	Wood logs (1).
Manufactured by ESSE Engineering Ltd, Ouzledale	15540 1 44104 00 2007.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 50% open position.	
Esse 301 SE stove.	The instruction manual reference "v45" dated 09/11/2010.	Wood logs (1).
Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The primary air control must not be fully air tight when closed.	
Esse 350 stove.	The instruction manual reference "v45" dated 09/11/2010.	Wood logs (1).
Manufactured by ESSE Engineering Ltd., Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.		
Esse 1622 inset stove.	Installation and operation manual reference "1622/Integra INSET revision c" dated July	Dry wood logs (1).
Manufactured by ESSE Engineering	2010.	
Ltd, Ouzledale Foundry, Long Ing, Barnoldswick, Lancashire, BB18 6BN.	The appliance must be fitted with a mechanical stop to fix secondary air control fully open.	
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers.	The instruction manual reference "HACK20-200_Bedienung_2011-06_EN" dated 06/2011.	Wood chips (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an	An integrated flue gas recirculation system must be used when using wood chips with a moisture content below 15%.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
der Trattnach, Gewerbepark 1, Austria.		
ETA HACK 20, 25, 35, 50, 70, 90, 130 and 200 woodchip boilers.	The instruction manual reference "HACK20-200_Bedienun 2011-06_EN" dated 06/2011.	Wood pellets (1).
Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	An integrated flue gas recirculation system must be used when burning wood pellets.	
ETA PC 20, 25 and 32 wood pellet boilers. Manufactured by ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.	The instruction manual reference "PC20-32_Bedienung_2011-06_EN" dated 06/2011.	Wood pellets (1).
ETA PE-K 35, 50, 70 and 90 wood pellet boilers.	The instruction manual reference "PE-K35-90_Bedienung_2011-06_EN" dated 06/2011.	Wood pellets (1).
Manufactured by ETA Heiztechnik GmbH, Christian Malecz, ETA Heiztechnik Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Gewerbepark 1, Austria.		
ETA PU 7, 11 and 15 wood pellet boilers.	The instruction manual reference "PU7-15_Bedienung_2011-06_EN" dated 06/2011.	Wood pellets (1).
Manufactured by ETA Heiztechnik GmbH, Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
ETA SH 20, 30, 40, 50 and 60 wood gasification boilers.	The instruction manual reference "SH20-60_Bedienung_2011-06_EN" dated 06/2011.	Wood logs (1).
Manufactured by ETA Heiztechnik GmbH, Gesellschaft mit beschrankter Haftung (GmbH), A 4716, Hofkirchen an der Trattnach, Gewerbepark 1, Austria.		
eVolution 4 Inset.	Instruction manual reference "eVo 4&7 Inset MS11-11" dated 9 November 2011.	Wood logs (1).
Manufactured by Broseley Fires Ltd, Knights Way, Battlefields Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 15mm open position.	
eVolution 5 model number M-EVO5.	The instruction manual reference "eVo 5 MS07-11" dated 8th July 2011.	Wood logs (1).
Manufactured by; Broseley Fires Ltd, Knights Way,	The appliance must be fitted with a system that prevents the closure of the air control to less than 70% open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	a 1.	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Battlefield Enterprise Park Shrewsbury, Shropshire, SY1 3AB.		
eVolution 7 Inset.	Instruction manual reference "eVo 4&7 Inset MS11-11" dated 9 November 2011.	Wood logs (1).
Manufactured by Broseley Fires Ltd, Knights Way, Battlefields Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond the 8mm open position.	
eVolution 26 boiler stove.	Instruction manual reference "MS10-11c" dated 09/01/2012.	Wood logs (1).
Manufactured by Broseley Fires Ltd, Knights Way, Battlefields Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a mechanical stop to prevent closure beyond the 40% open position.	
Evotherm P50, P100, P120, P150, P170, P200 pellet boilers	The manufacturer's instructions "Operating manual" reference "Version 1/2010/Rev. 4.21".	Wood pellets (1).
Manufactured by Evotherm, Heiztechnik Vertriebs Gesellschadft mit beschrankter Haftung (GmbH), Seeleiten 24, AT 5120, St Pantaleon, Austria.		
The Extraflame:	The manufacturer's instructions dated 5 March 2007, reference 004275101 011.	Wood pellets (1).
Babyfiamma, Bella and Bella Lux, Clementina Comfort Maxi, Contessa, Divina, Divina Plus and Divina Steel, Duchessa and Duchessa Steel,	2007, Telefence 00+273101 011.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels
		and the following fuel or fuels:
Ecologica, Esmeralda and Esmeralda Crystal, Falò 1CP, Falò 2CP and Falò 1XP, Isabella, Karolina, Preziosa,		or jucis.
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.		
The Extraflame Comfort Mini.	The manufacturer's instructions dated 2 October 2006, reference 004275115 REV 005.	Wood pellets (1).
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.		
The Extraflame Idro.	The manufacturer's instructions dated 28	Wood pellets (1).
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.	August 2006, reference 004275128 REV 002.	
The Extraflame Lucrezia Idro and Lucrezia Steel.	The manufacturer's instructions dated 12 July 2006, reference 004275110 REV 011.	Wood pellets (1).
Manufactured by Extraflame S.p.a in Montecchio Precalcino (Vicenza), Italy.		
FDC5 Stove.	Instruction manual reference "FDC Issue 02" dated 04/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
FDC5i inset stove.	Instruction manual reference "FDCi Issue 06" dated 03/12.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
FDC5iT Taper inset stove.	Instruction manual reference "FDCiT Issue 1" dated 04/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
FDC5iW Wide inset stoves.	Instruction manual reference "FDCi Issue 06" dated 03/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
FDC5W Wide stove. Manufactured by Charlton & Jenrick	Instruction manual reference "FDC Issue 02" dated 04/12.	Wood logs (1).
Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	
Fireball.	The instruction manual reference "7196801-Rev.07" dated 22nd December 2010.	Wood logs (1).
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Firefox 5 Clean Burn II, Gallery Classic 5 Clean Burn, Sirius 405	The instruction manual reference "FF5CBII REV:A" dated June 2011.	Dry wood logs (1).
Clean Burn and Sirius 405 Classic Clean Burn.	It must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Percy Doughty & Co Ltd, Imperial Point, Express Trading Estate Stone Hill Road, Farnworth, Bolton, BL4 9TN.		
Firefox 5CB (4.9kW); Vega 100CB (4.9kW); Sirius 405CB (4.9kW); Flame 5CB (4.9kW).	The instruction manual reference "FFXCBA" dated January 2010.	Wood logs (1).
Manufactured by Percy Doughty & Co, Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.		
Firefox 8 Clean Burn, Gallery Classic 8 Clean Burn, Sirius 545 Clean Burn and Sirius 545 Classic Clean Burn.	The instruction manual reference "FF8CB REV:A" dated June 2011. It must be fitted with a mechanical stop to prevent secondary air closure beyond the 50% open position.	Dry wood logs (1).
Manufactured by Percy Doughty & Co Ltd, Imperial Point, Express Trading Estate Stone Hill Road, Farnworth, Bolton, BL4 9TN.		
Fireline FGi5 stove.	Instruction manual reference "FGi.FPi.FXi Issue 06" dated 03/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fireline FP5W and FX5W Freestanding stove.	Instruction manual reference "FX.FP.Issue 06" dated 03/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 7mm open position.	
Fireline FPi5T, FGi5T and FXi5T Taper inset stoves.	Instruction manual reference "FXiT.FPiT.FGiT Issue 01" dated 03/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
Fireline FPi5W, FGi5W and FXi5W Wide inset stoves.	Instruction manual reference "FGi.FPi.FXi Issue 06" dated 03/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
Fireline FXi 5kW, Fireline FPi 5kW, Fireline FX5 and	The instruction manual reference "Issue 03" dated 03/10.	Wood logs (1).
Fireline FP5.	The appliance must be fitted with a system that prevents the closure of the secondary air	
Manufactured by Charlton and Jenrick Ltd, G1-G2 Halesfield 5, Telford, Shropshire, TF7 4QJ.	control beyond the 3.5mm open position.	
The Firematic 25, 50, 90 and 150.	The manufacturer's instructions dated June 2005, reference "Bedienungsanleitung Firematic V 1.1 ENG doc".	Chipped wood, wood pellets, or planed wood shavings (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	C 1:	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Strasze 22,A-1230 Wien, Austria.		
Firematic 45 and 60.	Instruction manual reference "05.007 Operating	Wood pellets
Manufactured by HERZ Armaturen Ges.m.b.H., Richard- Strauss-Strasze 22,A-1230 Wien, Austria.	Instructions — FM (1Ph) 20 35 45 60 v2.3" dated "08/2009".	conforming to ÖNORM M7135 with diameter of 6mm or wood chips up to a maximum size of 50mm and maximum water content 35% (1).
Firematic FM 130, FM 151, FM 180 and FM 199.	Instruction manual reference "Operating Instructions Herz firematic 130 — 199 BioControl" version Betriebsanleitung firematic 20-201 BioControl Englisch V 3.1.	Wood chips and wood pellets (1)
Manufactured by Herz Energietechnik GmbH, Herzstrasze 1, 7423 Pinkafeld, Austria.		
Firestorm 4.5 SE.	Instruction manual reference "4.5KW SE Issue (6928) 1" dated 28 April 2012.	Wood logs (1).
Manufactured by The Heat Resistant Glass Company Limited, Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The appliance must be fitted with a stop that will only allow a minimum 3mm air gap between the air control plate and the appliance when the secondary air is turned down to its minimum position.	
Firestorm 6.5 SE.	Instruction manual reference "6.5KW SE Issue (6928) 3" dated 28 April 2012.	Wood logs (1).
Manufactured by The Heat Resistant Glass Company Limited, Unit 2, Bracewell Avenue, Poulton Industrial Estate,	The appliance must be fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Poulton Le Fylde, FY6 8JF.		
Firestorm 10 SE.	Instruction manual reference "10 KW SE Issue (6928) 2" dated 28 April 2012.	Wood logs (1).
Manufactured by The Heat Resistant Glass Company Limited, Unit 2, Bracewell Avenue, Poulton Industrial Estate, Poulton Le Fylde, FY6 8JF.	The applicance must be fitted with a stop that will only allow a minimum air gap 6mm between the air control plate and the appliance when the secondary air is turned down to its minimum position.	
Firewarm 4SE stove.	Instruction manual reference "FW468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	
Firewarm 06C inset stove.	Instruction manual reference "FW06C" dated 26/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Firewarm 6SE stove.	Instruction manual reference "FW468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	
Firewarm 8SE stove. Manufactured by Heat Design, 30	Instruction manual reference "FW468SE" dated 25/07/12.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	
Firewarm 11C inset stove.	Instruction manual reference "FW11C" dated 26/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Flatford 5K, Barrington 5K and Hampstead 5K wood burning stoves.	Instruction manual reference "CH5K — V1" dated 14 March 2012. The appliance must be fitted with a mechanical	Wood logs (1).
Manufactured by Chesneys Limited, 192 — 200 Battersea Park Road, London, SW11 4ND.	stop to prevent secondary air control closure beyond the 18mm open position.	
Franco Belge Model 134 08 11 Savoy EA (8kW output) wood burning stove.	The Savoy EA Technical Manual, document reference 1290-1, reviewed 9 July 2009.	Wood logs (1).
Manufactured by Franco Belge, Staub Fonderie SARL, Rue Orphée Variscotte, 59660, Merville, France.		
Franco Belge Model 134 08 09 Savoy Mk II Elegance multifuel stove with KEA 13408 smoke control kit.	The Savoy EA Technical Manual, document reference 1290-1, reviewed 9 July 2009.	Wood logs (1).

(1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

 Fireplace	Conditions	
·	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.		
Franco Belge Montfort MK2 wood burning stove.	Instruction manual reference "1295-3" dated 17 November 2009.	Wood logs (1).
Manufactured by Franco Belge, Staub Fonderie SA, Rue Orphée Variscotte, 59660, Merville, France.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 25% open position.	
Fröling Lambdamat commercial wood chip boiler models 500, 750 and 1000.	The "Lambdamat communal Operating and Installation Manual" reference B 069 01 04 of February 2004.	Wood chips (1).
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria.		
Fröling P4 8, 15, 20, 25, 32, 38, 48 and 60 Pellet Boilers.	The manufacturer's instruction manual reference "BO430408 _en" dated July 2009.	Wood pellets with a diameter of 6mm (1).
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Fröling P4 80 and P4 100 wood pellet boilers.	Instruction manual reference "B043 — Version 8" dated 05/2012.	Wood pellets (1).
Manufactured by Fröling Heizkessel- und Behälterbau, Ges.m.b.H., Industriestrasze 12, A — 4710 Grieskirchen, Austria.		
Froling S4 Turbo 15 15kW; Froling S4 Turbo 22 22kW; Froling S4 Turbo 28 28kW; Froling S4 Turbo 34 34kW; Froling S4 Turbo 40 40kW; Froling S4 Turbo 50 50kW; and Froling S4 Turbo 60 60kW.	The Assembly Instruction manual "M0970208" dated November 2008 and Operating instruction manual "B0510108" dated November 2008.	Wood logs (1).
Manufactured by Froling Heizkessel und Behalterbau Ges. M.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria.		
Fröling T4 24, 30, 40, 50, 60, 75, 90, 100 and 110kW boilers.		Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau, Ges.m.b.H., Industriestrasze 12, A — 4710 Grieskirchen, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
The Fröling Turbomatic 28, 35, 48 and 55.	The fireplace must be installed in accordance with the manufacturer's installation instructions dated November 2003, reference M 060 01 03.	Wood chips with less than 35% moisture content that meet ÖNORM (a) M 7133:
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria.	The fireplace must be maintained and operated in accordance with the manufacturer's instructions dated August 2002, reference 99229a.	1998 size class G30 or wood pellets of 6mm diameter and a moisture content below 10% (1).
The Fröling Turbomatic 85, 100 and 110.	The fireplace must be installed in accordance with the manufacturer's installation instructions dated November 2003, reference M 060 01 03.	Wood chips with less than 35% moisture content that meet ÖNORM (a) M 7133;
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria.	The fireplace must be maintained and operated in accordance with the manufacturer's instructions dated August 2002, reference 99229a.	1998 size class G30 or G50, wood pellets of 6mm diameter and a moisture content below 10% (1).
The Fröling Turbomat 150 and 220.	The manufacturer's instructions dated August 2003, reference BO310003.	Wood pellets, or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12, A-4710 Grieskirchen, Austria.		
The Fröling Turbomat 320 and 500.	The manufacturer's instructions dated November 2004, reference B0340004.	Wood pellets, or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und Behälterbau Ges.m.b.H., Industriestrasze 12,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
A-4710 Grieskirchen, Austria.		
Fröling TX150 150kW boiler with Exhaust Gas Recirculation device.	The Installation Instruction manual reference "M1130009" dated 09/2010 and operating instruction manual "B 067 00 09" dated 09/2010.	Wood chips with a moisture content =30% and a maximum cross sectional area of 5cm2 or wood
Manufactured by Fröling Heizkessel- und Behälterbau, Ges.m.b.H., Industriestrasze 12, Austria.		pellets with a moisture content of =10% and a maximum diameter of 10mm ⁽¹⁾ .
Fröling TX 200 199kW and TX 250 250kW boilers with Exhaust Gas Recirculation device.	Instruction manual reference "B067 — Version 03" dated 05/ 2012.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Fröling Heizkessel- und, Behälterbau Ges.m.b.H., Industriestrasze 12, A — 4710 Grieskirchen, Austria.		
Future Fires Panoramic FX1.	Instruction manual reference "PANFXREV2" dated 31/10/12.	Wood logs (1).
Manufactured by Gen- Fab Limited, Swinton Bridge Industrial Estate, Whitelee Rd, Swinton, S64 8BH.		
The Gilles HPK-RA 13 kW, 15 kW, 20 kW, 25 kW, 30 kW, 35 kW, 40 kW, 45 kW, 49 kW, 60 kW, 70 kW, 75 kW, 85 kW, 95 kW, 100	The manufacturer's instructions dated January 2007, reference Gilles/0-145/1.	Wood chips and wood pellets (1).

(1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
kW, 120 kW, and 145 kW.		
Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.		
Gilles HPK-RA 160.	The instruction and operating manuals "BD-200-01a-01" and dated 11/2008,	Wood pellets, or wood chips (1).
Manufactured by Gilles Energie — und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.	"BD-200-01a-02" and dated 11/2008, "BD-200-01a-03" and dated 11/2008, "BD-200-01a-04" and dated 11/2008, "BD-200-01a-06" and dated 11/2008, "BD-200-03a-07" and dated 11/2008, and "BD-200-03a-09" and dated 11/2008.	
The Gilles HPK USK 150 kW, 180 kW, 240 kW and 300 kW.	The manufacturer's instructions dated January 2007, reference Gilles/150-300/1.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.		
The Gilles HPK USK 360 kW.	The manufacturer's operating instructions dated January 2008, reference Gilles 360/1.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.		
Gilles HPKI-K 180, 195, 240, 300, 360, 450, 550, 700, 900, 995, 1200 and 1600.	The instruction manual reference "Operating Instruction HPKI-K Underfeed Stoking. 1-general-hpki-k underfeed stoking" dated 11/2008.	Wood chips and pellets

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Gilles Energie — und Umwelttechnik Gmbh, Koaserbauer Str. 16A-4810 Gmunden, Austria.		
The Gilles UTSK 450 kW, 550 kW, 700 kW, 900 kW, 1200 kW, and 1600 kW Boilers.	The manufacturer's operating instructions dated January 2008, reference Gilles 360/1.	Wood pellets or wood chips (1).
Manufactured by GILLES Energie- und Umwelttechnik GmbH, Koaserbauer Str. 16 A-4810 Gmunden, Austria.		
Grant Spira Condensing Wood Pellet Boiler 6-26kW model number WPS626 and 9-36kW model number WPS936.	Instruction manual reference "IRL NO.012 Rev; 1" dated April 2012.	6mm wood pellets ⁽¹⁾ .
Manufactured by Grant UK Ltd, Hopton House, Hopton Industrial Estate, Devizes, Wiltshire, SN10 2EU.		
Greenflame 28 Pellet Boiler.	Instruction manual reference "Installation & Operation Manual V.2.1" dated 07/12.	6mm wood pellets (1).
Manufactured by Trianco Limited, Thorncliffe, Chapletown, Sheffield, S35 2PH.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
Тиерисе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Guntamatic Biocom and Powercorn 50 and 75.	The manufacturer's instruction manual reference "GUN/BIO/OP/ VI/0709" dated 29/7/09.	Wood pellets with a diameter of 6mm and a length of between 10 and 30 mm ⁽¹⁾ .
GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.		
Guntamatic Biocom and Powercorn 100.	The manufacturer's instruction manual reference "GUN/BIO/OP/VI/0709" dated 29/7/09.	Wood pellets with a diameter of 6mm and a length of between 10
Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.		and 30 mm, or wood chip less than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30 (1).
Guntamatic Powerchip 50 and 75.	The manufacturer's instruction manual reference "GUN/POW/OP/VI/0709" dated 29/7/09.	Wood pellets with a diameter of 6mm and a length of between 10
Manufactured by Guntamatic Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.		and 30 mm ⁽¹⁾ .
Guntamatic Powerchip 100.	The manufacturer's instruction manual reference "GUN/POW/OP/VI/0709" dated 29/7/09.	Wood pellets with a diameter of 6mm and a length of between 10
Manufactured by GUNTAMATIC Heiztechnik GmbH A-4722 PEUERBACH Bruck 7, Austria.		and 30 mm, or wood chip less than 35% moisture content and meeting ÖNORM M 7133:1998 size class G30 (1).
Hamont CATfire 350 USZI pellet boiler fitted with CATfire 300 cyclone.	The manufacturer's operating instruction reference "Operating Manual for Boilers CATfire 150-500kW" effective from 1/1/2008.	Wood pellets with a diameter of 6mm and a maximum length of 30 mm ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hamont Contracting and Trading, spol. s.r.o., Sedliste 227, postal code 739 36, district Frýdek-Mistek, Czech Republic.		
Hampstead 8, Hampstead LS 8, Hampstead XLS 8, Belgravia 8, Barrington 8, Petworth 8 and Flatford 8 stoves.	Instruction manual reference "CH8K — V12" dated 31 October 2011. The appliance must be fitted with a system that prevents closure of the air controls further than 40mm from open and with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs (1).
Manufactured by Chesneys Limited, 194-200 Battersea Park Road, London, SW11 4ND.		
Handöl 31, Handöl 31A, Handöl 32, Handöl 32A, Handöl 33T, Handöl 34T, Handöl 35T,Varde Ovne Look 1, Varde Ovne Look 2, Varde Ovne Look 3.	The manufacturer's installation instructions IAV SE/EX 0811-4 511941 Lighting instructions BAV SE/EX H30 511942. A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.	Untreated dry wood with less than 20% moisture (1).
Manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden.		
Handöl 50, Handöl 51, Handöl 52, Handöl 52T, Handöl 53, Handöl 54, Handöl 54T, Handöl 51L,Varde Ovne S1, Varde Ovne S2, Varde Ovne S3.	The manufacturer's installation instructions IAV SE/EX 0737-4 511866 Lighting instructions BAV SE/EX 0717-1 511865. A permanent stop must be in place on the air inlet to prevent closure beyond the 45% open position.	Untreated dry wood with less than 20% moisture (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by NIBE AB Box 134, 285 23 Markaryd, Sweden.		
Harrie Leenders Cylon; Harrie Leenders Doran 160; Harrie Leenders Doran 190; Harrie Leenders Fuga S; Harrie Leenders Fuga eL; Harrie Leenders Stor; Harrie Leenders Signa.	The instruction manual reference "Supplementary Instructions Amended June 2010". The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 15mm open position.	Wood logs (1).
Manufactured by Harrie Leenders, Industrieweg 25, 5688 DP Oirschot, The Netherlands.		
HDG Compact models 25/35 (25 kW, 35 kW) wood chip and pellet boilers.	The manufacturer's operating instructions for the HDG Compact 25/35 with HDG Hydronic reference "HDG Compact Version V01" of April 2009.	Wood chips or wood pellets (1).
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Compact models 50/65 (50 kW, 65 kW) wood chip and pellet boilers.	The manufacturer's operating instructions for the HDG Compact 50/65 with HDG Hydronic reference "HDG Compact Version V03" of April 2009.	Wood chips or wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
•	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
84323 Massing, Germany.		
HDG Compact model 80 (80 kW) wood chip and pellet boiler.	The manufacturer's operating instructions for the HDG Compact 80 with HDG Hydronic reference "HDG Compact Version V03" of April 2009.	Wood chips or wood pellets (1).
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	7 pm 2009.	
HDG Compact model 100 (100 kW) wood chip and pellet boiler; HDG Compact model 150, 200 (150 kW, 200 kW) wood chip and pellet boiler with model HDG 3113 cyclone.	The manufacturer's operating instructions for the HDG Compact 100/150/200 reference "HDG Compact 100-200 Version V1" of July 2008.	Wood chips or wood pellets ⁽¹⁾ .
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		
HDG Euro models 30, 40 and 50 (30 kW, 40 kW and 50 kW) wood log boilers.	The manufacturer's operating instructions for the HDG Euro 30/40/50 with Lambda Control 1 reference "HDG Euro V3.0 with HDG Lambda Control 1 Version V1" of June 2008.	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture
Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.		content of 20% (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
HDG Navaro models 20, 25 and 30 (20 kW, 25 kW and 30 kW) wood log boilers. Manufactured by HDG Bavaria, Gesellschaft mit beschränkter Haftung (GmbH) Siemensstrasse 22, 84323 Massing, Germany.	The manufacturer's operating instructions for the HDG Navora 20/25/30 with Lambda Control 1 reference "HDG Navora 20/25/30 with HDG Lambda Control 1 Version V2" of June 2008.	Split wood logs of 500 mm length and maximum edge length of 120 mm and a residual moisture content of 20% (1).
Heat Design TR5c inset stove.	Instruction manual reference "TRc Issue 02" dated 04/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 3.5mm open position.	
Heat Design TR5iT Taper inset stove.	Instruction manual reference "TRiT Issue 01" dated 04/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 5mm open position.	
Heat Design TR6c Wide inset stove.	Instruction manual reference "TRc Issue 02" dated 04/12.	Wood logs (1).
Manufactured by Charlton & Jenrick Ltd, Unit D, Stafford Park 2, Telford, Shropshire, TF3 3AR.	The appliance must be fitted with a system that prevents closure of the secondary air control slots beyond the 9mm open position.	
Herz BioFire BF 500, BF 600, BF 800, and BF 1000.	The instruction manual "Operating instructions HERZ BioFire 500 — 1000 Biocontrol" Reference "Betriebsanleitung Biofire 500-1000 Biocontrol Englisch V1.2.doc".	Wood chips and pellets

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Herz Engietechnik GmbH, Herstrabel, 7423 Pinkafeld, Austria.		
Herz Firematic FM 80 and Herz Firematic FM 100. Manufactured by Herz Engietechnik GmbH, Herstrabel, 7423 Pinkafeld, Austria.	The assembly and installation instructions "HERZ firematic 20 — 101 BioControl" Reference "04.001", installation instructions "Herz Firematic (1Ph) 20-101", as well as the operating instructions "HERZ firematic 20 — 101 BioControl" reference "Betriebsanleitung firematic 20-101 BioControl Englisch V 2.53.doc".	Wood chips and pellets (1)
Heta Scanline 500D, 510D, 520D and 530D wood burning stoves.	The instruction manual reference "Pevex1005/AH/ver2" and dated June 2011.	Dry wood logs (1).
Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Heta Scanline 7D, 7AD, 7BD, 7CD and 7DD wood burning	The instruction manual reference "Pevex1006/AH/ver2" dated June 2011.	Dry wood logs (1).
Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS.	The appliance must be fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	
Highlander 5 Clean Burn.	The manufacturer's instruction manual "Highlander. The Dunsley-Enviroburn-5.	Wood logs conforming to BS EN 13240:2001
Manufactured by Dunsley Heat Ltd, Bridge Mills, Huddersfield,	Clean Burn Stove Installation and operating instructions, D12-01-09, D060-01-09, D13-01-09, D12-12-08."	√.

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Holmfirth, West Yorkshire, HD9 3TW.		
Highlander 7 Enviroburn Solo multi-fuel stove (product codes 00325,	Installation and operating instructions manual reference "ENVIRO 7 DB001" dated 15/6/2012.	Dry wood logs (1).
00326 and 00327).	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air-	
Manufactured by Dunsley Heat Limited, Bridge Mills, Huddersfield Road, Holmfirth, Huddersfield, HD9 3TW.	wash beyond 2mm. Four fixed 5mm diameter air holes are provided for the tertiary air supply.	
Horse Flame Little Artemis model number HF277-SE wood	Instruction manual reference "AL905-SE/UK-NI-ROI/V2-D.18-07-12" dated July 2012.	Wood logs (1).
burning stove.	The appliance must be fitted with a mechanical stan to prevent closure of the secondary air.	
Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	stop to prevent closure of the secondary air control beyond the 3mm open position.	
Horse Flame Precision 1 model number HF905-SE.	The instruction manual reference "HF905/UK-NI-ROI/V2.1-06-11" dated June 2011.	Wood logs (1).
Manufactured by Hi- Flame Fireplace UK Ltd, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	
Horse Flame Precision II model number	Instruction manual reference "HF907-SE/UK-NI-ROI/V3-D. 14-07-12" dated July 2012.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

 Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
HF907-SE wood burning stove. Manufactured by Hi-Flame Fireplace UK Limited, Unit 5A, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air.	
Hothouse 4SE stove.	Instruction manual reference "HH468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	
Hothouse 06C inset stove.	Instruction manual reference "HH06C" dated 26/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Hothouse 6SE stove.	Instruction manual reference "HH468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	
Hothouse 8SE stove.	Instruction manual reference "HH468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Estate, Naas Road, Dublin 12, Ireland.		
Hothouse 11C inset stove.	Instruction manual reference "HH11C" dated 26/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Hotpod Unlimited; Hotpod Limited Edition.	The instruction manual reference "Version 3" dated June 2011.	Wood logs (1).
Manufactured by Hotpod LLP, PO Box 137, St Ives, Cornwall, TR26 2WW.		
The Hoval AgroLyt 20, 25, 35, 45 and 50.	The manufacturer's technical information and installation instructions dated January 2006, reference 4 205 194/00 and 4 205 193/00 dated	Wood logs with less than 20% moisture (1).
Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.	reference 4 205 194/00 and 4 205 193/00 dated June 2006.	
Hoval BioLyt Wood Pellet Boiler.	The instruction manual reference 'Hoval Operating Instructions, wood pellet heating	Wood pellets (1).
Manufactured by Hoval Ltd, Northgate, Newark, Nottinghamshire, NG24 1JN.	boiler BioLyt (50,70,120,140,160) dated 3/7/2008 and "Technical information assembly instructions" dated 3/10/2009.	
The Hoval BioLyt 50 Wood Pellet Boiler (49kW thermal output).	The manufacturer's technical information and installation instructions dated October 2005, reference 4 204794/00, and operating instructions dated January 2006, reference 4 204 793/01.	Wood pellets (1).
Manufactured by Hoval AG, Austrasse		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
70, 9490 Vaduz, Liechtenstein.		
The Hoval BioLyt 50 and 70 models.	The manufacturer's technical information and installation instructions dated June 2007, references 4 204 794/01 and 4 204 793/02.	Wood pellets (1).
Manufactured by Hoval AG, Austrasse 70, 9490 Vaduz, Liechtenstein.		
Hoval BioLyt 160 pellet boiler.	The instruction manual reference 'Hoval Operating Instructions, wood pellet heating boiler BioLyt (50,70,120,140,160) dated	Wood pellets. (1).
Manufactured by Hoval Ltd, Northgate, Newark, Nottinghamshire, NG24 1JN.	3/7/2008 and "Technical information assembly instructions" dated 3/10/2009	
Hoval Forester MGS 150, 180, 240, 300, 360, 450, 550, 700, 900 boilers.	The relevant instruction manual reference "Hoval Forester MGS_MMXXXv1" (where XXX is the unit size for example 150) dated July 2011.	Wood pellets or wood chips following CEN/TS 14961 (1).
Manufactured by Schmid AG, Wood firing systems PO Box 42, CH-8380 Eschikon Switzerland.		
Hoval Forester UFS 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600.	The instruction manual reference "Forester UFS" dated November 2009.	Wood pellets or wood chips following CEN/TS 14961 (1).
Manufactured by Schmid AG, Wood firing Systems, PO Box 42, CH-8360 Eschlikon, Switzerland.		
The Hoval STU 150, 200, 250, 300, 350, 425 and 500.	The manufacturer's technical information and installation instructions dated November 2007,	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Hoval UK Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN.	reference STUman/01, or dated June 2008, reference STU/man/01/1.	
The Hoval STU 600, 800 and 1000. Manufactured by Hoval UK Ltd, Northgate, Newark-on-Trent, Nottinghamshire, NG24 1JN.	Installation and operation manual referenced STU/man/01 dated 11/07 or the installation and operation manual referenced STU/man/01/1 dated June 2008.	Wood pellets (1).
HSV 50 + WTH 45, 49 or 55; HSV 80 + WTH 70 or 80; HSV 100 + WTH 100.	The manufacturer's installation manual version 44 for Wood Chip and Pellet Stoves, Type HSV 30-100. Reference "BA HSV30-100 RA/RAP V44 0608".	Wood chips or wood pellets (1).
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.		
Hunter Herald 4. Manufactured by Hunter Stoves	Instruction manual reference "JINHH04 revC" dated 22/09/2011 and "JINHH04&HHC05 Slider Stop revA" dated 22/07/11.	Wood logs (1).
Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Hunter Herald 5 Compact. Manufactured by Hunter Stoves Limited, Unit 6, Old	Instruction manual reference "JINHHC05 revC" dated 22/09/2011 and "JINHH04&HHC05 Slider Stop revA" dated 22/07/11.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	
Hunter Herald 5 Slimline.	Instruction manual reference "JINHHW05 revC" dated 22/09/2011.	Wood logs (1).
Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.		
Hunter Herald 6.	Instruction manual reference "JINHH04 revC" dated 22/09/2011.	Wood logs (1).
Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	uateu 22/09/2011.	
Hunter Herald i4.	Instruction manual reference "JINHVR04 Rev E" dated 02/12/11 and instruction manual	Wood logs (1).
Manufactured by Hunter Stoves	"JINHVR04SCK revB" dated 05/12/11.	
Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	The appliance must be fitted with "smoke control area kit JHVR0401".	
The Huntingdon 25 clear door (model number 7057) and	The manufacturer's instruction manual, reference "PM 249 Issue 1".	Untreated dry wood (1).
Huntingdon 25 tracery door (model number 7058).	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 75% open position.	
Manufactured by Stovax Ltd, Falcon Road, Sowerton Industrial Estate, Exeter, Devon EX2 7LF.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

T: 1	C. Ive	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
The Hwam Beethoven, Hwam Beethoven H, Hwam Mozart, Hwam Ravel, Hwam Vivaldi, Hwam 30 (4.5 kW nominal thermal output)	Euroheat Distributors (HBS) Limited's operational instructions dated November 2006, reference IN1 141 Ed B. The appliance must be fitted with a mechanism to prevent closure of the air wash/secondary air control	Untreated dry wood (1).
Manufactured by HWAM Heat Design AS Nydamsvej 53, 8362 Hørning, Denmark.		
The Insert 50 Crystal, Insert 70 and Insert 80 Crystal.	The instruction manual reference "6096801-Rev.17" dated 22nd December 2010.	Wood logs (1).
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 40% open position.	
Insert 100 Crystal.	The instruction manual reference "6096801-Rev.17" dated 22nd December 2010.	Wood logs (1).
Manufactured by, LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Instyle 400; Instyle 550.	The instruction manual reference "Instruction_manual_Instyle_1209_ENG".	Wood logs (1).
Manufactured by Dik Geurts Haardkachels BV; Industrieweg Oost 11, 6662 NE Elst (Gld), The Netherlands.		
Italy Built In.	The instruction manual reference "7095401 Rev.02" dated 13/12/2010.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Italy Termo DSA;	The instruction manual reference "7095802 Rev.06" dated 01/02/2011.	Wood logs (1).
Termosuprema Compact DSA.		
Manufactured by LaNordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Ivanhoe JS5000 multifuel.	Instruction manual reference "Ivanhoe multi- fuel stove instruction manual Issue 1" dated June 2012.	Wood logs (1).
Manufactured by James Smellie Limited, Unit N, Leona Industrial Estate, Nimmings Road, Halesowen, West Midlands B62 9JQ.	Julie 2012.	
Jetmaster 18f stove.	The instruction manual reference "106870/18f/60f/Issue No.5" dated "June	Dry wood logs (1).
Manufactured by Jetmaster Fires Ltd, Unit 2, Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	2011".	
Jotul F100 Stove.	The Instruction manual reference "129980" dated September 2002 and smoke control	Wood logs (1).
Manufactured by Jotul UK, Unit 1 The IOC Centre, Nash Road, Park Farm, Redditch,	area modification reference "UK F100 SC appendix" dated 2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Worcestershire, B98 7AS.	The appliance must be fitted with a permanent stop that prevents the closure of the secondary air control beyond the 50% open position.	
Jotul F162, F163, F262 and F263. Manufactured by Jotul UK Limited, 1 The IO Centre, Nash Road, Redditch, B98 7AS.	Instruction manual reference "Jotul F162/F162C/F163 Manual Version Po6" dated January 2011 and Supplementary instruction manual "Jotul F162/F163/262/263 SMOKE" dated 01/01/2012. The appliance must be fitted with a mechanical stop to prevent secondary air control closure	Wood logs (1).
Jydepejsen Country 510 and 760 5kW stoves.	beyond the 20% open position. The instruction user manual "Country001" reference "Jydepejsen A/S — June 2011" dated June 2011.	Wood logs ⁽¹⁾ .
Manufactured by Jydepejsen A/S, Ahornsvinget 3-7, Nr.Felding, DK-7500, Holstebro, Denmark.	A permanent stop must be fitted to the secondary air control such that it cannot be closed less than 35%.	
KARA KW990 woodchip boiler. Manufactured by KARA Energy Systems B.V., P.O. Box 570, 7600 AN Almelo, Plesmanweg 27, 7602 PD Almelo, The Netherlands.	Instruction manual reference "Maintenance and Operation Guide KARA Wood Fired Boiler Version 2012.02" dated 26/07/2012.	Woodchip (1).
KÖB Pyromat-DYN (KPM-DYN) 45, 65, 85. Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.	The instruction manual reference "ID 103689-L English" dated 01.01.2005 and instruction manual "ID: 103708-G English".	Wood logs (up to 0.5m) and off cuts of natural timber, wood chips and pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
KÖB Pyromat-ECO (KPM-ECO) models 35, 45, 55, 65, 75, 85.	The instruction manual reference "ID 104646-D English" dated 01.01.2005 and instruction manual "ID: 104642-B English".	Wood logs (up to 0.5m) and off cuts of natural timber (1).
Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.		
KÖB Pyromat-ECO (KPM-ECO) models 61, 81, 101, 151.	The instruction manual reference "ID 104646-D English" dated 01.01.2005 and instruction manual "ID: 104642-B English".	Wood logs (up to 1.0m) and off cuts of natural timber (1).
Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.		
KÖB Pyrot (KRT) models 100, 150, 220, 300, 400, 540.	The instruction manual reference "ID 104654-H English" dated 01.01.2005 and instruction manual "ID: 106811-H English".	Wood chips or wood pellets (1).
Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.		
KÖB Pyrtec (KPT) models 390, 530, 720, 950, 1250.	The instruction manual reference "ID 104661-F English" dated 01.01.2005 and instruction manual "ID: 105174-F English".	Wood chips or wood pellets (1).
Manufactured by Viessman Ltd, Hortonwood 30, Telford, Shropshire, TF1 7YP.	The appliance must be fitted with multi-cyclone dedusters.	
Kooga Cleanburn Stove.	The instruction manual reference "KCB 04/10A" dated April 2010.	Wood logs (1).
Manufactured by Percy Doughty &		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Co; Imperial Point, Express Trading Estate, Stonehill Road, Farnworth, Bolton, BL4 9TN.		
KOZ550, 639kW pellet boiler.	The appliance must be used with a Glosfume model BMF 208 ceramic particulate filter.	6mm diameter wood pellets ⁽¹⁾ .
Manufactured by Kayalioglu Kasabasi (Izmir-Istanbul Yolu Uzeri), PK23 Akhisar/ Manisa, Turkey.	The Green Energy Engineering Ltd (GEE) KOZ550 pellet boiler owner/operator's manual reference version 1A 2010 dated December 2010.	
Mainsa, Turkey.	The Glosfume Ltd maintenance and instruction manual for Glosfume BMF Biomass filter units (50 to 1000kW) version AEE001-VER4 dated December 2010.	
KP12, KP22 and KP62 wood pellet boilers. Manufactured by PONAST spol. s r.o., Na Potuckách 163, 757 01 Valaπské Mezirící, Czech Republic.	Service manual reference "QPP051-2" dated 25/05/2012 and instructions for operation manual "QPP049-3" dated 25/05/2012.	Wood pellets (1).
KWB Easyfire EF2 S/GS/V 8, 12, 15, 22, 25, 30 and 35 wood pellet boilers.	Operation manual reference "B KWB Easyfire EN, 05.2011" dated 05 2011 and installation manual "M KWB Easyfire, 05.2011" dated 05/2011.	Wood pellets (1).
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

 Fireplace	Conditions	
,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
KWB Multifire 15, 25, 30, 40, 50, 60, 80, 99 and 100 wood-pellet and wood-chip fired boilers.	The fireplace(s) must be installed, maintained and operated in accordance with the manufacturer's instructions dated August 2003, reference BA-USV 0803.	Wood chips and wood pellets (1).
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
KWB Multifire USV 49.5kW wood chip and wood pellet boiler.	Instruction manual reference "BA Multifire 06.2010" dated June 2010.	Wood chips and wood pellets (1).
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
The KWB TDS Powerfire 130, 240 and 300.	The manufacturer's instructions dated 14 May 2008, reference BA TDS-05.2008, including specification of recommended fuels.	Wood pellets or wood chips (1).
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Margarethen an der Raab, Austria.		
The KWB TDS Powerfire 150.	The manufacturer's instructions dated August 2005, reference BA TDS — 0805.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit Beschränkter Haftung (GmbH), Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
Lin-ka H 1500 Hot Water Boiler fitted with either a mono- cyclone (type LIN- KA 2000) or a multi- cyclone (type LIN-KA 3x2).	The instruction manual reference "LIN-KA H 1500 Hot Water Manual/Ver. 2005/Rev. 1.10" dated 27/01/2010.	Wood pellets of maximum 8mm diameter (1).
Manufactured by LIN- KA Maskinfabrik A/ S, Nylandsvej 38, DK-6940 Lem St. Denmark.		
The Little Thurlow wood burning stove.	The manufacturer's instructions dated 30 June 2007, issue No. 3.	Seasoned logs of less than 20% moisture and
Manufactured by Town and Country Fires Pickering, North Yorkshire.		of a maximum length of 350mm ⁽¹⁾ .
Little Wenlock Classic SE Wood Fuel Stove.	Operating instructions dated 19 December 2008, reference N00471AXX Rev 001 DP 081219.	Dry and split wood logs of a maximum length of 25cm and a
Manufactured by Aga, Station Road, Ketley,	001217.	maximum diameter of 10cm (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Telford, Shropshire, TF1 5AQ.		
Lotus Liva 1, Liva 2, Liva 3 and Liva 4G stoves.	The instruction manual "Mounting and User Instructions Lotus-Liva series Stoves" Version 4 dated January 2010.	Wood logs (1).
Manufactured by Lotus Heating Systems A/S; Agertoften 6, 5550 Langeskov, Denmark.		
Lotus Sola, Sola S, Sola M and Sola MST stoves.	The instruction manual "Mounting and User Instructions Lotus-Sola series Stoves" Version 2 dated January 2010.	Wood logs (1).
Manufactured by Lotus Heating Systems A/S, Agertoften 6, 5550 Langeskov, Denmark.		
The Løvenholm.	The manufacturer's installation and operation manual version 07/08.	Untreated wood with less than 20% moisture
Manufactured by Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.	manual version 07/00.	content (1).
The Løvenholm, Løvenholm Traditional, European and Pedestal Stoves.	The manufacturer's instructions "Løvenholm Multifuel stove installation and operating manual" version 06/09.	Untreated wood with less than 20% moisture content (1).
Manufactured by Hunter Stoves Ltd, Unit 6, Old Mill Industrial Estate, Stoke Canon, Exeter, Devon EX5 4RJ.		
Loxton 3 stoves.	Instruction manual reference "Mendip Stoves Ltd, 2012, ver 3" dated July 2012.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	The appliance must be fitted with a permanent stop to fix the secondary air control such that it cannot be closed more than 25% open.	
Loxton 5, Churchill 5 and Sqabox Uno stoves.	Instruction manual reference "Mendip Stoves Ltd, 2012, ver 3" dated July 2012.	Wood logs (1).
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	The appliance must be fitted with a permanent stop such that the secondary air "closed position" results in a 2.5mm gap in the two secondary air openings.	
Loxton 6, Loxton 8, Churchill 6, Churchill 8 and Sqabox Duo stoves.	Instruction manual reference "Mendip Stoves Ltd, 2012, ver 3" dated July 2012. The appliance must be fitted with a permanent	Wood logs (1).
Manufactured by Mendip Stoves Limited, Unit H1, Mendip Industrial Estate, Mendip Road, Rooksbridge, Somerset, BS26 2UG.	stop on the secondary air control such that it cannot be closed more than 35% open.	
Ludlow Wood Burning Smoke Exempt Stove (Ludlow Stove SE).	The instruction manual reference "N00529AXX REV:001" dated 13th July 2011.	Dry wood logs (1).
Manufactured by Aga, Station Road, Ketley, Telford, Shropshire, TF1 5AQ.		
Marvic Multifuel Cassette (inset) roomheater.	Instruction manual reference "INK.00.7927" dated 20/12/2011.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Wanders Fires & Stoves, Amtweg 4, Netterden, NL-7077 AL, The Netherlands.	The appliance must be fitted with a modification to the secondary air control to ensure that the air supply holes remain 3mm open when the operator has nominally shut the control.	
Meg 5.0 stove and Sirius 600 Inset stove.	Instruction manual reference "Manual Version 1.3" dated 27/07/2012.	Wood logs (1).
Manufactured by F.E Robinson, (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 10mm open position.	
MEG 7.5/Sirius 750 and MEG 4.5/Sirius 450.	The instruction manual reference "Meg Solid Fuel Stoves Manual (107)" dated 28th January 2011.	Wood logs (1).
Manufactured Meg Stoves, F.E. Robinson (Hooton) Ltd, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.		
Mendip SE Wood Burning 5kW Space Heating Stove.	Instruction manual reference "700273 Iss. 2 Rev. 1" dated January 2012.	Wood logs (1).
Manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Mendip SE Wood Burning 8kW Space Heating Stove.	Instruction manual reference "700275 Iss. 2 Rev. 1" dated January 2012.	Wood logs (1).
Manufactured by TR Engineering Limited,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
The Mescoli PB50, PB35, PB28.	The manufacturer's instruction and installation manual reference "SY315EVO P,C,B-COMBIFIRE 2 PB28/35/50 BOILERS"	Wood pellets following ÖNORM M7 135 or DIN plus
Manufactured by MESCOLI CALDAIE S.rI. Caldaie- Termocucine, Via del Commercio, 285 4 1058 Vignola, (MO) Italy.	Edition 1.7 Dated 1/2006.	(DIN 51731) ⁽¹⁾ .
Micromet MEG 7.5 (also known as the Sirius 750); Micromet MEG 4.5 (also known as the Sirius 450).	The instruction manual reference "Micromet Solid Fuel Stoves Manual (24)" dated 16/06/2010.	Dry wood logs ⁽¹⁾ .
Manufactured by Micromet, 125 Bridge St, Birkenhead, Merseyside, CH41 1BD.		
Milan Series 4.	The instruction manual reference "CH4K Milan-V2" dated 18 November 2010.	Wood logs (1).
Manufactured by Chesney's Ltd, 194 — 200 Battersea Park Road, London, SW11 4ND.	The appliance must be fitted with a system to prevent closure of the air control beyond the 25mm open position.	
Milan Series 6.	The instruction manual reference "CH6K Milan-V2" dated 18 November 2010.	Wood logs (1).
Manufactured by Chesney's Ltd, 194 — 200 Battersea Park Road, London, SW11 4ND.	The appliance must be fitted with a system to prevent closure of the air control beyond the 40mm open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
•	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Monaco multifuel Stove, Staub Fonderie- Franco Belge model 1340605. Manufactured by Staub Fonderie- Franco Belge, Rue Orphee Variscotte, BP73, 59660 Merville, France.	The instruction manual reference "1303 — 1" dated 04/05/2010. The appliances must be fitted with a mechanical stop to prevent closure of the secondary air control beyond 4mm from closed.	Wood logs (1).
Morsø-Ø4. Manufactured by MORSØ UK Ltd, Unit 7 — io centre, Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW.	The instruction manual reference "Ø-Collection" dated 01.02.2010 and instruction manual "72000400" dated 01.02.2010. Applies to units manufactured after 01 February 2010.	Wood logs (1).
The Morsø 1400 series consisting of the 1412 and 1442 models.	The manufacturer's instructions dated 10 January 2008, reference 72146800.	Wood logs with less than 20% moisture (1).
Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		
Morsø 1416, 1418, 1446 and 1448 4 kW stoves.	Instruction manual reference "Morsø 1416, 1418, 1446 & 1448. Instruction for Installation and use" dated 31/01/2012. Part No: 72150000.	Wood logs (1).
Manufactured by Morsø UK Limited, Unit 7, The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.		
The Morsø 3100 series consisting of the 3112 and 3142 models.	The manufacturer's instructions dated 4 February 2008, reference 72311200.	Wood logs with less than 20% moisture (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		
The Morsø 6140 series consisting of the 6140 and 6148 models.	The manufacturer's instructions dated 4 September 2007, reference 72610400.	Wood logs with less than 20% moisture (1).
Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark		
Morsø Model 7600 including Model 7642, 7644 and 7648.	The instructions for installation and use 7600 reference "72762200" dated 14.07.2010.	Wood logs with less than 20% moisture (1).
Manufactured by MORSØ UK Ltd, Unit 7, The io centre, Valley Drive, Swift Valley, Rugby, Warwickshire, CV21 1TW.	The air control must have been altered such that this equates to an increased minimum open position. Reference drawings Morsø 7600-137, 7600-138, 7600-139, 7600-140 and 7600-141.	
The Morsø Owl 3410, 3420 and 3440 for wood burning	The manufacturer's instructions dated 1 January 2000, reference 72345600.	Untreated dry wood which has been split, stacked and air dried; or air dried wood
Manufactured by Morsø Jernestøberi A/ S DK-7900 Nykøbing, Mors, Denmark.		briquettes ⁽¹⁾ .
Morsø S10-40 5 kW stove.	Instruction manual reference "Morsø S10. Instruction for Installation and use" dated 31/01/2012. Part No: 72104000.	Wood logs (1).
Manufactured by Morsø UK Limited, Unit 7, The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	51, 51, 2012. 1 dic 110. 72101000.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Morsø S10-70 5 kW stove. Manufactured by Morsø UK Limited, Unit 7, The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	Instruction manual reference "Morsø S10-70. Instruction for Installation and use" dated 31/01/2012. Part No: 72103000.	Wood logs (1).
Morsø S11-40, S11-42, S11-43 and S11-90 4 kW stoves.	Instruction manual reference "Morsø S11. Instruction for Installation and use" dated 31/01/2012. Part No: 72114200.	Wood logs (1).
Manufactured by Morsø UK Limited, Unit 7, The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.		
Morsø S81-90 4 kW stove.	Instruction manual reference "Morsø S81-90. Instruction for Installation and use" dated 30/01/2012.	Wood logs (1).
Manufactured by Morsø UK Limited, Unit 7, The io Centre, Valley Drive, Swift Valley, Rugby, CV21 1TW.	50/01/2012	
Nestor Martin C23 multifuel stove (7.7 kW);	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1213 Edition B" and dated June 2010.	Untreated dry wood (1).
Nestor Martin C33 multifuel stove (9.2kW);		
Nestor Martin D33 multifuel stove (8kW).		
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Frasnes Lez Couvin, Belgium.		
Nestor Martin "Harmony" H13 multifuel stove (3.5kW nominal thermal output).	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D" and dated January 2007.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin "Harmony" H13 multifuel stove (5kW);	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D5" and dated June 2010.	Untreated dry wood (1).
Nestor Martin "Stanford" S13 multifuel stove (3.5kW).	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin "Harmony" H23 (6kW) and H33 (8kW) multifuel stoves;	>Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D5" and dated June 2010.	Untreated dry wood (1).
Nestor Martin "Stanford" S23 (6kW) SP23 (6kW) S33 (8kW) and SP33 (8kW) multifuel stoves.		
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Frasnes Lez Couvin, Belgium.		
Nestor Martin IN13 Insert multifuel stove (5 kW).	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1214 edition B" and dated June 2010.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin IT 13 multifuel stove (3.5kW).	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1180 Edition D1" and dated June 2010.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	The minimum air bleed flap must be set at a minimum of 14.5mm.	
Nestor Martin R23 multifuel stove (6kW).	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1141 Edition B" and dated November 2006.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.		
Nestor Martin R33 (8kW) multifuel stove.	Euroheat Distributors (HBS) Limited's operation instructions reference "IN 1116 Edition D" and dated January 2007.	Untreated dry wood (1).
Manufactured by Nestor Martin S.A. 11 Rue de Lion, B-5660, Frasnes Lez Couvin, Belgium.	,	
Newark EGTL05.	The instruction manual reference "EGTL05 Version 1.4" dated 5th July 2011.	Wood logs (1).
Manufactured by Elite Group Trading Ltd, Room 1208, Kak Tak	voision 1.7 dated 3th July 2011.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

 Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	
Newton SE Wood Burning 5kW Space Heating Stove.	Instruction manual reference "700504 Iss. 2 Rev 1" dated January 2012.	Wood logs (1).
Manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Newton SE Wood Burning 8kW Space Heating Stove.	Instruction manual reference "700506 Iss. 3 Rev. 2" dated January 2012.	Wood logs (1).
Manufactured by TR Engineering Limited, Unit 7, Newton Chambers Way, Thorncliffe Industrial Estate, Chapeltown, Sheffield, S35 2PH.		
Nordic 350.	Instruction manual reference number "1001"	Wood logs (1).
Manufactured by C DE A Ingenieria Ltda, Jose Miguel Carrera 6, Colina, Santiago, 9361294, Chile.	dated 20/07/2012.	
Nørreskoven MkII.	The instruction manual reference "Cleanburn,	Wood logs (1).
Manufactured by Hunter Stoves Ltd, Unit 6, Old Mill	Nørreskoven MkII, Multifuel Stove. Installation and Operating Instructions, v01.11 "dated January 2011.	
Industrial Estate Stoke Canon, Devon, EX5 4RJ.	The appliance must have a factory fitted stop to prevent closure of secondary air control beyond 40%.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Norvik 5. Manufactured by Elite Group Trading Ltd, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.	The instruction manual reference "EGTL05A Version 1.5" dated 12 September 2011. The appliance must be fitted with a permanent stop to prevent any closure of the tertiary air control.	Wood logs (1).
Octoplus 10 and Octoplus 15 Boiler. Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	The installation instructions: Version 1.1 dated 19/04/2010; Operating manual Version 10.051 Dated 10/05/2010.	Wood pellets (1).
The ÖkoFEN Pellematic PE08, PE12, PE16, PE20, PE25, PE32, PEK12, PEK16, PEK20, PEK25, PES32, PES12, PES16, PES20, PES25, PES32, PESK12, PESK16, PESK20, PESK25, and PESK32.	The manufacturer's instructions dated February 2007, reference PE/HB/001.E.	Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm ⁽¹⁾ .
Manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria.		
The ÖkoFEN Pellematic PE36, PE48, PE56, PEK36, PEK48, PEK56, PES36, PES48,	The manufacturer's instructions dated March 2008, reference PBV 2000 CMP 1.4 (V2.31).	Wood pellets with a maximum diameter of 6mm and a maximum length of 4cm ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
PES56, PESK36, PESK48, PESK56.		
Manufactured by ÖkoFEN Forschungs- und Entwicklungs Ges.m.b.H of Gewerbepark1, 4133 Niederkappel, Austria.		
Olymberyl Baby Gabriel model number HF217-SE.	The instruction manual reference "HF217-SE/UK-NI-ROI/V2.16-06-11" Dated June 2011.	Wood logs (1).
Manufactured by Hi-Flame Fireplace UK Ltd, Unit 7B, Holmes Chapel Business Park, Manor Lane, Holmes Chapel, Cheshire, CW4 8AF.	It must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 3mm open position.	
Optifire 800 Green, Infire 800 Green, wood burning stoves.	Instruction manual reference "07DH8000A" dated 11/11.	Wood logs (1).
Manufactured by Bodart & Gonay Limited, Rue De Lambinon, 3 Harze, Belgium, 4920.	The appliance must be fitted with a "UK kit for smokeless areas OPTI IF 800".	
The Orchard Ovens models: FVR Speciale 80, 100, 110, 110 × 160 and 120; TOP Superiore 100 and 120; GR 100, 120, 140, 120 × 160, 140 × 160, 140 × 180 and 180; OT 100, 120, 140, 120 × 160, 140 × 160, 140 × 160, 140 × 160, 140 × 180 and 180; the Valoriani Piccolo.	The manufacturer's instructions dated 25 October 2004, references:	Untreated dry wood (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:		No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Valoriani of Via Caselli alla Fornace, 213 50066 Reggello, Firenze, Italy.			
	Instruction	Model	
	OOL inst.1	FVR 80	
	OOL inst.2	FVR100	
	OOL inst.3	FVR 110	
	OOL inst.4	FVR 120	
	OOL inst.5	FVR 110×160	
	OOL inst.6	TOP 100	
	OOL inst.7	TOP 120	
	OOL inst.8	GR 100 and OT 100	
	OOL inst.9	GR 120 and OT 120	
	OOL inst.10	GR 140 and OT 140	
	OOL inst.11	GR 120×160 and OT 120×160	
	OOL inst.12	GR 140×160 and OT 140×160	
	OOL inst.13	GR 140×180 and OT 140×180	
	OOL inst.14	GR 180 and OT 180	
	OOL inst.15	Valoriani Piccolo	
Oregon EGTL03.	The instruction manual reference "EGTL03 Version 1.3" dated 5th July 2011.		Wood logs (1).
Manufactured by Elite Group Trading Ltd, Room 1208, Kak Tak Commercial Building, 317-319 Des Voeux Road Central, Hong Kong, 999077.			

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Osby Parca PB2 2000 kW boiler. Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.	Operating & Maintenance manual, PB2 boiler reference "manual PB2_ENG_Rev2_JAN2012" dated January 2012.	Wood pellets (1).
Osby Parca PB2 3000 kW boiler. Manufactured by Enertech AB, Osby Parca Division, PO Box 93, SE-283 22 Osby, Sweden.	Operating & Maintenance manual, PB2 boiler reference "manual PB2_ENG_Rev2_JAN2012" dated January 2012.	Wood pellets, wood chips, wood briquettes
Parkray Caprice 4. Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual reference "JINCAP04 Rev E" dated 02/12/11 and instruction manual "JINCAP04SCK revB" dated 05/12/11. The appliance must be fitted with "smoke control area kit JCAP0401".	Wood logs (1).
Parkray Consort 5 and Parkray Consort 5 Compact. Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.	Instruction manual reference "JINCND05 revC" dated 22/09/2011 and "JINCND05&CNC05 Slider Stop revA" dated 22/07/11. The appliance must be fitted with a permanent stop that prevents closure of the secondary air slider beyond 30% open.	Wood logs (1).
Parkray Consort 5 Slimline. Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate,	Instruction manual reference "JINHHW05 revC" dated 22/09/11.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Stoke Canon, Devon, EX5 4RJ.		
Parkray Consort 7.	Instruction manual reference "JNCS07 revC" dated 22/09/11.	Wood logs (1).
Manufactured by Hunter Stoves Limited, Unit 6, Old Mill Industrial Estate, Stoke Canon, Devon, EX5 4RJ.		
Pelle 5kW stove, Vidar Small 5kW stove and Vidar Medium 7.6kW stove.	The instruction manual reference "8900009004" dated July 2011.	Dry wood logs ⁽¹⁾ .
Manufactured by Dik Geurts Haardkachels BV, Industrieweg Oost 11, 6662 NE Elst (Gld), the Netherlands.		
Pelletmaster PM15, 15 kW wood pellet boiler.	The manufacturer's operating instructions for the HDG Pelletmaster 15/25 reference HDG Pelletmaster Version V1 of October 2006.	Wood pellets (1).
Manufactured by HDG Bavaria Gesellschaft mit beschränkter Haftung (GmbH), Siemensstrasse 22, 84323 Massing, Germany.		
Pelletstar 10, 20, 30, 45 and 60.	The manufacturer's operating instructions dated November 2007, reference V2.2.	Wood pellets corresponding to ÖNORM M7135 of
Manufactured by HERZ Armaturen Ges.m.b.H, Richard- Strauss-Strasze 22,A-1230 Wien, Austria.		6mm diameter ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
PelletTop 15 and PelletTop 25 Boiler. Manufactured by Solarfocus Ltd, Andreas Simetzberger, Solarfocus, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	The installation instructions: Version 020905 dated 02/09/2005. Operating manual: Version 270906 dated 27/09/2006.	Wood pellets (1).
Pevex Bohemia X30, X40, X40 Cube, X50 and X60 multifuel stoves.	The manufacturer's Instruction manual reference "AH/Ver3" and dated July 2010.	Dry wood logs. (1).
Manufactured by Pevex Enterprises Ltd, Unit 16, Seven Acres Business Park, Newbourne Road, Waldringfield, Nr Woodbridge, IP12 4PS		
Pevex Bohemia X40 Inset multi-fuel appliance.	The instruction manual reference "Pevex1004/AH/ver2/" and dated June 2011	Dry wood logs (1).
Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business Park, Waldringfield, Ipswich, IP12 4PS.	The appliance must be fitted with permanent stops that ensure the primary and tertiary air controls do not close beyond 0.5cm open and 2cm open positions respectively.	
Pevex Serenity 40D inset multi-fuel appliance.	The instruction manual reference "Pevex1003/AH/ver2" and dated June 2011.	Dry wood logs (1).
Distributed by Pevex Enterprises Ltd, Unit 16 Seven Acres Business	The appliance must be fitted with permanent stops that ensure the secondary and tertiary air controls do not close beyond 1.1cm open and 2cm open positions respectively.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Park, Waldringfield, Ipswich, IP12 4PS.		
Portway 1.	The instruction manual reference: "Solid Fuel Stoves Manual issued — 20/08/2009 (291) 2".	Wood logs (1).
Manufactured by BFM Europe Ltd, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.	The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 25mm from the left position.	
Portway 2; Portway 3.	The instruction manual reference: "Solid Fuel Stoves Manual issued — 20/08/2009 (291) 2".	Wood logs (1).
Manufactured by BFM Europe Ltd, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.	The appliance must be used with a modification to the secondary air slide which inhibits closure further than the 20mm from the left position.	
Portway Inset.	The instruction manual reference "Solid Fuel Stoves Manual issued — 20/08/2009 (291) 2".	Wood logs (1).
Manufactured by BFM Europe Ltd, Trentham Lakes, Stoke on Trent, Staffordshire, ST4 4TJ.	A modification of the secondary air control must be implemented such that the 20mm from left position is maintained during use. In addition the primary air control must be modified such that the minimum setting allows a bleed of air to pass through.	
Pyroclassic IV.	Instruction manual reference "PYROS 04" dated August 2011.	Wood logs (1).
Manufactured by Pyroclassic Fires Limited, PO Box 28150, Havelock North 4157, Hawke Bay, New Zealand.	duted Mugust 2011.	
PZ 65 RL and PZ 100 RL pellet boilers.	Instruction manual reference "Assembly instruction — Instruction manual — servicing	Wood pellets (1).
Manufactured by Biotech Energietechnik GmbH, Furtmühlstrasse 32,	& cleaning PZ65RL/PZ100RL/PZ101RL" dated July 2012. Reference BTMoBeWe ENG.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
A-5101, Bergheim bei Salzburg, Austria.		
The Quadra-Fire 2100 Millennium Freestanding Wood Burning Stove.	The manufacturer's instructions dated 9 October 2003, reference 250-6931B.	Dry cured untreated wood of maximum size 38.1 cm × 10.16 cm × 5.08 cm (1).
Manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA.		
The Quadra-Fire Cumberland Gap Freestanding Wood Burning Stove.	The manufacturer's instructions dated 8 July 2003, reference 7006-186.	Dry cured untreated wood of maximum size 43.18 cm × 10.16 cm × 5.08 cm (1).
Manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA.		
The Quadra-Fire Yosemite Freestanding Wood Burning Stove.	The manufacturer's instructions dated 4 June 2003, reference 7004-187.	Dry cured untreated wood of maximum size 38.1 cm × 10.16 cm × 5.08 cm (1).
Manufactured by Hearth & Home Technologies 1445 North Highway, Colville, WA 99114, USA.		cm ^ 5.00 cm ".
Rais 2:1 inset stove.	The instruction manual reference "USER MANUAL Rais 2:1 Revision 2". Dated	Wood logs (1).
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	December 2009. Part number 9106510.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
Гиерисе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rais 700 inset stove.	The instruction manual reference "USER MANUAL Rais 700 Revision 0". Dated 2010.	Wood logs (1).
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	MINIOTE Rais 700 Revision 0 . Butea 2010.	
Rais Epoca, Rais Poleo 95 and Rais Poleo 106 stoves.	The instruction manual reference "USER MANUAL Rais Poleo 95 & Rais Poleo 106 Rais Epoca Revision 1". Dated December 2009. Part number 2106510.	Wood logs (1).
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.		
RAIS Q-Tee 57, 65 and 85.	The instruction manual reference "Manual for RAIS Q-Tee Revision 1" dated 28th June 2011 and Supplementary instructions Rais Q-Tee	Dry wood logs (1).
Manufactured by Rais	dated 7th July 2011.	
A/S Industrivej 20, 9900, Frederikshavn, Denmark.	It must be fitted with a mechanical stop to prevent air control closure beyond the 11.7mm open position.	
Rais Rondo Classic and Rais Mino II stoves.	The instruction manual reference "USER MANUAL Rais Rondo & Rais Mino II revision 2". Dated March 2008. Part number 5056510.	Wood logs (1).
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.		
Rais Rondo 92 and Rais Rondo 120 stoves.	The instruction manual reference "USER MANUAL Rais Rondo 92 & Rais Rondo 120 revision 2". Dated December 2009. Part number 4076510.	Wood logs (1).
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	number 40/0310.	
RAIS VIVA 98, RAIS VIVA 98G, RAIS VIVA 120, RAIS	Instruction manual reference "Manual for RAIS Rina, RAIS Viva" dated 29 August 2011 and	Wood logs ⁽¹⁾ .

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
VIVA 120G and RAIS RINA 90 wood burning stoves.	instruction manual "Supplementary Instructions Rais" dated 27 September 2011. The appliance must be fitted with a mechanical	
Manufactured by Rais A/S, Industrivej 20, 9900, Frederikshavn, Denmark.	The appliance must be fitted with a mechanical stop to prevent closure of the air damper beyond the 8.5mm open position.	
Redfyre Kensal 20 flat top (product code RF-EN20M), Redfyre Kensal 33 flat top (product code RF- KEN33M and RF-	The manufacturer's instruction manual dated July 2008 reference PM247 issue 1, and instruction manual dated January 2009 reference PM280 issue 1.	Untreated dry wood (1).
KEN33W).	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	
Manufactured by Redfyre Cookers, Osprey Road, Sowton Industrial Estate, Exeter, Devon, EX2 7JG.		
Rika Como pellet stove.	The instruction manual reference "IN1226 Edition 1" dated June 2011.	6 mm wood pellets (1).
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT — 4563 Micheldorf, Austria.		
Rika Evo Aqua 9 and 15.	The instruction manual reference "J18/HB" dated 27/02/2009.	6 mm wood pellets (1).
Manufactured by SHT Heiztechnik aus Salzburg GmbH, Rechtes Salzachufer 40 A-5101, Salzburg- Bergheim, Austria.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Rika Memo pellet stove.	The instruction manual reference "IN1228 Edition 1" dated June 2011.	6mm wood pellets (1).
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT — 4563 Micheldorf, Austria.		
Rika Pico pellet stove.	The instruction manual reference "IN1230 Edition 1" dated June 2011.	6 mm wood pellets (1).
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT — 4563 Micheldorf, Austria.		
Rika Revo pellet stove.	The instruction manual reference "IN1229 Edition 1" dated June 2011.	6 mm wood pellets (1).
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT — 4563 Micheldorf, Austria.		
Rika Tema 6kW stove.	Instruction manual reference "IN1218 Edition 2" dated January 2012.	Wood logs (1).
Manufactured by Rika Innovative Ofentechnik GmbH, Müllerviertel 20, AT — 4563 Micheldorf, Austria.	2 dated January 2012.	
Rika Topo pellet stove.	The instruction manual reference "IN1227 Edition 1" dated June 2011.	6 mm wood pellets (1).
Manufactured by RIKA Innovative Ofentechnik GmbH Müllerviertel 20 AT —	Lation 1 dated June 2011.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
4563 Micheldorf, Austria.		
Riva 40 Cassette 4.9kW stoves.	The instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010.	Wood logs ⁽¹⁾ .
Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Riva 40 Freestanding, Riva 40 Avanti, Riva 40 Avanti Midi, And Riva 40 Avanti Highline 4.9kW stoves.	The instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010. A permanent stop must be positioned to prevent	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	closure of the secondary air control below the 50% open position.	
Riva 45 Cassette (model numbers RV45 & RV45B) wood burning stoves.	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012.	Wood logs (1).
Manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control below the 50% open position.	
Riva 50 Cassette (model numbers RV50 & RV50B) wood burning stoves.	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012.	Wood logs ⁽¹⁾ .
	A permanent stop must be positioned to prevent closure of the secondary air control below the	

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Stovax Limited, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva 55 Cassette, Riva 66 Cassette, and Riva 66 Avanti Cassette stoves.	Instruction manual reference "PM375 Issue 5" dated June 2012 and instruction manual reference "PM235 Issue 5" dated June 2012.	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva 55 Avanti Midi and Riva 66 Freestanding 8kW stoves.	The instruction manual reference "PM235 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010.	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	
Riva Plus Small (5kW), Riva Plus Midi (6.5kW) and Riva Plus Medium (8 kW) stoves.	The instruction manual reference "PM226 Issue 2" dated August 2009 and smoke control kit instruction manual "PM375 Issue 2" dated January 2010.	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and the primary air control fixed to allow a bleed of air to enter the firebox from underneath the grate.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel
Riva Studio 1 (5kW) freestanding wood stove. Manufactured by Stovax Ltd; Falcon Road, Sowton	The instruction manual reference "PM231 Issue 3" dated June 2009 and smoke control kit instruction manual "PM402 Issue 1" dated November 2009. A permanent stop must be positioned to prevent closure of the secondary air control below the	or fuels: Wood logs ⁽¹⁾ .
Industrial Estate, Exeter, Devon, EX2 7LF.	25% open position.	
Riva Studio 2 (8kW) freestanding wood stove.	The instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual "PM400 Issue 3" dated June 2010.	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	
Riva Studio 1 Cassette (5kW). Manufactured by	The instruction manual reference "PM452 Issue 1" dated June 2010 and smoke control kit instruction manual "PM400 Issue 3" dated June 2010.	Wood logs (1).
Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	
Riva Studio 2 Cassette (8kW). Manufactured by	The instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual "PM400 Issue 1" dated November 2009.	Wood logs (1).
Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 45% open position and the primary air control fixed to prevent full closure to allow a bleed of	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
,	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
	air to enter the firebox at the base of the fuel bed.	
Riva Vision Small (5kW) — Multifuel; Riva Vision Midi (6.5kW) — Multifuel.	The instruction manual reference "PM274 Issue 2" dated October 2009 and smoke control kit instruction manual "PM400 Issue 1" dated November 2009.	Wood logs (1).
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 25% open position and the primary air control fixed to prevent full closure to allow a bleed of air to enter the firebox at the base of the fuel bed.	
Riva Vision Medium (8 kW) — Multifuel.	The instruction manual reference "PM278 Issue 2a" dated October 2009 and smoke control kit instruction manual "PM401 Issue 1" dated	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Rosedale Inset Smoke Control inset roomheater.	Instruction manual reference "Issue No. 04" dated 11.01.2012.	Wood logs (1).
Manufactured by Town and Country Fires Limited, Unit 1Enterprise Way, Thornton Road Industrial Estate, Pickering, North Yorkshire, YO18 7NA.	The appliance must be fitted with a mechanical stop to prevent secondary air control closure beyond the 30% open position.	
Rosedale SC Multifuel Stove.	The "Rosedale Smoke Control Stove Installation and User Instructions Issue 1" dated 1 May 2010.	Wood logs with a maximum of 20% moisture (1).
Manufactured by Town & Country Fires Ltd, 1 Enterprise Way, Thornton Road	The appliance must be fitted with a mechanical stop to prevent closure of the secondary air control beyond the 50% open position.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Industrial Estate, Pickering, North Yorkshire, YO18 7NA.		or facis.
Royal Klima 18 Idro wood pellet stove boiler.	Instruction manual reference "cod. 0047700880" dated 09/2011 and supplementary information "Clean Air Act 1993 and Smoke	Wood pellets (1).
Manufactured by Palazzetti Lelio S.p.A, Via Roveredo 103, Porcia (PN), 33080, Italy.	Control Areas" reference 004723000 dated 01/2012.	
Saltfire Ecoview 5, Fireglow Eco 5, and Ecowarm Crystal 5 stoves.	Instruction manual reference "Evoview5 Manual 1.0" dated 15/12/2011. The appliance must be fitted with a mechanical	Wood logs (1).
Manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, Dorset, BH20 4DY.	stop to prevent closure of the tertiary air beyond the 4mm open position.	
Saltfire Ecoview 12, Fireglow Eco 12, and Ecowarm Crystal 12 stoves.	Instruction manual reference "Evoview12 Manual 1.0" dated 15/12/2011. The appliance must be fitted with a mechanical	Wood logs (1).
Manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, Dorset, BH20 4DY.	stop to prevent closure of the tertiary air beyond the 4mm open position.	
Saltfire Oslo-Eco, Fireglow Eco 7 and Ecowarm Crystal 6.	The instruction manual reference "ECO7operation-Revision 2A" dated 24.01.2011.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Saltfire Stoves Ltd, Units 1 and 2, The Omega Centre, Sandford Lane, Wareham, BH20 4DY.		
San Remo 4SE stove.	Instruction manual reference "SR468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 5mm open.	
San Remo 6SE stove.	Instruction manual reference "SR468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 75% from closed.	
San Remo 8SE stove.	Instruction manual reference "SR468SE" dated 25/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a system to prevent closure of the secondary air control beyond 25% from closed.	
The Scan Anderson 4-5.	The manufacturer's instructions dated 15 November 2007, entitled "Scan Andersen 4-5", reference 09/05-GB.	Untreated dry wood (1).
Manufactured by Krog Iversen 7 Co., A/S DK-5492 Vissenbjerg, Denmark.	A permanent stop must be in place on the secondary air inlet to prevent closure beyond 20mm.	
Scan DSA 7-5 wood-burning Inset roomheater.	Instruction manual "Instructions for installation and use: SCAN DSA 6 & DSA 7-5" Edition 17.09.2010 — GB, supplement "DSA 7-5 — UK smoke control areas" reference "DSA 7-5	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	C 1	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Scan A/S PO Box 20, 5492 Vissenberg, Denmark.	SMOKE" dated 01/01/2012, and instructions for installation (including directions for use and stoking) reference "Edition 05.10.2010 — GB".	
	The appliance must be fitted with a mechanical stop to prevent closure of the air wash control lever beyond the 50% open position.	
Schmid UTSK 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600 kW.	The manufacturer's instruction manual "UTSK-ABC.22-AME-S-PPU" dated 25.09.2008 (where ABC is model number ie. 180, 240, 300, 360, 450, 550, 700, 900, 1200, 1600).	Wood pellets or wood chips following CEN/TS 14961:2005 (1).
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.		
Schmid UTSL 30, 40, 50, 65, 80, 110, 150 kW.	The manufacturer's instruction manual reference "Operating Manual Wooden Chips and Pellets Plant. Lignumat UTSL" dated 23.12.2004.	Wood pellets or wood chips following CEN/TS 14961:2005 (1).
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon, Switzerland.	23.12.2004.	
Schmid UTSP 180, 240, 300 kW.	The manufacturer's instruction manual "UTSK — ABC22-AME-S-PPU" dated 25.09.2008 (where ABC is model number i.e.	Wood pellets following CEN/TS 14961:2005 (1).
Manufactured by Schmid AG Woodfiring Systems, PO Box 42, CH-8380 Eschikon.	23.09.2008 (where ABC is model number i.e. 180, 240, 300).	14701.2003 ``.
Schmid UTSR 150, 180, 240, 300, 360, 450, 550, 700, 900 kW	The manufacturer's instruction manual "UTSR — ABC22-AME-S-PPV" dated 25.09.2008 (where ABC is model number i.e. 150, 180, 240, 300, 360, 450, 550, 700, 900)	Wood pellets or wood chips following CEN/TS 14961:2005 (1).
Manufactured by Schmid AG		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Woodfiring Systems, PO Box 42, CH-8380 Eschikon.		
Serrano 5, York Midi; Monterrey 6 Stoves.	The instruction manual reference "09TJD" dated 01 2010.	Wood logs (1).
Manufactured by Broseley Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	A system that prevents the closure of the secondary air flaps to be less than 8mm open position must be fitted.	
Serrano 5 Multi Fuel and Monterrey 6 Multi Fuel Stoves.	The Instruction manual reference "TJ09C" dated 21st December 2009.	Wood logs (1).
Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 8mm open position.	
Serrano 7 Multi Fuel stove.	The Instruction manual reference "TJ09C" dated 21st December 2009.	Wood logs (1).
Manufactured by Broseley Fires Ltd, Knights Way, Battlefield Enterprise Park, Shrewsbury, Shropshire, SY1 3AB.	The appliance must be fitted with a system that prevents the closure of the secondary air flaps to be less than 10mm open position.	
Sirius Traditional Stove.	Instruction and Operating Instruction manual reference "v173 of 09/11/2010" dated 09/11/2010.	Wood logs (1).
Manufactured by Tianjin Focus Arts & Crafts Co, Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan	07/11/2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
District, Tianjin, P.R. China 300350.		
The Stockton 3 flat top (product code 7118) Stockton 4 flat top (product code 7101 and 7102) and Stockton 5 flat top (product code 7127) Stockton 5 midline (product code 7130) Stockton 6 flat top (product codes 7100 and 7162) Stockton 6 Highline (product code 7117) and Stockton 7 flat top (product codes 7120 and 7163).	The manufacturer's instruction manual dated July 2008, reference "PM227 ENG Issue 2", and instruction manual dated January 2009, reference "PM271 Issue 2". A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood (1).
Manufactured by Stovax Ltd., Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF.		
The Stockton 5 flat top (model number 7119) Stockton 5 Canopy (model number 7160) and Stockton 5 Midline (model number 7133).	The manufacturer's instructions reference, "PM176 — issue 4". A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood (1).
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF.		
Stockton 7 Inset Convector (product	The manufacturer's instruction manual dated May 2008, reference "PM230 Issue 1", and	Untreated dry wood (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
codes 7125F and 7125C).	instruction manual dated January 2009, reference "PM281 Issue 1".	
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon EX2 7LF.	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	
Stockton Milner (4.6 kW) inset stove — smoke control version.	The instruction manual reference "PM416 Issue 1" (June 2010) and smoke control kit instruction manual "PM501 Issue 1" (June 2010).	Wood logs (1).
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Stoven Mayfair SE & Stoven Kensington SE 5kw Wood Burning Stoves.	Instruction manual reference "3-4" dated 27 November 2011. The appliance must be fitted with mechanical	Wood logs (1).
Manufactured by Ciang Stoves Limited, South Chuangye Road, (Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China 455000.	stops to prevent closure of the secondary air control beyond the 25% open position and the tertiary air beyond the 1mm open position.	
Strebel SRP TR 90, 90 kW output pellet boiler.	The Strebel SRP TR 90 pellet boiler installation manual reference "Installation and operation instructions for special pellet-furnace" version 09:2010.	6mm diameter wood pellets (1).
Manufactured by Strebel Ltd, 1F Albany Park Industrial Estate, Frimley Road, Camberley, Surrey, GU15 7P.	V2010.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Stretton Insert Smoke Exempt Wood Fuel Stove (Stretton Stove SE).	The instruction manual reference "N00530AXX REV:001" dated 12th July 2011.	Dry wood logs (1).
Manufactured by Aga, Station Road, Ketley Telford, Shropshire, TF1 5AQ.		
STU 195 and STU 975.	Instruction manual reference "Installation, Operation and Maintenance Instructions. STU wood-pellet fired hot water boiler skid	Wood pellets (1).
Manufactured by Hoval Limited, Northgate, Newark, Nottinghamshire, NG24 1JN.	assembly STUman CAA (SM)" dated May 2011.	
Suprema, Mamy and Italy Hard Top.	The instruction manual reference "7095701 Rev.09" dated 13/12/2010.	Wood logs (1).
Manufactured by La Nordica Spa, Via Summano 104 M. Precalcino, 36030, Vicenza, Italy.		
Talbott 150-CMH 150 kW output Biomass Air Heater.	The instruction manual for Talbott 150-CMH hand-fed Biomass Air Heater operating package reference "OM-150-CMH version.1"	Softwood, hardwood, medium density fibreboard (MDF) or
Manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.	dated January 2011.	chipboard offcuts ⁽¹⁾ .
Talbott's Automatic Biomass Air Heaters, models T1.5/A, T3/A, T5/A and TM/A.	The manufacturer's instructions reference "T/A JANUARY 1990".	Hardwood or softwood shavings or sawdust (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's Biomass Energy Models C1, C2, C3 and C4.	The manufacturer's instructions dated August 1995 reference "Issue C1000/C/Range".	Chipboard or wood shavings, forestry chips ⁽¹⁾ .
Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's model T75, T150, T300 Biomass Air Heaters.	The manufacturer's instructions dated 1st January 1995 reference — models T75, T150 and T300: "gen/sttech".	Wood offcuts, woodwaste, pellets, chipboard. (1).
Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.		
Talbott's T500 Biomass Air heater (afterburn model).	The manufacturer's instructions dated January 1st 1983 reference A10000.	Wood offcuts, woodwaste, pellets, chipboard (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Formerly manufactured by Talbott's Heating Ltd, and now manufactured by Talbott's Biomass Energy Systems Ltd, Tollgate Drive, Tollgate Industrial Estate, Stafford, ST16 3HS.	The afterburn cycle must last not less than 25 minutes and must come into operation each time the loading door is opened.	
Therminator II 22 and Therminator II 30 Boiler.	The installation instructions: "Version.:11/08/06" dated 07/2006;	Wood pellets (1).
Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006.	
Therminator II 27 and Therminator II 36 Boiler.	The installation instructions: "Version.:11/08/06" dated 07/2006;	Wood logs (1).
Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006.	
Therminator II 40 Boiler.	The installation instructions: "Version.:11/08/06" dated 07/2006;	Wood pellets or wood chips (1).
Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Operating Manual "V8.051" dated 09/2009. Maintenance Instructions: "Ver.:01/09/06" dated 2006.	
Therminator II 49 and Therminator II 60 Boiler.	The installation instructions: "Version.:11/08/06" dated 07/2006;	Wood logs or wood pellets or wood chips
	Operating Manual "V8.051" dated 09/2009.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Solarfocus Ltd, Werkstrasse 1, 4451 St.Ulrich, Steyr, Austria.	Maintenance Instructions: "Ver.:01/09/06" dated 2006.	
Thornhill T3 small.	The instruction manual reference "ED/11/05" dated January 2011.	Wood logs (1).
Manufactured by Thornhill Eco Design Ltd, 58-60 Wincheap, Canterbury, Kent, CT1 3RS.	The appliance must be fitted with an air plate that prevents the tertiary air controller from closing more than 17mm and opening more than 45mm.	
Tiger SuperClean. Manufactured by Tiger stoves, Focus Arts & Crafts Co., Industrial Area Gao Zhuangzi Village, Xin Zhuang Town, Jin Nan District, Tainjin, P. R. China 300350.	The instruction manual reference "INSTALLATION AND OPERATING INSTRUCTIONS document v.148" dated April 2010.	Wood logs (1).
Turbhogar Alfa 80T and 65T, Turbhogar Beta 80T, Turbhogar Delta 80T and 65T, Turbhogar Lambda 80T and 65T, Turbhogar Sigma 80T and 65T, Turbhogar Omega 80T and Turbhogar Tau 80T and 65T fireplace inserts.	The manual of assembly and use reference "RR100920" dated 20/09/2010 and supplementary instruction manual reference "UK100920" dated 20/09/2010. The appliance must be fitted with a system that prevents the full closure of the air control opening so that the air openings remain 3mm (30%) open at the minimum setting.	Wood logs ⁽¹⁾ .
Manufactured by Rofer & Rodi UK Ltd, Rofer & Rodi UK Ltd, Unit 10, Millennium Road, Airedale Business		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Centre, Skipton, North Yorkshire, BD23 2TZ.		
The Twin Heat CS 150i.	The manufacturer's operating instructions dated 17 December 2008, version 6.0.03.	Wood pellets of a maximum length of 30mm and
Manufactured by TWIN HEAT A/S, Nørrevangen 7, DK-9631 Gedsted, Denmark.		diameter of 6mm and conforming to CEN/TS 14961:2005 (1).
The Type USV wood pellet and wood chip fired boilers, model numbers USV-15, 25, 30, 40, 50, 60, 80 and 100	The manufacturer's instructions dated August 2003, reference BA-USV 0803.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St. Margarethen an der Raab, Austria.		
The Type USP wood pellet fired boilers, model numbers USP-10, 15, 20, 25 and 30.	The manufacturer's instructions dated 28 July 2003 reference BA-USP 0703.	Wood pellets (1).
Manufactured by KWB — Kraft und Wärme aus Biomasse Gesellschaft mit beschränkter Haftung (GmbH) of Industriestrasse 235, A-8321 St.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Margarethen an der Raab, Austria.		
Uniconfort EOS 45, EOS 50, EOS 55, EOS 65, EOS 70, EOS 75, EOS 80, EOS 85 fitted with a multi-cyclone.	Instruction manual reference "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets (1).
Manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.		
Uniconfort EOS 90 fitted with a multicyclone.	Instruction manual reference "Uniconfort EOS MANUAL: R1" dated May 2012.	Wood pellets or wood chips ⁽¹⁾ .
Manufactured by Uniconfort srl, Via dell'Industria, 21, 35018 San Martino di Lupari, PD, Italy.		
VarioWIN VA 120 12kW wood pellet boiler.	The installation instruction manual reference "092947/00" dated 01/2010 and operating instruction manual reference "092945/00" dated 01 2010.	Wood pellets, 6mm diameter, length 80% between 15—30mm and a density of at
Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager, Str.20, A-5201 Seerkirchen bei Salzburg, Austria.	unicu o i 2010.	least 1.1kg/dm3 ⁽¹⁾ .
Vesuvio 400 kW automatic pizza oven.	CLM Vesuvio oven instruction manual reference "Instruction and maintenance manual ENGLISH" version Review 0.1 dated	"CalorPan" 100% beech briquette, octagonal section,
Manufactured by CLM srl, Via I Maggio 35, 31043, Fontanelle (Treviso), Italy.		length 260—300mm, width and height 75—90mm manufactured from dried beech sawdust (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
View 3 (3.8 kW) and View 5 (4.9kW) multifuel stoves; View 5 (4.9kW) wood stove. Manufactured by Stovax Ltd, Falcon	The instruction manual reference "PM485 Issue 1" dated June 2010 and smoke control kit instruction manual reference "PM490 Issue 1" dated June 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the	Wood logs (1).
Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	50% open position.	
View 7 (7 kW) inset appliance Product code VW-7NMF.	The instruction manual reference "PM552 — Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM490 Issue 2" dated July 2011.	Wood logs (1).
Manufactured by Stovax Ltd: Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	
7LF. Vista Magnifico SE & Vista Perfetto SE 4.9kw wood burning stoves. Manufactured by Ciang Stoves Limited, South Chuangye Road, (Hanling Industrial	Newman Fireplaces Limited's Instruction manual reference "1-2" dated 24 October 2011. The appliance must be fitted with mechanical stops to prevent closure of the secondary air control beyond the 30% open position and the tertiary air beyond the 50% open position.	Wood logs (1).
(Hanling Industrial Estate), Beiguan Section, Anyang City, Henan Provence, China 455000.		
Vitae 06C inset stove.	Instruction manual reference "VIT06C" dated 26/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Estate, Naas Road, Dublin 12, Ireland.		
Vitae 11C inset stove.	Instruction manual reference "VIT11C" dated 26/07/12.	Wood logs (1).
Manufactured by Heat Design, 30 Hawthorn Road, Western Industrial Estate, Naas Road, Dublin 12, Ireland.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control beyond 20% open.	
Westcott 5SE.	The instruction manual reference "08/51351/0 — Issue 0", dated 07/09/10.	Wood logs (1).
Manufactured by Dimplex, GDC Group Ltd, Millbrook House, Grange Drive, Hedge End Southampton, SO30 2DF.		
Westfire Series One stove and Westfire Series Two stove.	The Westfire WF One and Two series installation manual and operating instructions and supplementary Instruction manual reference "Westfire supplementary instructions	Wood logs (1).
Manufactured by Westfire Tømrervej	June 2011/Version 1" dated 1st June 2011.	
3 DK-6800 Varde, Denmark.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	
The Westfire Uniq 15, 16 and 20 (also known as WF UNIQ 15, 16 and 20).	The manufacturer's instructions dated 2007, reference WF15 — WF16 — WF20 along with supplementary instructions dated 2007, reference 01 wfuk.2207.	Untreated dry wood (1).
Manufactured by Westfire Tømrervej 3 DK-6800 Varde, Denmark.	A permanent stop must be in place on the secondary air inlet to prevent closure beyond 50mm.	
Westfire Uniq 17, Westfire Uniq 18, Westfire Uniq 19, Westfire Uniq 23, Westfire Uniq 23 side	The instruction manual reference "WESTFIRE SUPPLEMENTARY INSTRUCTIONS JUNE 2010".	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Glass and Westfire Uniq 23 Inset. Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	The appliance must be fitted with a mechanical stop to prevent closure of the air slide beyond the 30mm open position.	
Westfire Uniq 21 stove, Westfire Uniq 21 pedestal stove and Westfire Uniq 21 wall hung stove.	The Westfire WF21 installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011.	Wood logs (1).
Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 60% open.	
Westfire Uniq 26 stove, Westfire Uniq 27 stove and Westfire Uniq 28 stove.	The Westfire WF26, WF27, WF28 installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st June 2011.	Wood logs (1).
Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	The appliance must be fitted with a permanent stop to the secondary air slider control to prevent closure more than 20mm from the fully closed position.	
Westfire Uniq 32 Inset stove and Westfire Uniq 32 Freestanding stove.	The Westfire WF23/Uniq23, WF32/Uniq 32 inset stove installation manual and operating instructions and supplementary instruction manual reference "Westfire supplementary instructions June 2011/Version 1" dated 1st	Wood logs (1).
Manufactured by Westfire APS, Tømrervej 3, DK-6800 Varde, Denmark.	June 2011. The appliance must be fitted with a permanent stop to prevent closure of the secondary air control less than 50% open.	
The Windhager Bio Win 90 and 120.	The manufacturer's instructions dated August 2008, reference 092125/00.	Wood pellets (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager-Str. 20, A-5201 Seekirchen bei Salzburg, Austria.		
The Windhager Bio Win 100, 150, 210 and 260.	The manufacturer's instruction manual dated May 2008, reference 0916197/00.	Wood pellets (1).
Manufactured by Windhager Zentralheizung GmbH, Anton-Windhager- Str. 20, A-5201 Seerkirchen bei Salzburg, Austria.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 100;	The instruction manual reference "OOLinst.8 GR 100 and OT 100 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 100.		
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120;	The instruction manual reference "OOLinst.9 GR 120 and OT 120 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 120.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140;	The instruction manual reference "OOLinst.10 GR 140 and OT 140 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 140.		
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 120×160;	The instruction manual reference "OOLinst.11 GR 120×160 and OT 120×160 v2" Dated January 2011.	Untreated wood of less than 20% moisture (1).
Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 120×160.		
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140×160;	The instruction manual reference "OOLinst.12 GR 140×160 and OT 140×160 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Wood Fired Ovens by Jamie Oliver Ltd's OT		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	N. C. 1: . 1
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Valoriani Ristorante 140×160.		
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 140×180;	The instruction manual reference "OOLinst.13 GR 140×180 and OT 140×180 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 140×180.		
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's GR Valoriani Ristorante 180;	The instruction manual reference "OOLinst.14 GR 180 and OT 180 v2" and dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Wood Fired Ovens by Jamie Oliver Ltd's OT Valoriani Ristorante 180.		
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 80.	The instruction manual reference "OOLinst.1 FVR 80 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

	G. Ivi	
Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 100.	The instruction manual reference "OOLinst.2 FVR 100 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110.	The instruction manual reference "OOLinst.3 FVR 110 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 110×160.	The instruction manual reference "OOLinst.5 FVR 110×160 v2" and dated January 2011.	Untreated wood of less than 20% moisture ⁽¹⁾ .
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Casa 120.	The instruction manual reference "OOLinst.4 FVR120 v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Manufactured by Valoriani of Via Caselli alla Fornace,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
212 500((P II	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Piccolo.	The instruction manual reference "OOLinst.15 Valoriani Piccolo v2" and dated January 2011.	Untreated wood of less than 20% moisture (1).
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 100.	The instruction manual reference "OOLinst.6 TOP 100 v2 Dated" January 2011.	Untreated wood of less than 20% moisture (1).
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Wood Fired Ovens by Jamie Oliver Ltd's Valoriani Villa 120.	The instruction manual reference "OOLinst.7 TOP 120 v2 Dated" January 2011.	Untreated wood of less than 20% moisture (1).
Manufactured by Valoriani of Via Caselli alla Fornace, 213, 50066 Reggello, Firenze, Italy.		
Woodpecker 15, 25 and 45 wood pellet boilers.	The instruction manual reference "Europe Issue 4" dated July 2010.	Wood pellets conforming to CEN TS 14961 (1).
Formerly manufactured by Garranlea Renewables Ltd, and now manufactured by Woodpecker Energy UK, Abbey Manor Business Centre,		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Preston Road, Yeovil, BA20 2FJ		
Woodpecker 50kW wood pellet boilers.	Instruction manual reference "Installation and Operating Manual Woodpecker 50 Model Wood Pellet Boiler System Version 2 dated	Wood pellets conforming to CEN TS 14961 (a) (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.	May 2012.	13 1 13 01 (u) .
Woodpecker Thermon 150 boiler.	Instruction manual reference "Thermon Europe Issue 1" dated January 2011.	6mm wood pellets (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2FJ		
Woodpecker Thermon 199 kW pellet boiler.	Instruction manual reference "Issue 2.0" dated February 2012.	6mm wood pellets (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2EN.		
Woodpecker Thermon 200 boiler.	Instruction manual reference "Thermon Europe Issue 1" dated January 2011.	6mm wood pellets (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2FJ		
Woodpecker Thermon 250 boiler.	Instruction manual reference "Thermon Europe Issue 1" dated January 2011.	6mm wood pellets (1).

(1) The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood

preservatives or coatings.

Fireplace	Conditions The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2FJ		
Woodpecker Thermon 300 boiler.	Instruction manual reference "Thermon Europe Issue 1" dated January 2011.	6mm wood pellets (1).
Manufactured by Woodpecker Energy UK, Abbey Manor Business Centre, Preston Road, Yeovil, BA20 2FJ.		
The Wood Waste Technology Ltd WT5.	The manufacturer's instructions dated 16 February 2009, reference WT5_v2.	Medium density fibreboard, chipboard, hardwood or softwood
Manufactured by Wood Waste Technology Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.		offcuts (1).
The Wood Waste Technology Heater, models WT10 and WT15.	The manufacturer's instructions dated 19 January 2005, reference WT10 and WT15.	Medium density fibreboard, chipboard, hardwood or softwood offcuts ⁽¹⁾ .
Manufactured by Wood Waste Technology Units 1 and 2, Drummond Road, Astonfields Industrial Estate, Stafford, Staffordshire, ST16 3HJ.		
WTA WT Auto 200 kW Airheater.	The instruction manual reference "WTA Installation Operation & Maintenance	Chipboard, medium density fibreboard,

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
Тиерисе	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Wood Waste Technology Ltd of Stafford, Units 1, 2 & 3, Drummond Road, Astonfields Industrial Estate, Stafford, ST16 3HJ.	Instructions" WTA v1 Issue A dated April 2011.	softwood, hardwood. All fuels to be chipped to a maximum size of 25mm and a maximum moisture content of 20%. Maximum fines (sawdust) content 5%.
WTH 150 and WTH 200 boilers.	The manufacturer's installation manual "version 91 for Large Capacity Boiler WTH 150-200. Reference BA GK V90b 0309".	Wood chips or wood pellets (1).
Manufactured by Hargassner Gesellschaft mit beschränkter Haftung (GmbH), Gunderding 8, A-4952, Weng, Austria.	130-200. Reference BA GR V 900 0309 .	
Xeoos 5kW stove Versions: Natur, Style, Harmony, Pur, Classic, Elegance and Stone.	The manufacturer's "operating and installation instructions Xeoos 5k W/8kW model 2008" reference "Revisions — Index 01/08 Fassung Januar 2008".	Wood logs conforming to DIN 51731 ⁽¹⁾ .
Xeoos 8kW stove Versions: Basic, Pur, Classic, Elegance Stone and Air.		
Manufactured by Specht Modulare Ofensysteme GmbH & Co, KG i.V. Dipl Ing. Frank Werner Projektmanagement Bahnhofstr, 2 D 35116 Hatzfeld		
Yeoman CL3 (3.8 kW) and CL5 (4.9 kW) multifuel stoves; Yeoman CL5 (4.9 kW) wood Stove.	The instruction manual reference "PM489 Issue 1" dated June 2010 and smoke control kit instruction manual "PM491 Issue 1" dated 5 April 2010.	Wood logs (1).

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Yeoman CL 7 (7 kW) inset appliance Product code YM-CL7NMF.	The instruction manual reference "PM553 — Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011.	Wood logs (1).
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	
Yeoman CL Milner Stove Product code YM-CLMB.	The instruction manual reference "PM559 — Issue 1" dated June 2011 and smoke control kit instruction manual reference "PM491 Issue 2" dated June 2011.	Wood logs (1).
Manufactured by Stovax Ltd, Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position.	
Yeoman Devon — Multifuel, flat top, 1 door (9kW); Yeoman Devon — Multifuel, flat top, 2 door (9kW);	The instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010.	Wood logs (1).
Yeoman Devon — Multifuel, low canopy, 1 door (9kW); Yeoman Devon — Multifuel, low canopy, 2 door (9kW); Yeoman Devon — Multifuel, high canopy, 1 door (9kW); Yeoman Devon — Multifuel, high canopy, 1 door (9kW); Yeoman Devon — Multifuel,	A permanent stop must be positioned to prevent closure of the secondary air control below the 50% open position and a system that ensures a gap of 1mm for bleed of primary air when the spin wheels are rotated to their closed positions must be fitted.	

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.

Fireplace	Conditions	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	No fuel is to be used in the fireplace other than authorised fuels and the following fuel or fuels:
high canopy, 2 door (9kW).		
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.		
Yeoman Exmoor — Multifuel, flat top (4.9kW); Yeoman Exmoor — Multifuel, low canopy (4.9kW); Yeoman Exe — Multifuel, flat top, 1 door (4.9kW); Yeoman Exe — Multifuel, flat top, 2 door (4.9kW); Yeoman Exe — Multifuel, low canopy, 1 door (4.9kW); Yeoman Exe — Multifuel, low canopy, 2 door (4.9kW);	The instruction manual reference "PM184 Issue 3" dated February 2008 and smoke control kit instruction manual "PM403 Issue 1" dated January 2010. A permanent stop must be positioned to prevent closure of the secondary air control below the 60% open position and a system that prevents full closure of the primary air controls must be fitted.	Wood logs (1).
Manufactured by Stovax Ltd; Falcon Road, Sowton Industrial Estate, Exeter, Devon, EX2 7LF.		

⁽¹⁾ The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.