



OFFERYNNAU STATUDOL  
CYMRU

WELSH STATUTORY  
INSTRUMENTS

**2015 Rhif 1517 (Cy. 176)**

**2015 No. 1517 (W. 176)**

**AER GLÂN, CYMRU**

**CLEAN AIR, WALES**

Rheoliadau Ardaloedd Rheoli Mwg  
(Tanwyddau Awdurdodedig)  
(Cymru) 2015

The Smoke Control Areas  
(Authorised Fuels) (Wales)  
Regulations 2015

**NODYN ESBONIADOL**

**EXPLANATORY NOTE**

*(Nid yw'r nodyn hwn yn rhan o'r Rheoliadau)*

*(This note is not part of the Regulations)*

Mae'r Rheoliadau hyn yn dirymu ac yn disodli gyda diwygiadau Rheoliadau Ardaloedd Mwg (Tanwyddau Awdurdodedig) (Cymru) 2014 (O.S. 2014/684 (Cy. 74)) ("Rheoliadau 2014").

These Regulations revoke and replace with amendments the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2014 (S.I. 2014/684 (W. 74)) ("the 2014 Regulations").

Mae'r Rheoliadau hyn yn pennu pob tanwydd sydd wedi ei awdurdodi i'w ddefnyddio mewn ardaloedd rheoli mwg yng Nghymru at ddibenion adran 20 o Ddeddf Aer Glân 1993 ("Deddf 1993"). Mae pob un o'r tanwyddau a restrwyd yn yr Atodlen i Rheoliadau 2014 yn union cyn i'r Rheoliadau hyn ddod i rym yn parhau i fod yn danwydd awdurdodedig. Mae naw o danwyddau ychwanegol wedi eu hawdurdodi am y tro cyntaf.

These Regulations specify all fuels which are currently authorised for use in smoke control areas in Wales for the purposes of section 20 of the Clean Air Act 1993 ("the 1993 Act"). All the fuels that were listed in the Schedule to the 2014 Regulations immediately prior to the coming into force of these Regulations continue to be authorised fuels. Nine additional fuels are authorised for the first time.

Mae adran 20 o Ddeddf 1993 yn darparu ei bod yn drosedd gollwng mwg o simnai adeilad, neu simnai sy'n gwasanaethu ffwrnais boeler sefydlog neu beiriannau diwydiannol, os yw'r simnai honno mewn ardal rheoli mwg. Er hynny, mae'n amddiffyniad os gellir profi mai drwy ddefnyddio tanwydd awdurdodedig yn unig yr achoswyd y gollyngiad honedig.

Section 20 of the 1993 Act provides that it is an offence to emit smoke from a chimney of a building or a chimney serving a furnace of a fixed boiler or an industrial plant, if that chimney is within a smoke control area. However, it is a defence to prove that the alleged emission was caused solely by the use of an authorised fuel.

Yng Nghymru, ystyr tanwydd awdurdodedig yw tanwydd y datganwyd ei fod yn danwydd awdurdodedig drwy reoliadau a wnaed gan Weinidogion Cymru.

In Wales, an authorised fuel means a fuel declared to be an authorised fuel by regulations made by the Welsh Ministers.

Ystyriwyd Cod Ymarfer Gweinidogion Cymru ar gynnal Aseidiadau Effaith Rheoleiddiol mewn perthynas â'r Rheoliadau hyn. O ganlyniad, ystyriwyd nad oedd yn angenrheidiol cynnal asesiad effaith rheoleiddiol o'r costau a'r manteision sy'n debygol o ddeillio o gydymffurfio â'r Rheoliadau hyn.

The Welsh Ministers' Code of Practice on the carrying out of Regulatory Impact Assessments was considered in relation to these Regulations. As a result, it was not considered necessary to carry out a regulatory impact assessment as to the likely costs and benefits of complying with these Regulations.

**2015 Rhif 1517 (Cy. 176)**

**2015 No. 1517 (W. 176)**

**AER GLÂN, CYMRU**

**CLEAN AIR, WALES**

**Rheoliadau Ardaloedd Rheoli Mwg  
(Tanwyddau Awdurdodedig)  
(Cymru) 2015**

**The Smoke Control Areas  
(Authorised Fuels) (Wales)  
Regulations 2015**

*Gwnaed* 8 Gorffennaf 2015

*Made* 8 July 2015

*Gosodwyd gerbron Cynulliad Cenedlaethol  
Cymru* 15 Gorffennaf 2015

*Laid before the National Assembly for Wales*  
15 July 2015

*Yn dod i rym* 4 Awst 2015

*Coming into force* 4 August 2015

Mae Gweinidogion Cymru yn gwneud y Rheoliadau canlynol drwy arfer y pwerau a roddwyd i'r Ysgrifennydd Gwladol gan adran 20(6) o Ddeddf Aer Glân 1993(1) ac a freiniwyd bellach yng Ngweinidogion Cymru(2) i'r graddau y maent yn arferadwy o ran Cymru:

The Welsh Ministers make the following Regulations in exercise of the powers conferred upon the Secretary of State by section 20(6) of the Clean Air Act 1993(1) and now vested in the Welsh Ministers(2) so far as exercisable in relation to Wales:

**Enwi, cychwyn a chymhwyso**

**Title, commencement and application**

1.—(1) Enw'r Rheoliadau hyn yw Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2015 a deuant i rym ar 4 Awst 2015.

1.—(1) The title of these Regulations is the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2015 and they come into force on 4 August 2015.

(2) Mae'r Rheoliadau hyn yn gymwys o ran Cymru.

(2) These Regulations apply in relation to Wales.

**Tanwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993**

**Authorised fuels for the purposes of Part III of the Clean Air Act 1993**

2. Datgenir bod glo caled, glo lled-galed, trydan, nwy, gloeau stêm isel eu hanweddolrwydd a'r tanwyddau a ddisgrifir yn yr Atodlen yn danwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993.

2. Anthracite, semi-anthracite, electricity, gas, low volatile steam coals and the fuels described in the Schedule are declared to be authorised fuels for the purposes of Part III of the Clean Air Act 1993.

---

(1) 1993 p. 11.

(2) Trosglwyddwyd swyddogaethau perthnasol yr Ysgrifennydd Gwladol, i'r graddau y maent yn arferadwy o ran Cymru, i Gynulliad Cenedlaethol Cymru yn rhinwedd erthygl 2 o Orchymyn Cynulliad Cenedlaethol Cymru (Trosglwyddo Swyddogaethau) 1999 (O.S. 1999/672), ac Atodlen 1 iddo. Mae'r swyddogaethau hynny bellach yn arferadwy gan Weinidogion Cymru yn rhinwedd adran 162 o Ddeddf Llywodraeth Cymru 2006 (p. 32) a pharagraff 30 o Atodlen 11 iddi.

---

(1) 1993 c. 11.

(2) The relevant functions of the Secretary of State were, so far as exercisable in relation to Wales, transferred to the National Assembly for Wales by virtue of article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672). Those functions are now exercisable by the Welsh Ministers by virtue of section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c. 32).

**Dirymu**

3. Mae Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2014(1) wedi eu dirymu.

**Revocation**

3. The Smoke Control Areas (Authorised Fuels) Regulations (Wales) 2014 are revoked(1);

*Carl Sargeant*

Y Gweinidog Cyfoeth Naturiol, un o Weinidogion Cymru

8 Gorffennaf 2015

Minister for Natural Resources, one of the Welsh Ministers

8 July 2015

---

(1) O.S. 2014/684 (Cy. 74).

---

(1) S.I. 2014/684 (W. 74).

## YR ATODLEN

Rheoliad 2

### TANWYDDAU AWDURDODEDIG

1. Brics glo Aimcor Excel, a weithgynhyrchir gan Applied Industrial Materials UK Limited yn Newfield, County Durham, neu a weithgynhyrchir gan Oxbow Carbon & Minerals UK Limited yn Windsor House, Cornwall Road, Harrogate, North Yorkshire—

- (a) a gyfansoddir o olog petrolewm (sef tua 60 i 75% o'r cyfanswm pwysau), glo anweddolrwydd-isel a golosg adweithiol (sef tua 20 i 25% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 73 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

2. Brics glo Aimcor Pureheat, a weithgynhyrchir gan Applied Industrial Materials UK Limited yn Immingham, North East Lincolnshire, neu a weithgynhyrchir gan Oxbow Carbon & Minerals UK Limited yn Windsor House, Cornwall Road, Harrogate, North Yorkshire—

- (a) a gyfansoddir o lo caled (sef tua 60% o'r cyfanswm pwysau), golosg petrolewm (sef tua 25% o'r cyfanswm pwysau) a rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo ar siâp gobennydd gyda hicyn ar ffurf llinell sengl ar un ochr a hicyn ar ffurf llinell ddwbl ar yr ochr arall;
- (d) sy'n pwyso 75 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

3. Brics glo Ancit, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 60 i 95% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 30% o'r cyfanswm pwysau), glo meddal (hyd at tua 15% o'r cyfanswm pwysau) a

## SCHEDULE

Regulation 2

### AUTHORISED FUELS

1. Aimcor Excel briquettes, manufactured by Applied Industrial Materials UK Limited at Newfield, County Durham, or manufactured by Oxbow Carbon & Minerals UK Limited at Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—

- (a) comprise petroleum coke (as to approximately 60 to 75% of the total weight), low volatile coal and reactive coke (as to approximately 20 to 25% of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 73 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

2. Aimcor Pureheat briquettes, manufactured by Applied Industrial Materials UK Limited at Immingham, North East Lincolnshire, or manufactured by Oxbow Carbon & Minerals UK Limited at Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—

- (a) comprise anthracite (as to approximately 60% of the total weight), petroleum coke (as to approximately 25% of the total weight) and binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are pillow-shaped briquettes with a single line indentation on one side and a double line indentation on the reverse side;
- (d) have an average weight of 75 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

3. Ancit briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 95% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight) and a molasses and

rhwymwr o driagl ac asid ffosfforig neu rhwymwr organig (sef gweddill y pwysau);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp clustog heb farciau arnynt;
- (d) sy'n pwyso 48 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**4. Boncyffion tân Big K Instant Lighting Fire Logs, a weithgynhyrchir gan Allspan BV yn Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—**

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 milimetr eu hyd a 80 milimetr o ddyfnder, gyda rhigolau ar hyd yr wyneb; ac
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**5. Y siarcol Big K Restaurant Grade Charcoal, a weithgynhyrchir gan Big K Products UK Limited yn Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, Yr Ariannin—**

- (a) a gyfansoddir o bren quebracho gwyn a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tua 450°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 milimetr a 150 milimetr; ac
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**6. Brics glo Black Diamond Gem, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—**

- (a) a gyfansoddir o lwch glo caled (sef tuag 20 i 30% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 12 i 22% o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;

phosphoric acid binder or an organic binder (as to the remaining weight);

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked cushion-shaped briquettes;
- (d) have an average weight of 48 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**4. Big K Instant Lighting Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—**

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth and with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**5. Big K Restaurant Grade Charcoal, manufactured by Big K Products UK Limited at Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, Argentina, which—**

- (a) comprise pyrolysed white quebracho wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 450°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**6. Black Diamond Gem briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—**

- (a) comprise anthracite duff (as to approximately 20 to 30% of the total weight), petroleum coke (as to approximately 40 to 45% of the total weight), bituminous coal (as to approximately 12 to 22% of the total weight) and molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;

- (c) sy'n frics glo ar siâp gobennydd wedi'u marcio â hicyn ar ffurf dwy linell gyfochrog sy'n rhedeg yn lledredol o amgylch y fricsen;
- (d) sy'n pwyso 160 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

7. Boncyffion tân Bord na Móna Firelogs, a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Iwerddon—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 255 milimetr o hyd gyda diamedr o 75 milimetr a rhigolau ar hyd un wyneb hydredol;
- (d) sy'n pwyso 1.3 cilogram (net) ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

8. Brics glo Bord na Móna Firepak (sy'n cael eu marchnata hefyd fel brics glo Arigna Special), a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Iwerddon—

- (a) a gyfansoddir o lo caled (sef tua 50% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr seiliedig ar starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres;
- (c) sy'n frics glo heb eu marcio, ar siâp gobennydd;
- (d) sy'n pwyso 50 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

9. Brics glo Brazier, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau), a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;

- (c) are pillow-shaped briquettes marked with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 160 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

7. Bord na Móna Firelogs, manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Ireland, which—

- (a) comprise slack wax (as to approximately 55% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 255 millimetres in length and 75 millimetres in diameter, and with grooves along one longitudinal face;
- (d) have an average weight of 1.3 kilograms (net); and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

8. Bord na Móna Firepak briquettes (also marketed as Arigna Special coal briquettes), manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Ireland, which—

- (a) comprise anthracite (as to approximately 50% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 10 to 30% of the total weight) and starch based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 50 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

9. Brazier briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;

- (c) sydd naill ai'n frics siâp gobennydd heb eu marcio neu'n frics siâp gobennydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetr i ffwrdd o'r llinell gyfatebol gyferbyn;
- (d) sydd â phwysau cyfartalog pob bricsen yn naill ai'n 50 neu'n 80 gram; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 2% o'r cyfanswm pwysau mewn cyflwr sych.

**10.** Brics glo Briteflame, a weithgynhyrchir gan Maxibrite Limited ar Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd,
- (d) sy'n pwyso 140 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.9% o'r cyfanswm pwysau mewn cyflwr sych.

**11.** Brics glo Briteheat, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 60 i 85% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 30% o'r cyfanswm pwysau), glo meddal (hyd at tua 15% o'r cyfanswm pwysau), a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;
- (c) sy'n frics glo ar siâp clustog gyda hicyn ar ffurf llinell yn rhedeg yn hydredol o gwmpas y fricsen;
- (d) sy'n pwyso 30 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**12.** Brics glo Briteheat Plus, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lwch glo caled (sef tua 75 i 95% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 20% o'r cyfanswm

- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;
- (d) have an average weight of either 50 or 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**10.** Briteflame briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight), and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 140 grams; and
- (e) have a sulphur content not exceeding 1.9% sulphur on a dry basis.

**11.** Briteheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 85% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion-shaped briquettes with an indented line running longitudinally around the briquette;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**12.** Briteheat Plus briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 75 to 95% of the total weight), petroleum coke (up to approximately 20% of the total

pwysau) a rhwymwr organig (sef gweddill y pwysau);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 80 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**13.** Bryant and May Firelogs, a weithgynhyrchir gan Swedish Match yn Kostenetz, Bwlgaria—

- (a) a gyfansoddir o gwyr paraffin (sef tua 50% o'r cyfanswm pwysau), pren poplys mâl (sef tua 25% o'r cyfanswm pwysau), blawd gwenith (sef tua 15% o'r cyfanswm pwysau), solidau cyneudwy ar wasgar mewn cwyr paraffin ar ffurf jel (sef tua 1 % o'r cyfanswm pwysau) a dŵr, cyfryngau chwyddo a chadwolyn (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys allwthio;
- (c) sydd â'u trawstoriad yn gwadrant gyda radiws o tuag 80 milimetr a'u hyd tua 265 milimetr gyda sribyn cynnau ar hyd un ymyl;
- (d) sy'n pwyso tuag 1.15 cilogram; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**14.** Brics glo Charglow, a weithgynhyrchir gan Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Gwlad Pwyl—

- (a) a gyfansoddir o gols glo meddal (sef tua 45 i 95% o'r cyfanswm pwysau), glo caled (sef tua 0 i 20% o'r cyfanswm pwysau), golosg petrolewm (sef tua 0 i 20% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres r tuag 110°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 100 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

**15.** Coalite, a weithgynhyrchir gan Coalite Products Limited yn Bolsover, ger Chesterfield, Derbyshire ac yn Grimethorpe, South Yorkshire drwy ddefnyddio proses o garboneiddio ar dymheredd isel.

weight) and an organic binder (as to the remaining weight);

- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow shaped briquettes;
- (d) have an average weight of 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**13.** Bryant and May Firelogs manufactured by Swedish Match at Kostenetz, Bulgaria, which—

- (a) comprise paraffin wax (as to approximately 50% of the total weight), ground poplar wood (as to approximately 25% of the total weight), wheatflour (as to approximately 15% of the total weight), ignitable solids dispersed in gelled paraffin wax (as to approximately 1% of the total weight) and water, swelling agents and preservative (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are of quadrant cross sections with a radius of approximately 80 millimetres, and length approximately 265 millimetres with an ignition strip along one edge;
- (d) have an approximate weight of 1.15 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**14.** Charglow briquettes, manufactured by Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Poland, which—

- (a) comprise bituminous coal char (as to approximately 45 to 95% of the total weight), anthracite (as to approximately 0 to 20% of the total weight), petroleum coke (as to approximately 0 to 20% of the total weight), bituminous coal (as to approximately 0 to 10% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing and heat treatment at about 110°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**15.** Coalite, manufactured by Coalite Products Limited at Bolsover, near Chesterfield, Derbyshire and at Grimethorpe, South Yorkshire using a low temperature carbonisation process.



**16.** Brics glo Coalite Ovals, a weithgynhrychir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd a thua 84.2 milimetr o hyd x 61.5 milimetr x 37.8 milimetr;
- (d) sy'n pwyso 118 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.9% o'r cyfanswm pwysau mewn cyflwr sych.

**17.** Golosg a weithgynhrychir gan—

- (a) Coal Products Limited yn Cwm Coking Works, Llanilltud Faerdref, Pontypridd, Rhondda Cynon Taf, ac a werthir fel "Sunbrite";
- (b) Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, South Yorkshire ac a werthir fel "Sunbrite" neu "Monckton Boiler Beans";
- (c) Corus UK Limited yn Teesside Works, Redcar & Cleveland ac a werthir fel "Redcar Coke Nuts (Doubles)"; ac
- (d) Coal Products Limited yn Cwm Coking Works, Llanilltud Faerdref, Pontypridd, Rhondda Cynon Taf ac a werthir "Cwm Coke Doubles".

**18.** Cosycoke (a farchnetir hefyd fel Lionheart Crusader neu Sunbrite Plus), a weithgynhrychir gan Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, South Yorkshire ac Aimcor Supercoke (sydd hefyd yn cael ei farchnata fel Supercoke), a weithgynhrychir gan M & G Fuels Limited yn Hartlepool Docks, Hartlepool, ac ym mhob achos—

- (a) a gyfansoddir o olog caled o faint penodol (sef tua 45 i 65% o'r cyfanswm pwysau) a golosg petrolewm o faint penodol (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy eu blendio;
- (c) sy'n hapsiapiau heb eu marcio; ac
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**16.** Coalite Ovals briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes approximately 84.2 millimetres in length and 61.5 millimetres x 37.8 millimetres;
- (d) have an average weight of 118 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.

**17.** Coke, manufactured by—

- (a) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taf, and sold as "Sunbrite";
- (b) Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire and sold as "Sunbrite" or "Monckton Boiler Beans";
- (c) Corus UK Limited at Teesside Works, Redcar & Cleveland and sold as "Redcar Coke Nuts (Doubles)"; and
- (d) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taf and sold as "Cwm Coke Doubles".

**18.** Cosycoke, (also marketed as Lionheart Crusader or Sunbrite Plus), manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire and Aimcor Supercoke (also marketed as Supercoke), manufactured by M & G Fuels Limited at Hartlepool Docks, Hartlepool, which in each case—

- (a) comprise sized hard coke (as to approximately 45 to 65% of the total weight) and sized petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by blending;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**19.** Y siarcol Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal, a weithgynhyrchir gan Direct Charcoal yn Ekamanzi Road, Dalton, KwaZulu Natal, Gweriniaeth De Affrica—

- (a) a gyfansoddir o bren *Acacia mercii* a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolisis mewn odyr ar tua 420 i 480°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 milimetr a 150 milimetr; a
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**20.** Y siarcol Direct Charcoal Blue Bag Restaurant Charcoal, a weithgynhyrchir gan Direct Charcoal Limited yn Ruta 25, km. 9,5 –Pilar (cp.1629) Buenos Aires, Yr Ariannyn—

- (a) a gyfansoddir o bren Quebracho gwyn a phren Guayacan wedi eu pyrolysu;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolisis mewn odyr ar tua 420 i 480°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 milimetr a 150 milimetr; a
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**21.** Brics glo Dragonbrite, a weithgynhyrchir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf—

- (a) a gyfansoddir o lwch y tŵr (sef tua 95% o gyfanswm y pwysau) a rhwymwr seiliedig ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo ar siâp gobennydd, wedi eu marcio â'r llythyren "T" ar un ochr;
- (d) sy'n pwysu 50 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1% o'r cyfanswm pwysau.

**22.** Brics glo Dragonglow, a weithgynhyrchir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf—

- (a) a gyfansoddir o lwch y tŵr (sef tua 95% o gyfanswm y pwysau) a rhwymwr seiliedig ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;

**19.** Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal, manufactured by Direct Charcoal at Ekamanzi Road, Dalton, KwaZulu Natal, Republic of South Africa which—

- (a) comprise pyrolised *Acacia mercii* wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 420 to 480°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**20.** Direct Charcoal Blue Bag Restaurant Charcoal, manufactured by Direct Charcoal Limited at Ruta 25, km. 9,5 –Pilar (cp.1629) Buenos Aires, Argentina which—

- (a) comprise pyrolised white Quebracho and Guayacan wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 420 to 480°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**21.** Dragonbrite briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf which—

- (a) comprise tower duff (as to approximately 95% of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are pillow-shaped briquettes marked with the letter "T" on one side;
- (d) have an average weight of 50 grams; and
- (e) have a sulphur content not exceeding 1% of the total weight.

**22.** Dragonglow briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf, which—

- (a) comprise tower duff (as to approximately 95% of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are unmarked pillow-shaped briquettes;

- (d) sy'n pwyso 100 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1% o'r cyfanswm pwysau.

**23.** Boncyffion tân Duraflame Firelogs, a weithgynhyrchir gan Paramelt BV, Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr petrolewm mwynol (sef tua 55% o'r cyfanswm pwysau) a ffibr pren caled mâl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 320 milimetr o hyd, 90 milimetr o uchder ac 85 milimetr o led;
- (d) sy'n pwyso 1.45 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**24.** Brics glo Ecoal, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), cols (sef tua 0 i 10% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo chweonglog heb eu marcio;
- (d) sy'n pwyso 125 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**25.** Brics glo Ecoal 50, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 30 i 55% o'r cyfanswm pwysau), biomas (sef tua 25 i 35% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 5% o'r cyfanswm pwysau) a rhwymwr organig naturiol (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a'u trin wedyn â gwres ar tua 300°C mewn amgylchedd rheoledig gydag ocsigen gostyngedig;

- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1% of the total weight.

**23.** Duraflame Firelogs, manufactured by Paramelt BV, Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, The Netherlands, which—

- (a) comprise mineral-based petroleum wax (as to approximately 55% of the total weight) and ground hardwood fibre (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 320 millimetres in length, 90 millimetres high and 85 millimetres wide;
- (d) have an average weight of 1.45 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**24.** Ecoal briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), char (as to approximately 0 to 10% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight) and molasses and phosphoric acid as a binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked hexagonal briquettes;
- (d) have an average weight of 125 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**25.** Ecoal 50 briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 30 to 55% of the total weight), biomass (as to approximately 25 to 35% of the total weight), petroleum coke (as to approximately 10 to 40% of the total weight), bituminous coal (as to approximately 0 to 5% of the total weight) and natural organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at approximately 300°C in a controlled, reduced oxygen environment;

- (c) sy'n frics glo chweonglog gyda un streipen sengl ar un ochr ar draws y wynebaw gwastad;
- (d) sy'n pwyso 135 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**26.** Brics glo Ecobrite, a weithgynhyrchir gan Arigna Fuels Limited yn Arigna, Carrick-on-Shannon, County Roscommon, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 96% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 250°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd mewn dau faint;
- (d) sydd, ar gyfartaledd, yn pwyso 37 gram yn achos y maint lleiaf a 48 gram yn achos y maint mwyaf; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

**27.** Brics glo EDF Fuel, a weithgynhyrchir gan The Green Factory yn y Laboratoire de Chimie Agro-industrielle UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue D'Azereiz, -BP 1629 65016 Tarbes Cedex, Ffrainc—

- (a) a gyfansoddir o tua 100 gram o Miscanthus heb ei brosesu (sef tua 45% o'r cyfanswm pwysau), tua 95 gram o ester Copra (sef tua 43% o'r cyfanswm pwysau), a thua 25 gram o rywyrwr a gynhyrchwyd o Miscanthus (broseidig gyda chalsiwm ocsid, sy'n ffurfio tua 0.5% o'r cyfanswm pwysau), sef gweddill y pwysau;
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys prosesu Miscanthus, cymysgu, poethwasgu, a throchi mewn baddon ester;
- (c) sy'n frics glo o siâp silindr heb eu marcio, 120 milimetr o uchder gyda diamedr o 60 milimetr, a thwll canolog ar siâp seren yn treiddio drwy hyd hiraf y fricsen;
- (d) sy'n pwyso 220 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**28.** Brics glo Excel+, a weithgynhyrchir gan Oxbow Coal BV yn Newfield Works, Bishop Auckland, County Durham—

- (c) are hexagonal-shaped briquettes with a single stripe on one side across the flats;
- (d) have an average weight of 135 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**26.** Ecobrite briquettes, manufactured by Arigna Fuels Limited at Arigna, Carrick-on-Shannon, County Roscommon, Ireland, which—

- (a) comprise anthracite fines (as to approximately 96% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are unmarked pillow-shaped briquettes in two sizes;
- (d) have an average weight of 37 grams for the smaller size and 48 grams for the larger size; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**27.** EDF Fuel Briquettes, manufactured by TheGreenFactory at the Laboratoire de Chimie Agro-industrielle UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue D'Azereiz, -BP 1629 65016 Tarbes Cedex, France, which—

- (a) comprise approximately 100 grams of unprocessed Miscanthus (as to approximately 45% of the total weight), approximately 95 grams of Copra ester (as to approximately 43% of the total weight), and approximately 25 grams of a binder produced from Miscanthus (processed with calcium oxide as to approximately 0.5% of the total weight) as to the remaining weight;
- (b) are manufactured from those constituents by a process involving Miscanthus processing, mixing, hot pressing and soaking in an ester bath;
- (c) are unmarked cylinder-shaped briquettes of 120 millimetres height and 60 millimetres diameter with a star-shaped hole running centrally through the longer length of the briquette;
- (d) have an average weight of 220 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**28.** Excel+ briquettes, manufactured by Oxbow Coal BV at Newfield Works, Bishop Auckland, County Durham, which—

- (a) a gyfansoddir o olog petrolewm (sef 65 i 70% o'r cyfanswm pwysau), glo caled (sef 25% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri, caledwr a sefydlogydd tymheredd isel (sef gweddill y pwysau);
- (b) a gynhyrchir ar y tymheredd amgylchynol drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo ar siâp gobennydd sgwâr, heb farciau;
- (d) sy'n pwyso 100 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 1.9% o'r cyfanswm pwysau.

**29.** Brics glo Extracite, a weithgynhyrchir gan Sophia-Jacoba Handelsgesellschaft GmbH yn Hückelhoven, Yr Almaen—

- (a) a gyfansoddir o lwch glo caled (sef tua 95.5% o'r cyfanswm pwysau) a lleisw amoniwm lignosylffonad yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 260°C;
- (c) sy'n frics glo ag arlliw ariannaidd ar siâp clustog, wedi eu marcio â'r llythrennau "S" a "J";
- (d) sy'n pwyso 40 gram ar gyfartaledd; ac
- (e) sydd â'u cynnwys o sylffwr tuag 1.2% o'r cyfanswm pwysau.

**30.** Brics glo Fireglo, a weithgynhyrchir gan Les Combustibles de Normandie yn Caen, Ffrainc, a chan La Société Rouennaise de Défumage yn Rouen, Ffrainc—

- (a) a gyfansoddir o lychau Cymreig wedi'u golchi (sef tua 92% o'r cyfanswm pwysau) a rhwymwr o byg glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 330°C;
- (c) sy'n ofoidau gyda thair llinell ar un ochr a'r ochr arall yn llyfn;
- (d) sy'n pwyso 30 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.8% o'r cyfanswm pwysau.

**31.** Y siarcol G N Grosvenor (Fuel Express) Restaurant Charcoal, a weithgynhyrchir gan Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay—

- (a) a gyfansoddir o'r coedydd caled *Prosopis nigra*, *Cordia alliodora*, *Centrolobium*,

- (a) comprise petroleum coke (as to 65 to 70% of the total weight), anthracite (as to 25% of the total weight) and a cold setting resin binder, hardener and low temperature stabiliser (as to the remaining weight);
- (b) are produced at ambient temperature by a process involving roll pressing and cold curing;
- (c) are unmarked square pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight.

**29.** Extracite briquettes, manufactured by Sophia-Jacoba Handelsgesellschaft GmbH at Hückelhoven, Germany, which—

- (a) comprise anthracite duff (as to approximately 95.5% of the total weight) and ammonium lignosulphonate lye as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are cushion-shaped briquettes with a silvery appearance and are marked with the letters "S" and "J";
- (d) have an average weight of 40 grams; and
- (e) have a sulphur content of approximately 1.2% of the total weight.

**30.** Fireglo briquettes, manufactured by Les Combustibles de Normandie at Caen, France, and by La Société Rouennaise de Défumage at Rouen, France, which—

- (a) comprise washed Welsh duffs (as to approximately 92% of the total weight) and coal pitch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 330°C;
- (c) are ovoids with three lines on one side and are smooth on the other side;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 0.8% of the total weight.

**31.** G N Grosvenor (Fuel Express) Restaurant Charcoal, manufactured by Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay, which—

- (a) comprises pyrolised *Prosopis nigra*, *Cordia alliodora*, *Centrolobium*, *Prosopis*

*Prosopis kuntzei, Caesalpinia, Goncalo alves a Tabebuia* wedi eu pyrolysu;

- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tuag 800°C;
- (c) sy'n ddarnau o siarcol rhwng 20 a 120 milimetr, heb eu marcio; ac
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau mewn cyflwr sych.

**32.** Brics glo Homefire, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 70% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 45% o'r cyfanswm pwysau), cols (sef tua 0 i 10% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 30% o'r cyfanswm pwysau) a rhwymwr organig neu rywmyr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) nad yw eu cynnwys o ddeunydd anweddol, fel brics glo gorffenedig, yn llai na 9% nac yn fwy na 15% o'r cyfanswm pwysau mewn cyflwr sych;
- (d) sy'n frics glo chweonglog heb eu marcio;
- (e) sy'n pwyso 140 gram ar gyfartaledd; ac
- (f) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**33.** Boncyffion tân Homefire Fire Logs, a weithgynhyrchir gan De Lange BV, Rustenbugerweg 3, 1646 WJ Ursem, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 50% o'r cyfanswm pwysau) a blawd llif (sef tua 50% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 280 milimetr o hyd x 75 milimetr x 75 milimetr, gydag un rhigol ar hyd pob un o'u pedwar wyneb sydd â'u hyd yn 280 milimetr;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

**34.** Homefire Ovals, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lwch glo caled (sef tua 57% o'r cyfanswm pwysau), golosg petrolewm (sef tua 17% o'r cyfanswm pwysau), glo meddal

*kuntzei, Caesalpinia, Goncalo alves* and *Tabebuia* hardwoods;

- (b) were manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20 and 120 millimetres; and
- (d) has a sulphur content not exceeding 2% of the total weight on a dry basis.

**32.** Homefire briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 40 to 70% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), char (as to approximately 0 to 10% of the total weight), bituminous coal (as to approximately 5 to 30% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) have a volatile matter content in the finished briquette of neither less than 9% nor more than 15% of the total weight on a dry basis;
- (d) are unmarked hexagonal briquettes;
- (e) have an average weight of 140 grams; and
- (f) have a sulphur content not exceeding 2% of the total weight.

**33.** Homefire Fire Logs, manufactured by De Lange BV, Rustenbugerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to approximately 50% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 280 millimetres in length and 75 millimetres x 75 millimetres with a single groove running along each of the four 280 millimetre length faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**34.** Homefire ovals, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 57% of the total weight), petroleum coke (as to approximately 17% of the total weight),

(sef tua 13% o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi'u marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwyso 135 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**35. Homefire Ovals (R), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—**

- (a) a gyfansoddir o ronynnau glo caled (sef tua 50 i 75% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 17% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo ar siâp gobennydd wedi'u marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwyso 130 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**36. Hot Drops, a weithgynhyrchir gan EU Zeme Limited yn Riga, Eksporta Street 15, LV-1045, Latfia—**

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau) a rhwymwr triagl ac asid orthoffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu, ac wedyn triniaeth â gwres ar tua 250 i 280°C;
- (c) sy'n frics glo, ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 40 milimetr a thrwch o tua 21 milimetr yng nghanol y fricsen;
- (d) sy'n pwyso 23 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.5% o'r cyfanswm pwysau.

**37. HouseFuel Smokeless Ovals, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf—**

bituminous coal (as to approximately 13% of the total weight) and molasses and phosphoric acid as binder (as to the remaining weight);

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 135 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**35. Homefire Ovals (R), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—**

- (a) comprise anthracite fines (as to approximately 50 to 75% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), bituminous coal (as to approximately 5 to 17% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 130 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**36. Hot Drops, manufactured by EU Zeme Limited at Riga, Eksporta Street 15, LV-1045, Latvia which—**

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at about 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and approximately 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

**37. HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taf, which—**

- (a) a gyfansoddir o ronynnau glo caled (sef tuag 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts fel rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 260°C;
- (c) sy'n frics glo ar siâp gobennydd heb farciau;
- (d) sy'n pwyso 78 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**38.** HouseFuel Smokeless Ovals, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Canolbarth Morgannwg—

- (a) a gyfansoddir o lo meddal a golosg petrolewm (y ddau hyd at 10 i 15% o'r cyfanswm pwysau) a llwch glo caled gyda rhwymwr o starts (sef gweddill pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 260°C;
- (c) sy'n frics glo ar siâp gobennydd heb farciau gyda'u dimensiynau mwyaf tua 68 milimetr, 63 milimetr a 38 milimetr;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.9% o'r cyfanswm pwysau mewn cyflwr sych.

**39.** Island Lump ac Island Nuts, a weithgynhyrchir gan Unocal Refinery, California, Unol Daleithiau America—

- (a) a gyfansoddir o olog petrolewm;
- (b) a weithgynhyrchwyd o'r golosg petrolewm drwy broses sy'n cynnwys trin â gwres a chwistrellu stêm;
- (c) sy'n hapsiapiau heb eu marcio;
- (d) sy'n pwyso 80 gram ar gyfartaledd (Island Lump) neu 30 gram ar gyfartaledd (Island Nuts); ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**40.** Brics glo Jewel, a weithgynhyrchir gan Eldon Colliery Limited yn Newfield Works, Bishop Auckland, County Durham—

- (a) a gyfansoddir o lo caled (sef tua 30 i 50% o'r cyfanswm pwysau), golosg petrolewm Long Beach (sef tua 50 i 70% o'r cyfanswm pwysau) a rhwymwr o garbohydrad (sef gweddill y pwysau);

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 78 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**38.** HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Mid Glamorgan, which—

- (a) comprise bituminous coal and petroleum coke (each as to approximately 10 to 15% of the total weight) and anthracite duff and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes with approximate maximum dimensions 68 millimetres, 63 millimetres and 38 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.9% on a dry basis.

**39.** Island Lump and Island Nuts, manufactured by Unocal Refinery, California, the United States of America, which—

- (a) comprise petroleum coke;
- (b) were manufactured from the petroleum coke by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes;
- (d) have an average weight of 80 grams (Island Lump) or 30 grams (Island Nuts); and
- (e) have a sulphur content not exceeding 2% of the total weight.

**40.** Jewel briquettes, manufactured by Eldon Colliery Limited at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise anthracite (as to approximately 30 to 50% of the total weight), Long Beach petroleum coke (as to approximately 50 to 70% of the total weight) and a carbohydrate binder (as to the remaining weight);



- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 150°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 33 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

**41.** Boncyffion La Hacienda Easy Logs, a weithgynhyrchir gan Allspan BV yn Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 milimetr o hyd a 80 milimetr o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**42.** Long Beach Lump nuts (a elwir hefyd yn LBL nuts), a weithgynhyrchir gan Aimcor Carbon Corporation yn Long Beach, California, Unol Daleithiau America neu a weithgynhyrchir gan Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, Unol Daleithiau America—

- (a) a gyfansoddir o olog petrolewm (sef tua 85 i 100% o'r cyfanswm pwysau), calchfaen (sef tua 0 i 10% o'r cyfanswm pwysau) a phyg tar glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys trin â gwres a chwistrellu stêm;
- (c) sy'n hapsiapiau heb eu marcio; ac
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**43.** Brics glo Maxibrite, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 250°C;
- (c) sy'n frics ar siâp clustog wedi'u marcio â'r llythren "M";

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 150°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 33 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**41.** La Hacienda Easy Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**42.** Long Beach Lump nuts (otherwise known as LBL nuts), manufactured by Aimcor Carbon Corporation at Long Beach, California, the United States of America, or manufactured by Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, the United States of America, which—

- (a) comprise petroleum coke (as to approximately 85 to 100% of the total weight), limestone (as to approximately 0 to 10% of the total weight) and coal tar pitch (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**43.** Maxibrite briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are cushion-shaped briquettes marked with the letter "M";

- (d) sy'n pwyso 35 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**44.** Brics glo Multiheat, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso naill ai 55 neu 80 gram y fricsen ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**45.** Brics glo Newburn, a weithgynhyrchir gan ECL Mineral Processing Limited yn Newfield Works, Newfield, Bishop Auckland, County Durham—

- (a) a gyfansoddir o olog petrolewm (sef tua 56 i 57% o'r cyfanswm pwysau), glo caled (sef tua 37 i 38% o'r cyfanswm pwysau) a rhwymwr powdr sych (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o galedu oer gan ddefnyddio gwasg rholer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd ac yn mesur 70 milimetr x 62 milimetr x 42 milimetr;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**46.** Brics glo Newburn, a weithgynhyrchir gan M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS—

- (a) a gyfansoddir o olog petrolewm (sef tua 56 i 57% o'r cyfanswm pwysau), glo caled (sef tua 37 to 38% o'r cyfanswm pwysau), a rhwymwr powdr sych (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o galedu oer gan ddefnyddio gwasg rholer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd ac yn mesur 70 milimetr x 62 milimetr x 42 milimetr;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac

- (d) have an average weight of 35 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**44.** Multiheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have average weights of either 55 or 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**45.** Newburn briquettes, manufactured by ECL Mineral Processing Limited of Newfield Works, Newfield, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using a roller press;
- (c) are unmarked pillow-shaped briquettes 70 millimetres x 62 millimetres x 42 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**46.** Newburn briquettes, manufactured by M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS which—

- (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using roller press;
- (c) are unmarked pillow shape briquette 70 millimetres x 62 millimetres x 42 millimetres;
- (d) have an average weight of 110 grams; and

- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**47.** Brics glo Newflame, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 260°C;
- (c) sy'n frics glo ar siâp gobennydd heb eu marcio;
- (d) sy'n pwyso 78 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**48.** Brics glo Newflame Plus, a weithgynhyrchir gan Maxibrite Limited, Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thriniaeth â gwres ar tua 260°C;
- (c) sy'n frics glo ar siâp gobennydd heb eu marcio, gyda'u dimensiynau mwyaf tua 68 milimetr x 63 milimetr x 38 milimetr;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 1.9% o'r cyfanswm pwysau pan fyddant yn sych.

**49.** Brics glo Newheat, a weithgynhyrchir gan Oxbow Coal BV yn Newfield Works, Bishop Auckland, County Durham—

- (a) a gyfansoddir o olog petrolewm (sef tua 60 i 65% o'r cyfanswm pwysau), glo caled (sef tua 30 i 35% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri, caledwr a sefydlogydd tymheredd isel (sef gweddill y pwysau);
- (b) a gynhyrchwyd ar y tymheredd amgylchynol drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo hirgrwn, ar siâp gobennydd heb eu marcio;
- (d) sy'n pwyso tua 100 gram ar gyfartaledd; ac

- (e) have a sulphur content not exceeding 2% of the total weight.

**47.** Newflame briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 78 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**48.** Newflame Plus briquettes, manufactured by Maxibrite Limited, Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes with approximate maximum dimensions 68 millimetres x 63 millimetres x 38 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.

**49.** Newheat briquettes, manufactured by Oxbow Coal BV at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to approximately 60 to 65% of the total weight), anthracite (as to approximately 30 to 35% of the total weight) and a cold setting resin binder, hardener and low temperature stabiliser (as to the remaining weight);
- (b) are produced at ambient temperature by a process involving roll pressing and cold curing;
- (c) are unmarked pillow-shaped oval briquettes;
- (d) have an average weight of approximately 100 grams; and

- (e) nad yw eu cynnwys o sylffwr yn fwy na 1.9% o'r cyfanswm pwysau.

**50.** Boncyffion tân Optima Fire Logs, a weithgynhyrchir gan Allspan BV yn Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses trin â gwres ac allwthio;
- (c) sydd tua 235 milimetr eu hyd a 80 milimetr o ddyfnder, gyda rhigolau ar hyd yr wynebaw;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**51.** Y siarcol Pagan Fuel's Restaurant Charcoal, a weithgynhyrchir gan Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay—

- (a) a gyfansoddir o'r coedydd caled *Prosopis nigra*, *Cordia alliodora*, *Centrolobeum*, *Prosopis kuntzei*, *Caesalpinia*, *Goncalo alves* and *Tabebuia* a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn olyn ar tuag 800°C;
- (c) sy'n ddarnau o siarcol rhwng 20 a 120 milimetr heb eu marcio; ac
- (d) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau mewn cyflwr sych.

**52.** Brics glo Phurnacite, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;
- (c) sy'n frics glo ar siâp ofoidau â dwy linell gyfochrog yn rhedeg yn hydredol o amgylch y fricsen;
- (d) sy'n pwyso 40 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**53.** Boncyffion tân Pyrobloc Fire Logs, a weithgynhyrchir gan Allspan BV yn Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—

- (e) have a sulphur content not exceeding 1.9% of the total weight.

**50.** Optima Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**51.** Pagan Fuel's Restaurant Charcoal, manufactured by Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay, which—

- (a) comprises pyrolised *Prosopis nigra*, *Cordia alliodora*, *Centrolobeum*, *Prosopis kuntzei*, *Caesalpinia*, *Goncalo alves* and *Tabebuia* hardwoods;
- (b) were manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20-120 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**52.** Phurnacite briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette;
- (d) have an average weight of 40 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**53.** Pyrobloc Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 265 milimetr o hyd ac 80 milimetr o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwyso 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**54.** Boncyffion tân Safelight Firelogs, a weithgynhyrchir gan Advanced Natural Fuels Limited, yn Pocklington, East Riding of Yorkshire—

- (a) a gyfansoddir o sglodion pren (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr o gwyr palmwydd (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys gwasgu'r cynhwysion, ar ôl eu cymysgu, ar dymheredd o tua 40°C i 50°C;
- (c) sy'n foncyffion tân petryal caled â dwy agen ddofn sy'n gorgyffwrdd ar yr wyneb uchaf, un agen ddi-dor ar yr wyneb isaf;
- (d) sy'n pwyso 1.8 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**55.** Brics glo Sovereign, a weithgynhyrchir gan Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, South Yorkshire—

- (a) a gyfansoddir o lo caled (sef tua 75% o'r cyfanswm pwysau), glo a golosg adweithiol (sef tua 21% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys allwthio;
- (c) sy'n frics glo chweonglog heb eu marcio;
- (d) sy'n pwyso 130 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**56.** Brics glo Stoveheat Premium, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o gyfanswm eu pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 265 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**54.** Safelight Firelogs, manufactured by Advanced Natural Fuels Limited, at Pocklington, East Riding of Yorkshire, which—

- (a) comprise woodchip (as to approximately 40 to 55% of the total weight) and palm wax binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving pressing of the mixed ingredients at about 40°C to 50°C;
- (c) are rectangular hard finish firelogs with two deep overlapping slots in the top surface, a single continuous slot in the base surface;
- (d) have an average weight of 1.8 kilograms; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**55.** Sovereign briquettes, manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire which—

- (a) comprise anthracite (as to approximately 75% of the total weight), coal and reactive coke (as to approximately 21% of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are unmarked hexagonal briquettes;
- (d) have an average weight of 130 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**56.** Stoveheat Premium briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;
- (c) sy'n frics glo ar siâp clustogau, gyda hicyn ar ffurf llinell sy'n ymestyn o amgylch y fricsen;
- (d) sy'n pwyso 30 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**57.** Supabrite Coke Doubles, a weithgynhyrchir gan H. J. Banks and Company Limited yn Inkerman Road Depot, Tow Law, County Durham—

- (a) a gyfansoddir o olog metelegol (sef tua 40 i 60% o'r cyfanswm pwysau) a golosg petrolewm (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys eu blendio a'u sgrinio;
- (c) sy'n hapsiapiau heb eu marcio; ac
- (d) nad yw eu cynnwys o sylffwr yn fwy nag 1.95% o'r cyfanswm pwysau.

**58.** Brics glo Supacite, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 240°C;
- (c) sy'n ofoidau heb eu marcio;
- (d) sy'n pwyso 45 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**59.** Brics glo Supertherm, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o gymysgedd (mewn cyfrannedd o 19:1) o lo caled a glo canolig ei anweddolrwydd (sef tua 93% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri neu rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n ofoidau heb eu marcio;
- (d) sy'n pwyso 160 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion shaped briquettes with an indented line running around the briquette;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**57.** Supabrite Coke Doubles, manufactured by H. J. Banks and Company Limited at Inkerman Road Depot, Tow Law, County Durham, which—

- (a) comprise metallurgical coke (as to approximately 40 to 60% of the total weight) and petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving blending and screening;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 1.95% of the total weight.

**58.** Supacite briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 240°C;
- (c) are unmarked ovoids;
- (d) have an average weight of 45 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**59.** Supertherm briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise a blend (in the proportion of 19:1) of anthracite and medium volatile coal (as to approximately 93% of the total weight) and cold-setting organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked ovoids;
- (d) have an average weight of 160 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**60.** Brics glo Supertherm II, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 36 i 51% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr organig neu rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n ofoidau wedi eu marcio ag un llinell ledredol ar draws un wyneb i bob bricsen;
- (d) sy'n pwyso 140 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau mewn cyflwr sych.

**61.** Brics glo Taybrite (a elwir fel arall yn frics glo Surefire), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres ar tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd sydd naill ai wedi'u marcio â hicyn ar ffurf un llinell hydredol ar bob wyneb, 10 milimetr i ffwrdd o'r llinell gyfatebol gyferbyn, neu sydd heb eu marcio;
- (d) sydd, yn y naill achos a'r llall, yn pwyso 80 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**62.** Brics glo Therma, a weithgynhyrchir gan Maxibrite Limited yn Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o rolio-wasgu a thrin â gwres ar tua 250°C;
- (c) sy'n frics glo hirgrwn/ar siâp deigrin gyda linell drwy'r canol;
- (d) sy'n pwyso 26 gram ar gyfartaledd; ac

**60.** Supertherm II briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are ovoids marked with a single latitudinal line running across one face of each briquette;
- (d) have an average weight of 140 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**61.** Taybrite briquettes (otherwise known as Surefire briquettes), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with a single indented line running longitudinally along each face, offset from its counterpart by 10 millimetres, or unmarked;
- (d) have an average weight of 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**62.** Therma Briquettes, manufactured by Maxibrite Limited at Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight) petroleum coke (as to approximately 12% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are oval/tear shaped briquettes with a line through the centre;
- (d) have an average weight of 26 grams; and

- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**63.** Brics glo Thermac, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, North East Lincolnshire—

- (a) a gyfansoddir o lo caled (sef tua 90% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 48 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy nag 1.5% o'r cyfanswm pwysau.

**64.** Boncyffion tân Tiger Tim, a weithgynhyrchir gan De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 50% o'r cyfanswm pwysau) a blawd llif (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses trin â gwres ac allwthio;
- (c) sydd tua 280 milimetr o hyd x 75 milimetr x 75 milimetr a chanddynt un rhigol yn rhedeg ar hyd pob un o'r pedwar wyneb sy'n 280 milimetr o hyd;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

**65.** Unicite, a weithgynhyrchir gan DJ Davies Fuels Limited yn Blaenau Fuel Depot, Rhydaman, Sir Gaerfyrddin, neu a weithgynhyrchir gan AI Simson yn Cabby Latch, Logie ger Kirriemuir, Angus—

- (a) sy'n gymysgedd o'r gwahanol danwyddau canlynol—
  - (i) nytiau mawr o lo caled, a
  - (ii) briciau tân Union o'r disgrifiad yn isbaragraff (d) a weithgynhyrchir gan RWE Power AG yn Cologne, Yr Almaen (sef dim mwy na thua 40 i 42% o'r cyfanswm pwysau Unicite);
- (b) nad yw eu cynnwys o sylffwr yn fwy na 0.5% o'r cyfanswm pwysau;
- (c) y datgenir nad yw'n danwydd awdurdodedig ac eithrio i'r graddau nad yw cyfran y briciau tân Union a losgir drwy ddefnyddio Unicite yn uwch na'r ystod ganrannau a bennir yn isbaragraff (a) (ii); ac

- (e) have a sulphur content not exceeding 2% of the total weight.

**63.** Thermac briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 90% of the total weight) and cold-setting organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 48 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**64.** Tiger Tim Firelogs, manufactured by De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 280 millimetres in length and 75 millimetres x 75 millimetres with a single groove running along each of the four 280 millimetre length faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**65.** Unicite, manufactured by DJ Davies Fuels Limited at Blaenau Fuel Depot, Ammanford, Carmarthenshire, or manufactured by AI Simson at Cabby Latch, Logie by Kirriemuir, Angus, which—

- (a) is a mixture of the following separate fuels—
  - (i) anthracite large nuts, and
  - (ii) Union briquettes of the description in sub paragraph (d) manufactured by RWE Power AG at Cologne, Germany (as to no more than approximately 40 to 42% of Unicite's total weight);
- (b) has a sulphur content not exceeding 0.5% of the total weight;
- (c) is declared to be an authorised fuel only in so far as the proportion of Union briquettes combusted in the use of Unicite does not exceed the percentage range specified in sub paragraph (a) (ii); and



- (d) i'r graddau y'i cyfansoddir o'r briciau tân Union y cyfeirir atynt yn is-baragraff (a) (ii), cyfansoddir ef o lignit cywasgedig, gyda phob bricsen dân yn mesur tua 75 milimetr o led, 60 milimetr o uchder a 55 milimetr o drwch.

**66.** Boncyffion tân Zip 100% Natural Firelogs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrâu triglyserid hydrogenaid o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 210 milimetr o hyd, 80 milimetr o led a 75 milimetr o uchder;
- (d) sy'n pwyso rhwng 1.085 ac 1.115 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

**67.** Boncyffion tân Zip 100% Natural Firelogs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrâu triglyserid hydrogenaid o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses trin â gwres ac allwthio;
- (c) sydd tua 245 milimetr o hyd, 75 milimetr o led a 68 milimetr o uchder;
- (d) sy'n pwyso rhwng 0.985 ac 1.015 cilogram y boncyff ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

**68.** Boncyffion ZIP 100% Natural Stove Logs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrâu triglyserid hydrogenaid o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);

- (d) in so far as it is constituted by the Union briquettes referred to in sub paragraph (a) (ii), consists of compressed lignite with each briquette measuring approximately 75 millimetres wide, 60 millimetres high and 55 millimetres thick.

**66.** Zip 100% Natural Firelogs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and a natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 210 millimetres in length, 80 millimetres in width and 75 millimetres in height;
- (d) have an average weight of between 1.085 and 1.115 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**67.** Zip 100% Natural Firelogs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and a natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 245 millimetres in length, 75 millimetres in width and 68 millimetres in height;
- (d) have an average weight of between 0.985 and 1.015 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**68.** ZIP 100% Natural Stove Logs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and natural molasses based binder (as to the remaining weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 165 milimetr o hyd, 80 milimetr o led a 75 milimetr o uchder;
- (d) sy'n pwysu rhwng 0.835 a 0.865 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

**69.** Boncyffion tân ZIP Cracklelog, boncyffion tân ZIP Crackle-log a boncyffion tân ZIP Crackling Log, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55% o'r cyfanswm pwysau), blawd llif pren caled (sef tua 42% o'r cyfanswm pwysau) a hadau clecian (sef tua 3.2% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 milimetr o hyd gyda diamedr o 80 milimetr a rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**70.** Boncyffion tân ZIP Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 265 milimetr o hyd ac 80 milimetr o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**71.** Boncyffion tân ZIP Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;

- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 165 millimetres in length, 80 millimetres in width and 75 millimetres in height;
- (d) have an average weight of between 0.835 and 0.865 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**69.** ZIP Cracklelog Firelogs, ZIP Crackle-log Firelogs and ZIP Crackling Log Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, The Netherlands, which—

- (a) comprise slack wax (as to approximately 55% of the total weight), hardwood sawdust (as to approximately 42% of the total weight) and crackle seeds (as to approximately 3.2% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in diameter, with grooves along the faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**70.** ZIP Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, The Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 265 millimetres in length and 80 millimetres in depth, with grooves along the faces;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**71.** ZIP Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, The Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;

- (c) sydd tua 235 milimetr o hyd a 80 milimetr o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

**72.** Boncyffion tân ZIP Firelogs, a weithgynhyrchir gan Woodflame Moerdijk BV, Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55 i 60% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 255 milimetr o hyd gyda diamedr o 75 milimetr a rhigolau ar hyd un wyneb hydredol;
- (d) sy'n pwysu 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.1% o'r cyfanswm pwysau.

---

©<sup>h</sup> Hawlfraint y Goron 2015

Argraffwyd a chyhoeddwyd yn y Deyrnas Unedig gan The Stationery Office Limited o dan awdurdod ac arolygiaeth Carol Tullo, Rheolwr Gwasg Ei Mawrhydi ac Argraffydd Deddfau Seneddol y Frenhines.

- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along the faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**72.** ZIP Firelogs, manufactured by Woodflame Moerdijk BV, Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, The Netherlands, which—

- (a) comprise slack wax (as to approximately 55 to 60% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 255 millimetres in length and 75 millimetres in diameter, with grooves along one longitudinal face;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

---

© Crown copyright 2015

Printed and Published in the UK by The Stationery Office Limited under the authority and superintendence of Carol Tullo, Controller of Her Majesty's Stationery Office and Queen's Printer of Acts of Parliament.

---

OFFERYNNAU STATUDOL  
CYMRU

---

---

WELSH STATUTORY  
INSTRUMENTS

---

**2015 Rhif 1517 (Cy. 176)**

**2015 No. 1517 (W. 176)**

**AER GLÂN, CYMRU**

**CLEAN AIR, WALES**

Rheoliadau Ardaloedd Rheoli Mwg  
(Tanwyddau Awdurdodedig)  
(Cymru) 2015

The Smoke Control Areas  
(Authorised Fuels) (Wales)  
Regulations 2015

£6.00

W2402/08/15

ON

ISBN 978-0-348-11146-0



9 780348 111460