



OFFERYNNAU STATUDOL  
CYMRU

WELSH STATUTORY  
INSTRUMENTS

**2017 Rhif 421 (Cy. 89)**

**2017 No. 421 (W. 89)**

**AER GLÂN, CYMRU**

**CLEAN AIR, WALES**

**Rheoliadau Ardaloedd Rheoli Mwg  
(Tanwyddau Awdurdodedig)  
(Cymru) 2017**

**The Smoke Control Areas  
(Authorised Fuels) (Wales)  
Regulations 2017**

**NODYN ESBONIADOL**

*(Nid yw'r nodyn hwn yn rhan o'r Rheoliadau)*

Mae'r Rheoliadau hyn yn dirymu ac yn disodli gyda diwygiadau Reoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2016 (O.S. 2016/812 (Cy. 202)) ("Rheoliadau 2016").

Mae adran 20 o Ddeddf Aer Glân 1993 ("Deddf 1993") yn darparu ei bod yn drosedd gollwng mwg o simnai adeilad neu simnai sy'n gwasanaethu ffwrnais boeler sefydlog neu beiriannau diwydiannol, os yw'r simnai honno mewn ardal rheoli mwg. Er hynny, yn rhinwedd adran 20(3) mae'n amddiffyniad os gellir profi mai drwy ddefnyddio tanwydd awdurdodedig yn unig yr achoswyd y gollyngiad honedig.

Yn rhinwedd adran 20(6), ystyr "tanwydd awdurdodedig" yw tanwydd y datganwyd drwy reoliadau ei fod wedi ei awdurdodi. Mae'r pŵer i wneud rheoliadau o'r fath yn arferadwy o ran Cymru gan Weinidogion Cymru.

Mae'r Rheoliadau hyn yn pennu pob tanwydd sydd wedi ei awdurdodi ar hyn o bryd i'w ddefnyddio mewn ardaloedd rheoli mwg yng Nghymru at ddibenion adran 20 o Ddeddf 1993.

Mae pob un o'r tanwyddau a restrwyd yn yr Atodlen i Reoliadau 2016 yn union cyn i'r Rheoliadau hyn ddod i rym yn parhau i fod yn danwyddau awdurdodedig, ac eithrio bod newid wedi ei wneud i fanyleb un tanwydd (ALDI Winter Flame Smokeless Fuel).

Mae un ar ddeg o danwyddau ychwanegol wedi eu hawdurdodi am y tro cyntaf (tri math o Big K Fire Log, dau fath o Gardeco Fire Log, dau fath o Homefire Fire Log, Hot Rocks, dau fath o La Hacienda Fire Log a Red Drops).

**EXPLANATORY NOTE**

*(This note is not part of the Regulations)*

These Regulations revoke and replace with amendments the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2016 (S.I. 2016/812 (W. 202)) ("the 2016 Regulations").

Section 20 of the Clean Air Act 1993 Act ("the 1993 Act") provides that it is an offence to emit smoke from a chimney of a building or a chimney serving a furnace of a fixed boiler or an industrial plant, if that chimney is within a smoke control area. However, by virtue of section 20(3), it is a defence to prove that the alleged emission was caused solely by the use of an authorised fuel.

By virtue of section 20(6), "authorised fuel" means a fuel declared by regulations to be an authorised fuel. The power to make such regulations is exercisable in relation to Wales by the Welsh Ministers.

These Regulations specify all fuels which are currently authorised for use in smoke control areas in Wales for the purposes of section 20 of the 1993 Act.

All the fuels that were listed in the Schedule to the 2016 Regulations immediately prior to the coming into force of these Regulations continue to be authorised fuels, with the exception that a change is made to the specification of one fuel (ALDI Winter Flame Smokeless Fuel).

Eleven additional fuels are authorised for the first time (three types of Big K Fire Log, two types of Gardeco Fire Log, two types of Homefire Fire Log, Hot Rocks, two types of La Hacienda Fire Log and Red Drops).

Ystyriwyd Cod Ymarfer Gweinidogion Cymru ar gynnal Aseidiadau Effaith Rheoleiddiol mewn perthynas â'r Rheoliadau hyn. Ystyriwyd nad oedd yn angenrheidiol cynnal aseiad effaith rheoleiddiol o'r costau a'r manteision sy'n debygol o ddeillio o gydymffurfio â'r Rheoliadau hyn.

The Welsh Ministers' Code of Practice on the carrying out of Regulatory Impact Assessments was considered in relation to these Regulations. It was not considered necessary to carry out a regulatory impact assessment as to the likely costs and benefits of complying with these Regulations.

**2017 Rhif 421 (Cy. 89)**

**2017 No. 421 (W. 89)**

**AER GLÂN, CYMRU**

**CLEAN AIR, WALES**

**Rheoliadau Ardaloedd Rheoli Mwg  
(Tanwyddau Awdurdodedig)  
(Cymru) 2017**

**The Smoke Control Areas  
(Authorised Fuels) (Wales)  
Regulations 2017**

*Gwnaed* 15 Mawrth 2017

*Made* 15 March 2017

*Gosodwyd gerbron Cynulliad Cenedlaethol  
Cymru* 17 Mawrth 2017

*Laid before the National Assembly for Wales*  
17 March 2017

*Yn dod i rym* 7 Ebrill 2017

*Coming into force* 7 April 2017

Mae Gweinidogion Cymru yn gwneud y Rheoliadau a ganlyn drwy arfer y pŵer a roddir gan adran 20(6) o Ddeddf Aer Glân 1993(1).

The Welsh Ministers make the following Regulations in exercise of the power conferred by section 20(6) of the Clean Air Act 1993(1).

#### **Enwi, cychwyn a chymhwyso**

1.—(1) Enw'r Rheoliadau hyn yw Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2017 a deuant i rym ar 7 Ebrill 2017.

(2) Mae'r Rheoliadau hyn yn gymwys o ran Cymru.

#### **Title, commencement and application**

1.—(1) The title of these Regulations is the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2017 and they come into force on 7 April 2017.

(2) These Regulations apply in relation to Wales.

#### **Tanwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993**

2. Datgenir bod glo caled, glo lled-galed, trydan, nwy, gloeau stêm isel eu hanweddolrwydd a'r tanwyddau a ddisgrifir yn yr Atodlen yn danwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993.

#### **Authorised fuels for the purposes of Part III of the Clean Air Act 1993**

2. Anthracite, semi-anthracite, electricity, gas, low volatile steam coals and the fuels described in the Schedule are declared to be authorised fuels for the purposes of Part III of the Clean Air Act 1993.

---

(1) 1993 p. 11. Trosglwyddwyd swyddogaeth berthnasol yr Ygrifennydd Gwladol, i'r graddau yr oedd yn arferadwy o ran Cymru, i Gynulliad Cenedlaethol Cymru yn rhinwedd erthygl 2 o Orchymyn Cynulliad Cenedlaethol Cymru (Trosglwyddo Swyddogaethau) 1999 (O.S 1999/672) ac Atodlen 1 iddo. Mae'r swyddogaeth honno'n arferadwy bellach gan Weinidogion Cymru yn rhinwedd adran 162 o Ddeddf Llywodraeth Cymru 2006 (p. 32) a pharagraff 30 o Atodlen 11 iddi.

---

(1) 1993 c. 11. The relevant function of the Secretary of State was, so far as exercisable in relation to Wales, transferred to the National Assembly for Wales by virtue of article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672). That function is now exercisable by the Welsh Ministers by virtue of section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c. 32).

**Dirymu**

3. Mae Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2016(1) wedi eu dirymu.

**Revocation**

3. The Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2016(1) are revoked.

*Carwyn Jones*

Prif Weinidog Cymru  
15 Mawrth 2017

First Minister of Wales  
15 March 2017

---

(1) O.S. 2016/812 (Cy. 202).

---

(1) S.I. 2016/812 (W. 202).

## Tanwyddau Awdurdodedig

1. ALDI Winter Flame Smokeless Fuel, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sydd naill ai'n frics glo heb eu marcio ar siâp gobennydd neu'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetr i ffwrdd o'r llinell gyfatebol gyferbyn;
- (d) sy'n pwyso naill ai 55 neu 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

2. Brics glo Aimcor Excel, a weithgynhyrchir gan Applied Industrial Materials UK Limited yn Newfield, Swydd Durham, neu a weithgynhyrchir gan Oxbow Carbon & Minerals UK Limited yn Windsor House, Cornwall Road, Harrogate, Gogledd Swydd Efrog—

- (a) a gyfansoddir o olog petrolewm (sef tua 60 i 75% o'r cyfanswm pwysau), glo anweddolrwydd-isel a golosg adweithiol (sef tua 20 i 25% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 73 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

## Authorised Fuels

1. ALDI Winter Flame Smokeless Fuel, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;
- (d) have an average weight of either 55 or 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

2. Aimcor Excel briquettes, manufactured by Applied Industrial Materials UK Limited at Newfield, County Durham, or manufactured by Oxbow Carbon & Minerals UK Limited at Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—

- (a) comprise petroleum coke (as to approximately 60 to 75% of the total weight), low volatile coal and reactive coke (as to approximately 20 to 25% of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 73 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**3.** Brics glo Aimcor Pureheat, a weithgynhyrchir gan Applied Industrial Materials UK Limited yn Immingham, Gogledd Ddwyrain Swydd Lincoln, neu a weithgynhyrchir gan Oxbow Carbon & Minerals UK Limited yn Windsor House, Cornwall Road, Harrogate, Gogledd Swydd Efrog—

- (a) a gyfansoddir o lo caled (sef tua 60% o'r cyfanswm pwysau), golosg petrolewm (sef tua 25% o'r cyfanswm pwysau) a rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo ar siâp gobennydd gyda hicyn ar ffurf llinell sengl ar un ochr a hicyn ar ffurf llinell ddwbl ar yr ochr arall;
- (d) sy'n pwyso 75 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**4.** Brics glo Ancit, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 95% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 30% o'r cyfanswm pwysau), glo meddal (hyd at tua 15% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp clustog;
- (d) sy'n pwyso 48 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**5.** Big K Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwyso 0.8 cilogram ar gyfartaledd; ac

**3.** Aimcor Pureheat briquettes, manufactured by Applied Industrial Materials UK Limited at Immingham, North East Lincolnshire, or manufactured by Oxbow Carbon & Minerals UK Limited at Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—

- (a) comprise anthracite (as to approximately 60% of the total weight), petroleum coke (as to approximately 25% of the total weight) and binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are pillow-shaped briquettes with a single line indentation on one side and a double line indentation on the reverse side;
- (d) have an average weight of 75 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**4.** Ancit briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 95% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight) and a molasses and phosphoric acid binder or an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked cushion-shaped briquettes;
- (d) have an average weight of 48 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**5.** Big K Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and

- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**6. Big K Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—**

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 193 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 0.9 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**7. Big K Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—**

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 215 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**8. Big K Instant Lighting Fire Logs, a weithgynhyrchir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—**

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

- (e) have a sulphur content not exceeding 0.1% of the total weight.

**6. Big K Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—**

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 193 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.9 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**7. Big K Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—**

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 215 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**8. Big K Instant Lighting Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—**

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth and with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**9.** Big K Restaurant Grade Charcoal, a weithgynhyrchir gan Big K Products UK Limited yn Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, yr Ariannin—

- (a) a gyfansoddir o bren quebracho gwyn a byrolswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyr ar tua 450°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**10.** Brics glo Black Diamond Gem, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 20 i 30% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 12 i 22% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n rhedeg yn lledredol o amgylch y fricsen;
- (d) sy'n pwysu 160 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

**11.** Bord na Móna Firelogs, a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Iwerddon—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 255 o filimetrau o hyd gyda diamedr o 75 o filimetrau, gyda rhigolau ar hyd un wyneb hydredol;
- (d) sy'n pwysu 1.3 cilogram (net) ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**9.** Big K Restaurant Grade Charcoal, manufactured by Big K Products UK Limited at Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, Argentina, which—

- (a) comprise pyrolysed white quebracho wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 450°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**10.** Black Diamond Gem briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 20 to 30% of the total weight), petroleum coke (as to approximately 40 to 45% of the total weight), bituminous coal (as to approximately 12 to 22% of the total weight) and molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 160 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**11.** Bord na Móna Firelogs, manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Ireland, which—

- (a) comprise slack wax (as to approximately 55% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 255 millimetres in length and 75 millimetres in diameter, and with grooves along one longitudinal face;
- (d) have an average weight of 1.3 kilograms (net); and
- (e) have a sulphur content not exceeding 0.1% of the total weight.



**12.** Brics glo Bord na Móna Firepak (a farchnetir hefyd fel brics glo Arigna Special), a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Iwerddon—

- (a) a gyfansoddir o lo caled (sef tua 50% o'r cyfanswm pwysau), golosg petrolewm (sef tuag 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr seiliedig ar starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres;
- (c) sy'n frics glo heb eu marcio, ar siâp gobennydd;
- (d) sy'n pwyso 50 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

**13.** Brics glo Brazier, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau), a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sydd naill ai'n frics heb eu marcio ar siâp gobennydd neu'n frics ar siâp gobennydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetr i ffwrdd o'r llinell gyfatebol gyferbyn;
- (d) sy'n pwyso naill ai 50 neu 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

**14.** Brics glo Briteflame, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;

**12.** Bord na Móna Firepak briquettes (also marketed as Arigna Special coal briquettes), manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Ireland, which—

- (a) comprise anthracite (as to approximately 50% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 10 to 30% of the total weight) and starch based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 50 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**13.** Brazier briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;
- (d) have an average weight of either 50 or 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**14.** Briteflame briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight), and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;

- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwysu 140 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

**15.** Brics glo Briteheat, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 85% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 30% o'r cyfanswm pwysau), glo meddal (hyd at tua 15% o'r cyfanswm pwysau), a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp clustog gyda hicyn ar ffurf llinell yn rhedeg yn hydredol o gwmpas y fricsen;
- (d) sy'n pwysu 30 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**16.** Brics glo Briteheat Plus, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 75 i 95% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 20% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwysu 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**17.** Bryant and May Firelogs, a weithgynhyrchir gan Swedish Match yn Kostenetz, Bwlgaria—

- (a) a gyfansoddir o gwyr paraffin (sef tua 50% o'r cyfanswm pwysau), pren poplys mâl (sef tua 25% o'r cyfanswm pwysau), blawd gwenith (sef tua 15% o'r cyfanswm pwysau), solidau cyneudwy ar wasgar mewn cwr paraffin ar ffurf jel (sef tua 1% o'r cyfanswm pwysau) a dŵr, cyfryngau chwyddo a chadwolyn (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys allwthio;

- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 140 grams; and
- (e) have a sulphur content not exceeding 1.9% sulphur on a dry basis.

**15.** Briteheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 85% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion-shaped briquettes with an indented line running longitudinally around the briquette;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**16.** Briteheat Plus briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 75 to 95% of the total weight), petroleum coke (up to approximately 20% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow shaped briquettes;
- (d) have an average weight of 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**17.** Bryant and May Firelogs, manufactured by Swedish Match at Kostenetz, Bulgaria, which—

- (a) comprise paraffin wax (as to approximately 50% of the total weight), ground poplar wood (as to approximately 25% of the total weight), wheatflour (as to approximately 15% of the total weight), ignitable solids dispersed in gelled paraffin wax (as to approximately 1% of the total weight) and water, swelling agents and preservative (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;

- (c) sydd â'u trawstoriad yn gwadrant gyda radiws o tua 80 o filimetrau a'u hyd tua 265 o filimetrau gyda sribyn cynnau ar hyd un ymyl;
- (d) sy'n pwysu tuag 1.15 cilogram; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**18.** Brics glo Charglow, a weithgynhyrchir gan Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Gwlad Pwyl—

- (a) a gyfansoddir o gols glo meddal (sef tua 45 i 95% o'r cyfanswm pwysau), glo caled (sef tua 0 i 20% o'r cyfanswm pwysau), golosg petrolewm (sef tua 0 i 20% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 110°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwysu 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

**19.** Coalite, a weithgynhyrchir gan Coalite Products Limited yn Bolsover, ger Chesterfield, Swydd Derby ac yn Grimethorpe, De Swydd Efrog drwy ddefnyddio proses o garboneiddio ar dymheredd isel.

**20.** Brics glo Coalite Ovals, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd tua 84 o filimetrau o hyd, 38 o filimetrau o led a 62 o filimetrau o uchder;
- (d) sy'n pwysu 118 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

- (c) are of quadrant cross sections with a radius of approximately 80 millimetres, and length approximately 265 millimetres with an ignition strip along one edge;
- (d) have an approximate weight of 1.15 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**18.** Charglow briquettes, manufactured by Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Poland, which—

- (a) comprise bituminous coal char (as to approximately 45 to 95% of the total weight), anthracite (as to approximately 0 to 20% of the total weight), petroleum coke (as to approximately 0 to 20% of the total weight), bituminous coal (as to approximately 0 to 10% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing and heat treatment at about 110°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**19.** Coalite, manufactured by Coalite Products Limited at Bolsover, near Chesterfield, Derbyshire and at Grimethorpe, South Yorkshire using a low temperature carbonisation process.

**20.** Coalite Ovals briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes that are approximately 84 millimetres in length, 38 millimetres in width and 62 millimetres in height;
- (d) have an average weight of 118 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.

**21. Golosg a weithgynhyrchir gan—**

- (a) Coal Products Limited yn Cwm Coking Works, Llanilltud Faerdref, Pontypridd, Rhondda Cynon Taf, ac a werthir fel “Sunbrite”;
- (b) Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, De Swydd Efrog ac a werthir fel “Sunbrite” neu “Monckton Boiler Beans”;
- (c) Corus UK Limited yn Teesside Works, Redcar & Cleveland ac a werthir fel “Redcar Coke Nuts (Doubles)”;
- (d) Coal Products Limited yn Cwm Coking Works, Llanilltud Faerdref, Pontypridd, Rhondda Cynon Taf ac a werthir fel “Cwm Coke Doubles”.

**22. Cosycoke** (a farchnetir hefyd fel Lionheart Crusader neu Sunbrite Plus), a weithgynhyrchir gan Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, De Swydd Efrog ac Aimcor Supercoke (a farchnetir hefyd fel Supercoke), a weithgynhyrchir gan M & G Fuels Limited yn Hartlepool Docks, Hartlepool, ac ym mhob achos—

- (a) a gyfansoddir o ologsg caled o faint penodol (sef tua 45 i 65% o'r cyfanswm pwysau) a golosg petrolewm o faint penodol (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy eu blendio;
- (c) sy'n hapsapiau heb eu marcio; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**23. Brics glo Cosyglo Smokeless** a weithgynhyrchir gan Arigna Fuels yn Arigna, Carrick-on-Shannon, County Roscommon, Iwerddon—

- (a) a gyfansoddir o lo caled (sef tua 35 i 50% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 45% o'r cyfanswm pwysau), glo meddal (hyd at tuag 20% o'r cyfanswm pwysau) a rhwymwr starts neu rywimwr organig arall (hyd at 5% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd tua 80 o filimetrau o hyd, 60 o filimetrau o led a 40 o filimetrau o uchder;
- (d) sy'n pwysu 110 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.8% o gyfanswm eu pwysau sych yn sylffwr.

**21. Coke, manufactured by—**

- (a) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taf, and sold as “Sunbrite”;
- (b) Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, and sold as “Sunbrite” or “Monckton Boiler Beans”;
- (c) Corus UK Limited at Teesside Works, Redcar & Cleveland, and sold as “Redcar Coke Nuts (Doubles)”;
- (d) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taf, and sold as “Cwm Coke Doubles”.

**22. Cosycoke** (also marketed as Lionheart Crusader or Sunbrite Plus), manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire and Aimcor Supercoke (also marketed as Supercoke), manufactured by M & G Fuels Limited at Hartlepool Docks, Hartlepool, which in each case—

- (a) comprise sized hard coke (as to approximately 45 to 65% of the total weight) and sized petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by blending;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**23. Cosyglo Smokeless briquettes**, manufactured by Arigna Fuels at Arigna, Carrick-on-Shannon, County Roscommon, Ireland, which—

- (a) comprise anthracite (as to approximately 35 to 50% of the total weight), petroleum coke (up to approximately 45% of the total weight), bituminous coal (up to approximately 20% of the total weight) and a starch or other organic binder (up to 5% of the total weight);
- (b) are manufactured from those constituents by a process involving roll-pressing and heat treatment at approximately 250°C;
- (c) are unmarked pillow-shaped briquettes that are approximately 80 millimetres in length, 60 millimetres in width and 40 millimetres in height;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.8% of the total weight on a dry basis.

**24.** CPL Restaurant Grade Charcoal – a weithgynhyrchir gan Kunfayakun Global Treasures Limited (KGT) yn Kunfayakun Stores, No. 1, Aranse Street, Station, Sagamu, Orgub State E17, Shagamu International Market, Nigeria—

- (a) a gyfansoddir o Anogeissus Leiocarpus, Burkea Africana, Distemonanthus Benthamianus a Viteloria Paracloxum wedi eu pyrolysu;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyd ar tua 450°C i 550°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 50 a 180 o filimetrau; a
- (d) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

**25.** Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal, a weithgynhyrchir gan Direct Charcoal yn Ekamanzi Road, Dalton, KwaZulu Natal, Gweriniaeth De Affrica—

- (a) a gyfansoddir o bren Acacia mercii a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyd ar tua 420 i 480°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**26.** Direct Charcoal Blue Bag Restaurant Charcoal, a weithgynhyrchir gan Direct Charcoal Limited yn Ruta 25, km. 9,5 –Pilar (cp.1629) Buenos Aires, yr Ariannin—

- (a) a gyfansoddir o bren quebracho gwyn a phren guayacan wedi eu pyrolysu;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyd ar tua 420 i 480°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**27.** Brics glo Dragonbrite, a weithgynhyrchir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf—

- (a) a gyfansoddir o lwch y tŵr (sef tua 95% o'r cyfanswm pwysau) a rhwymwr seiliedig ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo ar siâp gobennydd, wedi eu marcio â'r llythyren "T" ar un ochr;

**24.** CPL Restaurant Grade Charcoal, manufactured by Kunfayakun Global Treasures Limited (KGT) at Kunfayakun Stores, No. 1, Aranse Street, Station, Sagamu, Orgub State E17, Shagamu International Market, Nigeria, which—

- (a) comprises pyrolised Anogeissus Leiocarpus, Burkea Africana, Distemonanthus Benthamianus and Viteloria Paracloxum;
- (b) was manufactured using a kiln pyrolysis process at approximately 450°C to 550°C;
- (c) are unmarked charcoal pieces of between 50-180 millimetres; and
- (d) has a sulphur content not exceeding 1.9% of the total weight on a dry basis.

**25.** Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal, manufactured by Direct Charcoal at Ekamanzi Road, Dalton, KwaZulu Natal, Republic of South Africa, which—

- (a) comprise pyrolised Acacia mercii wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 420 to 480°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**26.** Direct Charcoal Blue Bag Restaurant Charcoal, manufactured by Direct Charcoal Limited at Ruta 25, km. 9,5 -Pilar (cp1629) Buenos Aires, Argentina, which—

- (a) comprise pyrolised white quebracho and guayacan wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 420 to 480°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**27.** Dragonbrite briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf, which—

- (a) comprise tower duff (as to approximately 95% of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are pillow-shaped briquettes marked with the letter "T" on one side;

- (d) sy'n pwyso 50 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1% o gyfanswm eu pwysau yn sylffwr.

**28.** Brics glo Dragonglow, a weithgynhyrchir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf—

- (a) a gyfansoddir o lwch y tŵr (sef tua 95% o'r cyfanswm pwysau) a rhwymwr seiliedig ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1% o gyfanswm eu pwysau yn sylffwr.

**29.** Duraflame Firelogs, a weithgynhyrchir gan Paramelt BV, Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr petrolewm mwynol (sef tua 55% o'r cyfanswm pwysau) a ffibr pren caled mâl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 320 o filimetrau o hyd, 90 o filimetrau o uchder ac 85 o filimetrau o led;
- (d) sy'n pwyso 1.45 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**30.** Brics glo Ecoal (a farchnetir hefyd fel brics glo Homefire Ecoal a Supertherm 30), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;

- (d) have an average weight of 50 grams; and
- (e) have a sulphur content not exceeding 1% of the total weight.

**28.** Dragonglow briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf, which—

- (a) comprise tower duff (as to approximately 95% of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1% of the total weight.

**29.** Duraflame Firelogs, manufactured by Paramelt BV, Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, the Netherlands, which—

- (a) comprise mineral-based petroleum wax (as to approximately 55% of the total weight) and ground hardwood fibre (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 320 millimetres in length, 90 millimetres in height and 85 millimetres wide;
- (d) have an average weight of 1.45 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**30.** Ecoal briquettes (also marketed as Homefire Ecoal briquettes and Supertherm 30), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and molasses and phosphoric acid as binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at approximately 300°C;

- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd fel arfer yn 72 o filimetrau o hyd, 58 o filimetrau o led a 42 o filimetrau o uchder neu sy'n frics glo chweonglog heb eu marcio sydd fel arfer yn 70 o filimetrau o hyd, 73 o filimetrau o led a 39 o filimetrau o uchder;
- (d) sy'n pwyso 125 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**31.** Brics glo Ecoal 50, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 30 i 55% o'r cyfanswm pwysau), biomas (sef tua 25 i 35% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 5% o'r cyfanswm pwysau) a rhwymwr organig naturiol (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a'u trin wedyn â gwres o tua 300°C mewn amgylchedd rheoledig gydag ocsigen gostyngedig;
- (c) sy'n frics glo chweonglog gydag un streipen sengl ar un ochr ar draws y wynebau gwastad;
- (d) sy'n pwyso 135 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**32.** Brics glo Ecobrite, a weithgynhyrchir gan Arigna Fuels Limited yn Arigna, Carrick-on-Shannon, County Roscommon, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 96% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd mewn dau faint;
- (d) sydd, ar gyfartaledd, yn pwyso 37 gram yn achos y maint lleiaf a 48 gram yn achos y maint mwyaf; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

- (c) are unmarked pillow shaped briquettes that are typically 72 millimetres in length, 58 millimetres in width and 42 millimetres in height or are unmarked hexagonal briquettes that are typically 70 millimetres in length, 73 millimetres in width and 39 millimetres in height;
- (d) have an average weight of 125 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**31.** Ecoal 50 briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 30 to 55% of the total weight), biomass (as to approximately 25 to 35% of the total weight), petroleum coke (as to approximately 10 to 40% of the total weight), bituminous coal (as to approximately 0 to 5% of the total weight) and natural organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at approximately 300°C in a controlled, reduced oxygen environment;
- (c) are hexagonal-shaped briquettes with a single stripe on one side across the flats;
- (d) have an average weight of 135 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**32.** Ecobrite briquettes, manufactured by Arigna Fuels Limited at Arigna, Carrick-on-Shannon, County Roscommon, Ireland, which—

- (a) comprise anthracite fines (as to approximately 96% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are unmarked pillow-shaped briquettes in two sizes;
- (d) have an average weight of 37 grams for the smaller size and 48 grams for the larger size; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**33.** EDF Fuel Briquettes, a weithgynhyrchir gan TheGreenFactory yn y Laboratoire de Chimie Agro-industrielle UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue D'Azereiz, - BP 1629 65016 Tarbes Cedex, Ffrainc—

- (a) a gyfansoddir o tua 100 gram o Miscanthus heb ei brosesu (sef tua 45% o'r cyfanswm pwysau), tua 95 gram o ester Copra (sef tua 43% o'r cyfanswm pwysau), a thua 25 gram o rywmyr a gynhyrchwyd o Miscanthus (wedi ei brosesu â chalsiwm ocsid, sy'n ffurfio tua 0.5% o'r cyfanswm pwysau), sef gweddill y pwysau;
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys prosesu Miscanthus, cymysgu, poethwasgu, a throchi mewn baddon ester;
- (c) sy'n frics glo heb eu marcio ar siâp silindr, 120 o filimetrau o uchder gyda diamedr o 60 o filimetrau, a thwll canolog ar siâp seren yn treiddio drwy hyd hiraf y fricsen;
- (d) sy'n pwyso 220 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**34.** Brics glo Excel+, a weithgynhyrchir gan Oxbow Coal BV yn Newfield Works, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o olog petrolewm (sef 65 i 70% o'r cyfanswm pwysau), glo caled (sef 25% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri, caledwr a sefydlogydd tymheredd isel (sef gweddill y pwysau);
- (b) a gynhyrchir ar y tymheredd amgylchynol drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sgwâr;
- (d) sy'n pwyso 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau yn sylffwr.

**35.** Brics glo Extracite, a weithgynhyrchir gan Sophia-Jacoba Handelsgesellschaft GmbH yn Hückelhoven, yr Almaen—

- (a) a gyfansoddir o lwch glo caled (sef tua 95.5% o'r cyfanswm pwysau) a lleisw amoniwm lignosylffonad yn rhwymwr (sef gweddill y pwysau);

**33.** EDF Fuel Briquettes, manufactured by TheGreenFactory at the Laboratoire de Chimie Agro-industrielle UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue D'Azereiz, - BP 1629 65016 Tarbes Cedex, France, which—

- (a) comprise approximately 100 grams of unprocessed Miscanthus (as to approximately 45% of the total weight), approximately 95 grams of Copra ester (as to approximately 43% of the total weight), and approximately 25 grams of a binder produced from Miscanthus (processed with calcium oxide as to approximately 0.5% of the total weight) as to the remaining weight;
- (b) are manufactured from those constituents by a process involving Miscanthus processing, mixing, hot pressing and soaking in an ester bath;
- (c) are unmarked cylinder-shaped briquettes of 120 millimetres in height and 60 millimetres in diameter with a star-shaped hole running centrally through the longer length of the briquette;
- (d) have an average weight of 220 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**34.** Excel+ briquettes, manufactured by Oxbow Coal BV at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to 65 to 70% of the total weight), anthracite (as to 25% of the total weight) and a cold setting resin binder, hardener and low temperature stabiliser (as to the remaining weight);
- (b) are produced at ambient temperature by a process involving roll pressing and cold curing;
- (c) are unmarked square pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight.

**35.** Extracite briquettes, manufactured by Sophia-Jacoba Handelsgesellschaft GmbH at Hückelhoven, Germany, which—

- (a) comprise anthracite duff (as to approximately 95.5% of the total weight) and ammonium lignosulphonate lye as binder (as to the remaining weight);



- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo ag arlliw ariannaidd ar siâp clustog, wedi eu marcio â'r llythrennau "S" a "J";
- (d) sy'n pwyso 40 gram ar gyfartaledd; ac
- (e) y mae cyfanswm eu pwysau yn cynnwys tua 1.2% o sylffwr.

**36.** Brics glo Fireglo, a weithgynhyrchir gan Les Combustibles de Normandie yn Caen, Ffrainc, a chan La Société Rouennaise de Défumage yn Rouen, Ffrainc—

- (a) a gyfansoddir o lychau Cymreig wedi eu golchi (sef tua 92% o'r cyfanswm pwysau) a rhwymwr o byg glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 330°C;
- (c) sy'n ofoidau gyda thair llinell ar un ochr a'r ochr arall yn llyfn;
- (d) sy'n pwyso 30 gram ar gyfartaledd; ac
- (e) nad yw mwy na 0.8% o gyfanswm eu pwysau yn sylffwr.

**37.** Brics glo Firegold, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 36 i 51% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr organig neu rhwymwr o driagl ac asid ffosfforig (sef 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd fel arfer yn 54 o filimetrau o hyd, 58 o filimetrau o led a 34 o filimetrau o uchder;
- (d) sy'n pwyso 87 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

**38.** Gardeco Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are cushion-shaped briquettes with a silvery appearance and are marked with the letters "S" and "J";
- (d) have an average weight of 40 grams; and
- (e) have a sulphur content of approximately 1.2% of the total weight.

**36.** Fireglo briquettes, manufactured by Les Combustibles de Normandie at Caen, France, and by La Société Rouennaise de Défumage at Rouen, France, which—

- (a) comprise washed Welsh duffs (as to approximately 92% of the total weight) and coal pitch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 330°C;
- (c) are ovoids with three lines on one side and are smooth on the other side;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 0.8% of the total weight.

**37.** Firegold briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow shaped briquettes that are typically 54 millimetres in length, 58 millimetres in width and 34 millimetres in height;
- (d) have an average weight of 87 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**38.** Gardeco Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**39.** Gardeco Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 237 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**40.** G N Grosvenor (Fuel Express) Restaurant Charcoal, a weithgynhyrchir gan Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay—

- (a) a gyfansoddir o'r coedydd caled *Prosopis nigra*, *Cordia alliodora*, *Centrolobium*, *Prosopis kuntzei*, *Caesalpinia*, *Goncalo alves* a *Tabebuia* wedi eu pyrolysu;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tuag 800°C;
- (c) sy'n ddarnau o siarcol rhwng 20 a 120 o filimetrau, heb eu marcio; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

**41.** Brics glo Homefire, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 70% o'r cyfanswm pwysau), golosg petrolewm (sef tuag 20 i 45% o'r cyfanswm pwysau), cols (sef tua 0 i 10% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 30% o'r cyfanswm pwysau) a rhwymwr organig neu rywyrwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;

- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**39.** Gardeco Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 237 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**40.** G N Grosvenor (Fuel Express) Restaurant Charcoal, manufactured by Pabensa SA Aviadores del Chaco, Asuncion, Paraguay, which—

- (a) comprises pyrolysed *Prosopis nigra*, *Cordia alliodora*, *Centrolobium*, *Prosopis kuntzei*, *Caesalpinia*, *Goncalo alves* and *Tabebuia* hardwoods;
- (b) were manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20 and 120 millimetres; and
- (d) has a sulphur content not exceeding 2% of the total weight on a dry basis.

**41.** Homefire briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 40 to 70% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), char (as to approximately 0 to 10% of the total weight), bituminous coal (as to approximately 5 to 30% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;

- (c) nad yw eu cynnwys o ddeunydd anwedddol, fel brics glo gorffenedig, yn llai na 9% nac yn fwy na 15% o'r cyfanswm pwysau sych;
- (d) sy'n frics glo chweonglog heb eu marcio;
- (e) sy'n pwyso 140 gram ar gyfartaledd; ac
- (f) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**42.** Homefire Fire Logs, a weithgynhyrchir gan De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 50% o'r cyfanswm pwysau) a blawd llif (sef tua 50% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 280 o filimetrau o hyd, 75 o filimetrau o led a 75 o filimetrau o uchder, gydag un rhigol ar hyd pob un o'u pedwar wyneb sydd â'u hyd yn 280 milimetr;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

**43.** Homefire Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwyso 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**44.** Homefire Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 215 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwyso 1 cilogram ar gyfartaledd; ac

- (c) have a volatile matter content in the finished briquette of neither less than 9% nor more than 15% of the total weight on a dry basis;
- (d) are unmarked hexagonal briquettes;
- (e) have an average weight of 140 grams; and
- (f) have a sulphur content not exceeding 2% of the total weight.

**42.** Homefire Fire Logs, manufactured by De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to approximately 50% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 280 millimetres in length, 75 millimetres in width and 75 millimetres in height, with a single groove running along each of the four 280 millimetre length faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**43.** Homefire Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**44.** Homefire Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 215 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1 kilograms; and

- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**45.** Homefire Ovals, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 57% o'r cyfanswm pwysau), golosg petrolewm (sef tua 17% o'r cyfanswm pwysau), glo meddal (sef tua 13% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwyso 135 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**46.** Homefire Ovals (R), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 50 i 75% o'r cyfanswm pwysau), golosg petrolewm (sef tuag 20 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 17% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwyso 130 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**47.** Hot Drops, a weithgynhyrchir gan EU Zeme Limited yn Riga, Eksporta Street 15, LV-1045, Latfia—

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid orthoffosfforig (sef gweddill y pwysau);

- (e) have a sulphur content not exceeding 0.1% of the total weight.

**45.** Homefire Ovals, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 57% of the total weight), petroleum coke (as to approximately 17% of the total weight), bituminous coal (as to approximately 13% of the total weight) and molasses and phosphoric acid as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 135 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**46.** Homefire Ovals (R), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 50 to 75% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), bituminous coal (as to approximately 5 to 17% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 130 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**47.** Hot Drops, manufactured by EU Zeme Limited at Riga, Eksporta Street 15, LV-1045, Latvia, which—

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu, ac wedyn eu trin â gwres o tua 250 i 280°C;
- (c) sy'n frics glo, ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 40 o filimetrau a thrwch o tua 21 o filimetrau yng nghanol y fricsen;
- (d) sy'n pwyso 23 gram ar gyfartaledd; ac
- (e) nad yw mwy na 0.5% o gyfanswm eu pwysau yn sylffwr.

**48.** Hot Rocks, a weithgynhyrchir gan EU Zeme Limited yn Riga, Eksporta Street 15, LV-1045, Latfia—

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau) a rhwymwr triagl ac asid orthoffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu, ac wedyn eu trin â gwres o tua 250 i 280°C;
- (c) sy'n frics glo, ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 40 o filimetrau a thrwch o tua 21 o filimetrau yng nghanol y fricsen;
- (d) sy'n pwyso 23 gram ar gyfartaledd; ac
- (e) nad yw mwy na 0.5% o gyfanswm eu pwysau yn sylffwr.

**49.** HouseFuel Smokeless Ovals, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 78 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

- (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at about 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and approximately 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

**48.** Hot Rocks, manufactured by EU Zeme Limited at Riga, Eksporta Street 15, LV-1045, Latvia, which—

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing followed by heat treatment at a temperature of approximately 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and about 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

**49.** HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 78 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**50.** HouseFuel Smokeless Ovals, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal a golosg petrolewm (y ddau hyd at tua 10 i 15% o'r cyfanswm pwysau) a llwch glo caled gyda rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd gyda'u dimensiynau mwyaf tua 68 o filimetrau, 63 o filimetrau a 38 o filimetrau;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

**51.** Island Lump ac Island Nuts, a weithgynhyrchir gan Unocal Refinery, California, Unol Daleithiau America—

- (a) a gyfansoddir o ologsg petrolewm;
- (b) a weithgynhyrchwyd o'r golosg petrolewm drwy broses sy'n cynnwys trin â gwres a chwistrellu stêm;
- (c) sy'n hapsapiau heb eu marcio;
- (d) sy'n pwyso 80 gram ar gyfartaledd (Island Lump) neu 30 gram ar gyfartaledd (Island Nuts); ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**52.** Brics glo Jewel, a weithgynhyrchir gan Eldon Colliery Limited yn Newfield Works, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o lo caled (sef tua 30 i 50% o'r cyfanswm pwysau), golosg petrolewm Long Beach (sef tua 50 i 70% o'r cyfanswm pwysau) a rhwymwr o garbohydrad (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 150°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 33 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

**50.** HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal and petroleum coke (each as to approximately 10 to 15% of the total weight) and anthracite duff and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes with approximate maximum dimensions 68 millimetres, 63 millimetres and 38 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.9% on a dry basis.

**51.** Island Lump and Island Nuts, manufactured by Unocal Refinery, California, the United States of America, which—

- (a) comprise petroleum coke;
- (b) were manufactured from the petroleum coke by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes;
- (d) have an average weight of 80 grams (Island Lump) or 30 grams (Island Nuts); and
- (e) have a sulphur content not exceeding 2% of the total weight.

**52.** Jewel briquettes, manufactured by Eldon Colliery Limited at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise anthracite (as to approximately 30 to 50% of the total weight), Long Beach petroleum coke (as to approximately 50 to 70% of the total weight) and a carbohydrate binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 150°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 33 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**53.** La Hacienda Easy Logs, a weithgynhychir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhychwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**54.** La Hacienda Fire Log, a weithgynhychir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhychwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**55.** La Hacienda Fire Log, a weithgynhychir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhychwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 237 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**53.** La Hacienda Easy Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**54.** La Hacienda Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**55.** La Hacienda Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 237 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**56.** Glo cnapiau Long Beach Lump (a elwir hefyd yn lo cnapiau LBL), a weithgynhrychir gan Aimcor Carbon Corporation yn Long Beach, California, Unol Daleithiau America neu a weithgynhrychir gan Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, Unol Daleithiau America—

- (a) a gyfansoddir o ologswm petrolewm (sef tua 85 i 100% o'r cyfanswm pwysau), calchfaen (sef tua 0 i 10% o'r cyfanswm pwysau) a phyg tar glo (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys trin â gwres a chwistrellu stêm;
- (c) sy'n hapsiapiau heb eu marcio; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**57.** Brics glo Maxibrite, a weithgynhrychir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo ar siâp clustog wedi eu marcio â'r llythyren "M";
- (d) sy'n pwyso 35 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**58.** Brics glo Multiheat, a weithgynhrychir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso naill ai 55 neu 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**56.** Long Beach Lump nuts (otherwise known as LBL nuts), manufactured by Aimcor Carbon Corporation at Long Beach, California, the United States of America, or manufactured by Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, the United States of America, which—

- (a) comprise petroleum coke (as to approximately 85 to 100% of the total weight), limestone (as to approximately 0 to 10% of the total weight) and coal tar pitch (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2% of the total weight.

**57.** Maxibrite briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are cushion-shaped briquettes marked with the letter "M";
- (d) have an average weight of 35 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**58.** Multiheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have average weights of either 55 or 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.



**59.** Brics glo Newburn, a weithgynhrychir gan ECL Mineral Processing Limited yn Newfield Works, Newfield, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o olog petrolewm (sef tua 56 i 57% o'r cyfanswm pwysau), glo caled (sef tua 37 i 38% o'r cyfanswm pwysau) a rhwymwr powdr sych (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses o galedu oer gan ddefnyddio gwasg rholer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd ac yn mesur 70 o filimetrau o hyd, 62 o filimetrau o led a 42 o filimetrau o uchder;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**60.** Brics glo Newburn, a weithgynhrychir gan M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS—

- (a) a gyfansoddir o olog petrolewm (sef tua 56 i 57% o'r cyfanswm pwysau), glo caled (sef tua 37 to 38% o'r cyfanswm pwysau), a rhwymwr powdr sych (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses o galedu oer gan ddefnyddio gwasg rholer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd ac yn mesur 70 o filimetrau x 62 o filimetrau x 42 o filimetrau;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**61.** Brics glo Newflame, a weithgynhrychir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhrychwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 78 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

**59.** Newburn briquettes, manufactured by ECL Mineral Processing Limited of Newfield Works, Newfield, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using a roller press;
- (c) are unmarked pillow-shaped briquettes that are 70 millimetres in length, 62 millimetres in width and 42 millimetres in height;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**60.** Newburn briquettes, manufactured by M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS, which—

- (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using roller press;
- (c) are unmarked pillow shape briquettes of 70 millimetres x 62 millimetres x 42 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**61.** Newflame briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 78 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**62.** Brics glo Newflame Plus, a weithgynhyrchir gan Maxibrite Limited, Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd, sydd tua 68 o filimetrau o hyd, 63 o filimetrau o led a 38 o filimetrau o uchder;
- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw mwy na 1.9% o gyfanswm eu pwysau sych yn sylffwr.

**63.** Brics glo Newheat, a weithgynhyrchir gan Oxbow Coal BV yn Newfield Works, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o olog petrolewm (sef tua 60 i 65% o'r cyfanswm pwysau), glo caled (sef tua 30 i 35% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri, caledwr a sefydlogydd tymheredd isel (sef gweddill y pwysau);
- (b) a gynhyrchwyd ar y tymheredd amgylchynol drwy broses sy'n cynnwys rhoio-wasgu a chaledu oer;
- (c) sy'n frics glo hirgrwn, heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso tua 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau yn sylffwr.

**64.** Optima Fire Logs, a weithgynhyrchir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebaw;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac

**62.** Newflame Plus briquettes, manufactured by Maxibrite Limited, Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes that are approximately 68 millimetres in length, 63 millimetres in width and 38 millimetres in height;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.

**63.** Newheat briquettes, manufactured by Oxbow Coal BV at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to approximately 60 to 65% of the total weight), anthracite (as to approximately 30 to 35% of the total weight) and a cold setting resin binder, hardener and low temperature stabiliser (as to the remaining weight);
- (b) are produced at ambient temperature by a process involving roll pressing and cold curing;
- (c) are unmarked pillow-shaped oval briquettes;
- (d) have an average weight of approximately 100 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight.

**64.** Optima Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and

- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**65.** Pagan Fuel's Restaurant Charcoal, a weithgynhyrchir gan Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay—

- (a) a gyfansoddir o'r coedydd caled *Prosopis nigra*, *Cordia alliodora*, *Centrolobeum*, *Prosopis kuntzei*, *Caesalpinia*, *Goncalo alves* a *Tabebuia* a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolisis mewn odyn ar tuag 800°C;
- (c) sy'n ddarnau o siarcol heb eu marcio rhwng 20 a 120 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

**66.** Brics glo Phurnacite, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp ofoidau â dwy linell gyfochrog yn rhedeg yn hydredol o amgylch y fricsen;
- (d) sy'n pwysu 40 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**67.** Pyrobloc Fire Logs, a weithgynhyrchir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 265 o filimetrau o hyd ac 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

- (e) have a sulphur content not exceeding 0.1% of the total weight.

**65.** Pagan Fuel's Restaurant Charcoal, manufactured by Pabensa SA Aviadores del Chaco, Asuncion, Paraguay, which—

- (a) comprises pyrolised *Prosopis nigra*, *Cordia alliodora*, *Centrolobeum*, *Prosopis kuntzei*, *Caesalpinia*, *Goncalo alves* and *Tabebuia* hardwoods;
- (b) were manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20-120 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**66.** Phurnacite briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette;
- (d) have an average weight of 40 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**67.** Pyrobloc Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 265 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**68.** Red Drops, a weithgynhyrchir gan EU Zeme Limited, Lāčplēša street 48, Rīga, LV-1011, Latfia—

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau), a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu, ac wedyn eu trin â gwres o tua 250 i 280°C;
- (c) sy'n frics glo ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 40 o filimetrau a thrwch o tua 21 o filimetrau yng nghanol y fricsen;
- (d) sy'n pwysu 23 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 0.5% o gyfanswm eu pwysau yn sylffwr.

**69.** Safelight Firelogs, a weithgynhyrchir gan Advanced Natural Fuels Limited, yn Pocklington, Dwyrain Swydd Efrog—

- (a) a gyfansoddir o sglodion pren (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr o gwyr palmwydd (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys gwasgu'r cynhwysion, ar ôl eu cymysgu, ar dymheredd o tua 40°C i 50°C;
- (c) sy'n foncyffion tân petryal caled â dwy agen ddofn sy'n gorgyffwrdd ar yr wyneb uchaf, un agen ddi-dor ar yr wyneb isaf;
- (d) sy'n pwysu 1.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**70.** Brics glo Sovereign, a weithgynhyrchir gan Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, De Swydd Efrog—

- (a) a gyfansoddir o lo caled (sef tua 75% o'r cyfanswm pwysau), glo a golosg adweithiol (sef tua 21% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys allwthio;
- (c) sy'n frics glo chweonglog heb eu marcio;
- (d) sy'n pwysu 130 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**68.** Red Drops manufactured by EU Zeme Limited, Lāčplēša street 48, Rīga, LV-1011, Latvia, which—

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing followed by heat treatment at a temperature of approximately 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and about 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

**69.** Safelight Firelogs, manufactured by Advanced Natural Fuels Limited, at Pocklington, East Riding of Yorkshire, which—

- (a) comprise woodchip (as to approximately 40 to 55% of the total weight) and palm wax binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving pressing of the mixed ingredients at about 40°C to 50°C;
- (c) are rectangular hard finish firelogs with two deep overlapping slots in the top surface, a single continuous slot in the base surface;
- (d) have an average weight of 1.8 kilograms; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**70.** Sovereign briquettes, manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, which—

- (a) comprise anthracite (as to approximately 75% of the total weight), coal and reactive coke (as to approximately 21% of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are unmarked hexagonal briquettes;
- (d) have an average weight of 130 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**71.** Brics glo Stoveheat Premium, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o gyfanswm eu pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp clustog, gyda hicyn ar ffurf llinell sy'n ymestyn o amgylch y fricsen;
- (d) sy'n pwyso 30 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**72.** Supabrite Coke Doubles, a weithgynhyrchir gan H. J. Banks and Company Limited yn Inkerman Road Depot, Tow Law, Swydd Durham—

- (a) a gyfansoddir o olog metelegol (sef tua 40 i 60% o'r cyfanswm pwysau) a golosg petrolewm (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys eu blendio a'u sgrinio;
- (c) sy'n hapsapiau heb eu marcio; a
- (d) nad yw mwy nag 1.95% o gyfanswm eu pwysau yn sylffwr.

**73.** Brics glo Supacite, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 240°C;
- (c) sy'n ofoidau heb eu marcio;
- (d) sy'n pwyso 45 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**71.** Stoveheat Premium briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion shaped briquettes with an indented line running around the briquette;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**72.** Supabrite Coke Doubles, manufactured by H J Banks and Company Limited at Inkerman Road Depot, Tow Law, County Durham, which—

- (a) comprise metallurgical coke (as to approximately 40 to 60% of the total weight) and petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving blending and screening;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 1.95% of the total weight.

**73.** Supacite briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 240°C;
- (c) are unmarked ovoids;
- (d) have an average weight of 45 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**74.** Brics glo Supertherm, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o gymysgedd (mewn cyfrannedd o 19:1) o lo caled a glo canolig ei anweddolrwydd (sef tua 93% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri neu rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n ofoidau heb eu marcio;
- (d) sy'n pwyso 160 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

**75.** Brics glo Supertherm II, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 36 i 51% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr organig neu rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n ofoidau wedi eu marcio ag un llinell ledredol ar draws un wyneb i bob bricsen neu'n ofoidau heb eu marcio;
- (d) sy'n pwyso 140 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

**76.** Brics glo Taybrite (a elwir fel arall yn frics glo Surefire), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd sydd naill ai wedi eu marcio â hycyn ar ffurf un llinell hydredol ar bob wyneb, 10 milimetr i fwrdd o'r llinell gyfatebol gyferbyn, neu sydd heb eu marcio;

**74.** Supertherm briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise a blend (in the proportion of 19:1) of anthracite and medium volatile coal (as to approximately 93% of the total weight) and cold-setting organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked ovoids;
- (d) have an average weight of 160 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**75.** Supertherm II briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are ovoids marked with a single latitudinal line running across one face of each briquette or unmarked ovoids;
- (d) have an average weight of 140 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

**76.** Taybrite briquettes (otherwise known as Surefire briquettes), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with a single indented line running longitudinally along each face, offset from its counterpart by 10 millimetres, or unmarked;

- (d) sy'n pwyso 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**77.** Therma Briquettes, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo hirgrwn/ar siâp deigrin gyda llinell drwy'r canol;
- (d) sy'n pwyso 26 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

**78.** Brics glo Thermac, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 90% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rhoio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 48 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

**79.** Tiger Tim Firelogs, a weithgynhyrchir gan De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 50% o'r cyfanswm pwysau) a blawd llif (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 280 o filimetrau o hyd, 75 o filimetrau o led a 75 o filimetrau o uchder a chanddynt un rhigol yn rhedeg ar hyd pob un o'r pedwar wyneb sy'n 280 milimetr o hyd;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

- (d) have an average weight of 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**77.** Therma Briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight) petroleum coke (as to approximately 12% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are oval/tear shaped briquettes with a line through the centre;
- (d) have an average weight of 26 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

**78.** Thermac briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 90% of the total weight) and cold-setting organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 48 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

**79.** Tiger Tim Firelogs, manufactured by De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 280 millimetres in length, 75 millimetres in width and 75 millimetres in height, with a single groove running along each of the four 280 millimetre length faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**80.** Unicite, a weithgynhyrchir gan DJ Davies Fuels Limited yn Blaenau Fuel Depot, Rhydaman, Sir Gaerfyrddin, neu a weithgynhyrchir gan AI Simson yn Cabby Latch, Logie ger Kirriemuir, Angus—

- (a) sy'n gymysgedd o'r gwahanol danwyddau a ganlyn—
  - (i) cnapiau mawr o lo caled, a
  - (ii) brics glo Union o'r disgrifiad yn is-baragraff (d) a weithgynhyrchir gan RWE Power AG yn Cologne, yr Almaen (sef dim mwy na thua 40 i 42% o gyfanswm pwysau Unicite);
- (b) nad yw ei gynnwys o sylffwr yn fwy na 0.5% o'r cyfanswm pwysau;
- (c) y datgenir nad yw'n danwydd awdurdodedig ond i'r graddau nad yw cyfran y brics glo Union a losgir drwy ddefnyddio Unicite yn uwch na'r ystod o ganrannau a bennir yn is-baragraff (a)(ii); a
- (d) i'r graddau y'i cyfansoddir o'r brics glo Union y cyfeirir atynt yn is-baragraff (a)(ii), a gyfansoddir o lignit cywagedig, gyda phob bricsen yn mesur tua 75 o filimetrau o led, 60 o filimetrau o uchder a 55 o filimetrau o drwch.

**81.** Zip 100% Natural Firelogs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrâu triglyserid hydrogenaid o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 210 o filimetrau o hyd, 80 o filimetrau o led a 75 o filimetrau o uchder;
- (d) sy'n pwyso rhwng 1.085 ac 1.115 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

**82.** Zip 100% Natural Firelogs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrâu triglyserid hydrogenaid o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);

**80.** Unicite, manufactured by DJ Davies Fuels Limited at Blaenau Fuel Depot, Ammanford, Carmarthenshire, or manufactured by AI Simson at Cabby Latch, Logie by Kirriemuir, Angus, which—

- (a) is a mixture of the following separate fuels—
  - (i) anthracite large nuts, and
  - (ii) Union briquettes of the description in sub paragraph (d) manufactured by RWE Power AG at Cologne, Germany (as to no more than approximately 40 to 42% of Unicite's total weight);
- (b) has a sulphur content not exceeding 0.5% of the total weight;
- (c) is declared to be an authorised fuel only in so far as the proportion of Union briquettes combusted in the use of Unicite does not exceed the percentage range specified in sub paragraph (a)(ii); and
- (d) in so far as it is constituted by the Union briquettes referred to in sub paragraph (a)(ii), consists of compressed lignite with each briquette measuring approximately 75 millimetres wide, 60 millimetres high and 55 millimetres thick.

**81.** Zip 100% Natural Firelogs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and a natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 210 millimetres in length, 80 millimetres in width and 75 millimetres in height;
- (d) have an average weight of between 1.085 and 1.115 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**82.** Zip 100% Natural Firelogs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and a natural molasses based binder (as to the remaining weight);



- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 245 milimetr o hyd, 75 milimetr o led a 68 milimetr o uchder;
- (d) sy'n pwyso rhwng 0.985 ac 1.015 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

**83.** ZIP 100% Natural Stove Logs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrâu triglyserid hydrogenaidd o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 165 o filimetrau o hyd, 80 o filimetrau o led a 75 o filimetrau o uchder;
- (d) sy'n pwyso rhwng 0.835 a 0.865 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

**84.** ZIP Cracklelog Firelogs, ZIP Crackle-log Firelogs a ZIP Crackling Log Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55% o'r cyfanswm pwysau), blawd llif pren caled (sef tua 42% o'r cyfanswm pwysau) a hadau clecian (sef tua 3.2% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd gyda diamedr o 80 o filimetrau, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**85.** ZIP Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);

- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 245 millimetres in length, 75 millimetres in width and 68 millimetres in height;
- (d) have an average weight of between 0.985 and 1.015 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**83.** ZIP 100% Natural Stove Logs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 165 millimetres in length, 80 millimetres in width and 75 millimetres in height;
- (d) have an average weight of between 0.835 and 0.865 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

**84.** ZIP Cracklelog Firelogs, ZIP Crackle-log Firelogs and ZIP Crackling Log Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 55% of the total weight), hardwood sawdust (as to approximately 42% of the total weight) and crackle seeds (as to approximately 3.2% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in diameter, with grooves along the faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**85.** ZIP Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to the remaining weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 265 o filimetrau o hyd ac 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebaw;
- (d) sy'n pwyso 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**86.** ZIP Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebaw;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

**87.** ZIP Firelogs, a weithgynhyrchir gan Woodflame Moerdijk BV, Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55 i 60% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 255 o filimetrau o hyd gyda diamedr o 75 o filimetrau, gyda rhigolau ar hyd un wyneb hydredol;
- (d) sy'n pwyso 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 265 millimetres in length and 80 millimetres in depth, with grooves along the faces;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**86.** ZIP Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along the faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

**87.** ZIP Firelogs, manufactured by Woodflame Moerdijk BV, Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, the Netherlands, which—

- (a) comprise slack wax (as to approximately 55 to 60% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 255 millimetres in length and 75 millimetres in diameter, with grooves along one longitudinal face;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.



