



OFFERYNNAU STATUDOL
CYMRU

2019 Rhif 50 (Cy. 15)

AER GLÂN, CYMRU

Rheoliadau Ardaloedd Rheoli Mwg
(Tanwyddau Awdurdodedig)
(Cymru) 2019

NODYN ESBONIADOL

(*Nid yw'r nodyn hwn yn rhan o'r Rheoliadau*)

Mae'r Rheoliadau hyn yn dirymu ac yn disodli gyda diwygiadau Reoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2017 (O.S. 2017/421 (Cy. 89)) ("Rheoliadau 2017").

Mae adran 20 o Ddeddf Aer Glân 1993 ("Deddf 1993") yn darparu ei bod yn drosedd gollwng mwg o simnai adeilad neu simnai sy'n gwasanaethu ffwrnais boeler sefydlog neu beiriannau diwydiannol, os yw'r simnai honno mewn ardal rheoli mwg. Er hynny, yn rhinwedd adran 20(3) mae'n amddiffyniad os gellir profi mai drwy ddefnyddio tanwydd awdurdodedig yn unig yr achoswyd y gollyngiad honedig.

Yn rhinwedd adran 20(6), ystyr "tanwydd awdurdodedig" yw tanwydd y datganwyd drwy reoliadau ei fod wedi ei awdurdodi. Mae'r pŵer i wneud rheoliadau o'r fath yn arferadwy o ran Cymru gan Weinidogion Cymru.

Mae'r Rheoliadau hyn yn pennu pob tanwydd sydd wedi ei awdurdodi ar hyn o bryd i'w ddefnyddio mewn ardaloedd rheoli mwg yng Nghymru at ddibenion adran 20 o Ddeddf 1993.

Mae'r tanwyddau a restrwyd yn yr Atodlen i Reoliadau 2017 yn union cyn i'r Rheoliadau hyn ddod i rym yn parhau i fod yn danwyddau awdurdodedig, ac eithrio bod newidiadau wedi eu gwneud i fanylob tri thanwydd (ALDI Winter Flame Smokeless Fuel, brics glo Brazier a brics glo Multiheat).

Mae pedwar ar ddeg o danwyddau ychwanegol wedi eu hawdurdodi am y tro cyntaf.

WELSH STATUTORY
INSTRUMENTS

2019 No. 50 (W. 15)

CLEAN AIR, WALES

The Smoke Control Areas
(Authorised Fuels) (Wales)
Regulations 2019

EXPLANATORY NOTE

(*This note is not part of the Regulations*)

These Regulations revoke and replace with amendments the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2017 (S.I. 2017/421 (W. 89)) ("the 2017 Regulations").

Section 20 of the Clean Air Act 1993 Act ("the 1993 Act") provides that it is an offence to emit smoke from a chimney of a building or a chimney serving a furnace of a fixed boiler or an industrial plant, if that chimney is within a smoke control area. However, by virtue of section 20(3), it is a defence to prove that the alleged emission was caused solely by the use of an authorised fuel.

By virtue of section 20(6), "authorised fuel" means a fuel declared by regulations to be an authorised fuel. The power to make such regulations is exercisable in relation to Wales by the Welsh Ministers.

These Regulations specify all fuels which are currently authorised for use in smoke control areas in Wales for the purposes of section 20 of the 1993 Act.

The fuels that were listed in the Schedule to the 2017 Regulations immediately prior to the coming into force of these Regulations continue to be authorised fuels, with the exception that changes have been made to the specification of three fuels (ALDI Winter Flame Smokeless Fuel, Brazier briquettes and Multiheat briquettes).

Fourteen additional fuels are authorised for the first time.

Ystyriwyd Cod Ymarfer Gweinidogion Cymru ar gynnal Asesiadau Effaith Rheoleiddiol mewn perthynas â'r Rheoliadau hyn. Ystyriwyd nad oedd yn angenrheidiol cynnal asesiad effaith rheoleiddiol o'r costau a'r manteision sy'n debygol o ddeillio o gydymffurfio â'r Rheoliadau hyn.

The Welsh Ministers' Code of Practice on the carrying out of Regulatory Impact Assessments was considered in relation to these Regulations. It was not considered necessary to carry out a regulatory impact assessment as to the likely costs and benefits of complying with these Regulations.

2019 Rhif 50 (Cy. 15)

AER GLÂN, CYMRU

Rheoliadau Ardaloedd Rheoli Mwg
(Tanwyddau Awdurdodedig)
(Cymru) 2019

Gwnaed	15 Ionawr 2019
Gosodwyd gerbron Cynlliad Cenedlaethol Cymru	16 Ionawr 2019
Yn dod i rym	6 Chwefror 2019

Mae Gweinidogion Cymru yn gwneud y Rheoliadau a ganlyn drwy arfer y pŵer a roddir gan adran 20(6) o Ddeddf Aer Glân 1993(1).

Enwi, cychwyn a chymhwysyo

1.—(1) Enw'r Rheoliadau hyn yw Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2019 a deuant i rym ar 6 Chwefror 2019.
(2) Mae'r Rheoliadau hyn yn gymwys o ran Cymru.

Tanwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993

2. Datgenir bod glo caled, glo lled-galed, trydan, nwy, gloeau stêm isel eu hanweddolrwydd a'r tanwyddau a ddisgrifir yn yr Atodlen yn danwyddau awdurdodedig at ddibenion Rhan III o Ddeddf Aer Glân 1993.

2019 No. 50 (W. 15)

CLEAN AIR, WALES

The Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2019

Made	15 January 2019
Laid before the National Assembly for Wales	16 January 2019
Coming into force	6 February 2019

The Welsh Ministers make the following Regulations in exercise of the power conferred by section 20(6) of the Clean Air Act 1993(1).

Title, commencement and application

1.—(1) The title of these Regulations is the Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2019 and they come into force on 6 February 2019.
(2) These Regulations apply in relation to Wales.

Authorised fuels for the purposes of Part III of the Clean Air Act 1993

2. Anthracite, semi-anthracite, electricity, gas, low volatile steam coals and the fuels described in the Schedule are declared to be authorised fuels for the purposes of Part III of the Clean Air Act 1993.

(1) 1993 c. 11. Trosglwyddwyd swyddogaeth berthnasol yr Ygrifennydd Gwladol, i'r graddau yr oedd yn arferadwy o ran Cymru, i Gynlliad Cenedlaethol Cymru yn rhinwedd ethygl 2 o Orchymyn Cynlliad Cenedlaethol Cymru (Trosglwyddo Swyddogaethau) 1999 (O.S. 1999/672) ac Atodlen 1 iddo. Mae'r swyddogaeth honno'n arferadwy bellach gan Weinidogion Cymru yn rhinwedd adran 162 o Ddeddf Llywodraeth Cymru 2006 (p. 32) a pharagraff 30 o Atodlen 11 iddi.

(1) 1993 c. 11. The relevant function of the Secretary of State was, so far as exercisable in relation to Wales, transferred to the National Assembly for Wales by virtue of article 2 of, and Schedule 1 to, the National Assembly for Wales (Transfer of Functions) Order 1999 (S.I. 1999/672). That function is now exercisable by the Welsh Ministers by virtue of section 162 of, and paragraph 30 of Schedule 11 to, the Government of Wales Act 2006 (c. 32).

Dirymu

3. Mae Rheoliadau Ardaloedd Rheoli Mwg (Tanwyddau Awdurdodedig) (Cymru) 2017(1) wedi eu dirymu.

Revocation

3. The Smoke Control Areas (Authorised Fuels) (Wales) Regulations 2017(1) are revoked.

Lesley Griffiths

Gweinidog yr Amgylchedd, Ynni a Materion Gwledig, un o Weinidogion Cymru

15 Ionawr 2019

Minister for Environment, Energy and Rural Affairs,
one of the Welsh Ministers.

15 January 2019

(1) O.S. 2017/421 (Cy. 89).

(1) S.I. 2017/421 (W. 89).

Tanwyddau Awdurdodedig

1. ALDI Winter Flame Smokeless Fuel, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 17% o'r cyfanswm pwysau) a rhwymwr o driagl/asid neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sydd naill ai'n frics glo heb eu marcio ar siâp gobennydd neu'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetref i ffwrdd o'r llinell gyfatebol gyferbyn;
- (d) sy'n pwyso 55 neu 80 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

2. Brics glo Aimcor Excel, a weithgynhyrchir gan Applied Industrial Materials UK Limited yn Newfield, Swydd Durham, neu a weithgynhyrchir gan Oxbow Carbon & Minerals UK Limited yn Windsor House, Cornwall Road, Harrogate, Gogledd Swydd Efrog—

- (a) a gyfansoddir o olosg petrolewm (sef tua 60 i 75% o'r cyfanswm pwysau), glo anweddolwydd-isel a golosg adweithiol (sef tua 20 i 25% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwyso 73 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

3. Brics glo Aimcor Pureheat, a weithgynhyrchir gan Applied Industrial Materials UK Limited yn Immingham, Gogledd Ddwyrain Swydd Lincoln, neu a weithgynhyrchir gan Oxbow Carbon & Minerals UK Limited yn Windsor House, Cornwall Road, Harrogate, Gogledd Swydd Efrog—

Authorised Fuels

1. ALDI Winter Flame Smokeless Fuel manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), bituminous coal (as to approximately 0 to 17% of the total weight) and molasses/acid or an organic binder (as the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment of up to 300°C;
- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;
- (d) have an average weight of 55 or 80 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

2. Aimcor Excel briquettes, manufactured by Applied Industrial Materials UK Limited at Newfield, County Durham, or manufactured by Oxbow Carbon & Minerals UK Limited at Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—

- (a) comprise petroleum coke (as to approximately 60 to 75% of the total weight), low volatile coal and reactive coke (as to approximately 20 to 25% of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 73 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

3. Aimcor Pureheat briquettes, manufactured by Applied Industrial Materials UK Limited at Immingham, North East Lincolnshire, or manufactured by Oxbow Carbon & Minerals UK Limited at Windsor House, Cornwall Road, Harrogate, North Yorkshire, which—

- (a) a gyfansoddir o lo caled (sef tua 60% o'r cyfanswm pwysau), golosg petrolewm (sef tua 25% o'r cyfanswm pwysau) a rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo ar siâp gobennydd gyda hicyn ar ffurf llinell sengl ar un ochr a hicyn ar ffurf llinell ddbwl ar yr ochr arall;
- (d) sy'n pwysu 75 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

4. Brics glo Ancit, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 95% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 30% o'r cyfanswm pwysau), glo meddal (hyd at tua 15% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp clustog;
- (d) sy'n pwysu 48 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

5. Big K Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

6. Big K Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);

- (a) comprise anthracite (as to approximately 60% of the total weight), petroleum coke (as to approximately 25% of the total weight) and binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are pillow-shaped briquettes with a single line indentation on one side and a double line indentation on the reverse side;
- (d) have an average weight of 75 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

4. Ancit briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 95% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight) and a molasses and phosphoric acid binder or an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are unmarked cushion-shaped briquettes;
- (d) have an average weight of 48 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

5. Big K Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

6. Big K Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 193 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 0.9 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

7. Big K Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 215 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

8. Big K Instant Lighting Fire Logs, a weithgynhyrchir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

9. Big K Restaurant Grade Charcoal, a weithgynhyrchir gan Big K Products UK Limited yn Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, yr Ariannin—

- (a) a gyfansoddir o bren quebracho gwyn a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tua 450°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 193 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.9 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

7. Big K Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 215 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

8. Big K Instant Lighting Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth and with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

9. Big K Restaurant Grade Charcoal, manufactured by Big K Products UK Limited at Parque Industrial Alvear, 2126 Alvear, Provincia de Santa Fe, Argentina, which—

- (a) comprise pyrolysed white quebracho wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 450°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

10. Big K Restaurant Grade Charcoal Briquettes a weithgynhyrchir gan Big K Esereso Carbon Products Ltd, PO Box 15469, Accra North, Ghana—

- (a) a gyfansoddir o bren Terminalia Superba a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses allwthio wedi ei dilyn gan broses o byrolysis mewn retort ar tua 450°C;
- (c) sy'n frics glo chweonglog, sy'n 4.5 i 5.5 centimedr o ddiamedr a'n 5 i 20 centimedr o hyd. Mae gan y brics graidd gwag sydd tua 1.5 centimedr o ddiamedr; a
- (d) nad yw mwy nag 0.1% o gyfanswm eu pwysau sych yn sylffwr.

11. Brics glo Black Diamond Gem, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o luch glo caled (sef tua 20 i 30% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 12 i 22% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n rhedeg yn lledredol o amgylch y fricsen;
- (d) sy'n pwys 160 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

12. Bord na Móna Firelogs, a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Iwerddon—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 255 o filimetrau o hyd gyda diamedr o 75 o filimetrau, gyda rhigolau ar hyd un wyneb hydredol;
- (d) sy'n pwys 1.3 cilogram (net) ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

10. Big K Restaurant Grade Charcoal Briquettes manufactured by Big K Esereso Carbon Products Ltd, PO Box 15469, Accra North, Ghana which—

- (a) comprises pyrolysed Terminalia Superba (Ofram);
- (b) were manufactured using an extrusion process followed by a retort pyrolysis process at approximately 450 °C;
- (c) are hexagonal shaped briquettes with a diameter of between 4.5 centimetres and 5.5 centimetres and length of between 5 centimetres and 20 centimetres. The briquettes have a hollow core about 1.5 centimetres diameter; and
- (d) have a sulphur content not exceeding 0.1% of the total weight on a dry basis.

11. Black Diamond Gem briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 20 to 30% of the total weight), petroleum coke (as to approximately 40 to 45% of the total weight), bituminous coal (as to approximately 12 to 22% of the total weight) and molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 160 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

12. Bord na Móna Firelogs, manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Ireland, which—

- (a) comprise slack wax (as to approximately 55% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 255 millimetres in length and 75 millimetres in diameter, and with grooves along one longitudinal face;
- (d) have an average weight of 1.3 kilograms (net); and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

13. Brics glo Bord na Móna Firepak (a farchnetir hefyd fel brics glo Arigna Special), a weithgynhyrchir gan Bord na Móna Fuels Limited, Newbridge, County Kildare, Iwerddon—

- (a) a gyfansoddir o lo caled (sef tua 50% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr seiliedig ar starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres;
- (c) sy'n frics glo heb eu marcio, ar siâp gobennydd;
- (d) sy'n pwys 50 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

14. Brand Choice Fire Log a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sy'n foncyffion Tân sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwys 0.8 cilogram fesul bonyff Tân ar gyfartaledd; ac
- (e) nad yw mwy nag 0.1% o gyfanswm eu pwysau yn sylffwr.

15. Brics glo Brazier a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 17% o'r cyfanswm pwysau) a rhwymwr o driagl/asid neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sydd naill ai'n frics glo heb eu marcio ar siâp gobennydd neu'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetir i ffwrdd o'r llinell gyfatebol gyferbyn;

13. Bord na Móna Firepak briquettes (also marketed as Arigna Special coal briquettes), manufactured by Bord na Móna Fuels Limited, Newbridge, County Kildare, Ireland, which—

- (a) comprise anthracite (as to approximately 50% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 10 to 30% of the total weight) and starch based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 50 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

14. Brand Choice Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, The Netherlands which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are firelogs that are approximately 172 millimetres in length and 75 millimetres in depth, 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms per firelog; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

15. Brazier briquettes manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), bituminous coal (as to approximately 0 to 17% of the total weight) and molasses/acid or an organic binder (as the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment of up to 300°C;
- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;

- (d) sy'n pwys 55 neu 80 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

16. Brics glo Briteflame, a weithgynhyrchrir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwys 140 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

17. Brics glo Briteheat, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 85% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 30% o'r cyfanswm pwysau), glo meddal (hyd at tua 15% o'r cyfanswm pwysau), a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp clustog gyda hicyn ar ffurf llinell yn rhedeg yn hydredol o gwmpas y fricsen;
- (d) sy'n pwys 30 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

18. Brics glo Briteheat Plus, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 75 i 95% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 20% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;

- (d) have an average weight of 55 or 80 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

16. Briteflame briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight), and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 140 grams; and
- (e) have a sulphur content not exceeding 1.9% sulphur on a dry basis.

17. Briteheat briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 85% of the total weight), petroleum coke (up to approximately 30% of the total weight), bituminous coal (up to approximately 15% of the total weight), and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion-shaped briquettes with an indented line running longitudinally around the briquette;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

18. Briteheat Plus briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 75 to 95% of the total weight), petroleum coke (up to approximately 20% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;

- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwys 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

19. Bryant and May Firelogs, a weithgynhyrchrir gan Swedish Match yn Kostenetz, Bwlgoria—

- (a) a gyfansoddir o gwyr paraffin (sef tua 50% o'r cyfanswm pwysau), pren poplys mäl (sef tua 25% o'r cyfanswm pwysau), blawd gwenith (sef tua 15% o'r cyfanswm pwysau), solidau cyneudwy ar wasgar mewn cwyrr paraffin ar ffurf jel (sef tua 1% o'r cyfanswm pwysau) a dŵr, cyfryngau chwyddo a chadwolyn (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys allwthio;
- (c) sydd â'u trawstoriad yn gwadrant gyda radiws o tua 80 o filimetrau a'u hyd tua 265 o filimetrau gyda stribyn cynnau ar hyd un ymyl;
- (d) sy'n pwys tuag 1.15 cilogram; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

20. Brics glo Charglow, a weithgynhyrchrir gan Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Gwlad Pwyl—

- (a) a gyfansoddir o gols glo meddal (sef tua 45 i 95% o'r cyfanswm pwysau), glo caled (sef tua 0 i 20% o'r cyfanswm pwysau), golosg petrolewm (sef tua 0 i 20% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 110°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwys 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

21. Coalite, a weithgynhyrchrir gan Coalite Products Limited yn Bolsover, ger Chesterfield, Swydd Derby ac yn Grimethorpe, De Swydd Efrog drwy ddefnyddio proses o garboneiddio ar dymheredd isel.

22. Brics glo Coalite Ovals, a weithgynhyrchrir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (c) are unmarked pillow shaped briquettes;
- (d) have an average weight of 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

19. Bryant and May Firelogs, manufactured by Swedish Match at Kostenetz, Bulgaria, which—

- (a) comprise paraffin wax (as to approximately 50% of the total weight), ground poplar wood (as to approximately 25% of the total weight), wheatflour (as to approximately 15% of the total weight), ignitable solids dispersed in gelled paraffin wax (as to approximately 1% of the total weight) and water, swelling agents and preservative (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are of quadrant cross sections with a radius of approximately 80 millimetres, and length approximately 265 millimetres with an ignition strip along one edge;
- (d) have an approximate weight of 1.15 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

20. Charglow briquettes, manufactured by Polchar Spolka z organiczona odpowiedzialnoscia, Police, Zachodniopomorskie, Poland, which—

- (a) comprise bituminous coal char (as to approximately 45 to 95% of the total weight), anthracite (as to approximately 0 to 20% of the total weight), petroleum coke (as to approximately 0 to 20% of the total weight), bituminous coal (as to approximately 0 to 10% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing and heat treatment at about 110°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

21. Coalite, manufactured by Coalite Products Limited at Bolsover, near Chesterfield, Derbyshire and at Grimethorpe, South Yorkshire using a low temperature carbonisation process.

22. Coalite Ovals briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd tua 84 o filimetrau o hyd, 38 o filimetrau o led a 62 o filimetrau o uchder;
- (d) sy'n pwysu 118 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

23. Golosg a weithgynhyrchir gan—

- (a) Coal Products Limited yn Cwm Coking Works, Llanilltuud Faerdref, Pontypridd, Rhondda Cynon Taf, ac a werthir fel "Sunbrite";
- (b) Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, De Swydd Efrog ac a werthir fel "Sunbrite" neu "Monckton Boiler Beans";
- (c) Corus UK Limited yn Teesside Works, Redcar & Cleveland ac a werthir fel "Redcar Coke Nuts (Doubles)"; a
- (d) Coal Products Limited yn Cwm Coking Works, Llanilltuud Faerdref, Pontypridd, Rhondda Cynon Taf ac a werthir fel "Cwm Coke Doubles".

24. Cosycoke (a farchnetir hefyd fel Lionheart Crusader neu Sunbrite Plus), a weithgynhyrchir gan Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, De Swydd Efrog ac Aimcor Supercoke (a farchnetir hefyd fel Supercoke), a weithgynhyrchir gan M & G Fuels Limited yn Hartlepool Docks, Hartlepool, ac ym mhob achos—

- (a) a gyfansoddir o olwg caled o faint penodol (sef tua 45 i 65% o'r cyfanswm pwysau) a golosg petrolewm o faint penodol (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy eu blendio;
- (c) sy'n hapsiapiau heb eu marcio; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

25. Brics glo Cosyglo Smokeless a weithgynhyrchir gan Arigna Fuels yn Arigna, Carrick-on-Shannon, County Roscommon, Iwerddon—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes that are approximately 84 millimetres in length, 38 millimetres in width and 62 millimetres in height;
- (d) have an average weight of 118 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.

23. Coke, manufactured by—

- (a) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taf, and sold as "Sunbrite";
- (b) Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, and sold as "Sunbrite" or "Monckton Boiler Beans";
- (c) Corus UK Limited at Teesside Works, Redcar & Cleveland, and sold as "Redcar Coke Nuts (Doubles)"; and
- (d) Coal Products Limited at Cwm Coking Works, Llantwit Fardre, Pontypridd, Rhondda Cynon Taf, and sold as "Cwm Coke Doubles".

24. Cosycoke (also marketed as Lionheart Crusader or Sunbrite Plus), manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire and Aimcor Supercoke (also marketed as Supercoke), manufactured by M & G Fuels Limited at Hartlepool Docks, Hartlepool, which in each case—

- (a) comprise sized hard coke (as to approximately 45 to 65% of the total weight) and sized petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by blending;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2% of the total weight.

25. Cosyglo Smokeless briquettes, manufactured by Arigna Fuels at Arigna, Carrick-on-Shannon, County Roscommon, Ireland, which—

- (a) a gyfansoddir o lo caled (sef tua 35 i 50% o'r cyfanswm pwysau), golosg petrolewm (hyd at tua 45% o'r cyfanswm pwysau), glo meddal (hyd at tuag 20% o'r cyfanswm pwysau) a rhwymwr starts neu rwymwr organig arall (hyd at 5% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd tua 80 o filimetrau o hyd, 60 o filimetrau o led a 40 o filimetrau o uchder;
- (d) sy'n pwysu 110 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.8% o gyfanswm eu pwysau sych yn sylffwr.

26. CPL Restaurant Grade Charcoal, a weithgynhyrchir gan Kunfayakun Global Treasures Limited (KGT) yn Kunfayakun Stores, No. 1, Aranse Street, Station, Sagamu, Orgub State E17, Shagamu International Market, Nigeria—

- (a) a gyfansoddir o Anogeissus Leiocarpus, Burkea Africana, Distemonanthus Benthamianus a Viteloria Paraclosum wedi eu pyrolysu;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tua 450°C i 550°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 50 a 180 o filimetrau; a
- (d) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

27. Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal, a weithgynhyrchir gan Direct Charcoal yn Ekamanzi Road, Dalton, KwaZulu Natal, Gweriniaeth De Afrika—

- (a) a gyfansoddir o bren Acacia mercii a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tua 420 i 480°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

28. Direct Charcoal Blue Bag Restaurant Charcoal, a weithgynhyrchir gan Direct Charcoal Limited yn Ruta 25, km. 9,5 -Pilar (cp.1629) Buenos Aires, yr Ariannin—

- (a) a gyfansoddir o bren quebracho gwyn a phren guayacan wedi eu pyrolysu;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tua 420 i 480°C;

- (a) comprise anthracite (as to approximately 35 to 50% of the total weight), petroleum coke (up to approximately 45% of the total weight), bituminous coal (up to approximately 20% of the total weight) and a starch or other organic binder (up to 5% of the total weight);
- (b) are manufactured from those constituents by a process involving roll-pressing and heat treatment at approximately 250°C;
- (c) are unmarked pillow-shaped briquettes that are approximately 80 millimetres in length, 60 millimetres in width and 40 millimetres in height;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.8% of the total weight on a dry basis.

26. CPL Restaurant Grade Charcoal, manufactured by Kunfayakun Global Treasures Limited (KGT) at Kunfayakun Stores, No. 1, Aranse Street, Station, Sagamu, Orgub State E17, Shagamu International Market, Nigeria, which—

- (a) comprises pyrolysed Anogeissus Leiocarpus, Burkea Africana, Distemonanthus Benthamianus and Viteloria Paraclosum;
- (b) was manufactured using a kiln pyrolysis process at approximately 450°C to 550°C;
- (c) are unmarked charcoal pieces of between 50-180 millimetres; and
- (d) has a sulphur content not exceeding 1.9% of the total weight on a dry basis.

27. Direct Charcoal Blue Bag Premium Grade Restaurant Charcoal, manufactured by Direct Charcoal at Ekamanzi Road, Dalton, KwaZulu Natal, Republic of South Africa, which—

- (a) comprise pyrolysed Acacia mercii wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 420 to 480°C;
- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

28. Direct Charcoal Blue Bag Restaurant Charcoal, manufactured by Direct Charcoal Limited at Ruta 25, km. 9,5 -Pilar (cp1629) Buenos Aires, Argentina, which—

- (a) comprise pyrolysed white quebracho and guayacan wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 420 to 480°C;

- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

29. Brics glo Dragonbrite, a weithgynhyrchir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf—

- (a) a gyfansoddir o lwch y tŵr (sef tua 95% o'r cyfanswm pwysau) a rhwymwr seiliedig ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo ar siâp gobennydd, wedi eu marcio â'r llythyren "T" ar un ochr;
- (d) sy'n pwys 50 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1% o gyfanswm eu pwysau yn sylffwr.

30. Brics glo Dragonglow, a weithgynhyrchir gan Tower Colliery Limited yn Aberdâr, Rhondda Cynon Taf—

- (a) a gyfansoddir o lwch y tŵr (sef tua 95% o'r cyfanswm pwysau) a rhwymwr seiliedig ar resin (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwys 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1% o gyfanswm eu pwysau yn sylffwr.

31. Brics glo Dual a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o olosg petrolewm (sef tua 55 i 80% o'r cyfanswm pwysau), glo caled (sef tua 8 i 20% o'r cyfanswm pwysau), glo meddal (sef tua 8 i 20% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sgwâr;
- (d) sy'n pwys 100 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

- (c) are unmarked charcoal pieces of between 30 millimetres to 150 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight.

29. Dragonbrite briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf, which—

- (a) comprise tower duff (as to approximately 95% of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are pillow-shaped briquettes marked with the letter "T" on one side;
- (d) have an average weight of 50 grams; and
- (e) have a sulphur content not exceeding 1% of the total weight.

30. Dragonglow briquettes, manufactured by Tower Colliery Limited at Aberdare, Rhondda Cynon Taf, which—

- (a) comprise tower duff (as to approximately 95% of the total weight) and a resin-based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving cold cure roll pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1% of the total weight.

31. Dual briquettes manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise petroleum coke (as to approximately 55 to 80% of the total weight), anthracite (as to approximately 8 to 20% of the total weight), bituminous coal (as to approximately 8 to 20% of the total weight) and an organic binder (as the remaining weight);
- (b) manufactured from those constituents by a process involving roll-pressing and cold cure;
- (c) are unmarked square pillow-shaped briquettes;
- (d) have an average weight of 100 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

32. Duraflame Firelogs, a weithgynhyrchrir gan Paramelt BV, Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr petrolewm mwynol (sef tua 55% o'r cyfanswm pwysau) a ffibr pren caled mäl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 320 o filimetrau o hyd, 90 o filimetrau o uchder ac 85 o filimetrau o led;
- (d) sy'n pwysu 1.45 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

33. Brics glo Ecoal (a farchnetir hefyd fel brics glo Homefire Ecoal a Supertherm 30), a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd fel arfer yn 72 o filimetrau o hyd, 58 o filimetrau o led a 42 o filimetrau o uchder neu sy'n frics glo chweonglog heb eu marcio sydd fel arfer yn 70 o filimetrau o hyd, 73 o filimetrau o led a 39 o filimetrau o uchder;
- (d) sy'n pwysu 125 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

34. Brics glo Ecoal 50, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 30 i 55% o'r cyfanswm pwysau), biomas (sef tua 25 i 35% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 5% o'r cyfanswm pwysau) a rhwymwr organig naturiol (sef gweddill y pwysau);

32. Duraflame Firelogs, manufactured by Paramelt BV, Costerstraat 18, PO Box 86, 1700 AB Heerhugowaard, the Netherlands, which—

- (a) comprise mineral-based petroleum wax (as to approximately 55% of the total weight) and ground hardwood fibre (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 320 millimetres in length, 90 millimetres in height and 85 millimetres wide;
- (d) have an average weight of 1.45 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

33. Ecoal briquettes (also marketed as Homefire Ecoal briquettes and Supertherm 30), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and molasses and phosphoric acid as binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at approximately 300°C;
- (c) are unmarked pillow shaped briquettes that are typically 72 millimetres in length, 58 millimetres in width and 42 millimetres in height or are unmarked hexagonal briquettes that are typically 70 millimetres in length, 73 millimetres in width and 39 millimetres in height;
- (d) have an average weight of 125 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

34. Ecoal 50 briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 30 to 55% of the total weight), biomass (as to approximately 25 to 35% of the total weight), petroleum coke (as to approximately 10 to 40% of the total weight), bituminous coal (as to approximately 0 to 5% of the total weight) and natural organic binder (as to the remaining weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a'u trin wedyn â gwres o tua 300°C mewn amgylchedd rheoledig gydag ocsigen gostyngedig;
- (c) sy'n frics glo chweonglog gydag un streipen sengl ar un ochr ar draws y wynebau gwastad;
- (d) sy'n pwysu 135 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

35. Brics glo Ecoal a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef tua 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd neu, sy'n frics glo chweonglog heb eu marcio neu, sy'n ofoidau siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch pob bricsen neu, sy'n frics glo chweonglog gydag un streipen sengl ar un ochr ar draws yr wyneb gwastad;
- (d) sy'n pwysu 125 i 135 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

36. Brics glo Ecoal a weithgynhyrchir gan CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef tua 20% o'r cyfanswm pwysau ar y mwyaf);

- (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at approximately 300°C in a controlled, reduced oxygen environment;
- (c) are hexagonal-shaped briquettes with a single stripe on one side across the flats;
- (d) have an average weight of 135 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

35. Ecoal Briquettes manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and an organic binder or, molasses and acid binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are unmarked-pillow shaped briquettes or, unmarked hexagonal briquettes or, pillow-shaped ovoids with two parallel indented lines running latitudinally around each briquette or, hexagonal briquettes with a single stripe on one side across the flat;
- (d) have an average weight of 125 to 135 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

36. Ecoal Briquettes manufactured by CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Ireland which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and an organic binder or, molasses and acid binder (as to a maximum of 20% of the total weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd neu, sy'n frics glo chweonglog heb eu marcio neu, sy'n ofoidau siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch pob bricsen neu, sy'n frics glo chweonglog gydag un streipen sengl ar un ochr ar draws yr wyneb gwastad;
- (d) sy'n pwys 125 i 135 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

37. Brics glo Ecobrite, a weithgynhyrchir gan Arigna Fuels Limited yn Arigna, Carrick-on-Shannon, County Roscommon, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 96% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd mewn dau faint;
- (d) sydd, ar gyfartaledd, yn pwys 37 gram yn achos y maint lleiaf a 48 gram yn achos y maint mwyaf; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

38. EDF Fuel Briquettes, a weithgynhyrchir gan TheGreenFactory yn y Laboratoire de Chimie Agro-industrielle UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue D'Azereiz, - BP 1629 65016 Tarbes Cedex, Ffrainc—

- (a) a gyfansoddir o tua 100 gram o Miscanthus heb ei brosesu (sef tua 45% o'r cyfanswm pwysau), tua 95 gram o ester Copra (sef tua 43% o'r cyfanswm pwysau), a thua 25 gram o rwymwr a gynhyrchwyd o Miscanthus (wedi ei brosesu â chalsiwm ocsid, sy'n ffurfio tua 0.5% o'r cyfanswm pwysau), sef gweddill y pwysau;
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys prosesu Miscanthus, cymysgu, poethwasgu, a throchi mewn baddon ester;
- (c) sy'n frics glo heb eu marcio ar siâp silindr, 120 o filimetrau o uchder gyda diamedr o 60 o filimetrau, a thwll canolog ar siâp seren yn treiddio drwy hyd hiraf y fricsen;

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are unmarked-pillow shaped briquettes or, unmarked hexagonal briquettes or, pillow-shaped ovoids with two parallel indented lines running latitudinally around each briquette or, hexagonal briquettes with a single stripe on one side across the flat;
- (d) have an average weight of 125 to 135 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

37. Ecobrite briquettes, manufactured by Arigna Fuels Limited at Arigna, Carrick-on-Shannon, County Roscommon, Ireland, which—

- (a) comprise anthracite fines (as to approximately 96% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 250°C;
- (c) are unmarked pillow-shaped briquettes in two sizes;
- (d) have an average weight of 37 grams for the smaller size and 48 grams for the larger size; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

38. EDF Fuel Briquettes, manufactured by TheGreenFactory at the Laboratoire de Chimie Agro-industrielle UMR 1010 INRA/INP-ENSIACET AGROMAT, Site de l'ENIT 47, Avenue D'Azereiz, - BP 1629 65016 Tarbes Cedex, France, which—

- (a) comprise approximately 100 grams of unprocessed Miscanthus (as to approximately 45% of the total weight), approximately 95 grams of Copra ester (as to approximately 43% of the total weight), and approximately 25 grams of a binder produced from Miscanthus (processed with calcium oxide as to approximately 0.5% of the total weight) as to the remaining weight;
- (b) are manufactured from those constituents by a process involving Miscanthus processing, mixing, hot pressing and soaking in an ester bath;
- (c) are unmarked cylinder-shaped briquettes of 120 millimetres in height and 60 millimetres in diameter with a star-shaped hole running centrally through the longer length of the briquette;

- (d) sy'n pwys 220 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

39. Brics glo Excel+, a weithgynhyrchir gan Oxbow Coal BV yn Newfield Works, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o olosg petrolewm (sef 65 i 70% o'r cyfanswm pwysau), glo caled (sef 25% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri, caledwr a sefydlogydd tymheredd isel (sef gweddill y pwysau);
- (b) a gynhyrchir ar y tymheredd amgylchynol drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sgwâr;
- (d) sy'n pwys 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau yn sylffwr.

40. Brics glo Extracite, a weithgynhyrchir gan Sophia-Jacoba Handelsgesellschaft GmbH yn Hückelhoven, yr Almaen—

- (a) a gyfansoddir o lwch glo caled (sef tua 95.5% o'r cyfanswm pwysau) a lleisw amoniwm lignosylffonad yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo ag arlliw ariannaidd ar siâp clustog, wedi eu marcio â'r llythrennau "S" a "J";
- (d) sy'n pwys 40 gram ar gyfartaledd; ac
- (e) y mae cyfanswm eu pwysau yn cynnwys tua 1.2% o sylffwr.

41. Fire Drops a weithgynhyrchir gan OU TrendSteel Products, Anri, Ropažu novads, Rigas rajons, Rigas, LV-2133, Latfia—

- (a) a gyfansoddir o falurion glo caled (sef tua 65.3% o'r cyfanswm pwysau), glo meddal sy'n achosi fflam hir (sef tua 25.7% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid orthoffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu, ac wedyn eu trin â gwres o tua 250-280°C;
- (c) sy'n frics glo ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 70mm a thrwch o tua 41 o filimetrau yng nghanol y fricsen;

- (d) have an average weight of 220 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

39. Excel+ briquettes, manufactured by Oxbow Coal BV at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to 65 to 70% of the total weight), anthracite (as to 25% of the total weight) and a cold setting resin binder, hardener and low temperature stabiliser (as to the remaining weight);
- (b) are produced at ambient temperature by a process involving roll pressing and cold curing;
- (c) are unmarked square pillow-shaped briquettes;
- (d) have an average weight of 100 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight.

40. Extracite briquettes, manufactured by Sophia-Jacoba Handelsgesellschaft GmbH at Hückelhoven, Germany, which—

- (a) comprise anthracite duff (as to approximately 95.5% of the total weight) and ammonium lignosulphonate lye as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are cushion-shaped briquettes with a silvery appearance and are marked with the letters "S" and "J";
- (d) have an average weight of 40 grams; and
- (e) have a sulphur content of approximately 1.2% of the total weight.

41. Fire Drops manufactured by OU TrendSteel Products, Anri, Ropažu novads, Rigas rajons, Rigas, LV-2133, Latvia which—

- (a) comprise crushed anthracite (as to approximately 65.3% per cent of the total weight), long-flame bituminous coal (as to approximately 25.7% per cent of the total weight) and molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) are manufactured from those constituents by a process involving roll pressing followed by heat treatment at a temperature of approximately 250-280°C;
- (c) are almost round pillow shaped briquettes that are 70mm in diameter and about 41mm thick at the centre of the briquette;

- (d) sy'n pwys 115 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 0.5% o gyfanswm eu pwysau yn sylffwr.

42. Brics glo Fireglo, a weithgynhyrchir gan Les Combustibles de Normandie yn Caen, Ffrainc, a chan La Société Rouennaise de Défumage yn Rouen, Ffrainc—

- (a) a gyfansoddir o lychau Cymreig wedi eu golchi (sef tua 92% o'r cyfanswm pwysau) a rhwymwr o byg glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 330°C;
- (c) sy'n ofoidau gyda thair llinell ar un ochr a'r ochr arall yn llyfn;
- (d) sy'n pwys 30 gram ar gyfartaledd; ac
- (e) nad yw mwy na 0.8% o gyfanswm eu pwysau yn sylffwr.

43. Fireglow Firelog a weithgynhyrchir gan Woodflame Moerdijk BV, Apolloweg 4, 4782 SB, Moerdijk, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55 i 60% o'r cyfanswm pwysau) a blawd llif pren caled (sef tua 40 i 45% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses drin â gwres ac allwthio;
- (c) sy'n fonyffion Tân sydd tua 180 o filimetrau o hyd, 80 o filimetrau o led a 70 o filimetrau o uchder, gydag un rhigol yn rhedeg ar hyd tri o'r pedwar wyneb;
- (d) sy'n pwys 0.80 cilogram fesul bonyff Tân ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

44. Brics glo Firegold, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 36 i 51% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid ffosfforig (sef 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd fel arfer yn 54 o filimetrau o hyd, 58 o filimetrau o led a 34 o filimetrau o uchder;

- (d) have an average weight of 115 grams per briquette; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

42. Fireglo briquettes, manufactured by Les Combustibles de Normandie at Caen, France, and by La Société Rouennaise de Défumage at Rouen, France, which—

- (a) comprise washed Welsh duffs (as to approximately 92% of the total weight) and coal pitch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 330°C;
- (c) are ovoids with three lines on one side and are smooth on the other side;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 0.8% of the total weight.

43. Fireglow firelog manufactured by Woodflame Moerdijk BV, Apolloweg 4, 4782 SB, Moerdijk, The Netherlands which—

- (a) comprise slack wax (as to approximately 55 to 60% of the total weight) and hardwood sawdust (as to approximately 40 to 45% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs that are approximately 180 millimetres in length and 80 millimetres in width and 70 millimetres in height, with a single groove running along three of the four faces;
- (d) have an average weight of 0.80 kilograms per firelog; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

44. Firegold briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow shaped briquettes that are typically 54 millimetres in length, 58 millimetres in width and 34 millimetres in height;

- (d) sy'n pwys 87 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

45. Flamefast firelog a weithgynhyrchir gan Woodflame Moerdijk BV, Apolloweg 4, 4782 SB, Moerdijk, Yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55 i 60% o'r cyfanswm pwysau) a blawd llif pren caled (sef tua 40 i 45% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses drin â gwres ac allwthio;
- (c) sy'n fonyffion Tân sydd tua 215 o filimetrau o hyd, 80 o filimetrau o led a 70 o filimetrau o uchder, gydag un rhigol yn rhedeg ar hyd tri o'r pedwar wyneb; a
- (d) sy'n pwys 0.95 cilogram fesul boneyff Tân ar gyfartaledd.

46. Gardeco Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwys 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

47. Gardeco Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 237 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwys 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

- (d) have an average weight of 87 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

45. Flamefast firelog manufactured by Woodflame Moerdijk BV, Apolloweg 4, 4782 SB, Moerdijk, The Netherlands which—

- (a) comprise slack wax (as to approximately 55 to 60% of the total weight) and hardwood sawdust (as to approximately 40 to 45% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are firelogs that are approximately 215 millimetres in length and 80 millimetres in width and 70 millimetres in height, with a single groove running along three of the four faces; and
- (d) have an average weight of 0.95 kilograms per firelog.

46. Gardeco Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

47. Gardeco Fire Log, manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 237 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

48. G N Grosvenor (Fuel Express) Restaurant Charcoal, a weithgynhyrchir gan Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay—

- (a) a gyfansoddir o'r coedydd caled Prosopsis nigra, Cordia alliodora, Centrolobium, Prosopsis kuntzei, Caesalpinia, Goncalo alves a Tabebuia wedi eu pyrolysu;
- (b) a weithgynhyrched gan ddefnyddio proses o byrolysis mewn odyn ar tuag 800°C;
- (c) sy'n ddarnau o siarcol rhwng 20 a 120 o filimetrau, heb eu marcio; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

49. Brics glo Homefire Ecoal a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef tua 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrched o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd neu, sy'n frics glo chweonglog heb eu marcio neu, sy'n ofoidau siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch pob bricsen neu, sy'n frics glo chweonglog gydag un streipen sengl ar un ochr ar draws yr wyneb gwastad;
- (d) sy'n pwysu 125 i 135 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

50. Brics glo Homefire Ecoal a weithgynhyrchir gan CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr

48. G N Grosvenor (Fuel Express) Restaurant Charcoal, manufactured by Pabensa SA Aviadores del Chaco, Asuncion, Paraguay, which—

- (a) comprises pyrolysed Prosopsis nigra, Cordia alliodora, Centrolobium, Prosopsis kuntzei, Caesalpinia, Goncalo alves and Tabebuia hardwoods;
- (b) were manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20 and 120 millimetres; and
- (d) has a sulphur content not exceeding 2% of the total weight on a dry basis.

49. Homefire Ecoal briquettes manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and an organic binder or, molasses and acid binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are unmarked-pillow shaped briquettes or, unmarked hexagonal briquettes or, pillow-shaped ovoids with two parallel indented lines running latitudinally around each briquette or, hexagonal briquettes with a single stripe on one side across the flat;
- (d) have an average weight of 125 to 135 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

50. Homefire Ecoal briquettes manufactured by CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Ireland which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and an organic binder or, molasses and acid

- organig neu rwymwr o driagl ac asid (sef tua 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
 - (c) sy'n frics glo heb eu marcio ar siâp gobennydd neu, sy'n frics glo chweonglog heb eu marcio neu, sy'n ofoidau siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch pob bricsen neu, sy'n frics glo chweonglog gydag un streipen sengl ar un ochr ar draws yr wyneb gwastad;
 - (d) sy'n pwysu 125 i 135 gram y fricsen ar gyfartaledd; ac
 - (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

51. Brics glo Homefire, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 70% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 45% o'r cyfanswm pwysau), cols (sef tua 0 i 10% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 30% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) nad yw eu cynnwys o ddeunydd anweddol, fel brics glo gorffenedig, yn llai na 9% nac yn fwy na 15% o'r cyfanswm pwysau sych;
- (d) sy'n frics glo chweonglog heb eu marcio;
- (e) sy'n pwysu 140 gram ar gyfartaledd; ac
- (f) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

52. Homefire Fire Logs, a weithgynhyrchir gan De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 50% o'r cyfanswm pwysau) a blawd llif (sef tua 50% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 280 o filimetrau o hyd, 75 o filimetrau o led a 75 o filimetrau o uchder, gydag un rhigol ar hyd pob un o'u pedwar wyneb sydd â'u hyd yn 280 milimetr;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac

binder (as to a maximum of 20% of the total weight);

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are unmarked-pillow shaped briquettes or, unmarked hexagonal briquettes or, pillow-shaped ovoids with two parallel indented lines running latitudinally around each briquette or, hexagonal briquettes with a single stripe on one side across the flat;
- (d) have an average weight of 125 to 135 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

51. Homefire briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 40 to 70% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), char (as to approximately 0 to 10% of the total weight), bituminous coal (as to approximately 5 to 30% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) have a volatile matter content in the finished briquette of neither less than 9% nor more than 15% of the total weight on a dry basis;
- (d) are unmarked hexagonal briquettes;
- (e) have an average weight of 140 grams; and
- (f) have a sulphur content not exceeding 2% of the total weight.

52. Homefire Fire Logs, manufactured by De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to approximately 50% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 280 millimetres in length, 75 millimetres in width and 75 millimetres in height, with a single groove running along each of the four 280 millimetre length faces;
- (d) have an average weight of 1.1 kilograms; and

- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

53. Homefire Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwys 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

54. Homefire Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 215 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwys 1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

55. Homefire Ovals, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 57% o'r cyfanswm pwysau), golosg petrolewm (sef tua 17% o'r cyfanswm pwysau), glo meddal (sef tua 13% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwys 135 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

- (e) have a sulphur content not exceeding 0.2% of the total weight.

53. Homefire Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

54. Homefire Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 215 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

55. Homefire Ovals, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 57% of the total weight), petroleum coke (as to approximately 17% of the total weight), bituminous coal (as to approximately 13% of the total weight) and molasses and phosphoric acid as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 135 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

56. Homefire Ovals (R), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 50 i 75% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 17% o'r cyfanswm pwysau) a rhwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwysu 130 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

57. Homefire Ovals (R) a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 50 i 75% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 17% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwysu 130 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

58. Homefire Ovals (R) a weithgynhyrchir gan CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 50 i 75% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 45% o'r cyfanswm pwysau), glo meddal (sef tua 5 i 17% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef gweddill y pwysau);

56. Homefire Ovals (R), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite fines (as to approximately 50 to 75% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), bituminous coal (as to approximately 5 to 17% of the total weight) and an organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 130 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

57. Homefire Ovals (R) manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 50 to 75% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), bituminous coal (as to approximately 5 to 17% of the total weight) and an organic binder or, molasses and acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 130 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

58. Homefire Ovals (R) manufactured by CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Ireland which—

- (a) comprise anthracite fines (as to approximately 50 to 75% of the total weight), petroleum coke (as to approximately 20 to 45% of the total weight), bituminous coal (as to approximately 5 to 17% of the total weight) and an organic binder or, molasses and acid binder (as to the remaining weight);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch y fricsen;
- (d) sy'n pwys 130 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

59. Brics glo Homeflame a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Morgannwg Ganol, De Cymru—

- (a) a gyfansoddir o lo meddal a golosg petrolewm (y ddu hyd at tua 10 i 15% o'r cyfanswm pwysau) a llwch glo caled a rhwymwr sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd sydd tua 68 o filimetrau o hyd, 63 o filimetrau o led a 38 o filimetrau o uchder;
- (d) sy'n pwys 110g y fricsen ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

60. Hot Drops, a weithgynhyrchir gan EU Zeme Limited yn Riga, Eksporta Street 15, LV-1045, Latfia—

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid orthoffosffor (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu, ac wedyn eu trin â gwres o tua 250 i 280°C;
- (c) sy'n frics glo, ar siâp gobennydd sydd bron yn grwn, gyda diametr o 40 o filimetrau a thrwch o tua 21 o filimetrau yng nghanol y fricsen;
- (d) sy'n pwys 23 gram ar gyfartaledd; ac
- (e) nad yw mwy na 0.5% o gyfanswm eu pwysau yn sylffwr.

61. Hot Rocks, a weithgynhyrchir gan EU Zeme Limited yn Riga, Eksporta Street 15, LV-1045, Latfia—

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to about 300°C;
- (c) are pillow-shaped briquettes with two parallel indented lines running latitudinally around the briquette;
- (d) have an average weight of 130 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

59. Homeflame briquettes manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Mid Glamorgan, South Wales which—

- (a) comprise of bituminous coal and petroleum coke (each as to approximately 10 to 15% of the total weight) and anthracite duff and cold setting binder (as to the remaining weight);
- (b) are manufactured from those constituents by a process involving roll pressing and cold curing;
- (c) are unmarked pillow-shaped briquettes that are approximately 68 millimeters in length, 63 millimeters in width and 38 millimetres in height;
- (d) have an average weight of 110g per briquette; and
- (e) have a sulphur content not exceeding 1.9% on a dry basis.

60. Hot Drops, manufactured by EU Zeme Limited at Riga, Eksporta Street 15, LV-1045, Latvia, which—

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll pressing followed by heat treatment at about 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and approximately 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

61. Hot Rocks, manufactured by EU Zeme Limited at Riga, Eksporta Street 15, LV-1045, Latvia, which—

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid orthoffosffor (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu, ac wedyn eu trin â gwres o tua 250 i 280°C;
- (c) sy'n frics glo, ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 40 o filimetrau a thrwch o tua 21 o filimetrau yng nghanol y fricsen;
- (d) sy'n pwys 23 gram ar gyfartaledd; ac
- (e) nad yw mwy na 0.5% o gyfanswm eu pwysau yn sylffwr.

62. HouseFuel Smokeless Ovals, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwys 78 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

63. HouseFuel Smokeless Ovals, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal a golosg petrolewm (y ddu hyd at tua 10 i 15% o'r cyfanswm pwysau) a llwch glo caled gyda rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd gyda'u dimensiynau mwyaf tua 68 o filimetrau, 63 o filimetrau a 38 o filimetrau;
- (d) sy'n pwys 110 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau sych yn sylffwr.

64. Island Lump ac Island Nuts, a weithgynhyrchir gan Unocal Refinery, California, Unol Daleithiau America—

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing followed by heat treatment at a temperature of approximately 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and about 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

62. HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 78 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

63. HouseFuel Smokeless Ovals, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal and petroleum coke (each as to approximately 10 to 15% of the total weight) and anthracite duff and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes with approximate maximum dimensions 68 millimetres, 63 millimetres and 38 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.9% on a dry basis.

64. Island Lump and Island Nuts, manufactured by Unocal Refinery, California, the United States of America, which—

- (a) a gyfansoddir o olosg petrolewm;
- (b) a weithgynhyrchwyd o'r golosg petrolewm drwy broses sy'n cynnwys trin â gwres a chwistrellu stêm;
- (c) sy'n hapsiapiau heb eu marcio;
- (d) sy'n pwyso 80 gram ar gyfartaledd (Island Lump) neu 30 gram ar gyfartaledd (Island Nuts); ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

65. Brics glo Jewel, a weithgynhyrchir gan Eldon Colliery Limited yn Newfield Works, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o lo caled (sef tua 30 i 50% o'r cyfanswm pwysau), golosg petrolewm Long Beach (sef tua 50 i 70% o'r cyfanswm pwysau) a rhwymwr o garbohydrad (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 150°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennyydd;
- (d) sy'n pwyso 33 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

66. La Hacienda Easy Logs, a weithgynhyrchir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

67. La Hacienda Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;

- (a) comprise petroleum coke;
- (b) were manufactured from the petroleum coke by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes;
- (d) have an average weight of 80 grams (Island Lump) or 30 grams (Island Nuts); and
- (e) have a sulphur content not exceeding 2% of the total weight.

65. Jewel briquettes, manufactured by Eldon Colliery Limited at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise anthracite (as to approximately 30 to 50% of the total weight), Long Beach petroleum coke (as to approximately 50 to 70% of the total weight) and a carbohydrate binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 150°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 33 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

66. La Hacienda Easy Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

67. La Hacienda Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;

- (c) sydd tua 172 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 0.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

68. La Hacienda Fire Log, a weithgynhyrchir gan Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, yr Iseldiroedd—

- (a) a gyfansoddir o 29% o gwyr paraffin, 20% o gwyr sy'n tarddu o blanhigion, 17% o belenni coed â diamedr o 6mm a 34% o flawd llif (yn ôl pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o gymysgu ac allwthio;
- (c) sydd tua 237 o filimetrau o hyd, 75 o filimetrau o ddyfnder a 75 o filimetrau o uchder, gyda 6 rhigol;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

69. Glo cnapiau Long Beach Lump (a elwir hefyd yn lo cnapiau LBL), a weithgynhyrchir gan Aimcor Carbon Corporation yn Long Beach, California, Unol Daleithiau America neu a weithgynhyrchir gan Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, Unol Daleithiau America—

- (a) a gyfansoddir o olosg petrolewm (sef tua 85 i 100% o'r cyfanswm pwysau), calchfaen (sef tua 0 i 10% o'r cyfanswm pwysau) a phyg tar glo (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys trin â gwres a chwistrellu stêm;
- (c) sy'n hapsiapiau heb eu marcio; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

70. Brics glo Maxibrite, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 250°C;
- (c) sy'n frics glo ar siâp clustog wedi eu marcio â'r llythyren "M";

- (c) are approximately 172 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 0.8 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

68. La Hacienda Fire Log manufactured by Top Flames Europe BV, Rustenburgerweg 3, 1646 WJ Ursem Gem, Alkmaar, the Netherlands, which—

- (a) comprise 29% paraffin wax, 20% plant derived wax, 17% 6mm diameter wood pellets and 34% sawdust (by weight);
- (b) were manufactured from those constituents by a process of mixing and extruding;
- (c) are approximately 237 millimetres in length, 75 millimetres in depth and 75 millimetres in height with 6 grooves;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

69. Long Beach Lump nuts (otherwise known as LBL nuts), manufactured by Aimcor Carbon Corporation at Long Beach, California, the United States of America, or manufactured by Oxbow Carbon & Minerals LLC, 330 Golden Shore, Suite 210, Long Beach, California 90802, the United States of America, which—

- (a) comprise petroleum coke (as to approximately 85 to 100% of the total weight), limestone (as to approximately 0 to 10% of the total weight) and coal tar pitch (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving heat treatment and steam injection;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 2% of the total weight.

70. Maxibrite briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;
- (c) are cushion-shaped briquettes marked with the letter "M";

- (d) sy'n pwys 35 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

71. Mr Charcoal: Grade A Restaurant Grill Charcoal a weithgynhyrchir gan Grupo Paben SA, Avda. Madame Lynch No 2833 c/ Punta Brava, Barrio Salvador del Mundo, Asunción, Paraguay—

- (a) a gyfansoddir o bren Aspidosperma Quebracho Blanco a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tua 450 i 600°C;
- (c) sy'n ddarnau o siarcol heb eu marcio, rhwng 30 o filimetrau a 150 o filimetrau o hyd; a
- (d) nad yw mwy na 0.1% o gyfanswm eu pwysau sych yn sylffwr.

72. Brics glo Multiheat, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau) glo meddal (sef tua 0 i 17% o'r cyfanswm pwysau) a rhwymwr o driagl/asid neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sydd naill ai'n frics glo heb eu marcio ar siâp gobennyydd, neu'n frics glo ar siâp gobennyydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetri ffwrdd o'r llinell gyfatebol gyferbyn;
- (d) sy'n pwys 55 neu 80 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

73. Brics glo Newburn, a weithgynhyrchir gan ECL Mineral Processing Limited yn Newfield Works, Newfield, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o losog petrolewm (sef tua 56 i 57% o'r cyfanswm pwysau), glo caled (sef tua 37 i 38% o'r cyfanswm pwysau) a rhwymwr powdr sych (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o galedu oer gan ddefnyddio gwasg rholer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennyydd ac yn mesur 70 o filimetrau o hyd, 62 o filimetrau o led a 42 o filimetrau o uchder;

- (d) have an average weight of 35 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

71. Mr Charcoal: Grade A Restaurant Grill Charcoal manufactured by Grupo Paben SA, Avda. Madame Lynch No 2833 c/ Punta Brava, Barrio Salvador del Mundo, Asunción, Paraguay which—

- (a) comprises pyrolysed Aspidosperma Quebracho Blanco wood;
- (b) were manufactured using a kiln pyrolysis process at approximately 450 to 600 °C;
- (c) are unmarked charcoal pieces between approximately 30 millimetres and 130 millimetres in length; and
- (d) have a sulphur content not exceeding 0.1% of the total weight on a dry basis.

72. Multiheat briquettes manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), bituminous coal (as to approximately 0 to 17% of the total weight) and molasses/acid or an organic binder (as the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment of up to 300°C;
- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;
- (d) have an average weight of 55 or 80 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

73. Newburn briquettes, manufactured by ECL Mineral Processing Limited of Newfield Works, Newfield, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using a roller press;
- (c) are unmarked pillow-shaped briquettes that are 70 millimetres in length, 62 millimetres in width and 42 millimetres in height;

- (d) sy'n pwysyo 110 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

74. Brics glo Newburn, a weithgynhyrchir gan M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS—

- (a) a gyfansoddir o olosg petrolewm (sef tua 56 i 57% o'r cyfanswm pwysau), glo caled (sef tua 37 to 38% o'r cyfanswm pwysau), a rhwymwr powdr sych (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o galedu oer gan ddefnyddio gwasg rholer;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd ac yn mesur 70 o filimetrau x 62 o filimetrau x 42 o filimetrau;
- (d) sy'n pwysyo 110 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

75. Brics glo Newflame, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwysyo 78 gram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 2% o'r cyfanswm pwysau.

76. Brics glo Newflame Plus, a weithgynhyrchir gan Maxibrite Limited, Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o lo meddal (sef tua 10 i 15% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 15% o'r cyfanswm pwysau), llwch glo caled (sef tua 70 i 80% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 260°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd, sydd tua 68 o filimetrau o hyd, 63 o filimetrau o led a 38 o filimetrau o uchder;

- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

74. Newburn briquettes, manufactured by M&G Solid Fuels LLP, Wilton International, Wilton, Middlesbrough, TS90 8WS, which—

- (a) comprise petroleum coke (as to approximately 56 to 57% of the total weight), anthracite (as to approximately 37 to 38% of the total weight), and a dry powder binder (as to the remaining weight);
- (b) were manufactured from those constituents by a cold cure process using roller press;
- (c) are unmarked pillow shape briquettes of 70 millimetres x 62 millimetres x 42 millimetres;
- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

75. Newflame briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 78 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

76. Newflame Plus briquettes, manufactured by Maxibrite Limited, Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise bituminous coal (as to approximately 10 to 15% of the total weight), petroleum coke (as to approximately 10 to 15% of the total weight), anthracite duff (as to approximately 70 to 80% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 260°C;
- (c) are unmarked pillow-shaped briquettes that are approximately 68 millimetres in length, 63 millimetres in width and 38 millimetres in height;

- (d) sy'n pwyso 110 gram ar gyfartaledd; ac
- (e) nad yw mwy na 1.9% o gyfanswm eu pwysau sych yn sylffwr.

77. Brics glo Newheat, a weithgynhyrchrir gan Oxbow Coal BV yn Newfield Works, Bishop Auckland, Swydd Durham—

- (a) a gyfansoddir o olosg petrolewm (sef tua 60 i 65% o'r cyfanswm pwysau), glo caled (sef tua 30 i 35% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri, caledwr a sefydlogydd tymheredd isel (sef gweddill y pwysau);
- (b) a gynhyrchwyd ar y tymheredd amgylchynol drwy broses sy'n cynnwys rholio-wasgu a chaledu oer;
- (c) sy'n frics glo hirgrwn, heb eu marcio ar siâp gobennyyd;
- (d) sy'n pwyso tua 100 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.9% o gyfanswm eu pwysau yn sylffwr.

78. Optima Fire Logs, a weithgynhyrchrir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwyso 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

79. Pagan Fuel's Restaurant Charcoal, a weithgynhyrchrir gan Pabensa S.A. Aviadores del Chaco, Asuncion, Paraguay—

- (a) a gyfansoddir o'r coedydd caled Prosopsis nigra, Cordia alliodora, Centrolobeum, Prosopsis kuntzei, Caesalpinia, Goncalo alves a Tabebuia a byrolyswyd;
- (b) a weithgynhyrchwyd gan ddefnyddio proses o byrolysis mewn odyn ar tuag 800°C;
- (c) sy'n ddarnau o siarcol heb eu marcio rhwng 20 a 120 o filimetrau; a
- (d) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

- (d) have an average weight of 110 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight on a dry basis.

77. Newheat briquettes, manufactured by Oxbow Coal BV at Newfield Works, Bishop Auckland, County Durham, which—

- (a) comprise petroleum coke (as to approximately 60 to 65% of the total weight), anthracite (as to approximately 30 to 35% of the total weight) and a cold setting resin binder, hardener and low temperature stabiliser (as to the remaining weight);
- (b) are produced at ambient temperature by a process involving roll pressing and cold curing;
- (c) are unmarked pillow-shaped oval briquettes;
- (d) have an average weight of approximately 100 grams; and
- (e) have a sulphur content not exceeding 1.9% of the total weight.

78. Optima Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

79. Pagan Fuel's Restaurant Charcoal, manufactured by Pabensa SA Aviadores del Chaco, Asuncion, Paraguay, which—

- (a) comprises pyrolysed Prosopsis nigra, Cordia alliodora, Centrolobeum, Prosopsis kuntzei, Caesalpinia, Goncalo alves and Tabebuia hardwoods;
- (b) were manufactured using a kiln pyrolysis process at approximately 800°C;
- (c) are unmarked charcoal pieces of between 20-120 millimetres; and
- (d) have a sulphur content not exceeding 2% of the total weight on a dry basis.

80. Brics glo Phurnacite, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp ofoidau â dwy linell gyfochrog yn rhedeg yn hydredol o amgylch y fricsen;
- (d) sy'n pwysu 40 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

81. Brics glo Phurnacite a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sy'n frics glo ar siâp ofoidau â dwy linell gyfochrog yn rhedeg yn hydredol o amgylch y fricsen;
- (d) sy'n pwysu 40 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

82. Brics glo Phurnacite a weithgynhyrchir gan CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Iwerddon—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;

80. Phurnacite briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette;
- (d) have an average weight of 40 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

81. Phurnacite briquettes manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and an organic binder or molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette;
- (d) have an average weight of 40 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

82. Phurnacite briquettes manufactured by CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Ireland which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and an organic binder or molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;

- (c) sy'n frics glo ar siâp ofoidau â dwy linell gyfochrog yn rhedeg yn hydredol o amgylch y fricsen;
- (d) sy'n pwys 40 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

83. Brics glo ProQ COCOCHA Coconut Shell a weithgynhyrchrir gan Siantan Suryatama PT, Golden Boulevard W2/19, BSD City, Tangerang, Indonesia—

- (a) a gyfansoddir o bowdr cragen cneuen goco wedi ei garboneiddio (sef tua 95% o'r cyfanswm pwysau), starts naturiol o blanhigion (sef tua 4.95% o'r cyfanswm pwysau), asid bensoaidd (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd drwy broses sy'n cynnwys carboneiddio cragen cneuen goco grai hyd at 600 gradd Celsius gan gynhyrchu'r powdr o gragen cneuen goco a chaiff ei falu, ei hidlo, ei gymysgu â'r cyfansoddion eraill, ei allwthio, ei dorri yna ei sychu hyd at 110 gradd Celsius;
- (c) sy'n frics glo ciwboid petryal heb eu marcio o faint 50 x 40 x 30 mm neu 40 x 30 x 25 mm;
- (d) sy'n pwys 54 a 56 gram y fricsen neu rhwng 26 a 28 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 1% o gyfanswm eu pwysau sych yn sylffwr.

84. Pyrobloc Fire Logs, a weithgynhyrchrir gan Allspan BV ym Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau), a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 265 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwys 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

85. Red Drops, a weithgynhyrchrir gan EU Zeme Limited, Lāčplēša street 48, Rīga, LV-1011, Latvia—

- (c) are ovoid-shaped briquettes with two parallel indented lines running longitudinally around the briquette;
- (d) have an average weight of 40 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

83. ProQ COCOCHA Coconut Shell Briquettes manufactured by Siantan Suryatama PT, Golden Boulevard W2/19, BSD City, Tangerang, Indonesia which—

- (a) comprised carbonised coconut shell powder (approximately 95% of total weight), natural plant starch (approximately 4.95% of total weight), benzoic acid (as the remaining weight);
- (b) were manufactured by a process involving carbonisation of raw coconut shell at up to 600 degrees Celsius producing the coconut shell powder which is milled, sieved, mixed with the other constituents, extruded, cut then dried at up to 110 degrees Celsius;
- (c) are unmarked rectangular cuboids briquettes of size 50 x 40 x 30 mm or 40 x 30 x 25 mm;
- (d) have an average weight of between 54 and 56 grams per briquette or 26 and 28 grams per briquette; and
- (e) have a sulphur content not exceeding 1% of the total weight of the dry product.

84. Pyrobloc Fire Logs, manufactured by Allspan BV at Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight), and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 265 millimetres in length and 80 millimetres in depth, with grooves along their faces;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

85. Red Drops manufactured by EU Zeme Limited, Lāčplēša street 48, Rīga, LV-1011, Latvia, which—

- (a) a gyfansoddir o falurion glo caled (sef tua 73% o'r cyfanswm pwysau), glo meddal (sef tua 18% o'r cyfanswm pwysau), a rhwymwr triagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu, ac wedyn eu trin â gwres o tua 250 i 280°C;
- (c) sy'n frics glo ar siâp gobennydd sydd bron yn grwn, gyda diamedr o 40 o filimetrau a thrwch o tua 21 o filimetrau yng nghanol y fricsen;
- (d) sy'n pwys 23 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 0.5% o gyfanswm eu pwysau yn sylffwr.

86. Safelight Firelogs, a weithgynhyrchir gan Advanced Natural Fuels Limited, yn Pocklington, Dwyrain Swydd Efrog—

- (a) a gyfansoddir o sglodion pren (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr o gwyr palmwydd (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys gwasgu'r cynhwysion, ar ôl eu cymysgu, ar dymheredd o tua 40°C i 50°C;
- (c) sy'n foncyffion tân petryal caled â dwy agen ddofn sy'n gorgyffwrdd ar yr wyneb uchaf, un agen ddi-dor ar yr wyneb isaf;
- (d) sy'n pwys 1.8 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

87. Smokeless Coal No5 a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petrolewm (sef tua 10 i 30% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 17% o'r cyfanswm pwysau) a rhwymwr o driagl/asid neu rwymwr organig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sydd naill ai'n frics glo heb eu marcio ar siâp gobennydd neu'n frics glo ar siâp gobennydd wedi eu marcio â hicyn ar ffurf llinell hydredol sengl ar bob wyneb, 10 milimetr i ffwrdd o'r llinell gyfatebol gyferbyn;
- (d) sy'n pwys 55 neu 80 gram y fricsen ar gyfartaledd; ac

- (a) comprise crushed anthracite (as to approximately 73% of the total weight), bituminous coal (as to approximately 18% of the total weight) and a molasses and orthophosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing followed by heat treatment at a temperature of approximately 250 to 280°C;
- (c) are almost round pillow-shaped briquettes that are 40 millimetres in diameter and about 21 millimetres thick at the centre of the briquette;
- (d) have an average weight of 23 grams; and
- (e) have a sulphur content not exceeding 0.5% of the total weight.

86. Safelight Firelogs, manufactured by Advanced Natural Fuels Limited, at Pocklington, East Riding of Yorkshire, which—

- (a) comprise woodchip (as to approximately 40 to 55% of the total weight) and palm wax binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving pressing of the mixed ingredients at about 40°C to 50°C;
- (c) are rectangular hard finish firelogs with two deep overlapping slots in the top surface, a single continuous slot in the base surface;
- (d) have an average weight of 1.8 kilograms; and
- (e) have a sulphur content not exceeding 2% of the total weight.

87. Smokeless Coal No5 manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight), bituminous coal (as to approximately 0 to 17% of the total weight) and molasses/acid or an organic binder (as the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment of up to 300°C;
- (c) are either unmarked pillow-shaped briquettes or, pillow-shaped briquettes marked with a single indented line running longitudinally along each face, off-set from its counterpart by 10 millimetres;
- (d) have an average weight of 55 or 80 grams per briquette; and

- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

88. Brics glo Sovereign, a weithgynhyrchrir gan Monckton Coke & Chemical Company Limited yn Royston, ger Barnsley, De Swydd Efrog—

- (a) a gyfansoddir o lo caled (sef tua 75% o'r cyfanswm pwysau), glo a golosg adweithiol (sef tua 21% o'r cyfanswm pwysau) a rhwymwr resin sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys allwthio;
- (c) sy'n frics glo chweonglog heb eu marcio;
- (d) sy'n pwys 130 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

89. Brics glo Stoveheat Premium, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lwch glo caled (sef tua 65 i 85% o gyfanswm eu pwysau), golosg petrolewm (sef tua 20% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp clustog, gyda hicyn ar ffurf llinell sy'n ymestyn o amgylch y fricsen;
- (d) sy'n pwys 30 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

90. Supabrite Coke Doubles, a weithgynhyrchrir gan H. J. Banks and Company Limited yn Inkerman Road Depot, Tow Law, Swydd Durham—

- (a) a gyfansoddir o olosg metelegol (sef tua 40 i 60% o'r cyfanswm pwysau) a golosg petrolewm (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys eu blendio a'u sgrinio;
- (c) sy'n hapsiapiau heb eu marcio; a
- (d) nad yw mwy nag 1.95% o gyfanswm eu pwysau yn sylffwr.

91. Brics glo Supacite, a weithgynhyrchrir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (e) have a sulphur content not exceeding 2% of the total weight.

88. Sovereign briquettes, manufactured by Monckton Coke & Chemical Company Limited at Royston, near Barnsley, South Yorkshire, which—

- (a) comprise anthracite (as to approximately 75% of the total weight), coal and reactive coke (as to approximately 21% of the total weight) and cold-setting resin binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving extrusion;
- (c) are unmarked hexagonal briquettes;
- (d) have an average weight of 130 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

89. Stoveheat Premium briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite duff (as to approximately 65 to 85% of the total weight), petroleum coke (as to approximately 20% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are cushion shaped briquettes with an indented line running around the briquette;
- (d) have an average weight of 30 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

90. Supabrite Coke Doubles, manufactured by H J Banks and Company Limited at Inkerman Road Depot, Tow Law, County Durham, which—

- (a) comprise metallurgical coke (as to approximately 40 to 60% of the total weight) and petroleum coke (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving blending and screening;
- (c) are unmarked random shapes; and
- (d) have a sulphur content not exceeding 1.95% of the total weight.

91. Supacite briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petrolewm (sef tua 12% o'r cyfanswm pwysau) a starts yn rhwymwr (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 240°C;
- (c) sy'n ofoidau heb eu marcio;
- (d) sy'n pwysu 45 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

92. Superburn Xtra a weithgynhyrchir gan Stafford Fuels Limited, Raheen, New Ross, Swydd Wexford, Y34 H028, Iwerddon—

- (a) a gyfansoddir o gymysgedd o lo caled (sef tua 20 i 60% o'r cyfanswm pwysau), Gronynnau Golosg Petrolewm (sef tuag 20 i 60% o'r cyfanswm pwysau), Gronynnau Glo Meddal (sef tua 15% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri (hyd at tua 6% o gyfanswm pwysau sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu oer;
- (c) sy'n ofoidau heb eu marcio o faint bras o 85 mm x 60 mm x 40 mm;
- (d) sy'n pwysu 130 gram fesul bric glo ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

93. Brics glo Supertherm, a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o gymysgedd (mewn cyfrannedd o 19:1) o lo caled a glo canolig ei anweddolrwydd (sef tua 93% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri neu rwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n ofoidau heb eu marcio;
- (d) sy'n pwysu 160 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

- (a) comprise anthracite fines (as to approximately 84% of the total weight), petroleum coke (as to approximately 12% of the total weight) and starch as binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 240°C;
- (c) are unmarked ovoids;
- (d) have an average weight of 45 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

92. Superburn Xtra manufactured by Stafford Fuels Limited, Raheen, New Ross, County Wexford, Y34 H028, Ireland which—

- (a) comprises a blend of Anthracite (as to approximately 20 to 60% of the total weight), Petroleum Coke Fines (as to approximately 20 to 60% of the total weight) and Bituminous Coal fines (up to approximately 15% of the total weight) with a cold-setting organic binder (up to approximately 6% of the total weight as the remaining weight);
- (b) were manufactured from those constituents by a process involving cold roll-pressing;
- (c) are unmarked ovoids of approximate size 85 mm x 60 mm x 40 mm;
- (d) have an average weight of 130 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

93. Supertherm briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise a blend (in the proportion of 19:1) of anthracite and medium volatile coal (as to approximately 93% of the total weight) and cold-setting organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked ovoids;
- (d) have an average weight of 160 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

94. Brics glo Supertherm II, a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 36 i 51% o'r cyfanswm pwysau), golosg petrolewm (sef tua 40 i 55% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n ofoidau wedi eu marcio ag un llinell ledredol ar draws un wyneb i bob bricsen neu'n ofoidau heb eu marcio;
- (d) sy'n pwysu 140 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau sych yn sylffwr.

95. Supertherm 30 a weithgynhyrchrir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20% o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef 20% o'r cyfanswm pwysau ar y mwyaf);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd neu, frics glo chweonglog heb eu marcio neu, sy'n ofoidau ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch pob bricsen neu, frics glo chweonglog gydag un streipen sengl ar un ochr ar draws yr wyneb gwastad;
- (d) sy'n pwysu 125 i 135 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

96. Supertherm 30 a weithgynhyrchrir gan CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Iwerddon—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 40 i 65% o'r cyfanswm pwysau), golosg petrolewm (sef tua 20 i 40% o'r cyfanswm pwysau), glo meddal (sef tua 0 i 20% o'r cyfanswm pwysau), biomas (sef tua 5 i 20%

94. Supertherm II briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 36 to 51% of the total weight), petroleum coke (as to approximately 40 to 55% of the total weight) and an organic binder or a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are ovoids marked with a single latitudinal line running across one face of each briquette or unmarked ovoids;
- (d) have an average weight of 140 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight on a dry basis.

95. Supertherm 30 manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight), biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and an organic binder or, molasses and acid binder (as to a maximum of 20% of the total weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are unmarked-pillow shaped briquettes or, unmarked hexagonal briquettes or, pillow-shaped ovoids with two parallel indented lines running latitudinally around each briquette or, hexagonal briquettes with a single stripe on one side across the flat;
- (d) have an average weight of 125 to 135 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

96. Supertherm 30 manufactured by CPL Fuels Ireland, Foynes Briquetting Works, Foynes Port, Foynes, Co. Limerick, Ireland which—

- (a) comprise anthracite fines (as to approximately 40 to 65% of the total weight), petroleum coke (as to approximately 20 to 40% of the total weight), bituminous coal (as to approximately 0 to 20% of the total weight),

o'r cyfanswm pwysau), cols biomas (sef tua 0 i 10% o'r cyfanswm pwysau) a rhwymwr organig neu rwymwr o driagl ac asid (sef 20% o'r cyfanswm pwysau ar y mwyaf);

- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o hyd at 300°C;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd neu, frics glo chweonglog heb eu marcio neu, sy'n ofoidau ar siâp gobennydd wedi eu marcio â hicyn ar ffurf dwy linell gyfochrog sy'n ymestyn yn lledredol o amgylch pob bricsen neu, frics glo chweonglog gydag un streipen sengl ar un ochr ar draws yr wyneb gwastad;
- (d) sy'n pwysu 125 i 135 gram y fricsen ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

97. Brics glo Taybrite (a elwir fel arall yn frics glo Surefire), a weithgynhyrchir gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 60 i 80% o'r cyfanswm pwysau), golosg petroleum (sef tua 10 i 30% o'r cyfanswm pwysau) a rhwymwr o driagl ac asid ffosfforig (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 300°C;
- (c) sy'n frics glo ar siâp gobennydd sydd naill ai wedi eu marcio â hicyn ar ffurf un llinell hydredol ar bob wyneb, 10 milimetru i ffwrdd o'r llinell gyfatebol gyferbyn, neu sydd heb eu marcio;
- (d) sy'n pwysu 80 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

98. Therma Briquettes, a weithgynhyrchir gan Maxibrite Limited yn Ystad Ddiwydiannol Mwyndy, Llantrisant, Rhondda Cynon Taf—

- (a) a gyfansoddir o ronynnau glo caled (sef tua 84% o'r cyfanswm pwysau), golosg petroleum (sef tua 12% o'r cyfanswm pwysau) a rhwymwr starts (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu a thrin â gwres o tua 250°C;

biomass (as to approximately 5 to 20% of the total weight), biomass char (as to approximately 0 to 10% of the total weight) and an organic binder or, molasses and acid binder (as to a maximum of 20% of the total weight);

- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment up to 300°C;
- (c) are unmarked-pillow shaped briquettes or, unmarked hexagonal briquettes or, pillow-shaped ovoids with two parallel indented lines running latitudinally around each briquette or, hexagonal briquettes with a single stripe on one side across the flat;
- (d) have an average weight of 125 to 135 grams per briquette; and
- (e) have a sulphur content not exceeding 2% of the total weight.

97. Taybrite briquettes (otherwise known as Surefire briquettes), manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 60 to 80% of the total weight), petroleum coke (as to approximately 10 to 30% of the total weight) and a molasses and phosphoric acid binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at about 300°C;
- (c) are pillow-shaped briquettes marked with a single indented line running longitudinally along each face, offset from its counterpart by 10 millimetres, or unmarked;
- (d) have an average weight of 80 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

98. Therma Briquettes, manufactured by Maxibrite Limited at Mwyndy Industrial Estate, Llantrisant, Rhondda Cynon Taf, which—

- (a) comprise anthracite fines (as to approximately 84% of the total weight) petroleum coke (as to approximately 12% of the total weight) and starch binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing and heat treatment at 250°C;

- (c) sy'n frics glo hirgrwn/ar siâp deigr yn gyda llinell drwy'r canol;
- (d) sy'n pwys 26 gram ar gyfartaledd; ac
- (e) nad yw mwy na 2% o gyfanswm eu pwysau yn sylffwr.

99. Brics glo Thermac, a weithgynhyrchr gan Coal Products Limited yn Immingham Briquetting Works, Immingham, Gogledd Ddwyrain Swydd Lincoln—

- (a) a gyfansoddir o lo caled (sef tua 90% o'r cyfanswm pwysau) a rhwymwr organig sy'n caledu wrth oeri (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses sy'n cynnwys rholio-wasgu;
- (c) sy'n frics glo heb eu marcio ar siâp gobennydd;
- (d) sy'n pwys 48 gram ar gyfartaledd; ac
- (e) nad yw mwy nag 1.5% o gyfanswm eu pwysau yn sylffwr.

100. Tiger Tim Firelogs, a weithgynhyrchr gan De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 50% o'r cyfanswm pwysau) a blawd llif (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 280 o filimetrau o hyd, 75 o filimetrau o led a 75 o filimetrau o uchder a chanddynt un rhigol yn rhedeg ar hyd pob un o'r pedwar wyneb sy'n 280 milimetr o hyd;
- (d) sy'n pwys 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

101. Unicite, a weithgynhyrchr gan DJ Davies Fuels Limited yn Blaenau Fuel Depot, Rhydaman, Sir Gaerfyrddin, neu a weithgynhyrchr gan AI Simson yn Cabby Latch, Logie ger Kirriemuir, Angus—

- (a) sy'n gymysgedd o'r gwahanol danwyddau a ganlyn—
 - (i) cnapiau mawr o lo caled, a
 - (ii) brics glo Union o'r disgrifiad yn is-baragraff (d) a weithgynhyrchr gan RWE Power AG yn Cologne, yr Almaen (sef dim mwy na thua 40 i 42% o gyfanswm pwysau Unicite);
- (b) nad yw ei gynnwys o sylffwr yn fwy na 0.5% o'r cyfanswm pwysau;

- (c) are oval/tear shaped briquettes with a line through the centre;
- (d) have an average weight of 26 grams; and
- (e) have a sulphur content not exceeding 2% of the total weight.

99. Thermac briquettes, manufactured by Coal Products Limited at Immingham Briquetting Works, Immingham, North East Lincolnshire, which—

- (a) comprise anthracite (as to approximately 90% of the total weight) and cold-setting organic binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process involving roll-pressing;
- (c) are unmarked pillow-shaped briquettes;
- (d) have an average weight of 48 grams; and
- (e) have a sulphur content not exceeding 1.5% of the total weight.

100. Tiger Tim Firelogs, manufactured by De Lange BV, Rustenburgerweg 3, 1646 WJ Ursem, the Netherlands, which—

- (a) comprise slack wax (as to approximately 50% of the total weight) and sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 280 millimetres in length, 75 millimetres in width and 75 millimetres in height, with a single groove running along each of the four 280 millimetre length faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

101. Unicite, manufactured by DJ Davies Fuels Limited at Blaenau Fuel Depot, Ammanford, Carmarthenshire, or manufactured by AI Simson at Cabby Latch, Logie by Kirriemuir, Angus, which—

- (a) is a mixture of the following separate fuels—
 - (i) anthracite large nuts, and
 - (ii) Union briquettes of the description in sub paragraph (d) manufactured by RWE Power AG at Cologne, Germany (as to no more than approximately 40 to 42% of Unicite's total weight);
- (b) has a sulphur content not exceeding 0.5% of the total weight;

- (c) y datgenir nad yw'n danwydd awdurdodedig ond i'r graddau nad yw cyfran y brics glo Union a losgir drwy ddefnyddio Unicite yn uwch na'r ystod o ganrannau a bennir yn is-baragraff (a)(ii); a
- (d) i'r graddau y'i cyfansoddir o'r brics glo Union y cyfeirir atynt yn is-baragraff (a)(ii), a gyfansoddir o lignit cywasgedig, gyda phob bricsen yn mesur tua 75 o filimetrau o led, 60 o filimetrau o uchder a 55 o filimetrau o drwch.

102. Zip 100% Natural Firelogs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrau triglycerid hydrogennaidd o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 210 o filimetrau o hyd, 80 o filimetrau o led a 75 o filimetrau o uchder;
- (d) sy'n pwysgo rhwng 1.085 ac 1.115 cilogram ar gyfartaledd; ac
- (e) nad yw eu cynnwys o sylffwr yn fwy na 0.2% o'r cyfanswm pwysau.

103. Zip 100% Natural Firelogs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (a) a gyfansoddir o gwyrau triglycerid hydrogennaidd o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 245 milimetr o hyd, 75 milimetr o led a 68 milimetr o uchder;
- (d) sy'n pwysgo rhwng 0.985 ac 1.015 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

104. ZIP 100% Natural Stove Logs, a weithgynhyrchir gan Standard Brands (Trading) Ireland Limited yn Castlebellingham, County Louth, Iwerddon—

- (c) is declared to be an authorised fuel only in so far as the proportion of Union briquettes combusted in the use of Unicite does not exceed the percentage range specified in subparagraph (a)(ii); and
- (d) in so far as it is constituted by the Union briquettes referred to in sub paragraph (a)(ii), consists of compressed lignite with each briquette measuring approximately 75 millimetres wide, 60 millimetres high and 55 millimetres thick.

102. Zip 100% Natural Firelogs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and a natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 210 millimetres in length, 80 millimetres in width and 75 millimetres in height;
- (d) have an average weight of between 1.085 and 1.115 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

103. Zip 100% Natural Firelogs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and a natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 245 millimetres in length, 75 millimetres in width and 68 millimetres in height;
- (d) have an average weight of between 0.985 and 1.015 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

104. ZIP 100% Natural Stove Logs, manufactured by Standard Brands (Trading) Ireland Limited at Castlebellingham, County Louth, Ireland, which—

- (a) a gyfansoddir o gwyrau triglyserid hydrogennaidd o darddiad naturiol (sef tua 53 i 57% o'r cyfanswm pwysau), ffibr helyg (sef tua 23 i 27% o'r cyfanswm pwysau) a rhwymwr naturiol seiliedig ar driagl (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 165 o filimetrau o hyd, 80 o filimetrau o led a 75 o filimetrau o uchder;
- (d) sy'n pwysgo rhwng 0.835 a 0.865 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.2% o gyfanswm eu pwysau yn sylffwr.

105. ZIP Cracklelog Firelogs, ZIP Crackle-log Firelogs a ZIP Crackling Log Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55% o'r cyfanswm pwysau), blawd llif pren caled (sef tua 42% o'r cyfanswm pwysau) a hadau clecian (sef tua 3.2% o'r cyfanswm pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd gyda diamedr o 80 o filimetrau, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysgo 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

106. ZIP Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 265 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysgo 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

107. ZIP Firelogs, a weithgynhyrchir gan Allspan BV, Macroweg 4, 5804 CL Venray, yr Iseldiroedd—

- (a) comprise naturally derived hydrogenated triglyceride waxes (as to approximately 53 to 57% of the total weight), willow fibre (as to approximately 23 to 27% of the total weight) and natural molasses based binder (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 165 millimetres in length, 80 millimetres in width and 75 millimetres in height;
- (d) have an average weight of between 0.835 and 0.865 kilograms; and
- (e) have a sulphur content not exceeding 0.2% of the total weight.

105. ZIP Cracklelog Firelogs, ZIP Crackle-log Firelogs and ZIP Crackling Log Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 55% of the total weight), hardwood sawdust (as to approximately 42% of the total weight) and crackle seeds (as to approximately 3.2% of the total weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in diameter, with grooves along the faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

106. ZIP Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 265 millimetres in length and 80 millimetres in depth, with grooves along the faces;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

107. ZIP Firelogs, manufactured by Allspan BV, Macroweg 4, 5804 CL Venray, the Netherlands, which—

- (a) a gyfansoddir o gwyr hydrin (sef tua 58 i 59% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 235 o filimetrau o hyd a 80 o filimetrau o ddyfnder, gyda rhigolau ar hyd yr wynebau;
- (d) sy'n pwysu 1.1 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

108. ZIP Firelogs, a weithgynhyrchir gan Woodflame Moerdijk BV, Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, yr Iseldiroedd—

- (a) a gyfansoddir o gwyr hydrin (sef tua 55 i 60% o'r cyfanswm pwysau) a blawd llif pren caled (sef gweddill y pwysau);
- (b) a weithgynhyrchwyd o'r cyfansoddion hynny drwy broses o drin â gwres ac allwthio;
- (c) sydd tua 255 o filimetrau o hyd gyda diamedr o 75 o filimetrau, gyda rhigolau ar hyd un wyneb hydredol;
- (d) sy'n pwysu 1.3 cilogram ar gyfartaledd; ac
- (e) nad yw mwy na 0.1% o gyfanswm eu pwysau yn sylffwr.

- (a) comprise slack wax (as to approximately 58 to 59% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 235 millimetres in length and 80 millimetres in depth, with grooves along the faces;
- (d) have an average weight of 1.1 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

108. ZIP Firelogs, manufactured by Woodflame Moerdijk BV, Apolloweg 4, Harbour No: M189A, 4782 SB Moerdijk, the Netherlands, which—

- (a) comprise slack wax (as to approximately 55 to 60% of the total weight) and hardwood sawdust (as to the remaining weight);
- (b) were manufactured from those constituents by a process of heat treatment and extrusion;
- (c) are approximately 255 millimetres in length and 75 millimetres in diameter, with grooves along one longitudinal face;
- (d) have an average weight of 1.3 kilograms; and
- (e) have a sulphur content not exceeding 0.1% of the total weight.

© Hawlfraint y Goron 2019

Argraffwyd a chyhoeddwyd yn y Deyrnas Unedig gan The Stationery Office Limited o dan awdurdod ac arolygiaeth Jeff James, Rheolwr Gwasg Ei Mawrhydi ac Argraffydd Deddfau Seneddol y Frenhines.

© Crown copyright 2019

Printed and published in the UK by The Stationery Office Limited under the authority and superintendence of Jeff James, Controller of Her Majesty's Stationery Office and Queen's Printer of Acts of Parliament.

