

SCHEDULE 6

Requirements for slurry storage systems

5.—(1) Any facilities used for the temporary storage of slurry before it is transferred to a slurry storage tank must have adequate capacity to store—

- (a) the maximum quantity of slurry that (disregarding any slurry which will be transferred directly into a slurry storage tank) is likely to be produced on the premises in any two day period, or
- (b) a lesser capacity that [F1NRW] agrees in writing is adequate to avoid any significant risk of pollution of controlled waters.

(2) Where slurry flows into a channel before discharging into a reception pit and the flow of slurry out of the channel is controlled by means of a sluice, the capacity of the reception pit must be adequate to hold the maximum quantity of slurry that can be released by opening the sluice.

Textual Amendments

- F1 Word in Sch. 6 substituted (31.12.2023) by [The Water Resources \(Control of Agricultural Pollution\) \(Wales\) \(Amendment\) \(No. 4\) Regulations 2023 \(S.I. 2023/1393\)](#), regs. 1, 7(f)

Commencement Information

- I1 Sch. 6 para. 5 in force at 1.4.2021, see [reg. 1\(3\)](#)

Changes to legislation:

There are currently no known outstanding effects for the The Water Resources (Control of Agricultural Pollution) (Wales) Regulations 2021, Paragraph 5.